

AUCT_EX Reference Card

(for version 11.50)

Conventions Used

Carriage Return or C-m	RET
Tabular or C-i	TAB
Linefeed or C-j	LFD

Shell Interaction

Run a command on the master file	C-c C-c
Run a command on the buffer	C-c C-b
Run a command on the region	C-c C-r
Fix the region	C-c C-t C-r
Kill job	C-c C-k
Recenter output buffer	C-c C-l
Next error in T _E X/LaTeX session	C-c ‘
Toggle debug of wonderful boxes	C-c C-w
View output file	C-c C-v

Commands you can run on the master file (with C-c C-c) or the region (with C-c C-r) include the following (starred versions are not available in all modes):

T _E X	*T _E X
LaTeX	*LaTeX
ConT _E Xt (once)	*ConT _E Xt
ConT _E Xt Full	*ConT _E Xt Full
Makeinfo	*Makeinfo
Makeinfo with HTML output	*Makeinfo HTML
Appropriate previewer	View
Print the output	Print
BibT _E X	BibT _E X
MakeIndex	Index
LaCheck	Check
Make (PostScript) File	File
Ispell	Spell

T_EXing options

T_EX runs can come in various types, which may be toggled and are indicated in the mode line.

PDF/DVI mode	C-c C-t C-p
Stop on errors (Interactive mode)	C-c C-t C-i
Use Source Specials for viewer control	C-c C-t C-s

Command Insertion

Insert Section	C-c C-s
Insert LaTeX environment	C-c C-e
Insert item	C-c LFD
Insert item (alias)	M-RET
Close LaTeX environment	C-c]
Insert T _E X macro \{\}	C-c C-m
Insert double brace	C-c {
Complete T _E X macro	M-TAB
Smart “quote”	"
Smart “dollar”	\$

Font Selection

Insert bold text	C-c C-f C-b
Insert <i>italics</i> text	C-c C-f C-i
Insert roman text	C-c C-f C-r
Insert <i>emphasized</i> text	C-c C-f C-e
Insert typewriter text	C-c C-f C-t
Insert <i>slanted</i> text	C-c C-f C-s
Delete font	C-c C-f C-d
Replace font	C-u C-c C-f <key>

Source Formatting

Indent current line	TAB
Indent next line	LFD
Format a paragraph	M-q
Format a region	C-c C-q C-r
Format a section	C-c C-q C-s
Format an environment	C-c C-q C-e
Mark an environment	C-c .
Mark a section	C-c *
Comment or uncomment region	C-c ;
Comment or uncomment paragraph	C-c %

Multifile Handling

Save Document	C-c C-d
Switch to master file or active buffer	C-c ^
Query for a master file	C-c _

Source Display

Toggle folding mode	C-c C-o C-f
Hide all items in buffer	C-c C-o C-b
Hide current macro	C-c C-o C-m
Hide current environment	C-c C-o C-e
Show all items in buffer permanently	C-c C-o C-x
Show current item permanently	C-c C-o C-c

Miscellaneous

Show documentation	C-c TAB
Math Mode	C-c ~
Reset Buffer	C-c C-n
Reset AUCT _E X	C-u C-c C-n

Copyright © 1987, 1993, 2004 Free Software Foundation, Inc.
Copyright © 1992 Kresten Krab Thorup
for AUCT_EX version 11.50

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.

Math Mode

Variables

All math mode commands are under the prefix key specified by LaTeX-math-abbrev-prefix, default is “”.

You can define your own math mode commands by setting the variable LaTeX-math-list before loading LaTeX-math-mode.

Greek Letters

α	(alpha)	a	τ	(tau)	t
β	(beta)	b	υ	(upsilon)	u
γ	(gamma)	g	ϕ	(phi)	f
δ	(delta)	d	χ	(chi)	q
ϵ	(epsilon)	e	ψ	(psi)	y
ζ	(zeta)	z	ω	(omega)	w
η	(eta)	h	Δ	(Delta)	D
θ	(theta)	j	Γ	(Gamma)	G
κ	(kappa)	k	Θ	(Theta)	Q
λ	(lambda)	l	Λ	(Lambda)	L
μ	(mu)	m	Π	(Pi)	P
ν	(nu)	n	Σ	(Sigma)	S
ξ	(xi)	x	Υ	(Upsilon)	U
π	(pi)	p	Φ	(Phi)	F
ρ	(rho)	r	Ψ	(Psi)	Y
σ	(sigma)	s	Ω	(Omega)	W

Symbols

\rightarrow	(rightarrow)	C-f	\supseteq	(supseteq)]
\leftarrow	(leftarrow)	C-b	\emptyset	(emptyset)	0
\uparrow	(uparrow)	C-p	\setminus	(setminus)	\
\downarrow	(downarrow)	C-n	\cup	(cup)	+
\leq	(leq)	<	\cap	(cap)	-
\geq	(geq)	>	\langle	(langle)	(
\tilde{x}	(tilde)	~	\rangle	(rangle))
∇	(nabla)	N	exp	(exp)	C-e
∞	(infty)	I	sin	(sin)	C-s
\forall	(forall)	A	cos	(cos)	C-c
\exists	(exists)	E	sup	(sup)	C-^
/	(not)	/	inf	(inf)	C-_
\in	(in)	i	det	(det)	C-d
\times	(times)	*	lim	(lim)	C-l
\cdot	(cdot)	.	tan	(tan)	C-t
\subset	(subset)	{	\hat{x}	(hat)	^
\supset	(supset)	}	\vee	(vee)	
\subseteq	(subseteq)	[\wedge	(wedge)	&

Miscellaneous

cal letters

c LETTER