
Python Library Reference

Release 1.6

Guido van Rossum
Fred L. Drake, Jr., editor

September 18, 2000

BeOpen PythonLabs
E-mail: python-docs@python.org

BEOPEN.COM TERMS AND CONDITIONS FOR PYTHON 2.0
BEOPEN PYTHON OPEN SOURCE LICENSE AGREEMENT VERSION 1

1. This LICENSE AGREEMENT is between BeOpen.com (“BeOpen”), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization (“Licensee”) accessing and otherwise using this software in source or binary form and its associated documentation (“the Software”).
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an “AS IS” basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the “BeOpen Python” logos available at <http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.
7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

CNRI OPEN SOURCE LICENSE AGREEMENT

Python 1.6 is made available subject to the terms and conditions in CNRI’s License Agreement. This Agreement together with Python 1.6 may be located on the Internet using the following unique, persistent identifier (known as a handle): 1895.22/1012. This Agreement may also be obtained from a proxy server on the Internet using the following URL: <http://hdl.handle.net/1895.22/1012>.

CWI PERMISSIONS STATEMENT AND DISCLAIMER

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Abstract

Python is an extensible, interpreted, object-oriented programming language. It supports a wide range of applications, from simple text processing scripts to interactive WWW browsers.

While the *Python Reference Manual* describes the exact syntax and semantics of the language, it does not describe the standard library that is distributed with the language, and which greatly enhances its immediate usability. This library contains built-in modules (written in C) that provide access to system functionality such as file I/O that would otherwise be inaccessible to Python programmers, as well as modules written in Python that provide standardized solutions for many problems that occur in everyday programming. Some of these modules are explicitly designed to encourage and enhance the portability of Python programs.

This library reference manual documents Python's standard library, as well as many optional library modules (which may or may not be available, depending on whether the underlying platform supports them and on the configuration choices made at compile time). It also documents the standard types of the language and its built-in functions and exceptions, many of which are not or incompletely documented in the Reference Manual.

This manual assumes basic knowledge about the Python language. For an informal introduction to Python, see the *Python Tutorial*; the *Python Reference Manual* remains the highest authority on syntactic and semantic questions. Finally, the manual entitled *Extending and Embedding the Python Interpreter* describes how to add new extensions to Python and how to embed it in other applications.

CONTENTS

1	Introduction	1
2	Built-in Types, Exceptions and Functions	3
2.1	Built-in Types	3
2.2	Built-in Exceptions	12
2.3	Built-in Functions	16
3	Python Services	25
3.1	sys — System-specific parameters and functions	25
3.2	types — Names for all built-in types	29
3.3	UserDict — Class wrapper for dictionary objects	31
3.4	UserList — Class wrapper for list objects	31
3.5	UserString — Class wrapper for string objects	31
3.6	operator — Standard operators as functions.	32
3.7	traceback — Print or retrieve a stack traceback	34
3.8	linecache — Random access to text lines	36
3.9	pickle — Python object serialization	36
3.10	cPickle — Alternate implementation of pickle	41
3.11	copy_reg — Register pickle support functions	41
3.12	shelve — Python object persistency	41
3.13	copy — Shallow and deep copy operations	42
3.14	marshal — Alternate Python object serialization	43
3.15	imp — Access the import internals	44
3.16	parser — Access Python parse trees	47
3.17	symbol — Constants used with Python parse trees	56
3.18	token — Constants used with Python parse trees	57
3.19	keyword — Testing for Python keywords	57
3.20	tokenize — Tokenizer for Python source	57
3.21	tabnanny — Detection of ambiguous indentation	58
3.22	pyclbr — Python class browser support	58
3.23	code — Interpreter base classes	59
3.24	codeop — Compile Python code	61
3.25	pprint — Data pretty printer.	61
3.26	repr — Alternate repr() implementation.	63
3.27	py_compile — Compile Python source files	65
3.28	compileall — Byte-compile Python libraries	65
3.29	dis — Disassembler.	66
3.30	new — Runtime implementation object creation	71
3.31	site — Site-specific configuration hook	72

3.32	<code>user</code> — User-specific configuration hook	73
3.33	<code>__builtin__</code> — Built-in functions	74
3.34	<code>__main__</code> — Top-level script environment.	74
4	String Services	75
4.1	<code>string</code> — Common string operations	75
4.2	<code>re</code> — Perl-style regular expression operations.	78
4.3	<code>regex</code> — Regular expression search and match operations.	85
4.4	<code>re.sub</code> — String operations using regular expressions	89
4.5	<code>struct</code> — Interpret strings as packed binary data	90
4.6	<code>fpformat</code> — Floating point conversions	92
4.7	<code>StringIO</code> — Read and write strings as files	93
4.8	<code>cStringIO</code> — Faster version of <code>StringIO</code>	93
4.9	<code>codecs</code> — Codec registry and base classes	93
5	Miscellaneous Services	95
5.1	<code>math</code> — Mathematical functions	95
5.2	<code>cmath</code> — Mathematical functions for complex numbers	97
5.3	<code>random</code> — Generate pseudo-random numbers	98
5.4	<code>whrandom</code> — Pseudo-random number generator	99
5.5	<code>bisect</code> — Array bisection algorithm	100
5.6	<code>array</code> — Efficient arrays of numeric values	100
5.7	<code>ConfigParser</code> — Configuration file parser	103
5.8	<code>fileinput</code> — Iterate over lines from multiple input streams	104
5.9	<code>calendar</code> — General calendar-related functions	105
5.10	<code>cmd</code> — Build line-oriented command interpreters.	106
5.11	<code>shlex</code> — Simple lexical analysis	108
6	Generic Operating System Services	111
6.1	<code>os</code> — Miscellaneous OS interfaces	111
6.2	<code>os.path</code> — Common pathname manipulations	121
6.3	<code>dircache</code> — Cached directory listings	123
6.4	<code>stat</code> — Interpreting <code>stat()</code> results	123
6.5	<code>statcache</code> — An optimization of <code>os.stat()</code>	125
6.6	<code>statvfs</code> — Constants used with <code>os.statvfs()</code>	126
6.7	<code>filecmp</code> — File Comparisons	126
6.8	<code>time</code> — Time access and conversions	127
6.9	<code>sched</code> — Event scheduler	130
6.10	<code>getpass</code> — Portable password input	131
6.11	<code>curses</code> — Terminal independent console handling	132
6.12	<code>getopt</code> — Parser for command line options.	136
6.13	<code>tempfile</code> — Generate temporary file names	137
6.14	<code>errno</code> — Standard <code>errno</code> system symbols.	138
6.15	<code>glob</code> — UNIX style pathname pattern expansion	144
6.16	<code>fnmatch</code> — UNIX filename pattern matching	144
6.17	<code>shutil</code> — High-level file operations	145
6.18	<code>locale</code> — Internationalization services	146
6.19	<code>mutex</code> — Mutual exclusion support	149
7	Optional Operating System Services	151
7.1	<code>signal</code> — Set handlers for asynchronous events.	151
7.2	<code>socket</code> — Low-level networking interface	153
7.3	<code>select</code> — Waiting for I/O completion	158
7.4	<code>thread</code> — Multiple threads of control	159
7.5	<code>threading</code> — Higher-level threading interface	160

7.6	Queue — A synchronized queue class	166
7.7	anydbm — Generic access to DBM-style databases	167
7.8	dumbdbm — Portable DBM implementation	168
7.9	dbhash — DBM-style interface to the BSD database library	168
7.10	whichdb — Guess which DBM module created a database	169
7.11	bsddb — Interface to Berkeley DB library	169
7.12	zlib — Compression compatible with gzip	171
7.13	gzip — Support for gzip files	173
7.14	zipfile — Work with ZIP archives	173
7.15	rlcompleter — Completion function for readline	175
8	Unix Specific Services	177
8.1	posix — The most common POSIX system calls	177
8.2	pwd — The password database	178
8.3	grp — The group database	179
8.4	crypt — Function to check UNIX passwords	179
8.5	d1 — Call C functions in shared objects	180
8.6	dbm — Simple “database” interface	181
8.7	gdbm — GNU’s reinterpretation of dbm	182
8.8	termios — POSIX style tty control	183
8.9	TERMIOS — Constants used with the termios module	184
8.10	tty — Terminal control functions	184
8.11	pty — Pseudo-terminal utilities	185
8.12	fcntl — The fcntl() and ioctl() system calls	185
8.13	pipes — Interface to shell pipelines	186
8.14	posixfile — File-like objects with locking support	187
8.15	resource — Resource usage information	189
8.16	nis — Interface to Sun’s NIS (Yellow Pages)	191
8.17	syslog — UNIX syslog library routines	192
8.18	popen2 — Subprocesses with accessible I/O streams	192
8.19	commands — Utilities for running commands	193
9	The Python Debugger	195
9.1	Debugger Commands	196
9.2	How It Works	198
10	The Python Profiler	201
10.1	Introduction to the profiler	201
10.2	How Is This Profiler Different From The Old Profiler?	201
10.3	Instant Users Manual	202
10.4	What Is Deterministic Profiling?	204
10.5	Reference Manual	204
10.6	Limitations	207
10.7	Calibration	207
10.8	Extensions — Deriving Better Profilers	208
11	Internet Protocols and Support	213
11.1	cgi — Common Gateway Interface support.	213
11.2	urllib — Open an arbitrary resource by URL	219
11.3	httplib — HTTP protocol client	223
11.4	ftplib — FTP protocol client	224
11.5	gopherlib — Gopher protocol client	227
11.6	poplib — POP3 protocol client	228
11.7	imaplib — IMAP4 protocol client	229
11.8	nntplib — NNTP protocol client	232

11.9	smtplib — SMTP protocol client	235
11.10	telnetlib — Telnet client	238
11.11	urlparse — Parse URLs into components.	241
11.12	SocketServer — A framework for network servers.	241
11.13	BaseHTTPServer — Basic HTTP server.	243
11.14	SimpleHTTPServer — A Do-Something Request Handler	246
11.15	CGIHTTPServer — A Do-Something Request Handler	247
11.16	asyncore — Asynchronous socket handler	247
12	Internet Data Handling	251
12.1	sgmllib — Simple SGML parser	251
12.2	htmllib — A parser for HTML documents	253
12.3	htmlentitydefs — Definitions of HTML general entities	255
12.4	xmllib — A parser for XML documents	255
12.5	formatter — Generic output formatting	258
12.6	rfc822 — Parse RFC 822 mail headers	261
12.7	mimertools — Tools for parsing MIME messages	264
12.8	MimeWriter — Generic MIME file writer	265
12.9	multifile — Support for files containing distinct parts	266
12.10	binhex — Encode and decode binhex4 files	268
12.11	uu — Encode and decode uuencode files	269
12.12	binascii — Convert between binary and ASCII	269
12.13	xdrlib — Encode and decode XDR data.	270
12.14	mailcap — Mailcap file handling.	273
12.15	mimetypes — Map filenames to MIME types	274
12.16	base64 — Encode and decode MIME base64 data	275
12.17	quopri — Encode and decode MIME quoted-printable data	276
12.18	mailbox — Read various mailbox formats	276
12.19	mhlib — Access to MH mailboxes	277
12.20	mimify — MIME processing of mail messages	278
12.21	netrc — netrc file processing	279
12.22	robotparser — Parser for robots.txt	280
13	Restricted Execution	283
13.1	rexec — Restricted execution framework	284
13.2	Bastion — Restricting access to objects	286
14	Multimedia Services	287
14.1	audioop — Manipulate raw audio data	287
14.2	imageop — Manipulate raw image data	290
14.3	aifc — Read and write AIFF and AIFC files	291
14.4	sunau — Read and write Sun AU files	293
14.5	wave — Read and write WAV files	295
14.6	chunk — Read IFF chunked data	297
14.7	colorsys — Conversions between color systems	298
14.8	rgbimg — Read and write “SGI RGB” files	299
14.9	imgchr — Determine the type of an image.	299
14.10	sndhdr — Determine type of sound file.	300
15	Cryptographic Services	301
15.1	md5 — MD5 message digest algorithm	301
15.2	sha — SHA message digest algorithm	302
15.3	mpz — GNU arbitrary magnitude integers	302
15.4	rotor — Enigma-like encryption and decryption.	303

16 SGI IRIX Specific Services	305
16.1 a1 — Audio functions on the SGI	305
16.2 AL — Constants used with the a1 module	307
16.3 cd — CD-ROM access on SGI systems	307
16.4 fl — FORMS library interface for GUI applications	310
16.5 FL — Constants used with the fl module	315
16.6 flp — Functions for loading stored FORMS designs	316
16.7 fm — <i>Font Manager</i> interface	316
16.8 gl — <i>Graphics Library</i> interface	317
16.9 DEVICE — Constants used with the gl module	319
16.10 GL — Constants used with the gl module	319
16.11 imgfile — Support for SGI imglib files	319
16.12 jpeg — Read and write JPEG files	320
17 SunOS Specific Services	323
17.1 sunaudiodev — Access to Sun audio hardware	323
17.2 SUNAUDIODEV — Constants used with sunaudiodev	324
18 MS Windows Specific Services	325
18.1 msvcrt — Useful routines from the MS VC++ runtime	325
18.2 winsound — Sound-playing interface for Windows	326
19 Undocumented Modules	329
19.1 Frameworks	329
19.2 Miscellaneous useful utilities	329
19.3 Platform specific modules	329
19.4 Multimedia	330
19.5 Obsolete	330
19.6 Extension modules	331
Module Index	333
Index	337

Introduction

The “Python library” contains several different kinds of components.

It contains data types that would normally be considered part of the “core” of a language, such as numbers and lists. For these types, the Python language core defines the form of literals and places some constraints on their semantics, but does not fully define the semantics. (On the other hand, the language core does define syntactic properties like the spelling and priorities of operators.)

The library also contains built-in functions and exceptions — objects that can be used by all Python code without the need of an `import` statement. Some of these are defined by the core language, but many are not essential for the core semantics and are only described here.

The bulk of the library, however, consists of a collection of modules. There are many ways to dissect this collection. Some modules are written in C and built in to the Python interpreter; others are written in Python and imported in source form. Some modules provide interfaces that are highly specific to Python, like printing a stack trace; some provide interfaces that are specific to particular operating systems, such as access to specific hardware; others provide interfaces that are specific to a particular application domain, like the World-Wide Web. Some modules are available in all versions and ports of Python; others are only available when the underlying system supports or requires them; yet others are available only when a particular configuration option was chosen at the time when Python was compiled and installed.

This manual is organized “from the inside out:” it first describes the built-in data types, then the built-in functions and exceptions, and finally the modules, grouped in chapters of related modules. The ordering of the chapters as well as the ordering of the modules within each chapter is roughly from most relevant to least important.

This means that if you start reading this manual from the start, and skip to the next chapter when you get bored, you will get a reasonable overview of the available modules and application areas that are supported by the Python library. Of course, you don’t *have* to read it like a novel — you can also browse the table of contents (in front of the manual), or look for a specific function, module or term in the index (in the back). And finally, if you enjoy learning about random subjects, you choose a random page number (see module [random](#)) and read a section or two. Regardless of the order in which you read the sections of this manual, it helps to start with chapter 2, “Built-in Types, Exceptions and Functions,” as the remainder of the manual assumes familiarity with this material.

Let the show begin!

Built-in Types, Exceptions and Functions

Names for built-in exceptions and functions are found in a separate symbol table. This table is searched last when the interpreter looks up the meaning of a name, so local and global user-defined names can override built-in names. Built-in types are described together here for easy reference.¹

The tables in this chapter document the priorities of operators by listing them in order of ascending priority (within a table) and grouping operators that have the same priority in the same box. Binary operators of the same priority group from left to right. (Unary operators group from right to left, but there you have no real choice.) See Chapter 5 of the *Python Reference Manual* for the complete picture on operator priorities.

2.1 Built-in Types

The following sections describe the standard types that are built into the interpreter. These are the numeric types, sequence types, and several others, including types themselves. There is no explicit Boolean type; use integers instead.

Some operations are supported by several object types; in particular, all objects can be compared, tested for truth value, and converted to a string (with the `'...'` notation). The latter conversion is implicitly used when an object is written by the `print` statement.

2.1.1 Truth Value Testing

Any object can be tested for truth value, for use in an `if` or `while` condition or as operand of the Boolean operations below. The following values are considered false:

- `None`
- zero of any numeric type, for example, `0`, `0L`, `0.0`, `0j`.
- any empty sequence, for example, `''`, `()`, `[]`.
- any empty mapping, for example, `{}`.
- instances of user-defined classes, if the class defines a `__nonzero__()` or `__len__()` method, when that method returns zero.²

All other values are considered true — so objects of many types are always true.

Operations and built-in functions that have a Boolean result always return `0` for false and `1` for true, unless otherwise stated. (Important exception: the Boolean operations `'or'` and `'and'` always return one of their operands.)

¹Most descriptions sorely lack explanations of the exceptions that may be raised — this will be fixed in a future version of this manual.

²Additional information on these special methods may be found in the *Python Reference Manual*.

2.1.2 Boolean Operations

These are the Boolean operations, ordered by ascending priority:

Operation	Result	Notes
<code>x or y</code>	if <code>x</code> is false, then <code>y</code> , else <code>x</code>	(1)
<code>x and y</code>	if <code>x</code> is false, then <code>x</code> , else <code>y</code>	(1)
<code>not x</code>	if <code>x</code> is false, then 1, else 0	(2)

Notes:

- (1) These only evaluate their second argument if needed for their outcome.
- (2) 'not' has a lower priority than non-Boolean operators, so `not a == b` is interpreted as `not (a == b)`, and `a == not b` is a syntax error.

2.1.3 Comparisons

Comparison operations are supported by all objects. They all have the same priority (which is higher than that of the Boolean operations). Comparisons can be chained arbitrarily; for example, `x < y <= z` is equivalent to `x < y` and `y <= z`, except that `y` is evaluated only once (but in both cases `z` is not evaluated at all when `x < y` is found to be false).

This table summarizes the comparison operations:

Operation	Meaning	Notes
<code><</code>	strictly less than	
<code><=</code>	less than or equal	
<code>></code>	strictly greater than	
<code>>=</code>	greater than or equal	
<code>==</code>	equal	
<code><></code>	not equal	(1)
<code>!=</code>	not equal	(1)
<code>is</code>	object identity	
<code>is not</code>	negated object identity	

Notes:

- (1) `<>` and `!=` are alternate spellings for the same operator. (I couldn't choose between `ABC` and `C!` :-) `!=` is the preferred spelling; `<>` is obsolescent.

Objects of different types, except different numeric types, never compare equal; such objects are ordered consistently but arbitrarily (so that sorting a heterogeneous array yields a consistent result). Furthermore, some types (for example, file objects) support only a degenerate notion of comparison where any two objects of that type are unequal. Again, such objects are ordered arbitrarily but consistently.

Instances of a class normally compare as non-equal unless the class defines the `__cmp__()` method. Refer to the *Python Reference Manual* for information on the use of this method to effect object comparisons.

Implementation note: Objects of different types except numbers are ordered by their type names; objects of the same types that don't support proper comparison are ordered by their address.

Two more operations with the same syntactic priority, 'in' and 'not in', are supported only by sequence types (below).

2.1.4 Numeric Types

There are four numeric types: *plain integers*, *long integers*, *floating point numbers*, and *complex numbers*. Plain integers (also just called *integers*) are implemented using `long` in C, which gives them at least 32 bits of precision. Long integers have unlimited precision. Floating point numbers are implemented using `double` in C. All bets on their precision are off unless you happen to know the machine you are working with.

Complex numbers have a real and imaginary part, which are both implemented using `double` in C. To extract these parts from a complex number `z`, use `z.real` and `z.imag`.

Numbers are created by numeric literals or as the result of built-in functions and operators. Unadorned integer literals (including hex and octal numbers) yield plain integers. Integer literals with an ‘L’ or ‘l’ suffix yield long integers (‘L’ is preferred because ‘11’ looks too much like eleven!). Numeric literals containing a decimal point or an exponent sign yield floating point numbers. Appending ‘j’ or ‘J’ to a numeric literal yields a complex number.

Python fully supports mixed arithmetic: when a binary arithmetic operator has operands of different numeric types, the operand with the “smaller” type is converted to that of the other, where plain integer is smaller than long integer is smaller than floating point is smaller than complex. Comparisons between numbers of mixed type use the same rule.³ The functions `int()`, `long()`, `float()`, and `complex()` can be used to coerce numbers to a specific type.

All numeric types support the following operations, sorted by ascending priority (operations in the same box have the same priority; all numeric operations have a higher priority than comparison operations):

Operation	Result	Notes
$x + y$	sum of x and y	
$x - y$	difference of x and y	
$x * y$	product of x and y	
x / y	quotient of x and y	(1)
$x \% y$	remainder of x / y	
$-x$	x negated	
$+x$	x unchanged	
<code>abs(x)</code>	absolute value or magnitude of x	
<code>int(x)</code>	x converted to integer	(2)
<code>long(x)</code>	x converted to long integer	(2)
<code>float(x)</code>	x converted to floating point	
<code>complex(re, im)</code>	a complex number with real part re , imaginary part im . im defaults to zero.	
<code>c.conjugate()</code>	conjugate of the complex number c	
<code>divmod(x, y)</code>	the pair $(x / y, x \% y)$	(3)
<code>pow(x, y)</code>	x to the power y	
$x ** y$	x to the power y	

Notes:

- (1) For (plain or long) integer division, the result is an integer. The result is always rounded towards minus infinity: $1/2$ is 0, $(-1)/2$ is -1, $1/(-2)$ is -1, and $(-1)/(-2)$ is 0. Note that the result is a long integer if either operand is a long integer, regardless of the numeric value.
- (2) Conversion from floating point to (long or plain) integer may round or truncate as in C; see functions `floor()` and `ceil()` in module `math` for well-defined conversions.
- (3) See section 2.3, “Built-in Functions,” for a full description.

Bit-string Operations on Integer Types

³As a consequence, the list `[1, 2]` is considered equal to `[1.0, 2.0]`, and similar for tuples.

Plain and long integer types support additional operations that make sense only for bit-strings. Negative numbers are treated as their 2's complement value (for long integers, this assumes a sufficiently large number of bits that no overflow occurs during the operation).

The priorities of the binary bit-wise operations are all lower than the numeric operations and higher than the comparisons; the unary operation '~' has the same priority as the other unary numeric operations ('+' and '-').

This table lists the bit-string operations sorted in ascending priority (operations in the same box have the same priority):

Operation	Result	Notes
$x \mid y$	bitwise <i>or</i> of x and y	
$x \wedge y$	bitwise <i>exclusive or</i> of x and y	
$x \& y$	bitwise <i>and</i> of x and y	
$x \ll n$	x shifted left by n bits	(1), (2)
$x \gg n$	x shifted right by n bits	(1), (3)
$\sim x$	the bits of x inverted	

Notes:

- (1) Negative shift counts are illegal and cause a `ValueError` to be raised.
- (2) A left shift by n bits is equivalent to multiplication by `pow(2, n)` without overflow check.
- (3) A right shift by n bits is equivalent to division by `pow(2, n)` without overflow check.

2.1.5 Sequence Types

There are three sequence types: strings, lists and tuples.

Strings literals are written in single or double quotes: `'xyzzy'`, `"frobozz"`. See chapter 2 of the *Python Reference Manual* for more about string literals. Lists are constructed with square brackets, separating items with commas: `[a, b, c]`. Tuples are constructed by the comma operator (not within square brackets), with or without enclosing parentheses, but an empty tuple must have the enclosing parentheses, e.g., `a, b, c` or `()`. A single item tuple must have a trailing comma, e.g., `(d,)`.

Sequence types support the following operations. The 'in' and 'not in' operations have the same priorities as the comparison operations. The '+' and '*' operations have the same priority as the corresponding numeric operations.⁴

This table lists the sequence operations sorted in ascending priority (operations in the same box have the same priority). In the table, s and t are sequences of the same type; n , i and j are integers:

Operation	Result	Notes
$x \text{ in } s$	1 if an item of s is equal to x , else 0	
$x \text{ not in } s$	0 if an item of s is equal to x , else 1	
$s + t$	the concatenation of s and t	
$s * n, n * s$	n copies of s concatenated	(1)
$s[i]$	i 'th item of s , origin 0	(2)
$s[i:j]$	slice of s from i to j	(2), (3)
<code>len(s)</code>	length of s	
<code>min(s)</code>	smallest item of s	
<code>max(s)</code>	largest item of s	

Notes:

⁴They must have since the parser can't tell the type of the operands.

- (1) Values of n less than 0 are treated as 0 (which yields an empty sequence of the same type as s).
- (2) If i or j is negative, the index is relative to the end of the string, i.e., $\text{len}(s) + i$ or $\text{len}(s) + j$ is substituted. But note that -0 is still 0.
- (3) The slice of s from i to j is defined as the sequence of items with index k such that $i \leq k < j$. If i or j is greater than $\text{len}(s)$, use $\text{len}(s)$. If i is omitted, use 0. If j is omitted, use $\text{len}(s)$. If i is greater than or equal to j , the slice is empty.

More String Operations

String objects have one unique built-in operation: the `%` operator (modulo) with a string left argument interprets this string as a C `sprintf()` format string to be applied to the right argument, and returns the string resulting from this formatting operation.

The right argument should be a tuple with one item for each argument required by the format string; if the string requires a single argument, the right argument may also be a single non-tuple object.⁵ The following format characters are understood: `%`, `c`, `s`, `i`, `d`, `u`, `o`, `x`, `X`, `e`, `E`, `f`, `g`, `G`. Width and precision may be a `*` to specify that an integer argument specifies the actual width or precision. The flag characters `-`, `+`, blank, `#` and `0` are understood. The size specifiers `h`, `l` or `L` may be present but are ignored. The `%s` conversion takes any Python object and converts it to a string using `str()` before formatting it. The ANSI features `%p` and `%n` are not supported. Since Python strings have an explicit length, `%s` conversions don't assume that `'\0'` is the end of the string.

For safety reasons, floating point precisions are clipped to 50; `%f` conversions for numbers whose absolute value is over $1e25$ are replaced by `%g` conversions.⁶ All other errors raise exceptions.

If the right argument is a dictionary (or any kind of mapping), then the formats in the string must have a parenthesized key into that dictionary inserted immediately after the `'%'` character, and each format formats the corresponding entry from the mapping. For example:

```
>>> count = 2
>>> language = 'Python'
>>> print '%(language)s has %(count)03d quote types.' % vars()
Python has 002 quote types.
```

In this case no `*` specifiers may occur in a format (since they require a sequential parameter list).

Additional string operations are defined in standard module `string` and in built-in module `re`.

Mutable Sequence Types

List objects support additional operations that allow in-place modification of the object. These operations would be supported by other mutable sequence types (when added to the language) as well. Strings and tuples are immutable sequence types and such objects cannot be modified once created. The following operations are defined on mutable sequence types (where x is an arbitrary object):

⁵A tuple object in this case should be a singleton.

⁶These numbers are fairly arbitrary. They are intended to avoid printing endless strings of meaningless digits without hampering correct use and without having to know the exact precision of floating point values on a particular machine.

Operation	Result	Notes
<code>s[i] = x</code>	item <i>i</i> of <i>s</i> is replaced by <i>x</i>	
<code>s[i:j] = t</code>	slice of <i>s</i> from <i>i</i> to <i>j</i> is replaced by <i>t</i>	
<code>del s[i:j]</code>	same as <code>s[i:j] = []</code>	
<code>s.append(x)</code>	same as <code>s[len(s):len(s)] = [x]</code>	(1)
<code>s.extend(x)</code>	same as <code>s[len(s):len(s)] = x</code>	(2)
<code>s.count(x)</code>	return number of <i>i</i> 's for which <code>s[i] == x</code>	
<code>s.index(x)</code>	return smallest <i>i</i> such that <code>s[i] == x</code>	(3)
<code>s.insert(i, x)</code>	same as <code>s[i:i] = [x]</code> if <i>i</i> >= 0	
<code>s.pop([i])</code>	same as <code>x = s[i]; del s[i]; return x</code>	(4)
<code>s.remove(x)</code>	same as <code>del s[s.index(x)]</code>	(3)
<code>s.reverse()</code>	reverses the items of <i>s</i> in place	(5)
<code>s.sort([cmpfunc])</code>	sort the items of <i>s</i> in place	(5), (6)

Notes:

- (1) The C implementation of Python has historically accepted multiple parameters and implicitly joined them into a tuple; this will no longer work in Python 1.6. Use of this misfeature has been deprecated since Python 1.4.
- (2) Raises an exception when *x* is not a list object. The `extend()` method is experimental and not supported by mutable sequence types other than lists.
- (3) Raises `ValueError` when *x* is not found in *s*.
- (4) The `pop()` method is experimental and not supported by other mutable sequence types than lists. The optional argument *i* defaults to `-1`, so that by default the last item is removed and returned.
- (5) The `sort()` and `reverse()` methods modify the list in place for economy of space when sorting or reversing a large list. They don't return the sorted or reversed list to remind you of this side effect.
- (6) The `sort()` method takes an optional argument specifying a comparison function of two arguments (list items) which should return `-1`, `0` or `1` depending on whether the first argument is considered smaller than, equal to, or larger than the second argument. Note that this slows the sorting process down considerably; e.g. to sort a list in reverse order it is much faster to use calls to the methods `sort()` and `reverse()` than to use the built-in function `sort()` with a comparison function that reverses the ordering of the elements.

2.1.6 Mapping Types

A *mapping* object maps values of one type (the key type) to arbitrary objects. Mappings are mutable objects. There is currently only one standard mapping type, the *dictionary*. A dictionary's keys are almost arbitrary values. The only types of values not acceptable as keys are values containing lists or dictionaries or other mutable types that are compared by value rather than by object identity. Numeric types used for keys obey the normal rules for numeric comparison: if two numbers compare equal (e.g. `1` and `1.0`) then they can be used interchangeably to index the same dictionary entry.

Dictionaries are created by placing a comma-separated list of *key: value* pairs within braces, for example: `{'jack': 4098, 'sjoerd': 4127}` or `{4098: 'jack', 4127: 'sjoerd'}`.

The following operations are defined on mappings (where *a* and *b* are mappings, *k* is a key, and *v* and *x* are arbitrary objects):

Operation	Result	Notes
<code>len(a)</code>	the number of items in <i>a</i>	
<code>a[k]</code>	the item of <i>a</i> with key <i>k</i>	(1)
<code>a[k] = x</code>	set <i>a[k]</i> to <i>x</i>	
<code>del a[k]</code>	remove <i>a[k]</i> from <i>a</i>	(1)
<code>a.clear()</code>	remove all items from <i>a</i>	
<code>a.copy()</code>	a (shallow) copy of <i>a</i>	
<code>a.has_key(k)</code>	1 if <i>a</i> has a key <i>k</i> , else 0	
<code>a.items()</code>	a copy of <i>a</i> 's list of (<i>key</i> , <i>value</i>) pairs	(2)
<code>a.keys()</code>	a copy of <i>a</i> 's list of keys	(2)
<code>a.update(b)</code>	for <i>k</i> , <i>v</i> in <i>b.items()</i> : <i>a[k] = v</i>	(3)
<code>a.values()</code>	a copy of <i>a</i> 's list of values	(2)
<code>a.get(k[, x])</code>	<i>a[k]</i> if <i>a.has_key(k)</i> , else <i>x</i>	(4)

Notes:

- (1) Raises a `KeyError` exception if *k* is not in the map.
- (2) Keys and values are listed in random order. If `keys()` and `values()` are called with no intervening modifications to the dictionary, the two lists will directly correspond. This allows the creation of (*value*, *key*) pairs using `map(): 'pairs = map(None, a.values(), a.keys())'`.
- (3) *b* must be of the same type as *a*.
- (4) Never raises an exception if *k* is not in the map, instead it returns *x*. *x* is optional; when *x* is not provided and *k* is not in the map, `None` is returned.

2.1.7 Other Built-in Types

The interpreter supports several other kinds of objects. Most of these support only one or two operations.

Modules

The only special operation on a module is attribute access: *m.name*, where *m* is a module and *name* accesses a name defined in *m*'s symbol table. Module attributes can be assigned to. (Note that the `import` statement is not, strictly speaking, an operation on a module object; `import foo` does not require a module object named *foo* to exist, rather it requires an (external) *definition* for a module named *foo* somewhere.)

A special member of every module is `__dict__`. This is the dictionary containing the module's symbol table. Modifying this dictionary will actually change the module's symbol table, but direct assignment to the `__dict__` attribute is not possible (i.e., you can write `m.__dict__['a'] = 1`, which defines *m.a* to be 1, but you can't write `m.__dict__ = {}`).

Modules built into the interpreter are written like this: `<module 'sys' (built-in)>`. If loaded from a file, they are written as `<module 'os' from '/usr/local/lib/python1.5/os.pyc'>`.

Classes and Class Instances

See chapters 3 and 7 of the *Python Reference Manual* for these.

Functions

Function objects are created by function definitions. The only operation on a function object is to call it: *func(argument-list)*.

There are really two flavors of function objects: built-in functions and user-defined functions. Both support the same operation (to call the function), but the implementation is different, hence the different object types.

The implementation adds two special read-only attributes: `f.func_code` is a function's *code object* (see below) and `f.func_globals` is the dictionary used as the function's global name space (this is the same as `m.__dict__` where `m` is the module in which the function `f` was defined).

Methods

Methods are functions that are called using the attribute notation. There are two flavors: built-in methods (such as `append()` on lists) and class instance methods. Built-in methods are described with the types that support them.

The implementation adds two special read-only attributes to class instance methods: `m.im_self` is the object on which the method operates, and `m.im_func` is the function implementing the method. Calling `m(arg-1, arg-2, ..., arg-n)` is completely equivalent to calling `m.im_func(m.im_self, arg-1, arg-2, ..., arg-n)`.

See the *Python Reference Manual* for more information.

Code Objects

Code objects are used by the implementation to represent “pseudo-compiled” executable Python code such as a function body. They differ from function objects because they don't contain a reference to their global execution environment. Code objects are returned by the built-in `compile()` function and can be extracted from function objects through their `func_code` attribute.

A code object can be executed or evaluated by passing it (instead of a source string) to the `exec` statement or the built-in `eval()` function.

See the *Python Reference Manual* for more information.

Type Objects

Type objects represent the various object types. An object's type is accessed by the built-in function `type()`. There are no special operations on types. The standard module `types` defines names for all standard built-in types.

Types are written like this: `<type 'int'>`.

The Null Object

This object is returned by functions that don't explicitly return a value. It supports no special operations. There is exactly one null object, named `None` (a built-in name).

It is written as `None`.

The Ellipsis Object

This object is used by extended slice notation (see the *Python Reference Manual*). It supports no special operations. There is exactly one ellipsis object, named `Ellipsis` (a built-in name).

It is written as `Ellipsis`.

File Objects

File objects are implemented using C's `stdio` package and can be created with the built-in function `open()` described in section 2.3, "Built-in Functions." They are also returned by some other built-in functions and methods, e.g., `posix.popen()` and `posix.fdopen()` and the `makefile()` method of socket objects.

When a file operation fails for an I/O-related reason, the exception `IOError` is raised. This includes situations where the operation is not defined for some reason, like `seek()` on a tty device or writing a file opened for reading.

Files have the following methods:

close()

Close the file. A closed file cannot be read or written anymore.

flush()

Flush the internal buffer, like `stdio`'s `fflush()`.

isatty()

Return 1 if the file is connected to a tty(-like) device, else 0.

fileno()

Return the integer "file descriptor" that is used by the underlying implementation to request I/O operations from the operating system. This can be useful for other, lower level interfaces that use file descriptors, e.g. module `fcntl` or `os.read()` and friends.

read([size])

Read at most *size* bytes from the file (less if the read hits EOF before obtaining *size* bytes). If the *size* argument is negative or omitted, read all data until EOF is reached. The bytes are returned as a string object. An empty string is returned when EOF is encountered immediately. (For certain files, like ttys, it makes sense to continue reading after an EOF is hit.) Note that this method may call the underlying C function `fread()` more than once in an effort to acquire as close to *size* bytes as possible.

readline([size])

Read one entire line from the file. A trailing newline character is kept in the string⁷ (but may be absent when a file ends with an incomplete line). If the *size* argument is present and non-negative, it is a maximum byte count (including the trailing newline) and an incomplete line may be returned. An empty string is returned when EOF is hit immediately. Note: Unlike `stdio`'s `fgets()`, the returned string contains null characters (`'\0'`) if they occurred in the input.

readlines([sizehint])

Read until EOF using `readline()` and return a list containing the lines thus read. If the optional *sizehint* argument is present, instead of reading up to EOF, whole lines totalling approximately *sizehint* bytes (possibly after rounding up to an internal buffer size) are read.

seek(offset[, whence])

Set the file's current position, like `stdio`'s `fseek()`. The *whence* argument is optional and defaults to 0 (absolute file positioning); other values are 1 (seek relative to the current position) and 2 (seek relative to the file's end). There is no return value.

tell()

Return the file's current position, like `stdio`'s `ftell()`.

truncate([size])

Truncate the file's size. If the optional *size* argument present, the file is truncated to (at most) that size. The *size* defaults to the current position. Availability of this function depends on the operating system version (for example, not all UNIX versions support this operation).

write(str)

⁷The advantage of leaving the newline on is that an empty string can be returned to mean EOF without being ambiguous. Another advantage is that (in cases where it might matter, e.g. if you want to make an exact copy of a file while scanning its lines) you can tell whether the last line of a file ended in a newline or not (yes this happens!).

Write a string to the file. There is no return value. Note: Due to buffering, the string may not actually show up in the file until the `flush()` or `close()` method is called.

writelines(*list*)

Write a list of strings to the file. There is no return value. (The name is intended to match `readlines()`; `writelines()` does not add line separators.)

File objects also offer the following attributes:

closed

Boolean indicating the current state of the file object. This is a read-only attribute; the `close()` method changes the value.

mode

The I/O mode for the file. If the file was created using the `open()` built-in function, this will be the value of the *mode* parameter. This is a read-only attribute.

name

If the file object was created using `open()`, the name of the file. Otherwise, some string that indicates the source of the file object, of the form '< . . . >'. This is a read-only attribute.

softspace

Boolean that indicates whether a space character needs to be printed before another value when using the `print` statement. Classes that are trying to simulate a file object should also have a writable `softspace` attribute, which should be initialized to zero. This will be automatic for classes implemented in Python; types implemented in C will have to provide a writable `softspace` attribute.

Internal Objects

See the *Python Reference Manual* for this information. It describes code objects, stack frame objects, traceback objects, and slice objects.

2.1.8 Special Attributes

The implementation adds a few special read-only attributes to several object types, where they are relevant:

__dict__

A dictionary of some sort used to store an object's (writable) attributes.

__methods__

List of the methods of many built-in object types, e.g., `[].__methods__` yields `['append', 'count', 'index', 'insert', 'pop', 'remove', 'reverse', 'sort']`.

__members__

Similar to `__methods__`, but lists data attributes.

__class__

The class to which a class instance belongs.

__bases__

The tuple of base classes of a class object.

2.2 Built-in Exceptions

Exceptions can be class objects or string objects. While traditionally, most exceptions have been string objects, in Python 1.5, all standard exceptions have been converted to class objects, and users are encouraged to do the same. The

source code for those exceptions is present in the standard library module `exceptions`; this module never needs to be imported explicitly.

Two distinct string objects with the same value are considered different exceptions. This is done to force programmers to use exception names rather than their string value when specifying exception handlers. The string value of all built-in exceptions is their name, but this is not a requirement for user-defined exceptions or exceptions defined by library modules.

For class exceptions, in a `try` statement with an `except` clause that mentions a particular class, that clause also handles any exception classes derived from that class (but not exception classes from which *it* is derived). Two exception classes that are not related via subclassing are never equivalent, even if they have the same name.

The built-in exceptions listed below can be generated by the interpreter or built-in functions. Except where mentioned, they have an “associated value” indicating the detailed cause of the error. This may be a string or a tuple containing several items of information (e.g., an error code and a string explaining the code). The associated value is the second argument to the `raise` statement. For string exceptions, the associated value itself will be stored in the variable named as the second argument of the `except` clause (if any). For class exceptions, that variable receives the exception instance. If the exception class is derived from the standard root class `Exception`, the associated value is present as the exception instance’s `args` attribute, and possibly on other attributes as well.

User code can raise built-in exceptions. This can be used to test an exception handler or to report an error condition “just like” the situation in which the interpreter raises the same exception; but beware that there is nothing to prevent user code from raising an inappropriate error.

The following exceptions are only used as base classes for other exceptions.

Exception

The root class for exceptions. All built-in exceptions are derived from this class. All user-defined exceptions should also be derived from this class, but this is not (yet) enforced. The `str()` function, when applied to an instance of this class (or most derived classes) returns the string value of the argument or arguments, or an empty string if no arguments were given to the constructor. When used as a sequence, this accesses the arguments given to the constructor (handy for backward compatibility with old code). The arguments are also available on the instance’s `args` attribute, as a tuple.

StandardError

The base class for all built-in exceptions except `SystemExit`. `StandardError` itself is derived from the root class `Exception`.

ArithmeticError

The base class for those built-in exceptions that are raised for various arithmetic errors: `OverflowError`, `ZeroDivisionError`, `FloatingPointError`.

LookupError

The base class for the exceptions that are raised when a key or index used on a mapping or sequence is invalid: `IndexError`, `KeyError`.

EnvironmentError

The base class for exceptions that can occur outside the Python system: `IOError`, `OSError`. When exceptions of this type are created with a 2-tuple, the first item is available on the instance’s `errno` attribute (it is assumed to be an error number), and the second item is available on the `strerror` attribute (it is usually the associated error message). The tuple itself is also available on the `args` attribute. New in version 1.5.2.

When an `EnvironmentError` exception is instantiated with a 3-tuple, the first two items are available as above, while the third item is available on the `filename` attribute. However, for backwards compatibility, the `args` attribute contains only a 2-tuple of the first two constructor arguments.

The `filename` attribute is `None` when this exception is created with other than 3 arguments. The `errno` and `strerror` attributes are also `None` when the instance was created with other than 2 or 3 arguments. In this last case, `args` contains the verbatim constructor arguments as a tuple.

The following exceptions are the exceptions that are actually raised. They are class objects, except when the `-X` option

is used to revert back to string-based standard exceptions.

AssertionError

Raised when an `assert` statement fails.

AttributeError

Raised when an attribute reference or assignment fails. (When an object does not support attribute references or attribute assignments at all, `TypeError` is raised.)

EOFError

Raised when one of the built-in functions (`input()` or `raw_input()`) hits an end-of-file condition (EOF) without reading any data. (N.B.: the `read()` and `readline()` methods of file objects return an empty string when they hit EOF.)

FloatingPointError

Raised when a floating point operation fails. This exception is always defined, but can only be raised when Python is configured with the `--with-fpectl` option, or the `WANT_SIGFPE_HANDLER` symbol is defined in the 'config.h' file.

IOError

Raised when an I/O operation (such as a `print` statement, the built-in `open()` function or a method of a file object) fails for an I/O-related reason, e.g., "file not found" or "disk full".

This class is derived from `EnvironmentError`. See the discussion above for more information on exception instance attributes.

ImportError

Raised when an `import` statement fails to find the module definition or when a `from ... import` fails to find a name that is to be imported.

IndexError

Raised when a sequence subscript is out of range. (Slice indices are silently truncated to fall in the allowed range; if an index is not a plain integer, `TypeError` is raised.)

KeyError

Raised when a mapping (dictionary) key is not found in the set of existing keys.

KeyboardInterrupt

Raised when the user hits the interrupt key (normally `Control-C` or `DEL`). During execution, a check for interrupts is made regularly. Interrupts typed when a built-in function `input()` or `raw_input()` is waiting for input also raise this exception.

MemoryError

Raised when an operation runs out of memory but the situation may still be rescued (by deleting some objects). The associated value is a string indicating what kind of (internal) operation ran out of memory. Note that because of the underlying memory management architecture (C's `malloc()` function), the interpreter may not always be able to completely recover from this situation; it nevertheless raises an exception so that a stack traceback can be printed, in case a run-away program was the cause.

NameError

Raised when a local or global name is not found. This applies only to unqualified names. The associated value is the name that could not be found.

NotImplementedError

This exception is derived from `RuntimeError`. In user defined base classes, abstract methods should raise this exception when they require derived classes to override the method. New in version 1.5.2.

OSError

This class is derived from `EnvironmentError` and is used primarily as the `os` module's `os.error` exception. See `EnvironmentError` above for a description of the possible associated values. New in version 1.5.2.

OverflowError

Raised when the result of an arithmetic operation is too large to be represented. This cannot occur for long integers (which would rather raise `MemoryError` than give up). Because of the lack of standardization of floating point exception handling in C, most floating point operations also aren't checked. For plain integers, all operations that can overflow are checked except left shift, where typical applications prefer to drop bits than raise an exception.

RuntimeError

Raised when an error is detected that doesn't fall in any of the other categories. The associated value is a string indicating what precisely went wrong. (This exception is mostly a relic from a previous version of the interpreter; it is not used very much any more.)

SyntaxError

Raised when the parser encounters a syntax error. This may occur in an `import` statement, in an `exec` statement, in a call to the built-in function `eval()` or `input()`, or when reading the initial script or standard input (also interactively).

When class exceptions are used, instances of this class have attributes `filename`, `lineno`, `offset` and `text` for easier access to the details; for string exceptions, the associated value is usually a tuple of the form `(message, (filename, lineno, offset, text))`. For class exceptions, `str()` returns only the message.

SystemError

Raised when the interpreter finds an internal error, but the situation does not look so serious to cause it to abandon all hope. The associated value is a string indicating what went wrong (in low-level terms).

You should report this to the author or maintainer of your Python interpreter. Be sure to report the version string of the Python interpreter (`sys.version`; it is also printed at the start of an interactive Python session), the exact error message (the exception's associated value) and if possible the source of the program that triggered the error.

SystemExit

This exception is raised by the `sys.exit()` function. When it is not handled, the Python interpreter exits; no stack traceback is printed. If the associated value is a plain integer, it specifies the system exit status (passed to C's `exit()` function); if it is `None`, the exit status is zero; if it has another type (such as a string), the object's value is printed and the exit status is one.

Instances have an attribute `code` which is set to the proposed exit status or error message (defaulting to `None`). Also, this exception derives directly from `Exception` and not `StandardError`, since it is not technically an error.

A call to `sys.exit()` is translated into an exception so that clean-up handlers (`finally` clauses of `try` statements) can be executed, and so that a debugger can execute a script without running the risk of losing control. The `os._exit()` function can be used if it is absolutely positively necessary to exit immediately (e.g., after a `fork()` in the child process).

TypeError

Raised when a built-in operation or function is applied to an object of inappropriate type. The associated value is a string giving details about the type mismatch.

UnboundLocalError

Raised when a reference is made to a local variable in a function or method, but no value has been bound to that variable. This is a subclass of `NameError`. New in version 1.6.

UnicodeError

Raised when a Unicode-related encoding or decoding error occurs. It is a subclass of `ValueError`. New in version 1.6.

ValueError

Raised when a built-in operation or function receives an argument that has the right type but an inappropriate value, and the situation is not described by a more precise exception such as `IndexError`.

WindowsError

Raised when a Windows-specific error occurs or when the error number does not correspond to an `errno` value. The `errno` and `strerror` values are created from the return values of the `GetLastError()` and `FormatMessage()` functions from the Windows Platform API. This is a subclass of `OSError`. New in version 1.6.

ZeroDivisionError

Raised when the second argument of a division or modulo operation is zero. The associated value is a string indicating the type of the operands and the operation.

2.3 Built-in Functions

The Python interpreter has a number of functions built into it that are always available. They are listed here in alphabetical order.

`__import__(name[, globals[, locals[, fromlist]]])`

This function is invoked by the `import` statement. It mainly exists so that you can replace it with another function that has a compatible interface, in order to change the semantics of the `import` statement. For examples of why and how you would do this, see the standard library modules `ihooks` and `rexec`. See also the built-in module `imp`, which defines some useful operations out of which you can build your own `__import__()` function.

For example, the statement `import spam` results in the following call: `__import__('spam', globals(), locals(), [])`; the statement `from spam.ham import eggs` results in `__import__('spam.ham', globals(), locals(), ['eggs'])`. Note that even though `locals()` and `['eggs']` are passed in as arguments, the `__import__()` function does not set the local variable named `eggs`; this is done by subsequent code that is generated for the `import` statement. (In fact, the standard implementation does not use its `locals` argument at all, and uses its `globals` only to determine the package context of the `import` statement.)

When the `name` variable is of the form `package.module`, normally, the top-level package (the name up till the first dot) is returned, *not* the module named by `name`. However, when a non-empty `fromlist` argument is given, the module named by `name` is returned. This is done for compatibility with the bytecode generated for the different kinds of import statement; when using `import spam.ham.eggs`, the top-level package `spam` must be placed in the importing namespace, but when using `from spam.ham import eggs`, the `spam.ham` subpackage must be used to find the `eggs` variable. As a workaround for this behavior, use `getattr()` to extract the desired components. For example, you could define the following helper:

```
import string

def my_import(name):
    mod = __import__(name)
    components = string.split(name, '.')
    for comp in components[1:]:
        mod = getattr(mod, comp)
    return mod
```

`abs(x)`

Return the absolute value of a number. The argument may be a plain or long integer or a floating point number. If the argument is a complex number, its magnitude is returned.

`apply(function, args[, keywords])`

The `function` argument must be a callable object (a user-defined or built-in function or method, or a class object) and the `args` argument must be a sequence (if it is not a tuple, the sequence is first converted to a tuple). The `function` is called with `args` as the argument list; the number of arguments is the length of the tuple. (This is different from just calling `func(args)`, since in that case there is always exactly one argument.) If the optional

keywords argument is present, it must be a dictionary whose keys are strings. It specifies keyword arguments to be added to the end of the the argument list.

buffer(*object*[, *offset*[, *size*]])

The *object* argument must be an object that supports the buffer call interface (such as strings, arrays, and buffers). A new buffer object will be created which references the *object* argument. The buffer object will be a slice from the beginning of *object* (or from the specified *offset*). The slice will extend to the end of *object* (or will have a length given by the *size* argument).

callable(*object*)

Return true if the *object* argument appears callable, false if not. If this returns true, it is still possible that a call fails, but if it is false, calling *object* will never succeed. Note that classes are callable (calling a class returns a new instance); class instances are callable if they have a `__call__()` method.

chr(*i*)

Return a string of one character whose ASCII code is the integer *i*, e.g., `chr(97)` returns the string 'a'. This is the inverse of `ord()`. The argument must be in the range [0..255], inclusive; `ValueError` will be raised if *i* is outside that range.

cmp(*x*, *y*)

Compare the two objects *x* and *y* and return an integer according to the outcome. The return value is negative if $x < y$, zero if $x == y$ and strictly positive if $x > y$.

coerce(*x*, *y*)

Return a tuple consisting of the two numeric arguments converted to a common type, using the same rules as used by arithmetic operations.

compile(*string*, *filename*, *kind*)

Compile the *string* into a code object. Code objects can be executed by an `exec` statement or evaluated by a call to `eval()`. The *filename* argument should give the file from which the code was read; pass e.g. '<string>' if it wasn't read from a file. The *kind* argument specifies what kind of code must be compiled; it can be 'exec' if *string* consists of a sequence of statements, 'eval' if it consists of a single expression, or 'single' if it consists of a single interactive statement (in the latter case, expression statements that evaluate to something else than `None` will printed).

complex(*real*[, *imag*])

Create a complex number with the value $real + imag*j$ or convert a string or number to a complex number. Each argument may be any numeric type (including complex). If *imag* is omitted, it defaults to zero and the function serves as a numeric conversion function like `int()`, `long()` and `float()`; in this case it also accepts a string argument which should be a valid complex number.

delattr(*object*, *name*)

This is a relative of `setattr()`. The arguments are an object and a string. The string must be the name of one of the object's attributes. The function deletes the named attribute, provided the object allows it. For example, `delattr(x, 'foobar')` is equivalent to `del x.foobar`.

dir([*object*])

Without arguments, return the list of names in the current local symbol table. With an argument, attempts to return a list of valid attribute for that object. This information is gleaned from the object's `__dict__`, `__methods__` and `__members__` attributes, if defined. The list is not necessarily complete; e.g., for classes, attributes defined in base classes are not included, and for class instances, methods are not included. The resulting list is sorted alphabetically. For example:

```

>>> import sys
>>> dir()
['sys']
>>> dir(sys)
['argv', 'exit', 'modules', 'path', 'stderr', 'stdin', 'stdout']
>>>

```

divmod(*a*, *b*)

Take two numbers as arguments and return a pair of numbers consisting of their quotient and remainder when using long division. With mixed operand types, the rules for binary arithmetic operators apply. For plain and long integers, the result is the same as $(a / b, a \% b)$. For floating point numbers the result is $(q, a \% b)$, where q is usually `math.floor(a / b)` but may be 1 less than that. In any case $q * b + a \% b$ is very close to a , if $a \% b$ is non-zero it has the same sign as b , and $0 \leq \text{abs}(a \% b) < \text{abs}(b)$.

eval(*expression*[, *globals*[, *locals*]])

The arguments are a string and two optional dictionaries. The *expression* argument is parsed and evaluated as a Python expression (technically speaking, a condition list) using the *globals* and *locals* dictionaries as global and local name space. If the *locals* dictionary is omitted it defaults to the *globals* dictionary. If both dictionaries are omitted, the expression is executed in the environment where `eval` is called. The return value is the result of the evaluated expression. Syntax errors are reported as exceptions. Example:

```

>>> x = 1
>>> print eval('x+1')
2

```

This function can also be used to execute arbitrary code objects (e.g. created by `compile()`). In this case pass a code object instead of a string. The code object must have been compiled passing 'eval' to the *kind* argument.

Hints: dynamic execution of statements is supported by the `exec` statement. Execution of statements from a file is supported by the `execfile()` function. The `globals()` and `locals()` functions returns the current global and local dictionary, respectively, which may be useful to pass around for use by `eval()` or `execfile()`.

execfile(*file*[, *globals*[, *locals*]])

This function is similar to the `exec` statement, but parses a file instead of a string. It is different from the `import` statement in that it does not use the module administration — it reads the file unconditionally and does not create a new module.⁸

The arguments are a file name and two optional dictionaries. The file is parsed and evaluated as a sequence of Python statements (similarly to a module) using the *globals* and *locals* dictionaries as global and local name space. If the *locals* dictionary is omitted it defaults to the *globals* dictionary. If both dictionaries are omitted, the expression is executed in the environment where `execfile()` is called. The return value is `None`.

filter(*function*, *list*)

Construct a list from those elements of *list* for which *function* returns true. If *list* is a string or a tuple, the result also has that type; otherwise it is always a list. If *function* is `None`, the identity function is assumed, i.e. all elements of *list* that are false (zero or empty) are removed.

float(*x*)

Convert a string or a number to floating point. If the argument is a string, it must contain a possibly signed decimal or floating point number, possibly embedded in whitespace; this behaves identical to `string.atof(x)`. Otherwise, the argument may be a plain or long integer or a floating point number, and a floating point number with the same value (within Python's floating point precision) is returned.

Note: When passing in a string, values for NaN and Infinity may be returned, depending on the underlying C

⁸It is used relatively rarely so does not warrant being made into a statement.

library. The specific set of strings accepted which cause these values to be returned depends entirely on the C library and is known to vary.

getattr(*object*, *name*[, *default*])

Return the value of the named attributed of *object*. *name* must be a string. If the string is the name of one of the object's attributes, the result is the value of that attribute. For example, `getattr(x, 'foobar')` is equivalent to `x.foobar`. If the named attribute does not exist, *default* is returned if provided, otherwise `AttributeError` is raised.

globals()

Return a dictionary representing the current global symbol table. This is always the dictionary of the current module (inside a function or method, this is the module where it is defined, not the module from which it is called).

hasattr(*object*, *name*)

The arguments are an object and a string. The result is 1 if the string is the name of one of the object's attributes, 0 if not. (This is implemented by calling `getattr(object, name)` and seeing whether it raises an exception or not.)

hash(*object*)

Return the hash value of the object (if it has one). Hash values are integers. They are used to quickly compare dictionary keys during a dictionary lookup. Numeric values that compare equal have the same hash value (even if they are of different types, e.g. 1 and 1.0).

hex(*x*)

Convert an integer number (of any size) to a hexadecimal string. The result is a valid Python expression. Note: this always yields an unsigned literal, e.g. on a 32-bit machine, `hex(-1)` yields `'0xffffffff'`. When evaluated on a machine with the same word size, this literal is evaluated as -1; at a different word size, it may turn up as a large positive number or raise an `OverflowError` exception.

id(*object*)

Return the 'identity' of an object. This is an integer which is guaranteed to be unique and constant for this object during its lifetime. (Two objects whose lifetimes are disjunct may have the same `id()` value.) (Implementation note: this is the address of the object.)

input([*prompt*])

Equivalent to `eval(raw_input(prompt))`.

int(*x*[, *radix*])

Convert a string or number to a plain integer. If the argument is a string, it must contain a possibly signed decimal number representable as a Python integer, possibly embedded in whitespace; this behaves identical to `string.atoi(x[, radix])`. The *radix* parameter gives the base for the conversion and may be any integer in the range [2, 36]. If *radix* is specified and *x* is not a string, `TypeError` is raised. Otherwise, the argument may be a plain or long integer or a floating point number. Conversion of floating point numbers to integers is defined by the C semantics; normally the conversion truncates towards zero.⁹

intern(*string*)

Enter *string* in the table of "interned" strings and return the interned string – which is *string* itself or a copy. Interning strings is useful to gain a little performance on dictionary lookup – if the keys in a dictionary are interned, and the lookup key is interned, the key comparisons (after hashing) can be done by a pointer compare instead of a string compare. Normally, the names used in Python programs are automatically interned, and the dictionaries used to hold module, class or instance attributes have interned keys. Interned strings are immortal (i.e. never get garbage collected).

isinstance(*object*, *class*)

Return true if the *object* argument is an instance of the *class* argument, or of a (direct or indirect) subclass thereof. Also return true if *class* is a type object and *object* is an object of that type. If *object* is not a class instance or a object of the given type, the function always returns false. If *class* is neither a class object nor a

⁹This is ugly — the language definition should require truncation towards zero.

type object, a `TypeError` exception is raised.

issubclass(*class1*, *class2*)

Return true if *class1* is a subclass (direct or indirect) of *class2*. A class is considered a subclass of itself. If either argument is not a class object, a `TypeError` exception is raised.

len(*s*)

Return the length (the number of items) of an object. The argument may be a sequence (string, tuple or list) or a mapping (dictionary).

list(*sequence*)

Return a list whose items are the same and in the same order as *sequence*'s items. If *sequence* is already a list, a copy is made and returned, similar to *sequence*[:]. For instance, `list('abc')` returns `['a', 'b', 'c']` and `list((1, 2, 3))` returns `[1, 2, 3]`.

locals()

Return a dictionary representing the current local symbol table. **Warning:** the contents of this dictionary should not be modified; changes may not affect the values of local variables used by the interpreter.

long(*x*)

Convert a string or number to a long integer. If the argument is a string, it must contain a possibly signed decimal number of arbitrary size, possibly embedded in whitespace; this behaves identical to `string.atol(x)`. Otherwise, the argument may be a plain or long integer or a floating point number, and a long integer with the same value is returned. Conversion of floating point numbers to integers is defined by the C semantics; see the description of `int()`.

map(*function*, *list*, ...)

Apply *function* to every item of *list* and return a list of the results. If additional *list* arguments are passed, *function* must take that many arguments and is applied to the items of all lists in parallel; if a list is shorter than another it is assumed to be extended with `None` items. If *function* is `None`, the identity function is assumed; if there are multiple list arguments, `map()` returns a list consisting of tuples containing the corresponding items from all lists (i.e. a kind of transpose operation). The *list* arguments may be any kind of sequence; the result is always a list.

max(*s*[, *args...*])

With a single argument *s*, return the largest item of a non-empty sequence (e.g., a string, tuple or list). With more than one argument, return the largest of the arguments.

min(*s*[, *args...*])

With a single argument *s*, return the smallest item of a non-empty sequence (e.g., a string, tuple or list). With more than one argument, return the smallest of the arguments.

oct(*x*)

Convert an integer number (of any size) to an octal string. The result is a valid Python expression. Note: this always yields an unsigned literal, e.g. on a 32-bit machine, `oct(-1)` yields `'037777777777'`. When evaluated on a machine with the same word size, this literal is evaluated as `-1`; at a different word size, it may turn up as a large positive number or raise an `OverflowError` exception.

open(*filename*[, *mode*[, *bufsize*]])

Return a new file object (described earlier under Built-in Types). The first two arguments are the same as for `stdio's fopen()`: *filename* is the file name to be opened, *mode* indicates how the file is to be opened: `'r'` for reading, `'w'` for writing (truncating an existing file), and `'a'` opens it for appending (which on *some* UNIX systems means that *all* writes append to the end of the file, regardless of the current seek position).

Modes `'r+'`, `'w+'` and `'a+'` open the file for updating (note that `'w+'` truncates the file). Append `'b'` to the mode to open the file in binary mode, on systems that differentiate between binary and text files (else it is ignored). If the file cannot be opened, `IOError` is raised.

If *mode* is omitted, it defaults to `'r'`. When opening a binary file, you should append `'b'` to the *mode* value for improved portability. (It's useful even on systems which don't treat binary and text files differently, where it serves as documentation.) The optional *bufsize* argument specifies the file's desired buffer size: `0` means

unbuffered, 1 means line buffered, any other positive value means use a buffer of (approximately) that size. A negative *bufsize* means to use the system default, which is usually line buffered for for tty devices and fully buffered for other files. If omitted, the system default is used.¹⁰

ord(*c*)

Return the ASCII value of a string of one character or a Unicode character. E.g., `ord('a')` returns the integer 97, `ord(u' u2020')` returns 8224. This is the inverse of `chr()` for strings and of `unichr()` for Unicode characters.

pow(*x*, *y*[, *z*])

Return *x* to the power *y*; if *z* is present, return *x* to the power *y*, modulo *z* (computed more efficiently than `pow(x, y) % z`). The arguments must have numeric types. With mixed operand types, the rules for binary arithmetic operators apply. The effective operand type is also the type of the result; if the result is not expressible in this type, the function raises an exception; e.g., `pow(2, -1)` or `pow(2, 35000)` is not allowed.

range([*start*,] *stop*[, *step*])

This is a versatile function to create lists containing arithmetic progressions. It is most often used in `for` loops. The arguments must be plain integers. If the *step* argument is omitted, it defaults to 1. If the *start* argument is omitted, it defaults to 0. The full form returns a list of plain integers [*start*, *start* + *step*, *start* + 2 * *step*, ...]. If *step* is positive, the last element is the largest *start* + *i* * *step* less than *stop*; if *step* is negative, the last element is the largest *start* + *i* * *step* greater than *stop*. *step* must not be zero (or else `ValueError` is raised). Example:

```
>>> range(10)
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
>>> range(1, 11)
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
>>> range(0, 30, 5)
[0, 5, 10, 15, 20, 25]
>>> range(0, 10, 3)
[0, 3, 6, 9]
>>> range(0, -10, -1)
[0, -1, -2, -3, -4, -5, -6, -7, -8, -9]
>>> range(0)
[]
>>> range(1, 0)
[]
>>>
```

raw_input([*prompt*])

If the *prompt* argument is present, it is written to standard output without a trailing newline. The function then reads a line from input, converts it to a string (stripping a trailing newline), and returns that. When EOF is read, `EOFError` is raised. Example:

```
>>> s = raw_input('--> ')
--> Monty Python's Flying Circus
>>> s
"Monty Python's Flying Circus"
>>>
```

If the `readline` module was loaded, then `raw_input()` will use it to provide elaborate line editing and history features.

reduce(*function*, *sequence*[, *initializer*])

¹⁰Specifying a buffer size currently has no effect on systems that don't have `setvbuf()`. The interface to specify the buffer size is not done using a method that calls `setvbuf()`, because that may dump core when called after any I/O has been performed, and there's no reliable way to determine whether this is the case.

Apply *function* of two arguments cumulatively to the items of *sequence*, from left to right, so as to reduce the sequence to a single value. For example, `reduce(lambda x, y: x+y, [1, 2, 3, 4, 5])` calculates `((((1+2)+3)+4)+5)`. If the optional *initializer* is present, it is placed before the items of the sequence in the calculation, and serves as a default when the sequence is empty.

reload(*module*)

Re-parse and re-initialize an already imported *module*. The argument must be a module object, so it must have been successfully imported before. This is useful if you have edited the module source file using an external editor and want to try out the new version without leaving the Python interpreter. The return value is the module object (i.e. the same as the *module* argument).

There are a number of caveats:

If a module is syntactically correct but its initialization fails, the first `import` statement for it does not bind its name locally, but does store a (partially initialized) module object in `sys.modules`. To reload the module you must first `import` it again (this will bind the name to the partially initialized module object) before you can `reload()` it.

When a module is reloaded, its dictionary (containing the module's global variables) is retained. Redefinitions of names will override the old definitions, so this is generally not a problem. If the new version of a module does not define a name that was defined by the old version, the old definition remains. This feature can be used to the module's advantage if it maintains a global table or cache of objects — with a `try` statement it can test for the table's presence and skip its initialization if desired.

It is legal though generally not very useful to reload built-in or dynamically loaded modules, except for `sys`, `__main__` and `__builtin__`. In certain cases, however, extension modules are not designed to be initialized more than once, and may fail in arbitrary ways when reloaded.

If a module imports objects from another module using `from... import...`, calling `reload()` for the other module does not redefine the objects imported from it — one way around this is to re-execute the `from` statement, another is to use `import` and qualified names (*module.name*) instead.

If a module instantiates instances of a class, reloading the module that defines the class does not affect the method definitions of the instances — they continue to use the old class definition. The same is true for derived classes.

repr(*object*)

Return a string containing a printable representation of an object. This is the same value yielded by conversions (reverse quotes). It is sometimes useful to be able to access this operation as an ordinary function. For many types, this function makes an attempt to return a string that would yield an object with the same value when passed to `eval()`.

round(*x*[, *n*])

Return the floating point value *x* rounded to *n* digits after the decimal point. If *n* is omitted, it defaults to zero. The result is a floating point number. Values are rounded to the closest multiple of 10 to the power minus *n*; if two multiples are equally close, rounding is done away from 0 (so e.g. `round(0.5)` is `1.0` and `round(-0.5)` is `-1.0`).

setattr(*object*, *name*, *value*)

This is the counterpart of `getattr()`. The arguments are an object, a string and an arbitrary value. The string may name an existing attribute or a new attribute. The function assigns the value to the attribute, provided the object allows it. For example, `setattr(x, 'foobar', 123)` is equivalent to `x.foobar = 123`.

slice([*start*,] *stop*[, *step*])

Return a slice object representing the set of indices specified by `range(start, stop, step)`. The *start* and *step* arguments default to `None`. Slice objects have read-only data attributes *start*, *stop* and *step* which merely return the argument values (or their default). They have no other explicit functionality; however they are used by Numerical Python and other third party extensions. Slice objects are also generated when extended indexing syntax is used, e.g. for `'a[start:stop:step]'` or `'a[start:stop, i]'`.

str(*object*)

Return a string containing a nicely printable representation of an object. For strings, this returns the string

itself. The difference with `repr(object)` is that `str(object)` does not always attempt to return a string that is acceptable to `eval()`; its goal is to return a printable string.

tuple(*sequence*)

Return a tuple whose items are the same and in the same order as *sequence*'s items. If *sequence* is already a tuple, it is returned unchanged. For instance, `tuple('abc')` returns `('a', 'b', 'c')` and `tuple([1, 2, 3])` returns `(1, 2, 3)`.

type(*object*)

Return the type of an *object*. The return value is a type object. The standard module `types` defines names for all built-in types. For instance:

```
>>> import types
>>> if type(x) == types.StringType: print "It's a string"
```

unichr(*i*)

Return the Unicode string of one character whose Unicode code is the integer *i*, e.g., `unichr(97)` returns the string `u'a'`. This is the inverse of `ord()` for Unicode strings. The argument must be in the range `[0..65535]`, inclusive. `ValueError` is raised otherwise. New in version 1.6.

unicode(*string*[, *encoding*='utf-8'[, *errors*='strict']])

Decodes *string* using the codec for *encoding*. Error handling is done according to *errors*. The default behavior is to decode UTF-8 in strict mode, meaning that encoding errors raise `ValueError`. New in version 1.6.

vars([*object*])

Without arguments, return a dictionary corresponding to the current local symbol table. With a module, class or class instance object as argument (or anything else that has a `__dict__` attribute), returns a dictionary corresponding to the object's symbol table. The returned dictionary should not be modified: the effects on the corresponding symbol table are undefined.¹¹

xrange([*start*,] *stop*[, *step*])

This function is very similar to `range()`, but returns an "xrange object" instead of a list. This is an opaque sequence type which yields the same values as the corresponding list, without actually storing them all simultaneously. The advantage of `xrange()` over `range()` is minimal (since `xrange()` still has to create the values when asked for them) except when a very large range is used on a memory-starved machine (e.g. MS-DOS) or when all of the range's elements are never used (e.g. when the loop is usually terminated with `break`).

¹¹In the current implementation, local variable bindings cannot normally be affected this way, but variables retrieved from other scopes (e.g. modules) can be. This may change.

Python Services

The modules described in this chapter provide a wide range of services related to the Python interpreter and its interaction with its environment. Here's an overview:

<code>sys</code>	Access system-specific parameters and functions.
<code>types</code>	Names for all built-in types.
<code>UserDict</code>	Class wrapper for dictionary objects.
<code>UserList</code>	Class wrapper for list objects.
<code>UserString</code>	Class wrapper for string objects.
<code>operator</code>	All Python's standard operators as built-in functions.
<code>traceback</code>	Print or retrieve a stack traceback.
<code>linecache</code>	This module provides random access to individual lines from text files.
<code>pickle</code>	Convert Python objects to streams of bytes and back.
<code>cPickle</code>	Faster version of <code>pickle</code> , but not subclassable.
<code>copy_reg</code>	Register <code>pickle</code> support functions.
<code>shelve</code>	Python object persistency.
<code>copy</code>	Shallow and deep copy operations.
<code>marshal</code>	Convert Python objects to streams of bytes and back (with different constraints).
<code>imp</code>	Access the implementation of the <code>import</code> statement.
<code>parser</code>	Access parse trees for Python source code.
<code>symbol</code>	Constants representing internal nodes of the parse tree.
<code>token</code>	Constants representing terminal nodes of the parse tree.
<code>keyword</code>	Test whether a string is a keyword in Python.
<code>tokenize</code>	Lexical scanner for Python source code.
<code>tabnanny</code>	Tool for detecting white space related problems in Python source files in a directory tree.
<code>pyclbr</code>	Supports information extraction for a Python class browser.
<code>code</code>	Base classes for interactive Python interpreters.
<code>codeop</code>	Compile (possibly incomplete) Python code.
<code>pprint</code>	Data pretty printer.
<code>repr</code>	Alternate <code>repr()</code> implementation with size limits.
<code>py_compile</code>	Compile Python source files to byte-code files.
<code>compileall</code>	Tools for byte-compiling all Python source files in a directory tree.
<code>dis</code>	Disassembler.
<code>new</code>	Interface to the creation of runtime implementation objects.
<code>site</code>	A standard way to reference site-specific modules.
<code>user</code>	A standard way to reference user-specific modules.
<code>__builtin__</code>	The set of built-in functions.
<code>__main__</code>	The environment where the top-level script is run.

3.1 `sys` — System-specific parameters and functions

This module provides access to some variables used or maintained by the interpreter and to functions that interact strongly with the interpreter. It is always available.

argv

The list of command line arguments passed to a Python script. `argv[0]` is the script name (it is operating system dependent whether this is a full pathname or not). If the command was executed using the `-c` command line option to the interpreter, `argv[0]` is set to the string `'-c'`. If no script name was passed to the Python interpreter, `argv` has zero length.

builtin_module_names

A tuple of strings giving the names of all modules that are compiled into this Python interpreter. (This information is not available in any other way — `modules.keys()` only lists the imported modules.)

copyright

A string containing the copyright pertaining to the Python interpreter.

dllhandle

Integer specifying the handle of the Python DLL. Availability: Windows.

exc_info()

This function returns a tuple of three values that give information about the exception that is currently being handled. The information returned is specific both to the current thread and to the current stack frame. If the current stack frame is not handling an exception, the information is taken from the calling stack frame, or its caller, and so on until a stack frame is found that is handling an exception. Here, “handling an exception” is defined as “executing or having executed an except clause.” For any stack frame, only information about the most recently handled exception is accessible.

If no exception is being handled anywhere on the stack, a tuple containing three `None` values is returned. Otherwise, the values returned are `(type, value, traceback)`. Their meaning is: `type` gets the exception type of the exception being handled (a string or class object); `value` gets the exception parameter (its *associated value* or the second argument to `raise`, which is always a class instance if the exception type is a class object); `traceback` gets a traceback object (see the Reference Manual) which encapsulates the call stack at the point where the exception originally occurred.

Warning: assigning the `traceback` return value to a local variable in a function that is handling an exception will cause a circular reference. This will prevent anything referenced by a local variable in the same function or by the traceback from being garbage collected. Since most functions don’t need access to the traceback, the best solution is to use something like `type, value = sys.exc_info()[:2]` to extract only the exception type and value. If you do need the traceback, make sure to delete it after use (best done with a `try ... finally` statement) or to call `exc_info()` in a function that does not itself handle an exception.

exc_type

exc_value

exc_traceback

Deprecated since release 1.5. Use `exc_info()` instead.

Since they are global variables, they are not specific to the current thread, so their use is not safe in a multi-threaded program. When no exception is being handled, `exc_type` is set to `None` and the other two are undefined.

exec_prefix

A string giving the site-specific directory prefix where the platform-dependent Python files are installed; by default, this is also `’/usr/local’`. This can be set at build time with the `--exec-prefix` argument to the **configure** script. Specifically, all configuration files (e.g. the `’config.h’` header file) are installed in the directory `exec_prefix + ’/lib/pythonversion/config’`, and shared library modules are installed in `exec_prefix + ’/lib/pythonversion/lib-dynload’`, where `version` is equal to `version[:3]`.

executable

A string giving the name of the executable binary for the Python interpreter, on systems where this makes sense.

exit([arg])

Exit from Python. This is implemented by raising the `SystemExit` exception, so cleanup actions specified by finally clauses of `try` statements are honored, and it is possible to intercept the exit attempt at an outer level. The optional argument *arg* can be an integer giving the exit status (defaulting to zero), or another type of object. If it is an integer, zero is considered “successful termination” and any nonzero value is considered “abnormal termination” by shells and the like. Most systems require it to be in the range 0-127, and produce undefined results otherwise. Some systems have a convention for assigning specific meanings to specific exit codes, but these are generally underdeveloped; Unix programs generally use 2 for command line syntax errors and 1 for all other kind of errors. If another type of object is passed, `None` is equivalent to passing zero, and any other object is printed to `sys.stderr` and results in an exit code of 1. In particular, `sys.exit("some error message")` is a quick way to exit a program when an error occurs.

exitfunc

This value is not actually defined by the module, but can be set by the user (or by a program) to specify a cleanup action at program exit. When set, it should be a parameterless function. This function will be called when the interpreter exits. Note: the exit function is not called when the program is killed by a signal, when a Python fatal internal error is detected, or when `os._exit()` is called.

getrefcount(object)

Return the reference count of the *object*. The count returned is generally one higher than you might expect, because it includes the (temporary) reference as an argument to `getrefcount()`.

hexversion

The version number encoded as a single integer. This is guaranteed to increase with each version, including proper support for non-production releases. For example, to test that the Python interpreter is at least version 1.5.2, use:

```
if sys.hexversion >= 0x010502F0:
    # use some advanced feature
    ...
else:
    # use an alternative implementation or warn the user
    ...
```

This is called ‘hexversion’ since it only really looks meaningful when viewed as the result of passing it to the built-in `hex()` function. The `version_info` value may be used for a more human-friendly encoding of the same information. New in version 1.5.2.

last_type

last_value

last_traceback

These three variables are not always defined; they are set when an exception is not handled and the interpreter prints an error message and a stack traceback. Their intended use is to allow an interactive user to import a debugger module and engage in post-mortem debugging without having to re-execute the command that caused the error. (Typical use is `import pdb; pdb.pm()` to enter the post-mortem debugger; see the chapter “The Python Debugger” for more information.)

The meaning of the variables is the same as that of the return values from `exc_info()` above. (Since there is only one interactive thread, thread-safety is not a concern for these variables, unlike for `exc_type` etc.)

maxint

The largest positive integer supported by Python’s regular integer type. This is at least $2^{31}-1$. The largest negative integer is `-maxint-1` – the asymmetry results from the use of 2’s complement binary arithmetic.

modules

This is a dictionary that maps module names to modules which have already been loaded. This can be manipulated to force reloading of modules and other tricks. Note that removing a module from this dictionary is *not* the same as calling `reload()` on the corresponding module object.

path

A list of strings that specifies the search path for modules. Initialized from the environment variable `$PYTHON-PATH`, or an installation-dependent default.

The first item of this list, `path[0]`, is the directory containing the script that was used to invoke the Python interpreter. If the script directory is not available (e.g. if the interpreter is invoked interactively or if the script is read from standard input), `path[0]` is the empty string, which directs Python to search modules in the current directory first. Notice that the script directory is inserted *before* the entries inserted as a result of `$PYTHON-PATH`.

platform

This string contains a platform identifier, e.g. `'sunos5'` or `'linux1'`. This can be used to append platform-specific components to `path`, for instance.

prefix

A string giving the site-specific directory prefix where the platform independent Python files are installed; by default, this is the string `'/usr/local'`. This can be set at build time with the `--prefix` argument to the `configure` script. The main collection of Python library modules is installed in the directory `prefix + '/lib/pythonversion'` while the platform independent header files (all except `'config.h'`) are stored in `prefix + '/include/pythonversion'`, where `version` is equal to `version[:3]`.

ps1

ps2

Strings specifying the primary and secondary prompt of the interpreter. These are only defined if the interpreter is in interactive mode. Their initial values in this case are `'>>> '` and `'... '`. If a non-string object is assigned to either variable, its `str()` is re-evaluated each time the interpreter prepares to read a new interactive command; this can be used to implement a dynamic prompt.

setcheckinterval (*interval*)

Set the interpreter's "check interval". This integer value determines how often the interpreter checks for periodic things such as thread switches and signal handlers. The default is 10, meaning the check is performed every 10 Python virtual instructions. Setting it to a larger value may increase performance for programs using threads. Setting it to a value `<= 0` checks every virtual instruction, maximizing responsiveness as well as overhead.

setprofile (*profilefunc*)

Set the system's profile function, which allows you to implement a Python source code profiler in Python. See the chapter on the Python Profiler. The system's profile function is called similarly to the system's trace function (see `settrace()`), but it isn't called for each executed line of code (only on call and return and when an exception occurs). Also, its return value is not used, so it can just return `None`.

settrace (*tracefunc*)

Set the system's trace function, which allows you to implement a Python source code debugger in Python. See section "How It Works" in the chapter on the Python Debugger.

stdin

stdout

stderr

File objects corresponding to the interpreter's standard input, output and error streams. `stdin` is used for all interpreter input except for scripts but including calls to `input()` and `raw_input()`. `stdout` is used for the output of `print` and expression statements and for the prompts of `input()` and `raw_input()`. The interpreter's own prompts and (almost all of) its error messages go to `stderr`. `stdout` and `stderr` needn't be built-in file objects: any object is acceptable as long as it has a `write()` method that takes a string argument. (Changing these objects doesn't affect the standard I/O streams of processes executed by `os.popen()`, `os.system()` or the `exec*()` family of functions in the `os` module.)

__stdin__

__stdout__

__stderr__

These objects contain the original values of `stdin`, `stderr` and `stdout` at the start of the program. They are used during finalization, and could be useful to restore the actual files to known working file objects in case

they have been overwritten with a broken object.

tracebacklimit

When this variable is set to an integer value, it determines the maximum number of levels of traceback information printed when an unhandled exception occurs. The default is 1000. When set to 0 or less, all traceback information is suppressed and only the exception type and value are printed.

version

A string containing the version number of the Python interpreter plus additional information on the build number and compiler used. It has a value of the form `'version (#build_number, build_date, build_time) [compiler]'`. The first three characters are used to identify the version in the installation directories (where appropriate on each platform). An example:

```
>>> import sys
>>> sys.version
'1.5.2 (#0 Apr 13 1999, 10:51:12) [MSC 32 bit (Intel)]'
```

version_info

A tuple containing the five components of the version number: *major*, *minor*, *micro*, *releaselevel*, and *serial*. All values except *releaselevel* are integers; the release level is 'alpha', 'beta', 'candidate', or 'final'. The `version_info` value corresponding to the Python version 1.6 is (1, 6, 0, 'final', 0). New in version 1.6.

winver

The version number used to form registry keys on Windows platforms. This is stored as string resource 1000 in the Python DLL. The value is normally the first three characters of `version`. It is provided in the `sys` module for informational purposes; modifying this value has no effect on the registry keys used by Python. Availability: Windows.

3.2 `types` — Names for all built-in types

This module defines names for all object types that are used by the standard Python interpreter, but not for the types defined by various extension modules. It is safe to use `from types import *` — the module does not export any names besides the ones listed here. New names exported by future versions of this module will all end in `'Type'`.

Typical use is for functions that do different things depending on their argument types, like the following:

```
from types import *
def delete(list, item):
    if type(item) is IntType:
        del list[item]
    else:
        list.remove(item)
```

The module defines the following names:

NoneType

The type of None.

TypeType

The type of type objects (such as returned by `type()`).

IntType

The type of integers (e.g. 1).

LongType

The type of long integers (e.g. 1L).

FloatType

The type of floating point numbers (e.g. `1.0`).

ComplexType

The type of complex numbers (e.g. `1.0j`).

StringType

The type of character strings (e.g. `'Spam'`).

UnicodeType

The type of Unicode character strings (e.g. `u'Spam'`).

TupleType

The type of tuples (e.g. `(1, 2, 3, 'Spam')`).

ListType

The type of lists (e.g. `[0, 1, 2, 3]`).

DictType

The type of dictionaries (e.g. `{'Bacon': 1, 'Ham': 0}`).

DictionaryType

An alternate name for `DictType`.

FunctionType

The type of user-defined functions and lambdas.

LambdaType

An alternate name for `FunctionType`.

CodeType

The type for code objects such as returned by `compile()`.

ClassType

The type of user-defined classes.

InstanceType

The type of instances of user-defined classes.

MethodType

The type of methods of user-defined class instances.

UnboundMethodType

An alternate name for `MethodType`.

BuiltinFunctionType

The type of built-in functions like `len()` or `sys.exit()`.

BuiltinMethodType

An alternate name for `BuiltinFunction`.

ModuleType

The type of modules.

FileType

The type of open file objects such as `sys.stdout`.

XRangeType

The type of range objects returned by `xrange()`.

SliceType

The type of objects returned by `slice()`.

EllipsisType

The type of `Ellipsis`.

TracebackType

The type of traceback objects such as found in `sys.exc_traceback`.

FrameType

The type of frame objects such as found in `tb.tb_frame` if `tb` is a traceback object.

BufferType

The type of buffer objects created by the `buffer()` function.

3.3 UserDict — Class wrapper for dictionary objects

This module defines a class that acts as a wrapper around dictionary objects. It is a useful base class for your own dictionary-like classes, which can inherit from them and override existing methods or add new ones. In this way one can add new behaviours to dictionaries.

The `UserDict` module defines the `UserDict` class:

UserDict([*initialdata*])

Return a class instance that simulates a dictionary. The instance's contents are kept in a regular dictionary, which is accessible via the `data` attribute of `UserDict` instances. If *initialdata* is provided, `data` is initialized with its contents; note that a reference to *initialdata* will not be kept, allowing it be used for other purposes.

In addition to supporting the methods and operations of mappings (see section 2.1.6), `UserDict` instances provide the following attribute:

data

A real dictionary used to store the contents of the `UserDict` class.

3.4 UserList — Class wrapper for list objects

This module defines a class that acts as a wrapper around list objects. It is a useful base class for your own list-like classes, which can inherit from them and override existing methods or add new ones. In this way one can add new behaviours to lists.

The `UserList` module defines the `UserList` class:

UserList([*list*])

Return a class instance that simulates a list. The instance's contents are kept in a regular list, which is accessible via the `data` attribute of `UserList` instances. The instance's contents are initially set to a copy of *list*, defaulting to the empty list `[]`. *list* can be either a regular Python list, or an instance of `UserList` (or a subclass).

In addition to supporting the methods and operations of mutable sequences (see section 2.1.5), `UserList` instances provide the following attribute:

data

A real Python list object used to store the contents of the `UserList` class.

3.5 UserString — Class wrapper for string objects

This module defines a class that acts as a wrapper around string objects. It is a useful base class for your own string-like classes, which can inherit from them and override existing methods or add new ones. In this way one can add new behaviours to strings.

The `UserString` module defines the `UserString` class:

UserString([*sequence*])

Return a class instance that simulates a string or a Unicode string object. The instance's content is kept in a regular string or Unicode string object, which is accessible via the `data` attribute of `UserString` instances. The instance's contents are initially set to a copy of *sequence*. *sequence* can be either a regular Python string or Unicode string, an instance of `UserString` (or a subclass) or an arbitrary sequence which can be converted into a string.

In addition to supporting the methods and operations of string or Unicode objects (see section 2.1.5), `UserString` instances provide the following attribute:

data

A real Python string or Unicode object used to store the content of the `UserString` class.

MutableString([*sequence*])

This class is derived from the `UserString` above and redefines strings to be *mutable*. Mutable strings can't be used as dictionary keys, because dictionaries require *immutable* objects as keys. The main intention of this class is to serve as an educational example for inheritance and necessity to remove (override) the `__hash__` method in order to trap attempts to use a mutable object as dictionary key, which would be otherwise very errorprone and hard to track down.

3.6 operator — Standard operators as functions.

The `operator` module exports a set of functions implemented in C corresponding to the intrinsic operators of Python. For example, `operator.add(x, y)` is equivalent to the expression `x+y`. The function names are those used for special class methods; variants without leading and trailing `'__'` are also provided for convenience.

The `operator` module defines the following functions:

add(*a*, *b*)

`__add__`(*a*, *b*)

Return $a + b$, for *a* and *b* numbers.

sub(*a*, *b*)

`__sub__`(*a*, *b*)

Return $a - b$.

mul(*a*, *b*)

`__mul__`(*a*, *b*)

Return $a * b$, for *a* and *b* numbers.

div(*a*, *b*)

`__div__`(*a*, *b*)

Return a / b .

mod(*a*, *b*)

`__mod__`(*a*, *b*)

Return $a \% b$.

neg(*o*)

`__neg__`(*o*)

Return *o* negated.

pos(*o*)

`__pos__`(*o*)

Return *o* positive.

abs(*o*)

`__abs__`(*o*)

Return the absolute value of *o*.

inv(*o*)
__inv__(*o*)
 Return the inverse of *o*.

lshift(*a*, *b*)
__lshift__(*a*, *b*)
 Return *a* shifted left by *b*.

rshift(*a*, *b*)
__rshift__(*a*, *b*)
 Return *a* shifted right by *b*.

and_*(a, b)*
__and__(*a*, *b*)
 Return the bitwise and of *a* and *b*.

or_*(a, b)*
__or__(*a*, *b*)
 Return the bitwise or of *a* and *b*.

xor(*a*, *b*)
__xor__(*a*, *b*)
 Return the bitwise exclusive or of *a* and *b*.

not_*(o)*
__not__(*o*)
 Return the outcome of not *o*. (Note that there is no **__not__**() discipline for object instances; only the interpreter core defines this operation.)

truth(*o*)
 Return 1 if *o* is true, and 0 otherwise.

concat(*a*, *b*)
__concat__(*a*, *b*)
 Return *a* + *b* for *a* and *b* sequences.

repeat(*a*, *b*)
__repeat__(*a*, *b*)
 Return *a* * *b* where *a* is a sequence and *b* is an integer.

contains(*a*, *b*)
sequenceIncludes(*a*, *b*)
 Return the outcome of the test *b* in *a*. Note the reversed operands.

countOf(*a*, *b*)
 Return the number of occurrences of *b* in *a*.

indexOf(*a*, *b*)
 Return the index of the first of occurrence of *b* in *a*.

getitem(*a*, *b*)
__getitem__(*a*, *b*)
 Return the value of *a* at index *b*.

setitem(*a*, *b*, *c*)
__setitem__(*a*, *b*, *c*)
 Set the value of *a* at index *b* to *c*.

delitem(*a*, *b*)
__delitem__(*a*, *b*)
 Remove the value of *a* at index *b*.

```

getslice(a, b, c)
__getslice__(a, b, c)
    Return the slice of a from index b to index c-1.

setslice(a, b, c, v)
__setslice__(a, b, c, v)
    Set the slice of a from index b to index c-1 to the sequence v.

delslice(a, b, c)
__delslice__(a, b, c)
    Delete the slice of a from index b to index c-1.

```

Example: Build a dictionary that maps the ordinals from 0 to 256 to their character equivalents.

```

>>> import operator
>>> d = {}
>>> keys = range(256)
>>> vals = map(chr, keys)
>>> map(operator.setitem, [d]*len(keys), keys, vals)

```

3.7 traceback — Print or retrieve a stack traceback

This module provides a standard interface to extract, format and print stack traces of Python programs. It exactly mimics the behavior of the Python interpreter when it prints a stack trace. This is useful when you want to print stack traces under program control, e.g. in a “wrapper” around the interpreter.

The module uses traceback objects — this is the object type that is stored in the variables `sys.exc_traceback` and `sys.last_traceback` and returned as the third item from `sys.exc_info()`.

The module defines the following functions:

print_tb(*traceback*[, *limit*[, *file*]])

Print up to *limit* stack trace entries from *traceback*. If *limit* is omitted or None, all entries are printed. If *file* is omitted or None, the output goes to `sys.stderr`; otherwise it should be an open file or file-like object to receive the output.

print_exception(*type*, *value*, *traceback*[, *limit*[, *file*]])

Print exception information and up to *limit* stack trace entries from *traceback* to *file*. This differs from `print_tb()` in the following ways: (1) if *traceback* is not None, it prints a header ‘Traceback (innermost last):’; (2) it prints the exception *type* and *value* after the stack trace; (3) if *type* is `SyntaxError` and *value* has the appropriate format, it prints the line where the syntax error occurred with a caret indicating the approximate position of the error.

print_exc([*limit*[, *file*]])

This is a shorthand for ‘`print_exception(sys.exc_type, sys.exc_value, sys.exc_traceback, limit, file)`’. (In fact, it uses `sys.exc_info()` to retrieve the same information in a thread-safe way.)

print_last([*limit*[, *file*]])

This is a shorthand for ‘`print_exception(sys.last_type, sys.last_value, sys.last_traceback, limit, file)`’.

print_stack([*f*[, *limit*[, *file*]])

This function prints a stack trace from its invocation point. The optional *f* argument can be used to specify an alternate stack frame to start. The optional *limit* and *file* arguments have the same meaning as for `print_exception()`.

extract_tb(*traceback*[, *limit*])

Return a list of up to *limit* “pre-processed” stack trace entries extracted from the traceback object *traceback*. It is useful for alternate formatting of stack traces. If *limit* is omitted or `None`, all entries are extracted. A “pre-processed” stack trace entry is a quadruple (*filename*, *line number*, *function name*, *text*) representing the information that is usually printed for a stack trace. The *text* is a string with leading and trailing whitespace stripped; if the source is not available it is `None`.

extract_stack([*f*[, *limit*]])

Extract the raw traceback from the current stack frame. The return value has the same format as for `extract_tb()`. The optional *f* and *limit* arguments have the same meaning as for `print_stack()`.

format_list(*list*)

Given a list of tuples as returned by `extract_tb()` or `extract_stack()`, return a list of strings ready for printing. Each string in the resulting list corresponds to the item with the same index in the argument list. Each string ends in a newline; the strings may contain internal newlines as well, for those items whose source text line is not `None`.

format_exception_only(*type*, *value*)

Format the exception part of a traceback. The arguments are the exception type and value such as given by `sys.last_type` and `sys.last_value`. The return value is a list of strings, each ending in a newline. Normally, the list contains a single string; however, for `SyntaxError` exceptions, it contains several lines that (when printed) display detailed information about where the syntax error occurred. The message indicating which exception occurred is the always last string in the list.

format_exception(*type*, *value*, *tb*[, *limit*])

Format a stack trace and the exception information. The arguments have the same meaning as the corresponding arguments to `print_exception()`. The return value is a list of strings, each ending in a newline and some containing internal newlines. When these lines are concatenated and printed, exactly the same text is printed as does `print_exception()`.

format_tb(*tb*[, *limit*])

A shorthand for `format_list(extract_tb(tb, limit))`.

format_stack([*f*[, *limit*]])

A shorthand for `format_list(extract_stack(f, limit))`.

tb_lineno(*tb*)

This function returns the current line number set in the traceback object. This is normally the same as the `tb.tb_lineno` field of the object, but when optimization is used (the `-O` flag) this field is not updated correctly; this function calculates the correct value.

3.7.1 Traceback Example

This simple example implements a basic read-eval-print loop, similar to (but less useful than) the standard Python interactive interpreter loop. For a more complete implementation of the interpreter loop, refer to the [code](#) module.

```

import sys, traceback

def run_user_code(envdir):
    source = raw_input(">>> ")
    try:
        exec source in envdir
    except:
        print "Exception in user code:"
        print '-'*60
        traceback.print_exc(file=sys.stdout)
        print '-'*60

envdir = {}
while 1:
    run_user_code(envdir)

```

3.8 linecache — Random access to text lines

The `linecache` module allows one to get any line from any file, while attempting to optimize internally, using a cache, the common case where many lines are read from a single file. This is used by the `traceback` module to retrieve source lines for inclusion in the formatted traceback.

The `linecache` module defines the following functions:

getline(*filename*, *lineno*)

Get line *lineno* from file named *filename*. This function will never throw an exception — it will return '' on errors (the terminating newline character will be included for lines that are found).

If a file named *filename* is not found, the function will look for it in the module search path, `sys.path`.

clearcache()

Clear the cache. Use this function if you no longer need lines from files previously read using `getline()`.

checkcache()

Check the cache for validity. Use this function if files in the cache may have changed on disk, and you require the updated version.

Example:

```

>>> import linecache
>>> linecache.getline('/etc/passwd', 4)
'sys:x:3:3:sys:/dev:/bin/sh\012'

```

3.9 pickle — Python object serialization

The `pickle` module implements a basic but powerful algorithm for “pickling” (a.k.a. serializing, marshalling or flattening) nearly arbitrary Python objects. This is the act of converting objects to a stream of bytes (and back: “unpickling”). This is a more primitive notion than persistency — although `pickle` reads and writes file objects, it does not handle the issue of naming persistent objects, nor the (even more complicated) area of concurrent access to persistent objects. The `pickle` module can transform a complex object into a byte stream and it can transform the

byte stream into an object with the same internal structure. The most obvious thing to do with these byte streams is to write them onto a file, but it is also conceivable to send them across a network or store them in a database. The module `shelve` provides a simple interface to pickle and unpickle objects on DBM-style database files.

Note: The `pickle` module is rather slow. A reimplementaion of the same algorithm in C, which is up to 1000 times faster, is available as the `cPickle` module. This has the same interface except that `Pickler` and `Unpickler` are factory functions, not classes (so they cannot be used as base classes for inheritance).

Although the `pickle` module can use the built-in module `marshal` internally, it differs from `marshal` in the way it handles certain kinds of data:

- Recursive objects (objects containing references to themselves): `pickle` keeps track of the objects it has already serialized, so later references to the same object won't be serialized again. (The `marshal` module breaks for this.)
- Object sharing (references to the same object in different places): This is similar to self-referencing objects; `pickle` stores the object once, and ensures that all other references point to the master copy. Shared objects remain shared, which can be very important for mutable objects.
- User-defined classes and their instances: `marshal` does not support these at all, but `pickle` can save and restore class instances transparently. The class definition must be importable and live in the same module as when the object was stored.

The data format used by `pickle` is Python-specific. This has the advantage that there are no restrictions imposed by external standards such as XDR (which can't represent pointer sharing); however it means that non-Python programs may not be able to reconstruct pickled Python objects.

By default, the `pickle` data format uses a printable ASCII representation. This is slightly more voluminous than a binary representation. The big advantage of using printable ASCII (and of some other characteristics of `pickle`'s representation) is that for debugging or recovery purposes it is possible for a human to read the pickled file with a standard text editor.

A binary format, which is slightly more efficient, can be chosen by specifying a nonzero (true) value for the `bin` argument to the `Pickler` constructor or the `dump()` and `dumps()` functions. The binary format is not the default because of backwards compatibility with the Python 1.4 `pickle` module. In a future version, the default may change to binary.

The `pickle` module doesn't handle code objects, which the `marshal` module does. I suppose `pickle` could, and maybe it should, but there's probably no great need for it right now (as long as `marshal` continues to be used for reading and writing code objects), and at least this avoids the possibility of smuggling Trojan horses into a program.

For the benefit of persistency modules written using `pickle`, it supports the notion of a reference to an object outside the pickled data stream. Such objects are referenced by a name, which is an arbitrary string of printable ASCII characters. The resolution of such names is not defined by the `pickle` module — the persistent object module will have to implement a method `persistent_load()`. To write references to persistent objects, the persistent module must define a method `persistent_id()` which returns either `None` or the persistent ID of the object.

There are some restrictions on the pickling of class instances.

First of all, the class must be defined at the top level in a module. Furthermore, all its instance variables must be picklable.

When a pickled class instance is unpickled, its `__init__()` method is normally *not* invoked. **Note:** This is a deviation from previous versions of this module; the change was introduced in Python 1.5b2. The reason for the change is that in many cases it is desirable to have a constructor that requires arguments; it is a (minor) nuisance to have to provide a `__getinitargs__()` method.

If it is desirable that the `__init__()` method be called on unpickling, a class can define a method `__getinitargs__()`, which should return a *tuple* containing the arguments to be passed to the class construc-

tor (`__init__()`). This method is called at pickle time; the tuple it returns is incorporated in the pickle for the instance.

Classes can further influence how their instances are pickled — if the class defines the method `__getstate__()`, it is called and the return state is pickled as the contents for the instance, and if the class defines the method `__setstate__()`, it is called with the unpickled state. (Note that these methods can also be used to implement copying class instances.) If there is no `__getstate__()` method, the instance's `__dict__` is pickled. If there is no `__setstate__()` method, the pickled object must be a dictionary and its items are assigned to the new instance's dictionary. (If a class defines both `__getstate__()` and `__setstate__()`, the state object needn't be a dictionary — these methods can do what they want.) This protocol is also used by the shallow and deep copying operations defined in the `copy` module.

Note that when class instances are pickled, their class's code and data are not pickled along with them. Only the instance data are pickled. This is done on purpose, so you can fix bugs in a class or add methods and still load objects that were created with an earlier version of the class. If you plan to have long-lived objects that will see many versions of a class, it may be worthwhile to put a version number in the objects so that suitable conversions can be made by the class's `__setstate__()` method.

When a class itself is pickled, only its name is pickled — the class definition is not pickled, but re-imported by the unpickling process. Therefore, the restriction that the class must be defined at the top level in a module applies to pickled classes as well.

The interface can be summarized as follows.

To pickle an object `x` onto a file `f`, open for writing:

```
p = pickle.Pickler(f)
p.dump(x)
```

A shorthand for this is:

```
pickle.dump(x, f)
```

To unpickle an object `x` from a file `f`, open for reading:

```
u = pickle.Unpickler(f)
x = u.load()
```

A shorthand is:

```
x = pickle.load(f)
```

The `Pickler` class only calls the method `f.write()` with a string argument. The `Unpickler` calls the methods `f.read()` (with an integer argument) and `f.readline()` (without argument), both returning a string. It is explicitly allowed to pass non-file objects here, as long as they have the right methods.

The constructor for the `Pickler` class has an optional second argument, *bin*. If this is present and true, the binary pickle format is used; if it is absent or false, the (less efficient, but backwards compatible) text pickle format is used. The `Unpickler` class does not have an argument to distinguish between binary and text pickle formats; it accepts either format.

The following types can be pickled:

- None
- integers, long integers, floating point numbers

- normal and Unicode strings
- tuples, lists and dictionaries containing only picklable objects
- functions defined at the top level of a module (by name reference, not storage of the implementation)
- built-in functions
- classes that are defined at the top level in a module
- instances of such classes whose `__dict__` or `__setstate__()` is picklable

Attempts to pickle unpicklable objects will raise the `PicklingError` exception; when this happens, an unspecified number of bytes may have been written to the file.

It is possible to make multiple calls to the `dump()` method of the same `Pickler` instance. These must then be matched to the same number of calls to the `load()` method of the corresponding `Unpickler` instance. If the same object is pickled by multiple `dump()` calls, the `load()` will all yield references to the same object. *Warning:* this is intended for pickling multiple objects without intervening modifications to the objects or their parts. If you modify an object and then pickle it again using the same `Pickler` instance, the object is not pickled again — a reference to it is pickled and the `Unpickler` will return the old value, not the modified one. (There are two problems here: (a) detecting changes, and (b) marshalling a minimal set of changes. I have no answers. Garbage Collection may also become a problem here.)

Apart from the `Pickler` and `Unpickler` classes, the module defines the following functions, and an exception:

dump(*object*, *file*[, *bin*])

Write a pickled representation of *object* to the open file object *file*. This is equivalent to `Pickler(file, bin).dump(object)`. If the optional *bin* argument is present and nonzero, the binary pickle format is used; if it is zero or absent, the (less efficient) text pickle format is used.

load(*file*)

Read a pickled object from the open file object *file*. This is equivalent to `Unpickler(file).load()`.

dumps(*object*[, *bin*])

Return the pickled representation of the object as a string, instead of writing it to a file. If the optional *bin* argument is present and nonzero, the binary pickle format is used; if it is zero or absent, the (less efficient) text pickle format is used.

loads(*string*)

Read a pickled object from a string instead of a file. Characters in the string past the pickled object's representation are ignored.

PicklingError

This exception is raised when an unpicklable object is passed to `Pickler.dump()`.

See Also:

[Module `copy_reg`](#) (section 3.11):

pickle interface constructor registration

[Module `shelve`](#) (section 3.12):

indexed databases of objects; uses `pickle`

[Module `copy`](#) (section 3.13):

shallow and deep object copying

[Module `marshal`](#) (section 3.14):

high-performance serialization of built-in types

3.9.1 Example

Here's a simple example of how to modify pickling behavior for a class. The `TextReader` class opens a text file, and returns the line number and line contents each time its `readline()` method is called. If a `TextReader` instance is pickled, all attributes *except* the file object member are saved. When the instance is unpickled, the file is reopened, and reading resumes from the last location. The `__setstate__()` and `__getstate__()` methods are used to implement this behavior.

```
# illustrate __setstate__ and __getstate__ methods
# used in pickling.

class TextReader:
    "Print and number lines in a text file."
    def __init__(self,file):
        self.file = file
        self.fh = open(file,'r')
        self.lineno = 0

    def readline(self):
        self.lineno = self.lineno + 1
        line = self.fh.readline()
        if not line:
            return None
        return "%d: %s" % (self.lineno,line[:-1])

    # return data representation for pickled object
    def __getstate__(self):
        odict = self.__dict__    # get attribute dictionary
        del odict['fh']         # remove filehandle entry
        return odict

    # restore object state from data representation generated
    # by __getstate__
    def __setstate__(self,dict):
        fh = open(dict['file']) # reopen file
        count = dict['lineno']  # read from file...
        while count:           # until line count is restored
            fh.readline()
            count = count - 1
        dict['fh'] = fh        # create filehandle entry
        self.__dict__ = dict  # make dict our attribute dictionary
```

A sample usage might be something like this:

```

>>> import TextReader
>>> obj = TextReader.TextReader("TextReader.py")
>>> obj.readline()
'1: #!/usr/local/bin/python'
>>> # (more invocations of obj.readline() here)
... obj.readline()
'7: class TextReader:'
>>> import pickle
>>> pickle.dump(obj,open('save.p','w'))

    (start another Python session)

>>> import pickle
>>> reader = pickle.load(open('save.p'))
>>> reader.readline()
'8:      "Print and number lines in a text file."'

```

3.10 cPickle — Alternate implementation of pickle

The `cPickle` module provides a similar interface and identical functionality as the `pickle` module, but can be up to 1000 times faster since it is implemented in C. The only other important difference to note is that `Pickler()` and `Unpickler()` are functions and not classes, and so cannot be subclassed. This should not be an issue in most cases.

The format of the pickle data is identical to that produced using the `pickle` module, so it is possible to use `pickle` and `cPickle` interchangeably with existing pickles.

(Since the pickle data format is actually a tiny stack-oriented programming language, and there are some freedoms in the encodings of certain objects, it's possible that the two modules produce different pickled data for the same input objects; however they will always be able to read each others pickles back in.)

3.11 copy_reg — Register pickle support functions

The `copy_reg` module provides support for the `pickle` and `cPickle` modules. The `copy` module is likely to use this in the future as well. It provides configuration information about object constructors which are not classes. Such constructors may be factory functions or class instances.

constructor (*object*)

Declares *object* to be a valid constructor.

pickle (*type*, *function*[, *constructor*])

Declares that *function* should be used as a “reduction” function for objects of type or class *type*. *function* should return either a string or a tuple. The optional *constructor* parameter, if provided, is a callable object which can be used to reconstruct the object when called with the tuple of arguments returned by *function* at pickling time.

3.12 shelve — Python object persistency

A “shelf” is a persistent, dictionary-like object. The difference with “dbm” databases is that the values (not the keys!) in a shelf can be essentially arbitrary Python objects — anything that the `pickle` module can handle. This includes most class instances, recursive data types, and objects containing lots of shared sub-objects. The keys are ordinary strings.

To summarize the interface (key is a string, data is an arbitrary object):

```
import shelve

d = shelve.open(filename) # open, with (g)dbm filename -- no suffix

d[key] = data # store data at key (overwrites old data if
              # using an existing key)
data = d[key] # retrieve data at key (raise KeyError if no
              # such key)
del d[key]    # delete data stored at key (raises KeyError
              # if no such key)
flag = d.has_key(key) # true if the key exists
list = d.keys() # a list of all existing keys (slow!)

d.close()    # close it
```

Restrictions:

- The choice of which database package will be used (e.g. [dbm](#) or [gdbm](#)) depends on which interface is available. Therefore it is not safe to open the database directly using [dbm](#). The database is also (unfortunately) subject to the limitations of [dbm](#), if it is used — this means that (the pickled representation of) the objects stored in the database should be fairly small, and in rare cases key collisions may cause the database to refuse updates.
- Dependent on the implementation, closing a persistent dictionary may or may not be necessary to flush changes to disk.
- The `shelve` module does not support *concurrent* read/write access to shelved objects. (Multiple simultaneous read accesses are safe.) When a program has a shelf open for writing, no other program should have it open for reading or writing. UNIX file locking can be used to solve this, but this differs across UNIX versions and requires knowledge about the database implementation used.

See Also:

[Module `anydbm`](#) (section 7.7):

Generic interface to dbm-style databases.

[Module `dbhash`](#) (section 7.9):

BSD db database interface.

[Module `dbm`](#) (section 8.6):

Standard UNIX database interface.

[Module `dumbdbm`](#) (section 7.8):

Portable implementation of the dbm interface.

[Module `gdbm`](#) (section 8.7):

GNU database interface, based on the dbm interface.

[Module `pickle`](#) (section 3.9):

Object serialization used by `shelve`.

[Module `cPickle`](#) (section 3.10):

High-performance version of [pickle](#).

3.13 `copy` — Shallow and deep copy operations

This module provides generic (shallow and deep) copying operations.

Interface summary:

```
import copy

x = copy.copy(y)          # make a shallow copy of y
x = copy.deepcopy(y)     # make a deep copy of y
```

For module specific errors, `copy.error` is raised.

The difference between shallow and deep copying is only relevant for compound objects (objects that contain other objects, like lists or class instances):

- A *shallow copy* constructs a new compound object and then (to the extent possible) inserts *references* into it to the objects found in the original.
- A *deep copy* constructs a new compound object and then, recursively, inserts *copies* into it of the objects found in the original.

Two problems often exist with deep copy operations that don't exist with shallow copy operations:

- Recursive objects (compound objects that, directly or indirectly, contain a reference to themselves) may cause a recursive loop.
- Because deep copy copies *everything* it may copy too much, e.g., administrative data structures that should be shared even between copies.

The `deepcopy()` function avoids these problems by:

- keeping a “memo” dictionary of objects already copied during the current copying pass; and
- letting user-defined classes override the copying operation or the set of components copied.

This version does not copy types like module, class, function, method, stack trace, stack frame, file, socket, window, array, or any similar types.

Classes can use the same interfaces to control copying that they use to control pickling: they can define methods called `__getinitargs__()`, `__getstate__()` and `__setstate__()`. See the description of module `pickle` for information on these methods. The `copy` module does not use the `copy_reg` registration module.

In order for a class to define its own copy implementation, it can define special methods `__copy__()` and `__deepcopy__()`. The former is called to implement the shallow copy operation; no additional arguments are passed. The latter is called to implement the deep copy operation; it is passed one argument, the memo dictionary. If the `__deepcopy__()` implementation needs to make a deep copy of a component, it should call the `deepcopy()` function with the component as first argument and the memo dictionary as second argument.

See Also:

[Module `pickle`](#) (section 3.9):

Discussion of the special disciplines used to support object state retrieval and restoration.

3.14 marshal — Alternate Python object serialization

This module contains functions that can read and write Python values in a binary format. The format is specific to Python, but independent of machine architecture issues (e.g., you can write a Python value to a file on a PC, transport the file to a Sun, and read it back there). Details of the format are undocumented on purpose; it may change between Python versions (although it rarely does).¹

This is not a general “persistence” module. For general persistence and transfer of Python objects through RPC calls, see the modules `pickle` and `shelve`. The `marshal` module exists mainly to support reading and writing the “pseudo-compiled” code for Python modules of ‘.pyc’ files.

Not all Python object types are supported; in general, only objects whose value is independent from a particular invocation of Python can be written and read by this module. The following types are supported: `None`, integers, long integers, floating point numbers, strings, Unicode objects, tuples, lists, dictionaries, and code objects, where it should be understood that tuples, lists and dictionaries are only supported as long as the values contained therein are themselves supported; and recursive lists and dictionaries should not be written (they will cause infinite loops).

Caveat: On machines where C’s `long int` type has more than 32 bits (such as the DEC Alpha), it is possible to create plain Python integers that are longer than 32 bits. Since the current `marshal` module uses 32 bits to transfer plain Python integers, such values are silently truncated. This particularly affects the use of very long integer literals in Python modules — these will be accepted by the parser on such machines, but will be silently be truncated when the module is read from the ‘.pyc’ instead.²

There are functions that read/write files as well as functions operating on strings.

The module defines these functions:

dump(*value*, *file*)

Write the value on the open file. The value must be a supported type. The file must be an open file object such as `sys.stdout` or returned by `open()` or `posix.popen()`. It must be opened in binary mode (‘wb’ or ‘w+b’).

If the value has (or contains an object that has) an unsupported type, a `ValueError` exception is raised — but garbage data will also be written to the file. The object will not be properly read back by `load()`.

load(*file*)

Read one value from the open file and return it. If no valid value is read, raise `EOFError`, `ValueError` or `TypeError`. The file must be an open file object opened in binary mode (‘rb’ or ‘r+b’).

Warning: If an object containing an unsupported type was marshalled with `dump()`, `load()` will substitute `None` for the unmarshallable type.

dumps(*value*)

Return the string that would be written to a file by `dump(value, file)`. The value must be a supported type. Raise a `ValueError` exception if value has (or contains an object that has) an unsupported type.

loads(*string*)

Convert the string to a value. If no valid value is found, raise `EOFError`, `ValueError` or `TypeError`. Extra characters in the string are ignored.

3.15 `imp` — Access the `import` internals

This module provides an interface to the mechanisms used to implement the `import` statement. It defines the following constants and functions:

get_magic()

¹The name of this module stems from a bit of terminology used by the designers of Modula-3 (amongst others), who use the term “marshalling” for shipping of data around in a self-contained form. Strictly speaking, “to marshal” means to convert some data from internal to external form (in an RPC buffer for instance) and “unmarshalling” for the reverse process.

²A solution would be to refuse such literals in the parser, since they are inherently non-portable. Another solution would be to let the `marshal` module raise an exception when an integer value would be truncated. At least one of these solutions will be implemented in a future version.

Return the magic string value used to recognize byte-compiled code files ('.pyc' files). (This value may be different for each Python version.)

get_suffixes()

Return a list of triples, each describing a particular type of module. Each triple has the form (*suffix*, *mode*, *type*), where *suffix* is a string to be appended to the module name to form the filename to search for, *mode* is the mode string to pass to the built-in `open()` function to open the file (this can be 'r' for text files or 'rb' for binary files), and *type* is the file type, which has one of the values `PY_SOURCE`, `PY_COMPILED`, or `C_EXTENSION`, described below.

find_module(name[, path])

Try to find the module *name* on the search path *path*. If *path* is a list of directory names, each directory is searched for files with any of the suffixes returned by `get_suffixes()` above. Invalid names in the list are silently ignored (but all list items must be strings). If *path* is omitted or `None`, the list of directory names given by `sys.path` is searched, but first it searches a few special places: it tries to find a built-in module with the given name (`C_BUILTIN`), then a frozen module (`PY_FROZEN`), and on some systems some other places are looked in as well (on the Mac, it looks for a resource (`PY_RESOURCE`); on Windows, it looks in the registry which may point to a specific file).

If search is successful, the return value is a triple (*file*, *pathname*, *description*) where *file* is an open file object positioned at the beginning, *pathname* is the pathname of the file found, and *description* is a triple as contained in the list returned by `get_suffixes()` describing the kind of module found. If the module does not live in a file, the returned *file* is `None`, *filename* is the empty string, and the *description* tuple contains empty strings for its suffix and mode; the module type is as indicated in parentheses above. If the search is unsuccessful, `ImportError` is raised. Other exceptions indicate problems with the arguments or environment.

This function does not handle hierarchical module names (names containing dots). In order to find *P.M*, i.e., submodule *M* of package *P*, use `find_module()` and `load_module()` to find and load package *P*, and then use `find_module()` with the *path* argument set to `P.__path__`. When *P* itself has a dotted name, apply this recipe recursively.

load_module(name, file, filename, description)

Load a module that was previously found by `find_module()` (or by an otherwise conducted search yielding compatible results). This function does more than importing the module: if the module was already imported, it is equivalent to a `reload()`! The *name* argument indicates the full module name (including the package name, if this is a submodule of a package). The *file* argument is an open file, and *filename* is the corresponding file name; these can be `None` and `' '`, respectively, when the module is not being loaded from a file. The *description* argument is a tuple as returned by `find_module()` describing what kind of module must be loaded.

If the load is successful, the return value is the module object; otherwise, an exception (usually `ImportError`) is raised.

Important: the caller is responsible for closing the *file* argument, if it was not `None`, even when an exception is raised. This is best done using a `try ... finally` statement.

new_module(name)

Return a new empty module object called *name*. This object is *not* inserted in `sys.modules`.

The following constants with integer values, defined in this module, are used to indicate the search result of `find_module()`.

PY_SOURCE

The module was found as a source file.

PY_COMPILED

The module was found as a compiled code object file.

C_EXTENSION

The module was found as dynamically loadable shared library.

PY_RESOURCE

The module was found as a Macintosh resource. This value can only be returned on a Macintosh.

PKG_DIRECTORY

The module was found as a package directory.

C_BUILTIN

The module was found as a built-in module.

PY_FROZEN

The module was found as a frozen module (see `init_frozen()`).

The following constant and functions are obsolete; their functionality is available through `find_module()` or `load_module()`. They are kept around for backward compatibility:

SEARCH_ERROR

Unused.

init_builtin(*name*)

Initialize the built-in module called *name* and return its module object. If the module was already initialized, it will be initialized *again*. A few modules cannot be initialized twice — attempting to initialize these again will raise an `ImportError` exception. If there is no built-in module called *name*, `None` is returned.

init_frozen(*name*)

Initialize the frozen module called *name* and return its module object. If the module was already initialized, it will be initialized *again*. If there is no frozen module called *name*, `None` is returned. (Frozen modules are modules written in Python whose compiled byte-code object is incorporated into a custom-built Python interpreter by Python's **freeze** utility. See 'Tools/freeze/' for now.)

is_builtin(*name*)

Return 1 if there is a built-in module called *name* which can be initialized again. Return -1 if there is a built-in module called *name* which cannot be initialized again (see `init_builtin()`). Return 0 if there is no built-in module called *name*.

is_frozen(*name*)

Return 1 if there is a frozen module (see `init_frozen()`) called *name*, or 0 if there is no such module.

load_compiled(*name*, *pathname*, *file*)

Load and initialize a module implemented as a byte-compiled code file and return its module object. If the module was already initialized, it will be initialized *again*. The *name* argument is used to create or access a module object. The *pathname* argument points to the byte-compiled code file. The *file* argument is the byte-compiled code file, open for reading in binary mode, from the beginning. It must currently be a real file object, not a user-defined class emulating a file.

load_dynamic(*name*, *pathname*[, *file*])

Load and initialize a module implemented as a dynamically loadable shared library and return its module object. If the module was already initialized, it will be initialized *again*. Some modules don't like that and may raise an exception. The *pathname* argument must point to the shared library. The *name* argument is used to construct the name of the initialization function: an external C function called '`initname()`' in the shared library is called. The optional *file* argument is ignored. (Note: using shared libraries is highly system dependent, and not all systems support it.)

load_source(*name*, *pathname*, *file*)

Load and initialize a module implemented as a Python source file and return its module object. If the module was already initialized, it will be initialized *again*. The *name* argument is used to create or access a module object. The *pathname* argument points to the source file. The *file* argument is the source file, open for reading as text, from the beginning. It must currently be a real file object, not a user-defined class emulating a file. Note that if a properly matching byte-compiled file (with suffix '`.pyc`' or '`.pyo`') exists, it will be used instead of parsing the given source file.

3.15.1 Examples

The following function emulates what was the standard import statement up to Python 1.4 (i.e., no hierarchical module names). (This *implementation* wouldn't work in that version, since `find_module()` has been extended and `load_module()` has been added in 1.4.)

```
import imp import sys

def __import__(name, globals=None, locals=None, fromlist=None):
    # Fast path: see if the module has already been imported.
    try:
        return sys.modules[name]
    except KeyError:
        pass

    # If any of the following calls raises an exception,
    # there's a problem we can't handle -- let the caller handle it.

    fp, pathname, description = imp.find_module(name)

    try:
        return imp.load_module(name, fp, pathname, description)
    finally:
        # Since we may exit via an exception, close fp explicitly.
        if fp:
            fp.close()
```

A more complete example that implements hierarchical module names and includes a `reload()` function can be found in the standard module `knee` (which is intended as an example only — don't rely on any part of it being a standard interface).

3.16 parser — Access Python parse trees

The `parser` module provides an interface to Python's internal parser and byte-code compiler. The primary purpose for this interface is to allow Python code to edit the parse tree of a Python expression and create executable code from this. This is better than trying to parse and modify an arbitrary Python code fragment as a string because parsing is performed in a manner identical to the code forming the application. It is also faster.

There are a few things to note about this module which are important to making use of the data structures created. This is not a tutorial on editing the parse trees for Python code, but some examples of using the `parser` module are presented.

Most importantly, a good understanding of the Python grammar processed by the internal parser is required. For full information on the language syntax, refer to the *Python Language Reference*. The parser itself is created from a grammar specification defined in the file 'Grammar/Grammar' in the standard Python distribution. The parse trees stored in the AST objects created by this module are the actual output from the internal parser when created by the `expr()` or `suite()` functions, described below. The AST objects created by `sequence2ast()` faithfully simulate those structures. Be aware that the values of the sequences which are considered "correct" will vary from one version of Python to another as the formal grammar for the language is revised. However, transporting code from one Python version to another as source text will always allow correct parse trees to be created in the target version, with the only restriction being that migrating to an older version of the interpreter will not support more recent language constructs. The parse trees are not typically compatible from one version to another, whereas source code has always been forward-compatible.

Each element of the sequences returned by `ast2list()` or `ast2tuple()` has a simple form. Sequences representing non-terminal elements in the grammar always have a length greater than one. The first element is an in-

teger which identifies a production in the grammar. These integers are given symbolic names in the C header file 'Include/graminit.h' and the Python module `symbol`. Each additional element of the sequence represents a component of the production as recognized in the input string: these are always sequences which have the same form as the parent. An important aspect of this structure which should be noted is that keywords used to identify the parent node type, such as the keyword `if` in an `if_stmt`, are included in the node tree without any special treatment. For example, the `if` keyword is represented by the tuple `(1, 'if')`, where 1 is the numeric value associated with all `NAME` tokens, including variable and function names defined by the user. In an alternate form returned when line number information is requested, the same token might be represented as `(1, 'if', 12)`, where the 12 represents the line number at which the terminal symbol was found.

Terminal elements are represented in much the same way, but without any child elements and the addition of the source text which was identified. The example of the `if` keyword above is representative. The various types of terminal symbols are defined in the C header file 'Include/token.h' and the Python module `token`.

The AST objects are not required to support the functionality of this module, but are provided for three purposes: to allow an application to amortize the cost of processing complex parse trees, to provide a parse tree representation which conserves memory space when compared to the Python list or tuple representation, and to ease the creation of additional modules in C which manipulate parse trees. A simple "wrapper" class may be created in Python to hide the use of AST objects.

The `parser` module defines functions for a few distinct purposes. The most important purposes are to create AST objects and to convert AST objects to other representations such as parse trees and compiled code objects, but there are also functions which serve to query the type of parse tree represented by an AST object.

See Also:

Module `symbol` (section 3.17):

Useful constants representing internal nodes of the parse tree.

Module `token` (section 3.18):

Useful constants representing leaf nodes of the parse tree and functions for testing node values.

3.16.1 Creating AST Objects

AST objects may be created from source code or from a parse tree. When creating an AST object from source, different functions are used to create the 'eval' and 'exec' forms.

`expr`(*source*)

The `expr()` function parses the parameter *source* as if it were an input to `'compile(source, 'file.py', 'eval')`'. If the parse succeeds, an AST object is created to hold the internal parse tree representation, otherwise an appropriate exception is thrown.

`suite`(*source*)

The `suite()` function parses the parameter *source* as if it were an input to `'compile(source, 'file.py', 'exec')`'. If the parse succeeds, an AST object is created to hold the internal parse tree representation, otherwise an appropriate exception is thrown.

`sequence2ast`(*sequence*)

This function accepts a parse tree represented as a sequence and builds an internal representation if possible. If it can validate that the tree conforms to the Python grammar and all nodes are valid node types in the host version of Python, an AST object is created from the internal representation and returned to the called. If there is a problem creating the internal representation, or if the tree cannot be validated, a `ParserError` exception is thrown. An AST object created this way should not be assumed to compile correctly; normal exceptions thrown by compilation may still be initiated when the AST object is passed to `compileast()`. This may indicate problems not related to syntax (such as a `MemoryError` exception), but may also be due to constructs such as the result of parsing `del f(0)`, which escapes the Python parser but is checked by the bytecode compiler.

Sequences representing terminal tokens may be represented as either two-element lists of the form `(1, 'name')` or as three-element lists of the form `(1, 'name', 56)`. If the third element is present, it is

assumed to be a valid line number. The line number may be specified for any subset of the terminal symbols in the input tree.

tuple2ast(*sequence*)

This is the same function as `sequence2ast()`. This entry point is maintained for backward compatibility.

3.16.2 Converting AST Objects

AST objects, regardless of the input used to create them, may be converted to parse trees represented as list- or tuple-trees, or may be compiled into executable code objects. Parse trees may be extracted with or without line numbering information.

ast2list(*ast*[, *line_info*])

This function accepts an AST object from the caller in *ast* and returns a Python list representing the equivalent parse tree. The resulting list representation can be used for inspection or the creation of a new parse tree in list form. This function does not fail so long as memory is available to build the list representation. If the parse tree will only be used for inspection, `ast2tuple()` should be used instead to reduce memory consumption and fragmentation. When the list representation is required, this function is significantly faster than retrieving a tuple representation and converting that to nested lists.

If *line_info* is true, line number information will be included for all terminal tokens as a third element of the list representing the token. Note that the line number provided specifies the line on which the token *ends*. This information is omitted if the flag is false or omitted.

ast2tuple(*ast*[, *line_info*])

This function accepts an AST object from the caller in *ast* and returns a Python tuple representing the equivalent parse tree. Other than returning a tuple instead of a list, this function is identical to `ast2list()`.

If *line_info* is true, line number information will be included for all terminal tokens as a third element of the list representing the token. This information is omitted if the flag is false or omitted.

compileast(*ast*[, *filename* = '<ast>'])

The Python byte compiler can be invoked on an AST object to produce code objects which can be used as part of an `exec` statement or a call to the built-in `eval()` function. This function provides the interface to the compiler, passing the internal parse tree from *ast* to the parser, using the source file name specified by the *filename* parameter. The default value supplied for *filename* indicates that the source was an AST object.

Compiling an AST object may result in exceptions related to compilation; an example would be a `SyntaxError` caused by the parse tree for `del f(0)`: this statement is considered legal within the formal grammar for Python but is not a legal language construct. The `SyntaxError` raised for this condition is actually generated by the Python byte-compiler normally, which is why it can be raised at this point by the `parser` module. Most causes of compilation failure can be diagnosed programmatically by inspection of the parse tree.

3.16.3 Queries on AST Objects

Two functions are provided which allow an application to determine if an AST was created as an expression or a suite. Neither of these functions can be used to determine if an AST was created from source code via `expr()` or `suite()` or from a parse tree via `sequence2ast()`.

isexpr(*ast*)

When *ast* represents an 'eval' form, this function returns true, otherwise it returns false. This is useful, since code objects normally cannot be queried for this information using existing built-in functions. Note that the code objects created by `compileast()` cannot be queried like this either, and are identical to those created by the built-in `compile()` function.

issuite(*ast*)

This function mirrors `isexpr()` in that it reports whether an AST object represents an 'exec' form, com-

monly known as a “suite.” It is not safe to assume that this function is equivalent to `not isexpr(ast)`, as additional syntactic fragments may be supported in the future.

3.16.4 Exceptions and Error Handling

The parser module defines a single exception, but may also pass other built-in exceptions from other portions of the Python runtime environment. See each function for information about the exceptions it can raise.

ParserError

Exception raised when a failure occurs within the parser module. This is generally produced for validation failures rather than the built in `SyntaxError` thrown during normal parsing. The exception argument is either a string describing the reason of the failure or a tuple containing a sequence causing the failure from a parse tree passed to `sequence2ast()` and an explanatory string. Calls to `sequence2ast()` need to be able to handle either type of exception, while calls to other functions in the module will only need to be aware of the simple string values.

Note that the functions `compileast()`, `expr()`, and `suite()` may throw exceptions which are normally thrown by the parsing and compilation process. These include the built in exceptions `MemoryError`, `OverflowError`, `SyntaxError`, and `SystemError`. In these cases, these exceptions carry all the meaning normally associated with them. Refer to the descriptions of each function for detailed information.

3.16.5 AST Objects

Ordered and equality comparisons are supported between AST objects. Pickling of AST objects (using the `pickle` module) is also supported.

ASTType

The type of the objects returned by `expr()`, `suite()` and `sequence2ast()`.

AST objects have the following methods:

compile(`[filename]`)
Same as `compileast(ast, filename)`.

isexpr()
Same as `isexpr(ast)`.

issuite()
Same as `issuite(ast)`.

tolist(`[line_info]`)
Same as `ast2list(ast, line_info)`.

totuple(`[line_info]`)
Same as `ast2tuple(ast, line_info)`.

3.16.6 Examples

The parser modules allows operations to be performed on the parse tree of Python source code before the bytecode is generated, and provides for inspection of the parse tree for information gathering purposes. Two examples are presented. The simple example demonstrates emulation of the `compile()` built-in function and the complex example shows the use of a parse tree for information discovery.

Emulation of `compile()`

While many useful operations may take place between parsing and bytecode generation, the simplest operation is to do nothing. For this purpose, using the `parser` module to produce an intermediate data structure is equivalent to the code

```
>>> code = compile('a + 5', 'file.py', 'eval')
>>> a = 5
>>> eval(code)
10
```

The equivalent operation using the `parser` module is somewhat longer, and allows the intermediate internal parse tree to be retained as an AST object:

```
>>> import parser
>>> ast = parser.expr('a + 5')
>>> code = ast.compile('file.py')
>>> a = 5
>>> eval(code)
10
```

An application which needs both AST and code objects can package this code into readily available functions:

```
import parser

def load_suite(source_string):
    ast = parser.suite(source_string)
    return ast, ast.compile()

def load_expression(source_string):
    ast = parser.expr(source_string)
    return ast, ast.compile()
```

Information Discovery

Some applications benefit from direct access to the parse tree. The remainder of this section demonstrates how the parse tree provides access to module documentation defined in docstrings without requiring that the code being examined be loaded into a running interpreter via `import`. This can be very useful for performing analyses of untrusted code.

Generally, the example will demonstrate how the parse tree may be traversed to distill interesting information. Two functions and a set of classes are developed which provide programmatic access to high level function and class definitions provided by a module. The classes extract information from the parse tree and provide access to the information at a useful semantic level, one function provides a simple low-level pattern matching capability, and the other function defines a high-level interface to the classes by handling file operations on behalf of the caller. All source files mentioned here which are not part of the Python installation are located in the `'Demo/parser/'` directory of the distribution.

The dynamic nature of Python allows the programmer a great deal of flexibility, but most modules need only a limited measure of this when defining classes, functions, and methods. In this example, the only definitions that will be considered are those which are defined in the top level of their context, e.g., a function defined by a `def` statement at

column zero of a module, but not a function defined within a branch of an `if ... else` construct, though there are some good reasons for doing so in some situations. Nesting of definitions will be handled by the code developed in the example.

To construct the upper-level extraction methods, we need to know what the parse tree structure looks like and how much of it we actually need to be concerned about. Python uses a moderately deep parse tree so there are a large number of intermediate nodes. It is important to read and understand the formal grammar used by Python. This is specified in the file `'Grammar/Grammar'` in the distribution. Consider the simplest case of interest when searching for docstrings: a module consisting of a docstring and nothing else. (See file `'docstring.py'`.)

```
"""Some documentation.
"""
```

Using the interpreter to take a look at the parse tree, we find a bewildering mass of numbers and parentheses, with the documentation buried deep in nested tuples.

```
>>> import parser
>>> import pprint
>>> ast = parser.suite(open('docstring.py').read())
>>> tup = ast.totuple()
>>> pprint.pprint(tup)
(257,
 (264,
  (265,
   (266,
    (267,
     (307,
      (287,
       (288,
        (289,
         (290,
          (292,
           (293,
            (294,
             (295,
              (296,
               (297,
                (298,
                 (299,
                  (300, (3, '"""Some documentation.\012"""')))))))))))))))
  (4, '')),
 (4, ''),
 (0, ''))
```

The numbers at the first element of each node in the tree are the node types; they map directly to terminal and non-terminal symbols in the grammar. Unfortunately, they are represented as integers in the internal representation, and the Python structures generated do not change that. However, the `symbol` and `token` modules provide symbolic names for the node types and dictionaries which map from the integers to the symbolic names for the node types.

In the output presented above, the outermost tuple contains four elements: the integer 257 and three additional tuples. Node type 257 has the symbolic name `file_input`. Each of these inner tuples contains an integer as the first element; these integers, 264, 4, and 0, represent the node types `stmt`, `NEWLINE`, and `ENDMARKER`, respectively. Note that these values may change depending on the version of Python you are using; consult `'symbol.py'` and `'token.py'` for details of the mapping. It should be fairly clear that the outermost node is related primarily to the input source rather than the contents of the file, and may be disregarded for the moment. The `stmt` node is much more interesting. In

particular, all docstrings are found in subtrees which are formed exactly as this node is formed, with the only difference being the string itself. The association between the docstring in a similar tree and the defined entity (class, function, or module) which it describes is given by the position of the docstring subtree within the tree defining the described structure.

By replacing the actual docstring with something to signify a variable component of the tree, we allow a simple pattern matching approach to check any given subtree for equivalence to the general pattern for docstrings. Since the example demonstrates information extraction, we can safely require that the tree be in tuple form rather than list form, allowing a simple variable representation to be ['variable_name']. A simple recursive function can implement the pattern matching, returning a boolean and a dictionary of variable name to value mappings. (See file 'example.py'.)

```
from types import ListType, TupleType

def match(pattern, data, vars=None):
    if vars is None:
        vars = {}
    if type(pattern) is ListType:
        vars[pattern[0]] = data
        return 1, vars
    if type(pattern) is not TupleType:
        return (pattern == data), vars
    if len(data) != len(pattern):
        return 0, vars
    for pattern, data in map(None, pattern, data):
        same, vars = match(pattern, data, vars)
        if not same:
            break
    return same, vars
```

Using this simple representation for syntactic variables and the symbolic node types, the pattern for the candidate docstring subtrees becomes fairly readable. (See file 'example.py'.)

```

import symbol
import token

DOCSTRING_STMT_PATTERN = (
    symbol.stmt,
    (symbol.simple_stmt,
     (symbol.small_stmt,
      (symbol.expr_stmt,
       (symbol.testlist,
        (symbol.test,
         (symbol.and_test,
          (symbol.not_test,
           (symbol.comparison,
            (symbol.expr,
             (symbol.xor_expr,
              (symbol.and_expr,
               (symbol.shift_expr,
                (symbol.arith_expr,
                 (symbol.term,
                  (symbol.factor,
                   (symbol.power,
                    (symbol.atom,
                     (token.STRING, ['docstring'])
                    ))))))))))))))),
     (token.NEWLINE, ''))
)

```

Using the `match()` function with this pattern, extracting the module docstring from the parse tree created previously is easy:

```

>>> found, vars = match(DOCSTRING_STMT_PATTERN, tup[1])
>>> found
1
>>> vars
{'docstring': '""Some documentation.\012""'}

```

Once specific data can be extracted from a location where it is expected, the question of where information can be expected needs to be answered. When dealing with docstrings, the answer is fairly simple: the docstring is the first `stmt` node in a code block (`file_input` or `suite` node types). A module consists of a single `file_input` node, and class and function definitions each contain exactly one `suite` node. Classes and functions are readily identified as subtrees of code block nodes which start with `(stmt, (compound_stmt, (classdef, ... or (stmt, (compound_stmt, (funcdef, ...`. Note that these subtrees cannot be matched by `match()` since it does not support multiple sibling nodes to match without regard to number. A more elaborate matching function could be used to overcome this limitation, but this is sufficient for the example.

Given the ability to determine whether a statement might be a docstring and extract the actual string from the statement, some work needs to be performed to walk the parse tree for an entire module and extract information about the names defined in each context of the module and associate any docstrings with the names. The code to perform this work is not complicated, but bears some explanation.

The public interface to the classes is straightforward and should probably be somewhat more flexible. Each “major” block of the module is described by an object providing several methods for inquiry and a constructor which accepts at least the subtree of the complete parse tree which it represents. The `ModuleInfo` constructor accepts an optional `name` parameter since it cannot otherwise determine the name of the module.

The public classes include `ClassInfo`, `FunctionInfo`, and `ModuleInfo`. All objects provide the meth-

ods `get_name()`, `get_docstring()`, `get_class_names()`, and `get_class_info()`. The `Class-Info` objects support `get_method_names()` and `get_method_info()` while the other classes provide `get_function_names()` and `get_function_info()`.

Within each of the forms of code block that the public classes represent, most of the required information is in the same form and is accessed in the same way, with classes having the distinction that functions defined at the top level are referred to as “methods.” Since the difference in nomenclature reflects a real semantic distinction from functions defined outside of a class, the implementation needs to maintain the distinction. Hence, most of the functionality of the public classes can be implemented in a common base class, `SuiteInfoBase`, with the accessors for function and method information provided elsewhere. Note that there is only one class which represents function and method information; this parallels the use of the `def` statement to define both types of elements.

Most of the accessor functions are declared in `SuiteInfoBase` and do not need to be overridden by subclasses. More importantly, the extraction of most information from a parse tree is handled through a method called by the `SuiteInfoBase` constructor. The example code for most of the classes is clear when read alongside the formal grammar, but the method which recursively creates new information objects requires further examination. Here is the relevant part of the `SuiteInfoBase` definition from ‘example.py’:

```
class SuiteInfoBase:
    _docstring = ''
    _name = ''

    def __init__(self, tree = None):
        self._class_info = {}
        self._function_info = {}
        if tree:
            self._extract_info(tree)

    def _extract_info(self, tree):
        # extract docstring
        if len(tree) == 2:
            found, vars = match(DOCSTRING_STMT_PATTERN[1], tree[1])
        else:
            found, vars = match(DOCSTRING_STMT_PATTERN, tree[3])
        if found:
            self._docstring = eval(vars['docstring'])
        # discover inner definitions
        for node in tree[1:]:
            found, vars = match(COMPOUND_STMT_PATTERN, node)
            if found:
                cstmt = vars['compound']
                if cstmt[0] == symbol.funcdef:
                    name = cstmt[2][1]
                    self._function_info[name] = FunctionInfo(cstmt)
                elif cstmt[0] == symbol.classdef:
                    name = cstmt[2][1]
                    self._class_info[name] = ClassInfo(cstmt)
```

After initializing some internal state, the constructor calls the `_extract_info()` method. This method performs the bulk of the information extraction which takes place in the entire example. The extraction has two distinct phases: the location of the docstring for the parse tree passed in, and the discovery of additional definitions within the code block represented by the parse tree.

The initial `if` test determines whether the nested suite is of the “short form” or the “long form.” The short form is used when the code block is on the same line as the definition of the code block, as in

```
def square(x): "Square an argument."; return x ** 2
```

while the long form uses an indented block and allows nested definitions:

```
def make_power(exp):  
    "Make a function that raises an argument to the exponent 'exp'."  
    def raiser(x, y=exp):  
        return x ** y  
    return raiser
```

When the short form is used, the code block may contain a docstring as the first, and possibly only, `small_stmt` element. The extraction of such a docstring is slightly different and requires only a portion of the complete pattern used in the more common case. As implemented, the docstring will only be found if there is only one `small_stmt` node in the `simple_stmt` node. Since most functions and methods which use the short form do not provide a docstring, this may be considered sufficient. The extraction of the docstring proceeds using the `match()` function as described above, and the value of the docstring is stored as an attribute of the `SuiteInfoBase` object.

After docstring extraction, a simple definition discovery algorithm operates on the `stmt` nodes of the `suite` node. The special case of the short form is not tested; since there are no `stmt` nodes in the short form, the algorithm will silently skip the single `simple_stmt` node and correctly not discover any nested definitions.

Each statement in the code block is categorized as a class definition, function or method definition, or something else. For the definition statements, the name of the element defined is extracted and a representation object appropriate to the definition is created with the defining subtree passed as an argument to the constructor. The representation objects are stored in instance variables and may be retrieved by name using the appropriate accessor methods.

The public classes provide any accessors required which are more specific than those provided by the `SuiteInfoBase` class, but the real extraction algorithm remains common to all forms of code blocks. A high-level function can be used to extract the complete set of information from a source file. (See file 'example.py'.)

```
def get_docs(fileName):  
    import os  
    import parser  
  
    source = open(fileName).read()  
    basename = os.path.basename(os.path.splitext(fileName)[0])  
    ast = parser.suite(source)  
    return ModuleInfo(ast.totuple(), basename)
```

This provides an easy-to-use interface to the documentation of a module. If information is required which is not extracted by the code of this example, the code may be extended at clearly defined points to provide additional capabilities.

3.17 `symbol` — Constants used with Python parse trees

This module provides constants which represent the numeric values of internal nodes of the parse tree. Unlike most Python constants, these use lower-case names. Refer to the file 'Grammar/Grammar' in the Python distribution for the definitions of the names in the context of the language grammar. The specific numeric values which the names map to may change between Python versions.

This module also provides one additional data object:

sym_name

Dictionary mapping the numeric values of the constants defined in this module back to name strings, allowing more human-readable representation of parse trees to be generated.

See Also:

[Module parser](#) (section 3.16):
second example uses this module

3.18 token — Constants used with Python parse trees

This module provides constants which represent the numeric values of leaf nodes of the parse tree (terminal tokens). Refer to the file ‘Grammar/Grammar’ in the Python distribution for the definitions of the names in the context of the language grammar. The specific numeric values which the names map to may change between Python versions.

This module also provides one data object and some functions. The functions mirror definitions in the Python C header files.

tok_name

Dictionary mapping the numeric values of the constants defined in this module back to name strings, allowing more human-readable representation of parse trees to be generated.

ISTERMINAL(*x*)

Return true for terminal token values.

ISNONTERMINAL(*x*)

Return true for non-terminal token values.

ISEOF(*x*)

Return true if *x* is the marker indicating the end of input.

See Also:

[Module parser](#) (section 3.16):
second example uses this module

3.19 keyword — Testing for Python keywords

This module allows a Python program to determine if a string is a keyword. A single function is provided:

iskeyword(*s*)

Return true if *s* is a Python keyword.

3.20 tokenize — Tokenizer for Python source

The `tokenize` module provides a lexical scanner for Python source code, implemented in Python. The scanner in this module returns comments as tokens as well, making it useful for implementing “pretty-printers,” including colorizers for on-screen displays.

The scanner is exposed by a single function:

tokenize(*readline*[, *tokeneater*])

The `tokenize()` function accepts two parameters: one representing the input stream, and one providing an output mechanism for `tokenize()`.

The first parameter, *readline*, must be a callable object which provides the same interface as the `readline()`

method of built-in file objects (see section 2.1.7). Each call to the function should return one line of input as a string.

The second parameter, *tokeneater*, must also be a callable object. It is called with five parameters: the token type, the token string, a tuple (*srow*, *scol*) specifying the row and column where the token begins in the source, a tuple (*erow*, *ecol*) giving the ending position of the token, and the line on which the token was found. The line passed is the *logical* line; continuation lines are included.

All constants from the `token` module are also exported from `tokenize`, as is one additional token type value that might be passed to the *tokeneater* function by `tokenize()`:

COMMENT

Token value used to indicate a comment.

3.21 `tabnanny` — Detection of ambiguous indentation

For the time being this module is intended to be called as a script. However it is possible to import it into an IDE and use the function `check()` described below.

Warning: The API provided by this module is likely to change in future releases; such changes may not be backward compatible.

check(*file_or_dir*)

If *file_or_dir* is a directory and not a symbolic link, then recursively descend the directory tree named by *file_or_dir*, checking all `.py` files along the way. If *file_or_dir* is an ordinary Python source file, it is checked for whitespace related problems. The diagnostic messages are written to standard output using the `print` statement.

verbose

Flag indicating whether to print verbose messages. This is set to true by the `-v` option if called as a script.

filename_only

Flag indicating whether to print only the filenames of files containing whitespace related problems. This is set to true by the `-q` option if called as a script.

NannyNag

Raised by `tokeneater()` if detecting an ambiguous indent. Captured and handled in `check()`.

tokeneater(*type*, *token*, *start*, *end*, *line*)

This function is used by `check()` as a callback parameter to the function `tokenize.tokenize()`.

See Also:

Module `tokenize` (section 3.20):

Lexical scanner for Python source code.

3.22 `pyclbr` — Python class browser support

The `pyclbr` can be used to determine some limited information about the classes and methods defined in a module. The information provided is sufficient to implement a traditional three-pane class browser. The information is extracted from the source code rather than from an imported module, so this module is safe to use with untrusted source code. This restriction makes it impossible to use this module with modules not implemented in Python, including many standard and optional extension modules.

readmodule(*module*[, *path*])

Read a module and return a dictionary mapping class names to class descriptor objects. The parameter *module* should be the name of a module as a string; it may be the name of a module within a package. The *path* parameter

should be a sequence, and is used to augment the value of `sys.path`, which is used to locate module source code.

3.22.1 Class Descriptor Objects

The class descriptor objects used as values in the dictionary returned by `readmodule()` provide the following data members:

module

The name of the module defining the class described by the class descriptor.

name

The name of the class.

super

A list of class descriptors which describe the immediate base classes of the class being described. Classes which are named as superclasses but which are not discoverable by `readmodule()` are listed as a string with the class name instead of class descriptors.

methods

A dictionary mapping method names to line numbers.

file

Name of the file containing the class statement defining the class.

lineno

The line number of the class statement within the file named by `file`.

3.23 code — Interpreter base classes

The `code` module provides facilities to implement read-eval-print loops in Python. Two classes and convenience functions are included which can be used to build applications which provide an interactive interpreter prompt.

InteractiveInterpreter([*locals*])

This class deals with parsing and interpreter state (the user's namespace); it does not deal with input buffering or prompting or input file naming (the filename is always passed in explicitly). The optional *locals* argument specifies the dictionary in which code will be executed; it defaults to a newly created dictionary with key `'__name__'` set to `'__console__'` and key `'__doc__'` set to `None`.

InteractiveConsole([*locals* [, *filename*]])

Closely emulate the behavior of the interactive Python interpreter. This class builds on `InteractiveInterpreter` and adds prompting using the familiar `sys.ps1` and `sys.ps2`, and input buffering.

interact([*banner* [, *readfunc* [, *local*]]])

Convenience function to run a read-eval-print loop. This creates a new instance of `InteractiveConsole` and sets *readfunc* to be used as the `raw_input()` method, if provided. If *local* is provided, it is passed to the `InteractiveConsole` constructor for use as the default namespace for the interpreter loop. The `interact()` method of the instance is then run with *banner* passed as the banner to use, if provided. The console object is discarded after use.

compile_command(*source* [, *filename* [, *symbol*]])

This function is useful for programs that want to emulate Python's interpreter main loop (a.k.a. the read-eval-print loop). The tricky part is to determine when the user has entered an incomplete command that can be completed by entering more text (as opposed to a complete command or a syntax error). This function *almost* always makes the same decision as the real interpreter main loop.

source is the source string; *filename* is the optional filename from which source was read, defaulting to `'<input>'`; and *symbol* is the optional grammar start symbol, which should be either `'single'` (the default) or

`'eval'`.

Returns a code object (the same as `compile(source, filename, symbol)`) if the command is complete and valid; `None` if the command is incomplete; raises `SyntaxError` if the command is complete and contains a syntax error, or raises `OverflowError` if the command includes a numeric constant which exceeds the range of the appropriate numeric type.

3.23.1 Interactive Interpreter Objects

runsource(*source*[, *filename*[, *symbol*]])

Compile and run some source in the interpreter. Arguments are the same as for `compile_command()`; the default for *filename* is `'<input>'`, and for *symbol* is `'single'`. One several things can happen:

- The input is incorrect; `compile_command()` raised an exception (`SyntaxError` or `OverflowError`). A syntax traceback will be printed by calling the `showsyntaxerror()` method. `runsource()` returns 0.
- The input is incomplete, and more input is required; `compile_command()` returned `None`. `runsource()` returns 1.
- The input is complete; `compile_command()` returned a code object. The code is executed by calling the `runcode()` (which also handles run-time exceptions, except for `SystemExit`). `runsource()` returns 0.

The return value can be used to decide whether to use `sys.ps1` or `sys.ps2` to prompt the next line.

runcode(*code*)

Execute a code object. When an exception occurs, `showtraceback()` is called to display a traceback. All exceptions are caught except `SystemExit`, which is allowed to propagate.

A note about `KeyboardInterrupt`: this exception may occur elsewhere in this code, and may not always be caught. The caller should be prepared to deal with it.

showsyntaxerror([*filename*])

Display the syntax error that just occurred. This does not display a stack trace because there isn't one for syntax errors. If *filename* is given, it is stuffed into the exception instead of the default filename provided by Python's parser, because it always uses `'<string>'` when reading from a string. The output is written by the `write()` method.

showtraceback()

Display the exception that just occurred. We remove the first stack item because it is within the interpreter object implementation. The output is written by the `write()` method.

write(*data*)

Write a string to standard output. Derived classes should override this to provide the appropriate output handling as needed.

3.23.2 Interactive Console Objects

The `InteractiveConsole` class is a subclass of `InteractiveInterpreter`, and so offers all the methods of the interpreter objects as well as the following additions.

interact([*banner*])

Closely emulate the interactive Python console. The optional banner argument specify the banner to print before the first interaction; by default it prints a banner similar to the one printed by the standard Python interpreter, followed by the class name of the console object in parentheses (so as not to confuse this with the real interpreter – since it's so close!).

push(*line*)

Push a line of source text to the interpreter. The line should not have a trailing newline; it may have internal newlines. The line is appended to a buffer and the interpreter's `runsource()` method is called with the concatenated contents of the buffer as source. If this indicates that the command was executed or invalid, the buffer is reset; otherwise, the command is incomplete, and the buffer is left as it was after the line was appended. The return value is 1 if more input is required, 0 if the line was dealt with in some way (this is the same as `runsource()`).

resetbuffer()

Remove any unhandled source text from the input buffer.

raw_input([*prompt*])

Write a prompt and read a line. The returned line does not include the trailing newline. When the user enters the EOF key sequence, `EOFError` is raised. The base implementation uses the built-in function `raw_input()`; a subclass may replace this with a different implementation.

3.24 codeop — Compile Python code

The `codeop` module provides a function to compile Python code with hints on whether it is certainly complete, possibly complete or definitely incomplete. This is used by the `code` module and should not normally be used directly.

The `codeop` module defines the following function:

compile_command(*source*[, *filename*[, *symbol*]])

Tries to compile *source*, which should be a string of Python code and return a code object if *source* is valid Python code. In that case, the filename attribute of the code object will be *filename*, which defaults to '<input>'. Returns None if *source* is not valid Python code, but is a prefix of valid Python code.

If there is a problem with *source*, an exception will be raised. `SyntaxError` is raised if there is invalid Python syntax, and `OverflowError` if there is an invalid numeric constant.

The *symbol* argument determines whether *source* is compiled as a statement ('single', the default) or as an expression ('eval'). Any other value will cause `ValueError` to be raised.

Caveat: It is possible (but not likely) that the parser stops parsing with a successful outcome before reaching the end of the source; in this case, trailing symbols may be ignored instead of causing an error. For example, a backslash followed by two newlines may be followed by arbitrary garbage. This will be fixed once the API for the parser is better.

3.25 pprint — Data pretty printer.

The `pprint` module provides a capability to “pretty-print” arbitrary Python data structures in a form which can be used as input to the interpreter. If the formatted structures include objects which are not fundamental Python types, the representation may not be loadable. This may be the case if objects such as files, sockets, classes, or instances are included, as well as many other builtin objects which are not representable as Python constants.

The formatted representation keeps objects on a single line if it can, and breaks them onto multiple lines if they don't fit within the allowed width. Construct `PrettyPrinter` objects explicitly if you need to adjust the width constraint.

The `pprint` module defines one class:

PrettyPrinter(...)

Construct a `PrettyPrinter` instance. This constructor understands several keyword parameters. An output stream may be set using the *stream* keyword; the only method used on the stream object is the file protocol's `write()` method. If not specified, the `PrettyPrinter` adopts `sys.stdout`. Three additional parameters may be used to control the formatted representation. The keywords are *indent*, *depth*, and *width*. The amount

of indentation added for each recursive level is specified by *indent*; the default is one. Other values can cause output to look a little odd, but can make nesting easier to spot. The number of levels which may be printed is controlled by *depth*; if the data structure being printed is too deep, the next contained level is replaced by `'...'`. By default, there is no constraint on the depth of the objects being formatted. The desired output width is constrained using the *width* parameter; the default is eighty characters. If a structure cannot be formatted within the constrained width, a best effort will be made.

```
>>> import pprint, sys
>>> stuff = sys.path[:]
>>> stuff.insert(0, stuff[:])
>>> pp = pprint.PrettyPrinter(indent=4)
>>> pp.pprint(stuff)
[ [ ' ',
    '/usr/local/lib/python1.5',
    '/usr/local/lib/python1.5/test',
    '/usr/local/lib/python1.5/sunos5',
    '/usr/local/lib/python1.5/sharedmodules',
    '/usr/local/lib/python1.5/tkinter' ],
  ' ',
  '/usr/local/lib/python1.5',
  '/usr/local/lib/python1.5/test',
  '/usr/local/lib/python1.5/sunos5',
  '/usr/local/lib/python1.5/sharedmodules',
  '/usr/local/lib/python1.5/tkinter' ]
>>>
>>> import parser
>>> tup = parser.ast2tuple(
...     parser.suite(open('pprint.py').read()))[1][1][1]
>>> pp = pprint.PrettyPrinter(depth=6)
>>> pp.pprint(tup)
(266, (267, (307, (287, (288, (...))))))
```

The `PrettyPrinter` class supports several derivative functions:

`pformat(object)`

Return the formatted representation of *object* as a string. The default parameters for formatting are used.

`pprint(object[, stream])`

Prints the formatted representation of *object* on *stream*, followed by a newline. If *stream* is omitted, `sys.stdout` is used. This may be used in the interactive interpreter instead of a `print` statement for inspecting values. The default parameters for formatting are used.

```
>>> stuff = sys.path[:]
>>> stuff.insert(0, stuff)
>>> pprint.pprint(stuff)
[<Recursion on list with id=869440>,
  ' ',
  '/usr/local/lib/python1.5',
  '/usr/local/lib/python1.5/test',
  '/usr/local/lib/python1.5/sunos5',
  '/usr/local/lib/python1.5/sharedmodules',
  '/usr/local/lib/python1.5/tkinter' ]
```

`isreadable(object)`

Determine if the formatted representation of *object* is “readable,” or can be used to reconstruct the value using `eval()`. This always returns false for recursive objects.

```
>>> pprint.isreadable(stuff)
0
```

isrecursive(*object*)

Determine if *object* requires a recursive representation.

One more support function is also defined:

saferepr(*object*)

Return a string representation of *object*, protected against recursive data structures. If the representation of *object* exposes a recursive entry, the recursive reference will be represented as ‘<Recursion on *typename* with *id=number*>’. The representation is not otherwise formatted.

```
>>> pprint.saferepr(stuff)
" [<Recursion on list with id=682968>, '', '/usr/local/lib/python1.5', '/usr/local/lib/python1.5/test', '/usr/local/lib/python1.5/sunos5', '/usr/local/lib/python1.5/sharedmodules', '/usr/local/lib/python1.5/tkinter'] "
```

3.25.1 PrettyPrinter Objects

PrettyPrinter instances have the following methods:

pformat(*object*)

Return the formatted representation of *object*. This takes into Account the options passed to the PrettyPrinter constructor.

pprint(*object*)

Print the formatted representation of *object* on the configured stream, followed by a newline.

The following methods provide the implementations for the corresponding functions of the same names. Using these methods on an instance is slightly more efficient since new PrettyPrinter objects don't need to be created.

isreadable(*object*)

Determine if the formatted representation of the object is “readable,” or can be used to reconstruct the value using `eval()`. Note that this returns false for recursive objects. If the *depth* parameter of the PrettyPrinter is set and the object is deeper than allowed, this returns false.

isrecursive(*object*)

Determine if the object requires a recursive representation.

3.26 repr — Alternate repr() implementation.

The `repr` module provides a means for producing object representations with limits on the size of the resulting strings. This is used in the Python debugger and may be useful in other contexts as well.

This module provides a class, an instance, and a function:

Repr()

Class which provides formatting services useful in implementing functions similar to the built-in `repr()`; size limits for different object types are added to avoid the generation of representations which are excessively long.

aRepr

This is an instance of `Repr` which is used to provide the `repr()` function described below. Changing the attributes of this object will affect the size limits used by `repr()` and the Python debugger.

repr(*obj*)

This is the `repr()` method of `aRepr`. It returns a string similar to that returned by the built-in function of the same name, but with limits on most sizes.

3.26.1 Repr Objects

`Repr` instances provide several members which can be used to provide size limits for the representations of different object types, and methods which format specific object types.

maxlevel

Depth limit on the creation of recursive representations. The default is 6.

maxdict

maxlist

maxtuple

Limits on the number of entries represented for the named object type. The default for `maxdict` is 4, for the others, 6.

maxlong

Maximum number of characters in the representation for a long integer. Digits are dropped from the middle. The default is 40.

maxstring

Limit on the number of characters in the representation of the string. Note that the “normal” representation of the string is used as the character source: if escape sequences are needed in the representation, these may be mangled when the representation is shortened. The default is 30.

maxother

This limit is used to control the size of object types for which no specific formatting method is available on the `Repr` object. It is applied in a similar manner as `maxstring`. The default is 20.

repr(*obj*)

The equivalent to the built-in `repr()` that uses the formatting imposed by the instance.

repr1(*obj*, *level*)

Recursive implementation used by `repr()`. This uses the type of *obj* to determine which formatting method to call, passing it *obj* and *level*. The type-specific methods should call `repr1()` to perform recursive formatting, with *level* - 1 for the value of *level* in the recursive call.

repr_type(*obj*, *level*)

Formatting methods for specific types are implemented as methods with a name based on the type name. In the method name, *type* is replaced by `string.join(string.split(type(obj).__name__, '_'))`. Dispatch to these methods is handled by `repr1()`. Type-specific methods which need to recursively format a value should call `'self.repr1(subobj, level - 1)'`.

3.26.2 Subclassing Repr Objects

The use of dynamic dispatching by `Repr.repr1()` allows subclasses of `Repr` to add support for additional built-in object types or to modify the handling of types already supported. This example shows how special support for file objects could be added:

```

import repr
import sys

class MyRepr(repr.Repr):
    def repr_file(self, obj, level):
        if obj.name in ['<stdin>', '<stdout>', '<stderr>']:
            return obj.name
        else:
            return `obj`

aRepr = MyRepr()
print aRepr.repr(sys.stdin)          # prints '<stdin>'

```

3.27 `py_compile` — Compile Python source files

The `py_compile` module provides a single function to generate a byte-code file from a source file.

Though not often needed, this function can be useful when installing modules for shared use, especially if some of the users may not have permission to write the byte-code cache files in the directory containing the source code.

`compile`(*file*[, *cfile*[, *dfile*]])

Compile a source file to byte-code and write out the byte-code cache file. The source code is loaded from the file name *file*. The byte-code is written to *cfile*, which defaults to *file* + 'c' ('o' if optimization is enabled in the current interpreter). If *dfile* is specified, it is used as the name of the source file in error messages instead of *file*.

See Also:

[Module `compileall`](#) (section 3.28):

Utilities to compile all Python source files in a directory tree.

3.28 `compileall` — Byte-compile Python libraries

This module provides some utility functions to support installing Python libraries. These functions compile Python source files in a directory tree, allowing users without permission to write to the libraries to take advantage of cached byte-code files.

The source file for this module may also be used as a script to compile Python sources in directories named on the command line or in `sys.path`.

`compile_dir`(*dir*[, *maxlevels*[, *ddir*[, *force*]])

Recursively descend the directory tree named by *dir*, compiling all '.py' files along the way. The *maxlevels* parameter is used to limit the depth of the recursion; it defaults to 10. If *ddir* is given, it is used as the base path from which the filenames used in error messages will be generated. If *force* is true, modules are re-compiled even if the timestamps are up to date.

`compile_path`([*skip_curdir*[, *maxlevels*[, *force*]])

Byte-compile all the '.py' files found along `sys.path`. If *skip_curdir* is true (the default), the current directory is not included in the search. The *maxlevels* and *force* parameters default to 0 and are passed to the `compile_dir()` function.

See Also:

[Module `py_compile`](#) (section 3.27):

Byte-compile a single source file.

3.29 `dis` — Disassembler.

The `dis` module supports the analysis of Python byte code by disassembling it. Since there is no Python assembler, this module defines the Python assembly language. The Python byte code which this module takes as an input is defined in the file ‘`Include/opcode.h`’ and used by the compiler and the interpreter.

Example: Given the function `myfunc`:

```
def myfunc(alist):
    return len(alist)
```

the following command can be used to get the disassembly of `myfunc()`:

```
>>> dis.dis(myfunc)
      0 SET_LINENO          1
      3 SET_LINENO          2
      6 LOAD_GLOBAL         0 (len)
      9 LOAD_FAST           0 (alist)
     12 CALL_FUNCTION        1
     15 RETURN_VALUE
     16 LOAD_CONST          0 (None)
     19 RETURN_VALUE
```

The `dis` module defines the following functions:

`dis`([*bytestr*])

Disassemble the *bytestr* object. *bytestr* can denote either a class, a method, a function, or a code object. For a class, it disassembles all methods. For a single code sequence, it prints one line per byte code instruction. If no object is provided, it disassembles the last traceback.

`distb`([*tb*])

Disassembles the top-of-stack function of a traceback, using the last traceback if none was passed. The instruction causing the exception is indicated.

`disassemble`(*code*[, *lasti*])

Disassembles a code object, indicating the last instruction if *lasti* was provided. The output is divided in the following columns:

- 1.the current instruction, indicated as ‘-->’,
- 2.a labelled instruction, indicated with ‘>>’,
- 3.the address of the instruction,
- 4.the operation code name,
- 5.operation parameters, and
- 6.interpretation of the parameters in parentheses.

The parameter interpretation recognizes local and global variable names, constant values, branch targets, and compare operators.

disco(*code*[, *lasti*])

A synonym for `disassemble`. It is more convenient to type, and kept for compatibility with earlier Python releases.

opname

Sequence of operation names, indexable using the byte code.

cmp_op

Sequence of all compare operation names.

hasconst

Sequence of byte codes that have a constant parameter.

hasname

Sequence of byte codes that access an attribute by name.

hasjrel

Sequence of byte codes that have a relative jump target.

hasjabs

Sequence of byte codes that have an absolute jump target.

haslocal

Sequence of byte codes that access a local variable.

hascompare

Sequence of byte codes of boolean operations.

3.29.1 Python Byte Code Instructions

The Python compiler currently generates the following byte code instructions.

STOP_CODE

Indicates end-of-code to the compiler, not used by the interpreter.

POP_TOP

Removes the top-of-stack (TOS) item.

ROT_TWO

Swaps the two top-most stack items.

ROT_THREE

Lifts second and third stack item one position up, moves top down to position three.

DUP_TOP

Duplicates the reference on top of the stack.

Unary Operations take the top of the stack, apply the operation, and push the result back on the stack.

UNARY_POSITIVE

Implements $TOS = +TOS$.

UNARY_NEG

Implements $TOS = -TOS$.

UNARY_NOT

Implements $TOS = \text{not } TOS$.

UNARY_CONVERT

Implements $TOS = `TOS`$.

UNARY_INVERT

Implements $TOS = \sim TOS$.

Binary operations remove the top of the stack (TOS) and the second top-most stack item (TOS1) from the stack. They perform the operation, and put the result back on the stack.

BINARY_POWER

Implements $TOS = TOS1 ** TOS$.

BINARY_MULTIPLY

Implements $TOS = TOS1 * TOS$.

BINARY_DIVIDE

Implements $TOS = TOS1 / TOS$.

BINARY_MODULO

Implements $TOS = TOS1 \%TOS$.

BINARY_ADD

Implements $TOS = TOS1 + TOS$.

BINARY_SUBTRACT

Implements $TOS = TOS1 - TOS$.

BINARY_SUBSCR

Implements $TOS = TOS1[TOS]$.

BINARY_LSHIFT

Implements $TOS = TOS1 \ll TOS$.

BINARY_RSHIFT

Implements $TOS = TOS1 \gg TOS$.

BINARY_AND

Implements $TOS = TOS1 \text{ and } TOS$.

BINARY_XOR

Implements $TOS = TOS1 \wedge TOS$.

BINARY_OR

Implements $TOS = TOS1 \text{ or } TOS$.

The slice opcodes take up to three parameters.

SLICE+0

Implements $TOS = TOS[:]$.

SLICE+1

Implements $TOS = TOS1[TOS:]$.

SLICE+2

Implements $TOS = TOS1[:TOS1]$.

SLICE+3

Implements $TOS = TOS2[TOS1:TOS]$.

Slice assignment needs even an additional parameter. As any statement, they put nothing on the stack.

STORE_SLICE+0

Implements $TOS[:] = TOS1$.

STORE_SLICE+1

Implements $TOS1[TOS:] = TOS2$.

STORE_SLICE+2

Implements $TOS1[:TOS] = TOS2$.

STORE_SLICE+3

Implements `TOS2[TOS1:TOS] = TOS3`.

DELETE_SLICE+0

Implements `del TOS[:]`.

DELETE_SLICE+1

Implements `del TOS1[TOS:]`.

DELETE_SLICE+2

Implements `del TOS1[:TOS]`.

DELETE_SLICE+3

Implements `del TOS2[TOS1:TOS]`.

STORE_SUBSCR

Implements `TOS1[TOS] = TOS2`.

DELETE_SUBSCR

Implements `del TOS1[TOS]`.

PRINT_EXPR

Implements the expression statement for the interactive mode. `TOS` is removed from the stack and printed. In non-interactive mode, an expression statement is terminated with `POP_STACK`.

PRINT_ITEM

Prints `TOS`. There is one such instruction for each item in the print statement.

PRINT_NEWLINE

Prints a new line on `sys.stdout`. This is generated as the last operation of a print statement, unless the statement ends with a comma.

BREAK_LOOP

Terminates a loop due to a break statement.

LOAD_LOCALS

Pushes a reference to the locals of the current scope on the stack. This is used in the code for a class definition: After the class body is evaluated, the locals are passed to the class definition.

RETURN_VALUE

Returns with `TOS` to the caller of the function.

EXEC_STMT

Implements `exec TOS2, TOS1, TOS`. The compiler fills missing optional parameters with `None`.

POP_BLOCK

Removes one block from the block stack. Per frame, there is a stack of blocks, denoting nested loops, try statements, and such.

END_FINALLY

Terminates a finally-block. The interpreter recalls whether the exception has to be re-raised, or whether the function returns, and continues with the outer-next block.

BUILD_CLASS

Creates a new class object. `TOS` is the methods dictionary, `TOS1` the tuple of the names of the base classes, and `TOS2` the class name.

All of the following opcodes expect arguments. An argument is two bytes, with the more significant byte last.

STORE_NAME *namei*

Implements `name = TOS`. *namei* is the index of *name* in the attribute `co_names` of the code object. The compiler tries to use `STORE_LOCAL` or `STORE_GLOBAL` if possible.

DELETE_NAME *namei*

Implements `del name`, where *namei* is the index into `co_names` attribute of the code object.

UNPACK_TUPLE *count*
 Unpacks TOS into *count* individual values, which are put onto the stack right-to-left.

UNPACK_LIST *count*
 Unpacks TOS into *count* individual values.

STORE_ATTR *namei*
 Implements `TOS.name = TOS1`, where *namei* is the index of name in `co_names`.

DELETE_ATTR *namei*
 Implements `del TOS.name`, using *namei* as index into `co_names`.

STORE_GLOBAL *namei*
 Works as `STORE_NAME`, but stores the name as a global.

DELETE_GLOBAL *namei*
 Works as `DELETE_NAME`, but deletes a global name.

LOAD_CONST *consti*
 Pushes `'co_consts[consti]'` onto the stack.

LOAD_NAME *namei*
 Pushes the value associated with `'co_names[namei]'` onto the stack.

BUILD_TUPLE *count*
 Creates a tuple consuming *count* items from the stack, and pushes the resulting tuple onto the stack.

BUILD_LIST *count*
 Works as `BUILD_TUPLE`, but creates a list.

BUILD_MAP *zero*
 Pushes an empty dictionary object onto the stack. The argument is ignored and set to zero by the compiler.

LOAD_ATTR *namei*
 Replaces TOS with `getattr(TOS, co_names[namei])`.

COMPARE_OP *opname*
 Performs a boolean operation. The operation name can be found in `cmp_op[opname]`.

IMPORT_NAME *namei*
 Imports the module `co_names[namei]`. The module object is pushed onto the stack. The current name space is not affected: for a proper import statement, a subsequent `STORE_FAST` instruction modifies the name space.

IMPORT_FROM *namei*
 Imports the attribute `co_names[namei]`. The module to import from is found in TOS and left there.

JUMP_FORWARD *delta*
 Increments byte code counter by *delta*.

JUMP_IF_TRUE *delta*
 If TOS is true, increment the byte code counter by *delta*. TOS is left on the stack.

JUMP_IF_FALSE *delta*
 If TOS is false, increment the byte code counter by *delta*. TOS is not changed.

JUMP_ABSOLUTE *target*
 Set byte code counter to *target*.

FOR_LOOP *delta*
 Iterate over a sequence. TOS is the current index, TOS1 the sequence. First, the next element is computed. If the sequence is exhausted, increment byte code counter by *delta*. Otherwise, push the sequence, the incremented counter, and the current item onto the stack.

LOAD_GLOBAL *namei*

Loads the global named `co_names[namei]` onto the stack.

SETUP_LOOP *delta*

Pushes a block for a loop onto the block stack. The block spans from the current instruction with a size of *delta* bytes.

SETUP_EXCEPT *delta*

Pushes a try block from a try-except clause onto the block stack. *delta* points to the first except block.

SETUP_FINALLY *delta*

Pushes a try block from a try-except clause onto the block stack. *delta* points to the finally block.

LOAD_FAST *var_num*

Pushes a reference to the local `co_varnames[var_num]` onto the stack.

STORE_FAST *var_num*

Stores TOS into the local `co_varnames[var_num]`.

DELETE_FAST *var_num*

Deletes local `co_varnames[var_num]`.

SET_LINENO *lineno*

Sets the current line number to *lineno*.

RAISE_VARARGS *argc*

Raises an exception. *argc* indicates the number of parameters to the raise statement, ranging from 1 to 3. The handler will find the traceback as TOS2, the parameter as TOS1, and the exception as TOS.

CALL_FUNCTION *argc*

Calls a function. The low byte of *argc* indicates the number of positional parameters, the high byte the number of keyword parameters. On the stack, the opcode finds the keyword parameters first. For each keyword argument, the value is on top of the key. Below the keyword parameters, the positional parameters are on the stack, with the right-most parameter on top. Below the parameters, the function object to call is on the stack.

MAKE_FUNCTION *argc*

Pushes a new function object on the stack. TOS is the code associated with the function. The function object is defined to have *argc* default parameters, which are found below TOS.

BUILD_SLICE *argc*

Pushes a slice object on the stack. *argc* must be 2 or 3. If it is 2, `slice(TOS1, TOS)` is pushed; if it is 3, `slice(TOS2, TOS1, TOS)` is pushed. See the `slice()` built-in function.

3.30 new — Runtime implementation object creation

The new module allows an interface to the interpreter object creation functions. This is for use primarily in marshal-type functions, when a new object needs to be created “magically” and not by using the regular creation functions. This module provides a low-level interface to the interpreter, so care must be exercised when using this module.

The new module defines the following functions:

instance(*class*, *dict*)

This function creates an instance of *class* with dictionary *dict* without calling the `__init__()` constructor. Note that there are no guarantees that the object will be in a consistent state.

instancemethod(*function*, *instance*, *class*)

This function will return a method object, bound to *instance*, or unbound if *instance* is `None`. *function* must be callable, and *instance* must be an instance object or `None`.

function(*code*, *globals*[, *name*[*argdefs*]])

Returns a (Python) function with the given code and globals. If *name* is given, it must be a string or `None`. If it is

a string, the function will have the given name, otherwise the function name will be taken from `code.co_name`. If `argdefs` is given, it must be a tuple and will be used to determine the default values of parameters.

code(*argcount, nlocals, stacksize, flags, codestring, constants, names, varnames, filename, name, firstlineno, lnotab*)
This function is an interface to the `PyCode_New()` C function.

module(*name*)
This function returns a new module object with name *name*. *name* must be a string.

classobj(*name, baseclasses, dict*)
This function returns a new class object, with name *name*, derived from *baseclasses* (which should be a tuple of classes) and with namespace *dict*.

3.31 site — Site-specific configuration hook

This module is automatically imported during initialization.

In earlier versions of Python (up to and including 1.5a3), scripts or modules that needed to use site-specific modules would place `import site` somewhere near the top of their code. This is no longer necessary.

This will append site-specific paths to the module search path.

It starts by constructing up to four directories from a head and a tail part. For the head part, it uses `sys.prefix` and `sys.exec_prefix`; empty heads are skipped. For the tail part, it uses the empty string (on Macintosh or Windows) or it uses first `'lib/pythonversion/site-packages'` and then `'lib/site-python'` (on UNIX). For each of the distinct head-tail combinations, it sees if it refers to an existing directory, and if so, adds to `sys.path`, and also inspected for path configuration files.

A path configuration file is a file whose name has the form `'package.pth'`; its contents are additional items (one per line) to be added to `sys.path`. Non-existing items are never added to `sys.path`, but no check is made that the item refers to a directory (rather than a file). No item is added to `sys.path` more than once. Blank lines and lines beginning with `#` are skipped.

For example, suppose `sys.prefix` and `sys.exec_prefix` are set to `'/usr/local'`. The Python 1.6 library is then installed in `'/usr/local/lib/python1.5'` (note that only the first three characters of `sys.version` are used to form the path name). Suppose this has a subdirectory `'/usr/local/lib/python1.5/site-packages'` with three subdirectories, `'foo'`, `'bar'` and `'spam'`, and two path configuration files, `'foo.pth'` and `'bar.pth'`. Assume `'foo.pth'` contains the following:

```
# foo package configuration

foo
bar
bletch
```

and `'bar.pth'` contains:

```
# bar package configuration

bar
```

Then the following directories are added to `sys.path`, in this order:

```
/usr/local/lib/python1.5/site-packages/bar
/usr/local/lib/python1.5/site-packages/foo
```

Note that ‘bletch’ is omitted because it doesn’t exist; the ‘bar’ directory precedes the ‘foo’ directory because ‘bar.pth’ comes alphabetically before ‘foo.pth’; and ‘spam’ is omitted because it is not mentioned in either path configuration file.

After these path manipulations, an attempt is made to import a module named `sitecustomize`, which can perform arbitrary site-specific customizations. If this import fails with an `ImportError` exception, it is silently ignored.

Note that for some non-UNIX systems, `sys.prefix` and `sys.exec_prefix` are empty, and the path manipulations are skipped; however the import of `sitecustomize` is still attempted.

3.32 `user` — User-specific configuration hook

As a policy, Python doesn’t run user-specified code on startup of Python programs. (Only interactive sessions execute the script specified in the `$PYTHONSTARTUP` environment variable if it exists).

However, some programs or sites may find it convenient to allow users to have a standard customization file, which gets run when a program requests it. This module implements such a mechanism. A program that wishes to use the mechanism must execute the statement

```
import user
```

The `user` module looks for a file ‘.pythonrc.py’ in the user’s home directory and if it can be opened, executes it (using `execfile()` in its own (i.e. the module `user`’s) global namespace. Errors during this phase are not caught; that’s up to the program that imports the `user` module, if it wishes. The home directory is assumed to be named by the `$HOME` environment variable; if this is not set, the current directory is used.

The user’s ‘.pythonrc.py’ could conceivably test for `sys.version` if it wishes to do different things depending on the Python version.

A warning to users: be very conservative in what you place in your ‘.pythonrc.py’ file. Since you don’t know which programs will use it, changing the behavior of standard modules or functions is generally not a good idea.

A suggestion for programmers who wish to use this mechanism: a simple way to let users specify options for your package is to have them define variables in their ‘.pythonrc.py’ file that you test in your module. For example, a module `spam` that has a verbosity level can look for a variable `user.spam_verbosity`, as follows:

```
import user
try:
    verbosity = user.spam_verbosity # user’s verbosity preference
except AttributeError:
    verbosity = 0                  # default verbosity
```

Programs with extensive customization needs are better off reading a program-specific customization file.

Programs with security or privacy concerns should *not* import this module; a user can easily break into a program by placing arbitrary code in the ‘.pythonrc.py’ file.

Modules for general use should *not* import this module; it may interfere with the operation of the importing program.

See Also:

[Module `site`](#) (section 3.31):
site-wide customization mechanism

3.33 `__builtin__` — Built-in functions

This module provides direct access to all ‘built-in’ identifiers of Python; e.g. `__builtin__.open` is the full name for the built-in function `open()`. See section 2.3, “Built-in Functions.”

3.34 `__main__` — Top-level script environment.

This module represents the (otherwise anonymous) scope in which the interpreter’s main program executes — commands read either from standard input or from a script file.

String Services

The modules described in this chapter provide a wide range of string manipulation operations. Here's an overview:

<code>string</code>	Common string operations.
<code>re</code>	Perl-style regular expression search and match operations.
<code>regex</code>	Regular expression search and match operations.
<code>regex</code>	Regular expression search and match operations.
<code>regsub</code>	Substitution and splitting operations that use regular expressions.
<code>struct</code>	Interpret strings as packed binary data.
<code>fpformat</code>	General floating point formatting functions.
<code>StringIO</code>	Read and write strings as if they were files.
<code>cStringIO</code>	Faster version of <code>StringIO</code> , but not subclassable.
<code>codocs</code>	Encode and decode data and streams.

4.1 `string` — Common string operations

This module defines some constants useful for checking character classes and some useful string functions. See the module `re` for string functions based on regular expressions.

The constants defined in this module are:

`digits`

The string `'0123456789'`.

`hexdigits`

The string `'0123456789abcdefABCDEF'`.

`letters`

The concatenation of the strings `lowercase` and `uppercase` described below.

`lowercase`

A string containing all the characters that are considered lowercase letters. On most systems this is the string `'abcdefghijklmnopqrstuvwxyz'`. Do not change its definition — the effect on the routines `upper()` and `swapcase()` is undefined.

`octdigits`

The string `'01234567'`.

`uppercase`

A string containing all the characters that are considered uppercase letters. On most systems this is the string `'ABCDEFGHIJKLMNOPQRSTUVWXYZ'`. Do not change its definition — the effect on the routines `lower()` and `swapcase()` is undefined.

`whitespace`

A string containing all characters that are considered whitespace. On most systems this includes the characters

space, tab, linefeed, return, formfeed, and vertical tab. Do not change its definition — the effect on the routines `strip()` and `split()` is undefined.

The functions defined in this module are:

atof(*s*)

Convert a string to a floating point number. The string must have the standard syntax for a floating point literal in Python, optionally preceded by a sign ('+' or '-'). Note that this behaves identical to the built-in function `float()` when passed a string.

Note: When passing in a string, values for NaN and Infinity may be returned, depending on the underlying C library. The specific set of strings accepted which cause these values to be returned depends entirely on the C library and is known to vary.

atoi(*s*[, *base*])

Convert string *s* to an integer in the given *base*. The string must consist of one or more digits, optionally preceded by a sign ('+' or '-'). The *base* defaults to 10. If it is 0, a default base is chosen depending on the leading characters of the string (after stripping the sign): '0x' or '0X' means 16, '0' means 8, anything else means 10. If *base* is 16, a leading '0x' or '0X' is always accepted. Note that when invoked without *base* or with *base* set to 10, this behaves identical to the built-in function `int()` when passed a string. (Also note: for a more flexible interpretation of numeric literals, use the built-in function `eval()`.)

atol(*s*[, *base*])

Convert string *s* to a long integer in the given *base*. The string must consist of one or more digits, optionally preceded by a sign ('+' or '-'). The *base* argument has the same meaning as for `atoi()`. A trailing 'l' or 'L' is not allowed, except if the base is 0. Note that when invoked without *base* or with *base* set to 10, this behaves identical to the built-in function `long()` when passed a string.

capitalize(*word*)

Capitalize the first character of the argument.

capwords(*s*)

Split the argument into words using `split()`, capitalize each word using `capitalize()`, and join the capitalized words using `join()`. Note that this replaces runs of whitespace characters by a single space, and removes leading and trailing whitespace.

expandtabs(*s*, [*tabsize*])

Expand tabs in a string, i.e. replace them by one or more spaces, depending on the current column and the given tab size. The column number is reset to zero after each newline occurring in the string. This doesn't understand other non-printing characters or escape sequences. The tab size defaults to 8.

find(*s*, *sub*[, *start*[, *end*]])

Return the lowest index in *s* where the substring *sub* is found such that *sub* is wholly contained in *s*[*start*:*end*]. Return -1 on failure. Defaults for *start* and *end* and interpretation of negative values is the same as for slices.

rfind(*s*, *sub*[, *start*[, *end*]])

Like `find()` but find the highest index.

index(*s*, *sub*[, *start*[, *end*]])

Like `find()` but raise `ValueError` when the substring is not found.

rindex(*s*, *sub*[, *start*[, *end*]])

Like `rfind()` but raise `ValueError` when the substring is not found.

count(*s*, *sub*[, *start*[, *end*]])

Return the number of (non-overlapping) occurrences of substring *sub* in string *s*[*start*:*end*]. Defaults for *start* and *end* and interpretation of negative values is the same as for slices.

lower(*s*)

Return a copy of *s*, but with upper case letters converted to lower case.

maketrans(*from*, *to*)

Return a translation table suitable for passing to `translate()` or `regex.compile()`, that will map each character in *from* into the character at the same position in *to*; *from* and *to* must have the same length.

Warning: don't use strings derived from `lowercase` and `uppercase` as arguments; in some locales, these don't have the same length. For case conversions, always use `lower()` and `upper()`.

split(*s*[, *sep*[, *maxsplit*]])

Return a list of the words of the string *s*. If the optional second argument *sep* is absent or `None`, the words are separated by arbitrary strings of whitespace characters (space, tab, newline, return, formfeed). If the second argument *sep* is present and not `None`, it specifies a string to be used as the word separator. The returned list will then have one more item than the number of non-overlapping occurrences of the separator in the string. The optional third argument *maxsplit* defaults to 0. If it is nonzero, at most *maxsplit* number of splits occur, and the remainder of the string is returned as the final element of the list (thus, the list will have at most *maxsplit*+1 elements).

splitfields(*s*[, *sep*[, *maxsplit*]])

This function behaves identically to `split()`. (In the past, `split()` was only used with one argument, while `splitfields()` was only used with two arguments.)

join(*words*[, *sep*])

Concatenate a list or tuple of words with intervening occurrences of *sep*. The default value for *sep* is a single space character. It is always true that `'string.join(string.split(s, sep), sep)'` equals *s*.

joinfields(*words*[, *sep*])

This function behaves identical to `join()`. (In the past, `join()` was only used with one argument, while `joinfields()` was only used with two arguments.)

lstrip(*s*)

Return a copy of *s* but without leading whitespace characters.

rstrip(*s*)

Return a copy of *s* but without trailing whitespace characters.

strip(*s*)

Return a copy of *s* without leading or trailing whitespace.

swapcase(*s*)

Return a copy of *s*, but with lower case letters converted to upper case and vice versa.

translate(*s*, *table*[, *deletechars*])

Delete all characters from *s* that are in *deletechars* (if present), and then translate the characters using *table*, which must be a 256-character string giving the translation for each character value, indexed by its ordinal.

upper(*s*)

Return a copy of *s*, but with lower case letters converted to upper case.

ljust(*s*, *width*)

rjust(*s*, *width*)

center(*s*, *width*)

These functions respectively left-justify, right-justify and center a string in a field of given width. They return a string that is at least *width* characters wide, created by padding the string *s* with spaces until the given width on the right, left or both sides. The string is never truncated.

zfill(*s*, *width*)

Pad a numeric string on the left with zero digits until the given width is reached. Strings starting with a sign are handled correctly.

replace(*str*, *old*, *new*[, *maxsplit*])

Return a copy of string *str* with all occurrences of substring *old* replaced by *new*. If the optional argument *maxsplit* is given, the first *maxsplit* occurrences are replaced.

This module is implemented in Python. Much of its functionality has been reimplemented in the built-in module

`strop`. However, you should *never* import the latter module directly. When `string` discovers that `strop` exists, it transparently replaces parts of itself with the implementation from `strop`. After initialization, there is *no* overhead in using `string` instead of `strop`.

4.2 `re` — Perl-style regular expression operations.

This module provides regular expression matching operations similar to those found in Perl. It's 8-bit clean: the strings being processed may contain both null bytes and characters whose high bit is set. Regular expression pattern strings may not contain null bytes, but can specify the null byte using the `\number` notation. Characters with the high bit set may be included. The `re` module is always available.

Regular expressions use the backslash character (`\`) to indicate special forms or to allow special characters to be used without invoking their special meaning. This collides with Python's usage of the same character for the same purpose in string literals; for example, to match a literal backslash, one might have to write `'\\'` as the pattern string, because the regular expression must be `\"`, and each backslash must be expressed as `\"` inside a regular Python string literal.

The solution is to use Python's raw string notation for regular expression patterns; backslashes are not handled in any special way in a string literal prefixed with `r`. So `r"\n"` is a two-character string containing `\` and `n`, while `"\n"` is a one-character string containing a newline. Usually patterns will be expressed in Python code using this raw string notation.

4.2.1 Regular Expression Syntax

A regular expression (or RE) specifies a set of strings that matches it; the functions in this module let you check if a particular string matches a given regular expression (or if a given regular expression matches a particular string, which comes down to the same thing).

Regular expressions can be concatenated to form new regular expressions; if *A* and *B* are both regular expressions, then *AB* is also an regular expression. If a string *p* matches *A* and another string *q* matches *B*, the string *pq* will match *AB*. Thus, complex expressions can easily be constructed from simpler primitive expressions like the ones described here. For details of the theory and implementation of regular expressions, consult the Friedl book referenced below, or almost any textbook about compiler construction.

A brief explanation of the format of regular expressions follows. For further information and a gentler presentation, consult the Regular Expression HOWTO, accessible from <http://www.python.org/doc/howto/>.

Regular expressions can contain both special and ordinary characters. Most ordinary characters, like `'A'`, `'a'`, or `'0'`, are the simplest regular expressions; they simply match themselves. You can concatenate ordinary characters, so `[last]` matches the string `'last'`. (In the rest of this section, we'll write RE's in `[this special style]`, usually without quotes, and strings to be matched `'in single quotes'`.)

Some characters, like `'|'` or `'('`, are special. Special characters either stand for classes of ordinary characters, or affect how the regular expressions around them are interpreted.

The special characters are:

- `'.'` (Dot.) In the default mode, this matches any character except a newline. If the `DOTALL` flag has been specified, this matches any character including a newline.
- `'^'` (Caret.) Matches the start of the string, and in `MULTILINE` mode also matches immediately after each newline.
- `'$'` Matches the end of the string, and in `MULTILINE` mode also matches before a newline. `[foo]` matches both `'foo'` and `'foobar'`, while the regular expression `[foo$]` matches only `'foo'`.

- ‘*’ Causes the resulting RE to match 0 or more repetitions of the preceding RE, as many repetitions as are possible. `[ab*]` will match ‘a’, ‘ab’, or ‘a’ followed by any number of ‘b’s.
- ‘+’ Causes the resulting RE to match 1 or more repetitions of the preceding RE. `[ab+]` will match ‘a’ followed by any non-zero number of ‘b’s; it will not match just ‘a’.
- ‘?’ Causes the resulting RE to match 0 or 1 repetitions of the preceding RE. `[ab?]` will match either ‘a’ or ‘ab’.
- *?, +?, ?? The ‘*’, ‘+’, and ‘?’ qualifiers are all *greedy*; they match as much text as possible. Sometimes this behaviour isn’t desired; if the RE `[<. *>]` is matched against `<H1>title</H1>`, it will match the entire string, and not just `<H1>`. Adding ‘?’ after the qualifier makes it perform the match in *non-greedy* or *minimal* fashion; as few characters as possible will be matched. Using `[.*?]` in the previous expression will match only `<H1>`.
- {*m*, *n*} Causes the resulting RE to match from *m* to *n* repetitions of the preceding RE, attempting to match as many repetitions as possible. For example, `[a{3,5}]` will match from 3 to 5 ‘a’ characters. Omitting *n* specifies an infinite upper bound; you can’t omit *m*.
- {*m*, *n*}? Causes the resulting RE to match from *m* to *n* repetitions of the preceding RE, attempting to match as few repetitions as possible. This is the non-greedy version of the previous qualifier. For example, on the 6-character string `aaaaaa`, `[a{3,5}]` will match 5 ‘a’ characters, while `[a{3,5}?]` will only match 3 characters.
- ‘\’ Either escapes special characters (permitting you to match characters like ‘*’, ‘?’, and so forth), or signals a special sequence; special sequences are discussed below.

If you’re not using a raw string to express the pattern, remember that Python also uses the backslash as an escape sequence in string literals; if the escape sequence isn’t recognized by Python’s parser, the backslash and subsequent character are included in the resulting string. However, if Python would recognize the resulting sequence, the backslash should be repeated twice. This is complicated and hard to understand, so it’s highly recommended that you use raw strings for all but the simplest expressions.
- [] Used to indicate a set of characters. Characters can be listed individually, or a range of characters can be indicated by giving two characters and separating them by a ‘-’. Special characters are not active inside sets. For example, `[akm$]` will match any of the characters ‘a’, ‘k’, ‘m’, or ‘\$’; `[a-z]` will match any lowercase letter, and `[a-zA-Z0-9]` matches any letter or digit. Character classes such as `\w` or `\S` (defined below) are also acceptable inside a range. If you want to include a ‘]’ or a ‘-’ inside a set, precede it with a backslash, or place it as the first character. The pattern `[]]` will match ‘] ’, for example.

You can match the characters not within a range by *complementing* the set. This is indicated by including a ‘^’ as the first character of the set; ‘^’ elsewhere will simply match the ‘^’ character. For example, `[^5]` will match any character except ‘5’.
- ‘|’ `A|B`, where A and B can be arbitrary REs, creates a regular expression that will match either A or B. This can be used inside groups (see below) as well. To match a literal ‘|’, use `[\]`, or enclose it inside a character class, as in `[[|]]`.
- (. . .) Matches whatever regular expression is inside the parentheses, and indicates the start and end of a group; the contents of a group can be retrieved after a match has been performed, and can be matched later in the string with the `\number` special sequence, described below. To match the literals ‘(’ or ‘)’, use `[(]` or `[\)]`, or enclose them inside a character class: `[([])]`.
- (? . . .) This is an extension notation (a ‘?’ following a ‘(’ is not meaningful otherwise). The first character after the ‘?’ determines what the meaning and further syntax of the construct is. Extensions usually do not create a new group; `(? P <name> . . .)` is the only exception to this rule. Following are the currently supported extensions.

- (`?iLmsx`) (One or more letters from the set 'i', 'L', 'm', 's', 'x'.) The group matches the empty string; the letters set the corresponding flags (`re.I`, `re.L`, `re.M`, `re.S`, `re.X`) for the entire regular expression. This is useful if you wish to include the flags as part of the regular expression, instead of passing a *flag* argument to the `compile()` function.
- (`? : . . .`) A non-grouping version of regular parentheses. Matches whatever regular expression is inside the parentheses, but the substring matched by the group *cannot* be retrieved after performing a match or referenced later in the pattern.
- (`?P<name> . . .`) Similar to regular parentheses, but the substring matched by the group is accessible via the symbolic group name *name*. Group names must be valid Python identifiers. A symbolic group is also a numbered group, just as if the group were not named. So the group named 'id' in the example above can also be referenced as the numbered group 1.
 For example, if the pattern is `(?P<id>[a-zA-Z_]\w*)`, the group can be referenced by its name in arguments to methods of match objects, such as `m.group('id')` or `m.end('id')`, and also by name in pattern text (e.g. `(?P=id)`) and replacement text (e.g. `\g<id>`).
- (`?P=name`) Matches whatever text was matched by the earlier group named *name*.
- (`?# . . .`) A comment; the contents of the parentheses are simply ignored.
- (`?= . . .`) Matches if `[. . .]` matches next, but doesn't consume any of the string. This is called a lookahead assertion. For example, `Isaac (?=Asimov)` will match 'Isaac' only if it's followed by 'Asimov'.
- (`?! . . .`) Matches if `[. . .]` doesn't match next. This is a negative lookahead assertion. For example, `Isaac (?!Asimov)` will match 'Isaac' only if it's *not* followed by 'Asimov'.

The special sequences consist of `\` and a character from the list below. If the ordinary character is not on the list, then the resulting RE will match the second character. For example, `\$` matches the character '\$'.

- `\number` Matches the contents of the group of the same number. Groups are numbered starting from 1. For example, `(.+)\1` matches 'the the' or '55 55', but not 'the end' (note the space after the group). This special sequence can only be used to match one of the first 99 groups. If the first digit of *number* is 0, or *number* is 3 octal digits long, it will not be interpreted as a group match, but as the character with octal value *number*. Inside the '[' and ']' of a character class, all numeric escapes are treated as characters.
- `\A` Matches only at the start of the string.
- `\b` Matches the empty string, but only at the beginning or end of a word. A word is defined as a sequence of alphanumeric characters, so the end of a word is indicated by whitespace or a non-alphanumeric character. Inside a character range, `\b` represents the backspace character, for compatibility with Python's string literals.
- `\B` Matches the empty string, but only when it is *not* at the beginning or end of a word.
- `\d` Matches any decimal digit; this is equivalent to the set `[0-9]`.
- `\D` Matches any non-digit character; this is equivalent to the set `[^0-9]`.
- `\s` Matches any whitespace character; this is equivalent to the set `[\t\n\r\f\v]`.
- `\S` Matches any non-whitespace character; this is equivalent to the set `[^\t\n\r\f\v]`.
- `\w` When the `LOCALE` flag is not specified, matches any alphanumeric character; this is equivalent to the set `[a-zA-Z0-9_]`. With `LOCALE`, it will match the set `[0-9_]` plus whatever characters are defined as letters for the current locale.

`\W` When the `LOCALE` flag is not specified, matches any non-alphanumeric character; this is equivalent to the set `^[^a-zA-Z0-9_]`. With `LOCALE`, it will match any character not in the set `[0-9_]`, and not defined as a letter for the current locale.

`\Z` Matches only at the end of the string.

`\\` Matches a literal backslash.

4.2.2 Matching vs. Searching

Python offers two different primitive operations based on regular expressions: `match` and `search`. If you are accustomed to Perl's semantics, the `search` operation is what you're looking for. See the `search()` function and corresponding method of compiled regular expression objects.

Note that `match` may differ from `search` using a regular expression beginning with `^`: `^` matches only at the start of the string, or in `MULTILINE` mode also immediately following a newline. The “match” operation succeeds only if the pattern matches at the start of the string regardless of mode, or at the starting position given by the optional `pos` argument regardless of whether a newline precedes it.

```
re.compile("a").match("ba", 1)           # succeeds
re.compile("^a").search("ba", 1)         # fails; 'a' not at start
re.compile("^a").search("\na", 1)       # fails; 'a' not at start
re.compile("^a", re.M).search("\na", 1)  # succeeds
re.compile("^a", re.M).search("ba", 1)   # fails; no preceding \n
```

4.2.3 Module Contents

The module defines the following functions and constants, and an exception:

`compile(pattern[, flags])`

Compile a regular expression pattern into a regular expression object, which can be used for matching using its `match()` and `search()` methods, described below.

The expression's behaviour can be modified by specifying a `flags` value. Values can be any of the following variables, combined using bitwise OR (the `|` operator).

The sequence

```
prog = re.compile(pat)
result = prog.match(str)
```

is equivalent to

```
result = re.match(pat, str)
```

but the version using `compile()` is more efficient when the expression will be used several times in a single program.

I

IGNORECASE

Perform case-insensitive matching; expressions like `[A-Z]` will match lowercase letters, too. This is not affected by the current locale.

L

LOCALE

Make $\backslash w$, $\backslash W$, $\backslash b$, $\backslash B$, dependent on the current locale.

M

MULTILINE

When specified, the pattern character \wedge matches at the beginning of the string and at the beginning of each line (immediately following each newline); and the pattern character $\$$ matches at the end of the string and at the end of each line (immediately preceding each newline). By default, \wedge matches only at the beginning of the string, and $\$$ only at the end of the string and immediately before the newline (if any) at the end of the string.

S

DOTALL

Make the \cdot special character match any character at all, including a newline; without this flag, \cdot will match anything *except* a newline.

X

VERBOSE

This flag allows you to write regular expressions that look nicer. Whitespace within the pattern is ignored, except when in a character class or preceded by an unescaped backslash, and, when a line contains a $\#$ neither in a character class or preceded by an unescaped backslash, all characters from the leftmost such $\#$ through the end of the line are ignored.

search(*pattern*, *string*[, *flags*])

Scan through *string* looking for a location where the regular expression *pattern* produces a match, and return a corresponding `MatchObject` instance. Return `None` if no position in the string matches the pattern; note that this is different from finding a zero-length match at some point in the string.

match(*pattern*, *string*[, *flags*])

If zero or more characters at the beginning of *string* match the regular expression *pattern*, return a corresponding `MatchObject` instance. Return `None` if the string does not match the pattern; note that this is different from a zero-length match.

Note: If you want to locate a match anywhere in *string*, use `search()` instead.

split(*pattern*, *string*, [, *maxsplit* = 0])

Split *string* by the occurrences of *pattern*. If capturing parentheses are used in *pattern*, then the text of all groups in the pattern are also returned as part of the resulting list. If *maxsplit* is nonzero, at most *maxsplit* splits occur, and the remainder of the string is returned as the final element of the list. (Incompatibility note: in the original Python 1.5 release, *maxsplit* was ignored. This has been fixed in later releases.)

```
>>> re.split('\W+', 'Words, words, words.')
['Words', 'words', 'words', '']
>>> re.split('(\W+)', 'Words, words, words.')
['Words', ', ', ', ', 'words', ', ', ', ', 'words', ', .', '']
>>> re.split('\W+', 'Words, words, words.', 1)
['Words', 'words, words.']
```

This function combines and extends the functionality of the old `re.sub.split()` and `re.sub.splitx()`.

findall(*pattern*, *string*)

Return a list of all non-overlapping matches of *pattern* in *string*. If one or more groups are present in the pattern, return a list of groups; this will be a list of tuples if the pattern has more than one group. Empty matches are included in the result. New in version 1.5.2.

sub(*pattern*, *repl*, *string*[, *count* = 0])

Return the string obtained by replacing the leftmost non-overlapping occurrences of *pattern* in *string* by the replacement *repl*. If the pattern isn't found, *string* is returned unchanged. *repl* can be a string or a function; if a function, it is called for every non-overlapping occurrence of *pattern*. The function takes a single match object argument, and returns the replacement string. For example:

```
>>> def dashrepl(matchobj):
...     if matchobj.group(0) == '-': return ' '
...     else: return '-'
>>> re.sub('-{1,2}', dashrepl, 'pro---gram-files')
'pro--gram files'
```

The pattern may be a string or a regex object; if you need to specify regular expression flags, you must use a regex object, or use embedded modifiers in a pattern; e.g. `'sub("(?i)b+", "x", "bbbb BBBB")'` returns `'x x'`.

The optional argument *count* is the maximum number of pattern occurrences to be replaced; *count* must be a non-negative integer, and the default value of 0 means to replace all occurrences.

Empty matches for the pattern are replaced only when not adjacent to a previous match, so `'sub('x*', '-', 'abc')'` returns `'-a-b-c-'`.

If *repl* is a string, any backslash escapes in it are processed. That is, `'\n'` is converted to a single newline character, `'\r'` is converted to a linefeed, and so forth. Unknown escapes such as `'\j'` are left alone. Backreferences, such as `'\6'`, are replaced with the substring matched by group 6 in the pattern.

In addition to character escapes and backreferences as described above, `'\g<name>'` will use the substring matched by the group named *name*, as defined by the `'(?P<name>...)'` syntax. `'\g<number>'` uses the corresponding group number; `'\g<2>'` is therefore equivalent to `'\2'`, but isn't ambiguous in a replacement such as `'\g<2>0'`. `'\20'` would be interpreted as a reference to group 20, not a reference to group 2 followed by the literal character `'0'`.

subn(*pattern*, *repl*, *string*[, *count* = 0])

Perform the same operation as `sub()`, but return a tuple (*new_string*, *number_of_subs_made*).

escape(*string*)

Return *string* with all non-alphanumerics backslashed; this is useful if you want to match an arbitrary literal string that may have regular expression metacharacters in it.

error

Exception raised when a string passed to one of the functions here is not a valid regular expression (e.g., unmatched parentheses) or when some other error occurs during compilation or matching. It is never an error if a string contains no match for a pattern.

4.2.4 Regular Expression Objects

Compiled regular expression objects support the following methods and attributes:

search(*string*[, *pos*][, *endpos*])

Scan through *string* looking for a location where this regular expression produces a match, and return a corresponding `MatchObject` instance. Return `None` if no position in the string matches the pattern; note that this is different from finding a zero-length match at some point in the string.

The optional *pos* and *endpos* parameters have the same meaning as for the `match()` method.

match(*string*[, *pos*][, *endpos*])

If zero or more characters at the beginning of *string* match this regular expression, return a corresponding `MatchObject` instance. Return `None` if the string does not match the pattern; note that this is different from a zero-length match.

Note: If you want to locate a match anywhere in *string*, use `search()` instead.

The optional second parameter *pos* gives an index in the string where the search is to start; it defaults to 0. This is not completely equivalent to slicing the string; the `'^'` pattern character matches at the real beginning of the string and at positions just after a newline, but not necessarily at the index where the search is to start.

The optional parameter *endpos* limits how far the string will be searched; it will be as if the string is *endpos* characters long, so only the characters from *pos* to *endpos* will be searched for a match.

split(*string*, [*maxsplit* = 0])

Identical to the `split()` function, using the compiled pattern.

findall(*string*)

Identical to the `findall()` function, using the compiled pattern.

sub(*repl*, *string*, [*count* = 0])

Identical to the `sub()` function, using the compiled pattern.

subn(*repl*, *string*, [*count* = 0])

Identical to the `subn()` function, using the compiled pattern.

flags

The flags argument used when the regex object was compiled, or 0 if no flags were provided.

groupindex

A dictionary mapping any symbolic group names defined by `(?P<id>)` to group numbers. The dictionary is empty if no symbolic groups were used in the pattern.

pattern

The pattern string from which the regex object was compiled.

4.2.5 Match Objects

`MatchObject` instances support the following methods and attributes:

group([*group1*, *group2*, ...])

Returns one or more subgroups of the match. If there is a single argument, the result is a single string; if there are multiple arguments, the result is a tuple with one item per argument. Without arguments, *group1* defaults to zero (i.e. the whole match is returned). If a *groupN* argument is zero, the corresponding return value is the entire matching string; if it is in the inclusive range [1..99], it is the string matching the the corresponding parenthesized group. If a group number is negative or larger than the number of groups defined in the pattern, an `IndexError` exception is raised. If a group is contained in a part of the pattern that did not match, the corresponding result is `None`. If a group is contained in a part of the pattern that matched multiple times, the last match is returned.

If the regular expression uses the `(?P<name>...)` syntax, the *groupN* arguments may also be strings identifying groups by their group name. If a string argument is not used as a group name in the pattern, an `IndexError` exception is raised.

A moderately complicated example:

```
m = re.match(r"(?P<int>\d+)\.(\d*)", '3.14')
```

After performing this match, `m.group(1)` is `'3'`, as is `m.group('int')`, and `m.group(2)` is `'14'`.

groups([*default*])

Return a tuple containing all the subgroups of the match, from 1 up to however many groups are in the pattern. The *default* argument is used for groups that did not participate in the match; it defaults to `None`. (Incompatibility note: in the original Python 1.5 release, if the tuple was one element long, a string would be returned instead. In later versions (from 1.5.1 on), a singleton tuple is returned in such cases.)

groupdict([*default*])

Return a dictionary containing all the *named* subgroups of the match, keyed by the subgroup name. The *default* argument is used for groups that did not participate in the match; it defaults to `None`.

start([*group*])

end([*group*])

Return the indices of the start and end of the substring matched by *group*; *group* defaults to zero (meaning the whole matched substring). Return `None` if *group* exists but did not contribute to the match. For a match object *m*, and a group *g* that did contribute to the match, the substring matched by group *g* (equivalent to `m.group(g)`) is

```
m.string[m.start(g):m.end(g)]
```

Note that `m.start(group)` will equal `m.end(group)` if *group* matched a null string. For example, after `m = re.search('b(c?)', 'cba')`, `m.start(0)` is 1, `m.end(0)` is 2, `m.start(1)` and `m.end(1)` are both 2, and `m.start(2)` raises an `IndexError` exception.

span([*group*])

For `MatchObject` *m*, return the 2-tuple (`m.start(group)`, `m.end(group)`). Note that if *group* did not contribute to the match, this is (`None`, `None`). Again, *group* defaults to zero.

pos

The value of *pos* which was passed to the `search()` or `match()` function. This is the index into the string at which the regex engine started looking for a match.

endpos

The value of *endpos* which was passed to the `search()` or `match()` function. This is the index into the string beyond which the regex engine will not go.

re

The regular expression object whose `match()` or `search()` method produced this `MatchObject` instance.

string

The string passed to `match()` or `search()`.

See Also:

Jeffrey Friedl, *Mastering Regular Expressions*, O'Reilly. The Python material in this book dates from before the `re` module, but it covers writing good regular expression patterns in great detail.

4.3 `regex` — Regular expression search and match operations.

This module provides regular expression matching operations similar to those found in Emacs.

Obsolescence note: This module is obsolete as of Python version 1.5; it is still being maintained because much existing code still uses it. All new code in need of regular expressions should use the new `re` module, which supports the more powerful and regular Perl-style regular expressions. Existing code should be converted. The standard library module `reconvert` helps in converting `regex` style regular expressions to `re` style regular expressions. (For more conversion help, see Andrew Kuchling's "regex-to-re HOWTO" at <http://www.python.org/doc/howto/regex-to-re/>.)

By default the patterns are Emacs-style regular expressions (with one exception). There is a way to change the syntax to match that of several well-known UNIX utilities. The exception is that Emacs' `'\s'` pattern is not supported, since the original implementation references the Emacs syntax tables.

This module is 8-bit clean: both patterns and strings may contain null bytes and characters whose high bit is set.

Please note: There is a little-known fact about Python string literals which means that you don't usually have to worry about doubling backslashes, even though they are used to escape special characters in string literals as well as in regular expressions. This is because Python doesn't remove backslashes from string literals if they are followed by an unrecognized escape character. *However*, if you want to include a literal *backslash* in a regular expression represented as a string literal, you have to *quadruple* it or enclose it in a singleton character class. E.g. to extract L^AT_EX `'\section{...}'` headers from a document, you can use this pattern: `'[\\]section{\(.*\)}'`. *Another*

exception: the escape sequence ‘\b’ is significant in string literals (where it means the ASCII bell character) as well as in Emacs regular expressions (where it stands for a word boundary), so in order to search for a word boundary, you should use the pattern ‘\\b’. Similarly, a backslash followed by a digit 0-7 should be doubled to avoid interpretation as an octal escape.

4.3.1 Regular Expressions

A regular expression (or RE) specifies a set of strings that matches it; the functions in this module let you check if a particular string matches a given regular expression (or if a given regular expression matches a particular string, which comes down to the same thing).

Regular expressions can be concatenated to form new regular expressions; if *A* and *B* are both regular expressions, then *AB* is also a regular expression. If a string *p* matches *A* and another string *q* matches *B*, the string *pq* will match *AB*. Thus, complex expressions can easily be constructed from simpler ones like the primitives described here. For details of the theory and implementation of regular expressions, consult almost any textbook about compiler construction.

A brief explanation of the format of regular expressions follows.

Regular expressions can contain both special and ordinary characters. Ordinary characters, like ‘A’, ‘a’, or ‘0’, are the simplest regular expressions; they simply match themselves. You can concatenate ordinary characters, so ‘last’ matches the characters ‘last’. (In the rest of this section, we’ll write RE’s in this special font, usually without quotes, and strings to be matched ‘in single quotes’.)

Special characters either stand for classes of ordinary characters, or affect how the regular expressions around them are interpreted.

The special characters are:

- . (Dot.) Matches any character except a newline.
- ^ (Caret.) Matches the start of the string.
- \$ Matches the end of the string. `foo` matches both ‘foo’ and ‘foobar’, while the regular expression ‘`foo$`’ matches only ‘foo’.
- * Causes the resulting RE to match 0 or more repetitions of the preceding RE. `ab*` will match ‘a’, ‘ab’, or ‘a’ followed by any number of ‘b’s.
- + Causes the resulting RE to match 1 or more repetitions of the preceding RE. `ab+` will match ‘a’ followed by any non-zero number of ‘b’s; it will not match just ‘a’.
- ? Causes the resulting RE to match 0 or 1 repetitions of the preceding RE. `ab?` will match either ‘a’ or ‘ab’.
- \ Either escapes special characters (permitting you to match characters like ‘*?+&\$’), or signals a special sequence; special sequences are discussed below. Remember that Python also uses the backslash as an escape sequence in string literals; if the escape sequence isn’t recognized by Python’s parser, the backslash and subsequent character are included in the resulting string. However, if Python would recognize the resulting sequence, the backslash should be repeated twice.
- [] Used to indicate a set of characters. Characters can be listed individually, or a range is indicated by giving two characters and separating them by a ‘-’. Special characters are not active inside sets. For example, `[akm$]` will match any of the characters ‘a’, ‘k’, ‘m’, or ‘\$’; `[a-z]` will match any lowercase letter.
If you want to include a `]` inside a set, it must be the first character of the set; to include a `-`, place it as the first or last character.
Characters *not* within a range can be matched by including a `^` as the first character of the set; `^` elsewhere will simply match the ‘^’ character.

The special sequences consist of ``\` and a character from the list below. If the ordinary character is not on the list, then the resulting RE will match the second character. For example, `\$` matches the character '\$'. Ones where the backslash should be doubled in string literals are indicated.

`\|` `A|B`, where A and B can be arbitrary REs, creates a regular expression that will match either A or B. This can be used inside groups (see below) as well.

`\(\)` Indicates the start and end of a group; the contents of a group can be matched later in the string with the `\[1-9]` special sequence, described next.

`\\1, ... \\7, \\8, \\9`

Matches the contents of the group of the same number. For example, `\(.+\) \\1` matches 'the the' or '55 55', but not 'the end' (note the space after the group). This special sequence can only be used to match one of the first 9 groups; groups with higher numbers can be matched using the `\v` sequence. (`\\8` and `\\9` don't need a double backslash because they are not octal digits.)

`\\b` Matches the empty string, but only at the beginning or end of a word. A word is defined as a sequence of alphanumeric characters, so the end of a word is indicated by whitespace or a non-alphanumeric character.

`\\B` Matches the empty string, but when it is *not* at the beginning or end of a word.

`\\v` Must be followed by a two digit decimal number, and matches the contents of the group of the same number. The group number must be between 1 and 99, inclusive.

`\\w` Matches any alphanumeric character; this is equivalent to the set `[a-zA-Z0-9]`.

`\\W` Matches any non-alphanumeric character; this is equivalent to the set `[^a-zA-Z0-9]`.

`\\<` Matches the empty string, but only at the beginning of a word. A word is defined as a sequence of alphanumeric characters, so the end of a word is indicated by whitespace or a non-alphanumeric character.

`\\>` Matches the empty string, but only at the end of a word.

`\\\\` Matches a literal backslash.

`\'` Like `^`, this only matches at the start of the string.

`\\'` Like `$`, this only matches at the end of the string.

4.3.2 Module Contents

The module defines these functions, and an exception:

match(*pattern*, *string*)

Return how many characters at the beginning of *string* match the regular expression *pattern*. Return -1 if the string does not match the pattern (this is different from a zero-length match!).

search(*pattern*, *string*)

Return the first position in *string* that matches the regular expression *pattern*. Return -1 if no position in the string matches the pattern (this is different from a zero-length match anywhere!).

compile(*pattern*[, *translate*])

Compile a regular expression pattern into a regular expression object, which can be used for matching using its `match()` and `search()` methods, described below. The optional argument *translate*, if present, must be a 256-character string indicating how characters (both of the pattern and of the strings to be matched) are translated before comparing them; the *i*-th element of the string gives the translation for the character with ASCII code *i*. This can be used to implement case-insensitive matching; see the `casefold` data item below.

The sequence

```
prog = regex.compile(pat)
result = prog.match(str)
```

is equivalent to

```
result = regex.match(pat, str)
```

but the version using `compile()` is more efficient when multiple regular expressions are used concurrently in a single program. (The compiled version of the last pattern passed to `regex.match()` or `regex.search()` is cached, so programs that use only a single regular expression at a time needn't worry about compiling regular expressions.)

set_syntax(*flags*)

Set the syntax to be used by future calls to `compile()`, `match()` and `search()`. (Already compiled expression objects are not affected.) The argument is an integer which is the OR of several flag bits. The return value is the previous value of the syntax flags. Names for the flags are defined in the standard module `regex_syntax`; read the file 'regex_syntax.py' for more information.

get_syntax()

Returns the current value of the syntax flags as an integer.

symcomp(*pattern*[, *translate*])

This is like `compile()`, but supports symbolic group names: if a parenthesis-enclosed group begins with a group name in angular brackets, e.g. '`\(<id>[a-z][a-z0-9]*\)`', the group can be referenced by its name in arguments to the `group()` method of the resulting compiled regular expression object, like this: `p.group('id')`. Group names may contain alphanumeric characters and '`_`' only.

error

Exception raised when a string passed to one of the functions here is not a valid regular expression (e.g., unmatched parentheses) or when some other error occurs during compilation or matching. (It is never an error if a string contains no match for a pattern.)

casefold

A string suitable to pass as the *translate* argument to `compile()` to map all upper case characters to their lowercase equivalents.

Compiled regular expression objects support these methods:

match(*string*[, *pos*])

Return how many characters at the beginning of *string* match the compiled regular expression. Return `-1` if the string does not match the pattern (this is different from a zero-length match!).

The optional second parameter, *pos*, gives an index in the string where the search is to start; it defaults to 0. This is not completely equivalent to slicing the string; the '`^`' pattern character matches at the real beginning of the string and at positions just after a newline, not necessarily at the index where the search is to start.

search(*string*[, *pos*])

Return the first position in *string* that matches the regular expression *pattern*. Return `-1` if no position in the string matches the pattern (this is different from a zero-length match anywhere!).

The optional second parameter has the same meaning as for the `match()` method.

group(*index*, *index*, ...)

This method is only valid when the last call to the `match()` or `search()` method found a match. It returns one or more groups of the match. If there is a single *index* argument, the result is a single string; if there are multiple arguments, the result is a tuple with one item per argument. If the *index* is zero, the corresponding return value is the entire matching string; if it is in the inclusive range [1..99], it is the string matching the corresponding parenthesized group (using the default syntax, groups are parenthesized using `\(` and `\)`). If no such group exists, the corresponding result is `None`.

If the regular expression was compiled by `symcomp()` instead of `compile()`, the *index* arguments may also be strings identifying groups by their group name.

Compiled regular expressions support these data attributes:

regs

When the last call to the `match()` or `search()` method found a match, this is a tuple of pairs of indexes corresponding to the beginning and end of all parenthesized groups in the pattern. Indices are relative to the string argument passed to `match()` or `search()`. The 0-th tuple gives the beginning and end of the whole pattern. When the last match or search failed, this is `None`.

last

When the last call to the `match()` or `search()` method found a match, this is the string argument passed to that method. When the last match or search failed, this is `None`.

translate

This is the value of the *translate* argument to `regex.compile()` that created this regular expression object. If the *translate* argument was omitted in the `regex.compile()` call, this is `None`.

givenpat

The regular expression pattern as passed to `compile()` or `symcomp()`.

realpat

The regular expression after stripping the group names for regular expressions compiled with `symcomp()`. Same as `givenpat` otherwise.

groupindex

A dictionary giving the mapping from symbolic group names to numerical group indexes for regular expressions compiled with `symcomp()`. `None` otherwise.

4.4 `regex` — String operations using regular expressions

This module defines a number of functions useful for working with regular expressions (see built-in module `regex`).

Warning: these functions are not thread-safe.

Obsolescence note: This module is obsolete as of Python version 1.5; it is still being maintained because much existing code still uses it. All new code in need of regular expressions should use the new `re` module, which supports the more powerful and regular Perl-style regular expressions. Existing code should be converted. The standard library module `reconvert` helps in converting `regex` style regular expressions to `re` style regular expressions. (For more conversion help, see Andrew Kuchling's "regex-to-re HOWTO" at <http://www.python.org/doc/howto/regex-to-re/>.)

sub(*pat*, *repl*, *str*)

Replace the first occurrence of pattern *pat* in string *str* by replacement *repl*. If the pattern isn't found, the string is returned unchanged. The pattern may be a string or an already compiled pattern. The replacement may contain references `'\digit'` to subpatterns and escaped backslashes.

gsub(*pat*, *repl*, *str*)

Replace all (non-overlapping) occurrences of pattern *pat* in string *str* by replacement *repl*. The same rules as for `sub()` apply. Empty matches for the pattern are replaced only when not adjacent to a previous match, so e.g. `gsub('', '-', 'abc')` returns `'-a-b-c-`'.

split(*str*, *pat*[, *maxsplit*])

Split the string *str* in fields separated by delimiters matching the pattern *pat*, and return a list containing the fields. Only non-empty matches for the pattern are considered, so e.g. `split('a:b', ':*')` returns `['a', 'b']` and `split('abc', '')` returns `['abc']`. The *maxsplit* defaults to 0. If it is nonzero, only *maxsplit* number of splits occur, and the remainder of the string is returned as the final element of the list.

splitx(*str*, *pat*[, *maxsplit*])

Split the string *str* in fields separated by delimiters matching the pattern *pat*, and return a list containing the fields as well as the separators. For example, `splitx('a:::b', ':::')` returns `['a', ':::', 'b']`. Otherwise, this function behaves the same as `split`.

capwords(*s*[, *pat*])

Capitalize words separated by optional pattern *pat*. The default pattern uses any characters except letters, digits and underscores as word delimiters. Capitalization is done by changing the first character of each word to upper case.

clear_cache()

The `re` module maintains a cache of compiled regular expressions, keyed on the regular expression string and the syntax of the `re` module at the time the expression was compiled. This function clears that cache.

4.5 struct — Interpret strings as packed binary data

This module performs conversions between Python values and C structs represented as Python strings. It uses *format strings* (explained below) as compact descriptions of the lay-out of the C structs and the intended conversion to/from Python values. This can be used in handling binary data stored in files or from network connections, among other sources.

The module defines the following exception and functions:

error

Exception raised on various occasions; argument is a string describing what is wrong.

pack(*fmt*, *v1*, *v2*, ...)

Return a string containing the values *v1*, *v2*, ... packed according to the given format. The arguments must match the values required by the format exactly.

unpack(*fmt*, *string*)

Unpack the string (presumably packed by `pack(fmt, ...)`) according to the given format. The result is a tuple even if it contains exactly one item. The string must contain exactly the amount of data required by the format (i.e. `len(string)` must equal `calcsize(fmt)`).

calcsize(*fmt*)

Return the size of the struct (and hence of the string) corresponding to the given format.

Format characters have the following meaning; the conversion between C and Python values should be obvious given their types:

Format	C Type	Python	Notes
'x'	pad byte	no value	
'c'	char	string of length 1	
'b'	signed char	integer	
'B'	unsigned char	integer	
'h'	short	integer	
'H'	unsigned short	integer	
'i'	int	integer	
'I'	unsigned int	long	(1)
'l'	long	integer	
'L'	unsigned long	long	
'f'	float	float	
'd'	double	float	
's'	char[]	string	
'p'	char[]	string	
'P'	void *	integer	

Notes:

- (1) The 'I' conversion code will convert to a Python long if the C `int` is the same size as a C `long`, which is typical on most modern systems. If a C `int` is smaller than a C `long`, an Python integer will be created instead.

A format character may be preceded by an integral repeat count; e.g. the format string '4h' means exactly the same as 'hhhh'.

Whitespace characters between formats are ignored; a count and its format must not contain whitespace though.

For the 's' format character, the count is interpreted as the size of the string, not a repeat count like for the other format characters; e.g. '10s' means a single 10-byte string, while '10c' means 10 characters. For packing, the string is truncated or padded with null bytes as appropriate to make it fit. For unpacking, the resulting string always has exactly the specified number of bytes. As a special case, '0s' means a single, empty string (while '0c' means 0 characters).

The 'p' format character can be used to encode a Pascal string. The first byte is the length of the stored string, with the bytes of the string following. If count is given, it is used as the total number of bytes used, including the length byte. If the string passed in to `pack()` is too long, the stored representation is truncated. If the string is too short, padding is used to ensure that exactly enough bytes are used to satisfy the count.

For the 'I' and 'L' format characters, the return value is a Python long integer.

For the 'P' format character, the return value is a Python integer or long integer, depending on the size needed to hold a pointer when it has been cast to an integer type. A NULL pointer will always be returned as the Python integer 0. When packing pointer-sized values, Python integer or long integer objects may be used. For example, the Alpha and Merced processors use 64-bit pointer values, meaning a Python long integer will be used to hold the pointer; other platforms use 32-bit pointers and will use a Python integer.

By default, C numbers are represented in the machine's native format and byte order, and properly aligned by skipping pad bytes if necessary (according to the rules used by the C compiler).

Alternatively, the first character of the format string can be used to indicate the byte order, size and alignment of the packed data, according to the following table:

Character	Byte order	Size and alignment
'@'	native	native
'='	native	standard
'<'	little-endian	standard
'>'	big-endian	standard
'!'	network (= big-endian)	standard

If the first character is not one of these, '@' is assumed.

Native byte order is big-endian or little-endian, depending on the host system (e.g. Motorola and Sun are big-endian; Intel and DEC are little-endian).

Native size and alignment are determined using the C compiler's `sizeof` expression. This is always combined with native byte order.

Standard size and alignment are as follows: no alignment is required for any type (so you have to use pad bytes); `short` is 2 bytes; `int` and `long` are 4 bytes. `float` and `double` are 32-bit and 64-bit IEEE floating point numbers, respectively.

Note the difference between '@' and '=': both use native byte order, but the size and alignment of the latter is standardized.

The form '!' is available for those poor souls who claim they can't remember whether network byte order is big-endian or little-endian.

There is no way to indicate non-native byte order (i.e. force byte-swapping); use the appropriate choice of ‘<’ or ‘>’.

The ‘P’ format character is only available for the native byte ordering (selected as the default or with the ‘@’ byte order character). The byte order character ‘=’ chooses to use little- or big-endian ordering based on the host system. The struct module does not interpret this as native ordering, so the ‘P’ format is not available.

Examples (all using native byte order, size and alignment, on a big-endian machine):

```
>>> from struct import *
>>> pack('hhl', 1, 2, 3)
'\000\001\000\002\000\000\000\003'
>>> unpack('hhl', '\000\001\000\002\000\000\000\003')
(1, 2, 3)
>>> calcsize('hhl')
8
```

Hint: to align the end of a structure to the alignment requirement of a particular type, end the format with the code for that type with a repeat count of zero, e.g. the format ‘1lh0l’ specifies two pad bytes at the end, assuming longs are aligned on 4-byte boundaries. This only works when native size and alignment are in effect; standard size and alignment does not enforce any alignment.

See Also:

[Module array](#) (section 5.6):

Packed binary storage of homogeneous data.

[Module xdrlib](#) (section 12.13):

Packing and unpacking of XDR data.

4.6 `fpformat` — Floating point conversions

The `fpformat` module defines functions for dealing with floating point numbers representations in 100% pure Python. **Note:** This module is unneeded: everything here could be done via the `%` string interpolation operator.

The `fpformat` module defines the following functions and an exception:

fix(*x*, *digs*)

Format *x* as `[-]ddd.ddd` with *digs* digits after the point and at least one digit before. If *digs* \leq 0, the decimal point is suppressed.

x can be either a number or a string that looks like one. *digs* is an integer.

Return value is a string.

sci(*x*, *digs*)

Format *x* as `[-]d.dddE[+-]ddd` with *digs* digits after the point and exactly one digit before. If *digs* \leq 0, one digit is kept and the point is suppressed.

x can be either a real number, or a string that looks like one. *digs* is an integer.

Return value is a string.

NotANumber

Exception raised when a string passed to `fix()` or `sci()` as the *x* parameter does not look like a number. This is a subclass of `ValueError` when the standard exceptions are strings. The exception value is the improperly formatted string that caused the exception to be raised.

Example:

```
>>> import fpformat
>>> fpformat.fix(1.23, 1)
'1.2'
```

4.7 StringIO — Read and write strings as files

This module implements a file-like class, `StringIO`, that reads and writes a string buffer (also known as *memory files*). See the description on file objects for operations (section 2.1.7).

StringIO([*buffer*])

When a `StringIO` object is created, it can be initialized to an existing string by passing the string to the constructor. If no string is given, the `StringIO` will start empty.

The following methods of `StringIO` objects require special mention:

getvalue()

Retrieve the entire contents of the “file” at any time before the `StringIO` object’s `close`() method is called.

close()

Free the memory buffer.

4.8 cStringIO — Faster version of StringIO

The module `cStringIO` provides an interface similar to that of the `StringIO` module. Heavy use of `StringIO.StringIO` objects can be made more efficient by using the function `StringIO`() from this module instead.

Since this module provides a factory function which returns objects of built-in types, there’s no way to build your own version using subclassing. Use the original `StringIO` module in that case.

The following data objects are provided as well:

InputType

The type object of the objects created by calling `StringIO` with a string parameter.

OutputType

The type object of the objects returned by calling `StringIO` with no parameters.

There is a C API to the module as well; refer to the module source for more information.

4.9 codecs — Codec registry and base classes

This module defines base classes for standard Python codecs (encoders and decoders) and provides access to the internal Python codec registry which manages the codec lookup process.

It defines the following functions:

register(*search_function*)

Register a codec search function. Search functions are expected to take one argument, the encoding name in all lower case letters, and return a tuple of functions (*encoder*, *decoder*, *stream_reader*, *stream_writer*) taking the following arguments:

encoder and *decoder*: These must be functions or methods which have the same interface as the `.encode/.decode` methods of Codec instances (see Codec Interface). The functions/methods are expected to work in a stateless

mode.

stream_reader and *stream_writer*: These have to be factory functions providing the following interface:

```
factory(stream, errors='strict')
```

The factory functions must return objects providing the interfaces defined by the base classes `StreamWriter` and `StreamReader`, respectively. Stream codecs can maintain state.

Possible values for *errors* are 'strict' (raise an exception in case of an encoding error), 'replace' (replace malformed data with a suitable replacement marker, such as '?') and 'ignore' (ignore malformed data and continue without further notice).

In case a search function cannot find a given encoding, it should return `None`.

lookup(*encoding*)

Looks up a codec tuple in the Python codec registry and returns the function tuple as defined above.

Encodings are first looked up in the registry's cache. If not found, the list of registered search functions is scanned. If no codecs tuple is found, a `LookupError` is raised. Otherwise, the codecs tuple is stored in the cache and returned to the caller.

To simplify working with encoded files or stream, the module also defines these utility functions:

```
open(filename, mode[, encoding=None[, errors='strict'[, buffering=1 ]]])
```

Open an encoded file using the given *mode* and return a wrapped version providing transparent encoding/decoding.

Note: The wrapped version will only accept the object format defined by the codecs, i.e. Unicode objects for most builtin codecs. Output is also codec dependent and will usually be Unicode as well.

encoding specifies the encoding which is to be used for the the file.

errors may be given to define the error handling. It defaults to 'strict' which causes a `ValueError` to be raised in case an encoding error occurs.

buffering has the same meaning as for the built-in `open()` function. It defaults to line buffered.

```
EncodedFile(file, input[, output=None[, errors='strict' ]])
```

Return a wrapped version of file which provides transparent encoding translation.

Strings written to the wrapped file are interpreted according to the given *input* encoding and then written to the original file as string using the *output* encoding. The intermediate encoding will usually be Unicode but depends on the specified codecs.

If *output* is not given, it defaults to *input*.

errors may be given to define the error handling. It defaults to 'strict' which causes `ValueError` to be raised in case an encoding error occurs.

...XXX document codec base classes...

The module also provides the following constants which are useful for reading and writing to platform dependent files:

BOM

BOM_BE

BOM_LE

BOM32_BE

BOM32_LE

BOM64_BE

BOM64_LE

These constants define the byte order marks (BOM) used in data streams to indicate the byte order used in the stream or file. BOM is either `BOM_BE` or `BOM_LE` depending on the platform's native byte order, while the others represent big endian ('_BE' suffix) and little endian ('_LE' suffix) byte order using 32-bit and 64-bit encodings.

Miscellaneous Services

The modules described in this chapter provide miscellaneous services that are available in all Python versions. Here's an overview:

<code>math</code>	Mathematical functions (<code>sin()</code> etc.).
<code>cmath</code>	Mathematical functions for complex numbers.
<code>random</code>	Generate pseudo-random numbers with various common distributions.
<code>whrandom</code>	Floating point pseudo-random number generator.
<code>bisect</code>	Array bisection algorithms for binary searching.
<code>array</code>	Efficient arrays of uniformly typed numeric values.
<code>ConfigParser</code>	Configuration file parser.
<code>fileinput</code>	Perl-like iteration over lines from multiple input streams, with “save in place” capability.
<code>calendar</code>	General functions for working with the calendar, including some emulation of the UNIX <code>cal</code> program.
<code>cmd</code>	Build line-oriented command interpreters; this is used by module <code>pdb</code> .
<code>shlex</code>	Simple lexical analysis for UNIX shell-like languages.

5.1 `math` — Mathematical functions

This module is always available. It provides access to the mathematical functions defined by the C standard.

These functions cannot be used with complex numbers; use the functions of the same name from the `cmath` module if you require support for complex numbers. The distinction between functions which support complex numbers and those which don't is made since most users do not want to learn quite as much mathematics as required to understand complex numbers. Receiving an exception instead of a complex result allows earlier detection of the unexpected complex number used as a parameter, so that the programmer can determine how and why it was generated in the first place.

The following functions provided by this module:

<code>acos(x)</code>	Return the arc cosine of x .
<code>asin(x)</code>	Return the arc sine of x .
<code>atan(x)</code>	Return the arc tangent of x .
<code>atan2(y, x)</code>	Return <code>atan(y / x)</code> .
<code>ceil(x)</code>	Return the ceiling of x as a real.

cos(x)
Return the cosine of x .

cosh(x)
Return the hyperbolic cosine of x .

exp(x)
Return $e^{**}x$.

fabs(x)
Return the absolute value of the real x .

floor(x)
Return the floor of x as a real.

fmod(x, y)
Return $x \% y$.

frexp(x)
Return the mantissa and exponent for x . The mantissa is positive.

hypot(x, y)
Return the Euclidean distance, $\sqrt{x*x + y*y}$.

ldexp(x, i)
Return $x * (2^{**}i)$.

log(x)
Return the natural logarithm of x .

log10(x)
Return the base-10 logarithm of x .

modf(x)
Return the fractional and integer parts of x . Both results carry the sign of x . The integer part is returned as a real.

pow(x, y)
Return $x^{**}y$.

sin(x)
Return the sine of x .

sinh(x)
Return the hyperbolic sine of x .

sqrt(x)
Return the square root of x .

tan(x)
Return the tangent of x .

tanh(x)
Return the hyperbolic tangent of x .

Note that `frexp()` and `modf()` have a different call/return pattern than their C equivalents: they take a single argument and return a pair of values, rather than returning their second return value through an ‘output parameter’ (there is no such thing in Python).

The module also defines two mathematical constants:

pi
The mathematical constant π .

e
The mathematical constant e .

See Also:

[Module `cmath`](#) (section 5.2):

Complex number versions of many of these functions.

5.2 `cmath` — Mathematical functions for complex numbers

This module is always available. It provides access to mathematical functions for complex numbers. The functions are:

`acos`(x)

Return the arc cosine of x .

`acosh`(x)

Return the hyperbolic arc cosine of x .

`asin`(x)

Return the arc sine of x .

`asinh`(x)

Return the hyperbolic arc sine of x .

`atan`(x)

Return the arc tangent of x .

`atanh`(x)

Return the hyperbolic arc tangent of x .

`cos`(x)

Return the cosine of x .

`cosh`(x)

Return the hyperbolic cosine of x .

`exp`(x)

Return the exponential value $e^{**}x$.

`log`(x)

Return the natural logarithm of x .

`log10`(x)

Return the base-10 logarithm of x .

`sin`(x)

Return the sine of x .

`sinh`(x)

Return the hyperbolic sine of x .

`sqrt`(x)

Return the square root of x .

`tan`(x)

Return the tangent of x .

`tanh`(x)

Return the hyperbolic tangent of x .

The module also defines two mathematical constants:

`pi`

The mathematical constant π , as a real.

e

The mathematical constant e , as a real.

Note that the selection of functions is similar, but not identical, to that in module `math`. The reason for having two modules is that some users aren't interested in complex numbers, and perhaps don't even know what they are. They would rather have `math.sqrt(-1)` raise an exception than return a complex number. Also note that the functions defined in `cmath` always return a complex number, even if the answer can be expressed as a real number (in which case the complex number has an imaginary part of zero).

5.3 `random` — Generate pseudo-random numbers

This module implements pseudo-random number generators for various distributions: on the real line, there are functions to compute normal or Gaussian, lognormal, negative exponential, gamma, and beta distributions. For generating distribution of angles, the circular uniform and von Mises distributions are available.

The `random` module supports the *Random Number Generator* interface, described in section 5.3.1. This interface of the module, as well as the distribution-specific functions described below, all use the pseudo-random generator provided by the `whrandom` module.

The following functions are defined to support specific distributions, and all return real values. Function parameters are named after the corresponding variables in the distribution's equation, as used in common mathematical practice; most of these equations can be found in any statistics text. These are expected to become part of the Random Number Generator interface in a future release.

betavariate(*alpha*, *beta*)

Beta distribution. Conditions on the parameters are $\alpha > -1$ and $\beta > -1$. Returned values range between 0 and 1.

cunifvariate(*mean*, *arc*)

Circular uniform distribution. *mean* is the mean angle, and *arc* is the range of the distribution, centered around the mean angle. Both values must be expressed in radians, and can range between 0 and π . Returned values will range between $\text{mean} - \text{arc}/2$ and $\text{mean} + \text{arc}/2$.

expovariate(*lambd*)

Exponential distribution. *lambd* is 1.0 divided by the desired mean. (The parameter would be called "lambda", but that is a reserved word in Python.) Returned values will range from 0 to positive infinity.

gamma(*alpha*, *beta*)

Gamma distribution. (Not the gamma function!) Conditions on the parameters are $\alpha > -1$ and $\beta > 0$.

gauss(*mu*, *sigma*)

Gaussian distribution. *mu* is the mean, and *sigma* is the standard deviation. This is slightly faster than the `normalvariate()` function defined below.

lognormvariate(*mu*, *sigma*)

Log normal distribution. If you take the natural logarithm of this distribution, you'll get a normal distribution with mean *mu* and standard deviation *sigma*. *mu* can have any value, and *sigma* must be greater than zero.

normalvariate(*mu*, *sigma*)

Normal distribution. *mu* is the mean, and *sigma* is the standard deviation.

vonmisesvariate(*mu*, *kappa*)

mu is the mean angle, expressed in radians between 0 and 2π , and *kappa* is the concentration parameter, which must be greater than or equal to zero. If *kappa* is equal to zero, this distribution reduces to a uniform random angle over the range 0 to 2π .

paretovariate(*alpha*)

Pareto distribution. *alpha* is the shape parameter.

weibullvariate(*alpha*, *beta*)

Weibull distribution. *alpha* is the scale parameter and *beta* is the shape parameter.

See Also:

Module [whrandom](#) (section 5.4):

The standard Python random number generator.

5.3.1 The Random Number Generator Interface

The *Random Number Generator* interface describes the methods which are available for all random number generators. This will be enhanced in future releases of Python.

In this release of Python, the modules [random](#), [whrandom](#), and instances of the `whrandom.whrandom` class all conform to this interface.

choice(*seq*)

Chooses a random element from the non-empty sequence *seq* and returns it.

randint(*a*, *b*)

Returns a random integer *N* such that $a \leq N \leq b$.

random()

Returns the next random floating point number in the range [0.0 ... 1.0).

uniform(*a*, *b*)

Returns a random real number *N* such that $a \leq N < b$.

5.4 whrandom — Pseudo-random number generator

This module implements a Wichmann-Hill pseudo-random number generator class that is also named `whrandom`. Instances of the `whrandom` class conform to the Random Number Generator interface described in section 5.3.1. They also offer the following method, specific to the Wichmann-Hill algorithm:

seed([*x*, *y*, *z*])

Initializes the random number generator from the integers *x*, *y* and *z*. When the module is first imported, the random number is initialized using values derived from the current time. If *x*, *y*, and *z* are either omitted or 0, the seed will be computed from the current system time. If one or two of the parameters are 0, but not all three, the zero values are replaced by ones. This causes some apparently different seeds to be equal, with the corresponding result on the pseudo-random series produced by the generator.

choice(*seq*)

Chooses a random element from the non-empty sequence *seq* and returns it.

randint(*a*, *b*)

Returns a random integer *N* such that $a \leq N \leq b$.

random()

Returns the next random floating point number in the range [0.0 ... 1.0).

seed(*x*, *y*, *z*)

Initializes the random number generator from the integers *x*, *y* and *z*. When the module is first imported, the random number is initialized using values derived from the current time.

uniform(*a*, *b*)

Returns a random real number *N* such that $a \leq N < b$.

When imported, the `whrandom` module also creates an instance of the `whrandom` class, and makes the methods of that instance available at the module level. Therefore one can write either `N = whrandom.random()` or:

```
generator = whrandom.whrandom()
N = generator.random()
```

Note that using separate instances of the generator leads to independent sequences of pseudo-random numbers.

See Also:

[Module random](#) (section 5.3):

Generators for various random distributions and documentation for the Random Number Generator interface.

Wichmann, B. A. & Hill, I. D., "Algorithm AS 183: An efficient and portable pseudo-random number generator", *Applied Statistics* 31 (1982) 188-190.

5.5 bisect — Array bisection algorithm

This module provides support for maintaining a list in sorted order without having to sort the list after each insertion. For long lists of items with expensive comparison operations, this can be an improvement over the more common approach. The module is called `bisect` because it uses a basic bisection algorithm to do its work. The source code may be most useful as a working example of the algorithm (i.e., the boundary conditions are already right!).

The following functions are provided:

bisect(*list*, *item*[, *lo*[, *hi*]])

Locate the proper insertion point for *item* in *list* to maintain sorted order. The parameters *lo* and *hi* may be used to specify a subset of the list which should be considered. The return value is suitable for use as the first parameter to `list.insert()`.

insort(*list*, *item*[, *lo*[, *hi*]])

Insert *item* in *list* in sorted order. This is equivalent to `list.insert(bisect.bisect(list, item, lo, hi), item)`.

5.5.1 Example

The `bisect()` function is generally useful for categorizing numeric data. This example uses `bisect()` to look up a letter grade for an exam total (say) based on a set of ordered numeric breakpoints: 85 and up is an 'A', 75..84 is a 'B', etc.

```
>>> grades = "FEDCBA"
>>> breakpoints = [30, 44, 66, 75, 85]
>>> from bisect import bisect
>>> def grade(total):
...     return grades[bisect(breakpoints, total)]
...
>>> grade(66)
'C'
>>> map(grade, [33, 99, 77, 44, 12, 88])
['E', 'A', 'B', 'D', 'F', 'A']
```

5.6 array — Efficient arrays of numeric values

This module defines a new object type which can efficiently represent an array of basic values: characters, integers, floating point numbers. Arrays are sequence types and behave very much like lists, except that the type of objects stored in them is constrained. The type is specified at object creation time by using a *type code*, which is a single character. The following type codes are defined:

Type code	C Type	Minimum size in bytes
'c'	character	1
'b'	signed int	1
'B'	unsigned int	1
'h'	signed int	2
'H'	unsigned int	2
'i'	signed int	2
'I'	unsigned int	2
'l'	signed int	4
'L'	unsigned int	4
'f'	float	4
'd'	double	8

The actual representation of values is determined by the machine architecture (strictly speaking, by the C implementation). The actual size can be accessed through the `itemsize` attribute. The values stored for 'L' and 'I' items will be represented as Python long integers when retrieved, because Python's plain integer type cannot represent the full range of C's unsigned (long) integers.

The module defines the following function and type object:

array(*typecode*[, *initializer*])

Return a new array whose items are restricted by *typecode*, and initialized from the optional *initializer* value, which must be a list or a string. The list or string is passed to the new array's `fromlist()` or `fromstring()` method (see below) to add initial items to the array.

ArrayType

Type object corresponding to the objects returned by `array()`.

Array objects support the following data items and methods:

typecode

The typecode character used to create the array.

itemsize

The length in bytes of one array item in the internal representation.

append(*x*)

Append a new item with value *x* to the end of the array.

buffer_info()

Return a tuple (*address*, *length*) giving the current memory address and the length in bytes of the buffer used to hold array's contents. This is occasionally useful when working with low-level (and inherently unsafe) I/O interfaces that require memory addresses, such as certain `ioctl()` operations. The returned numbers are valid as long as the array exists and no length-changing operations are applied to it.

byteswap()

"Byteswap" all items of the array. This is only supported for values which are 1, 2, 4, or 8 bytes in size; for other types of values, `RuntimeError` is raised. It is useful when reading data from a file written on a machine with a different byte order.

fromfile(*f*, *n*)

Read *n* items (as machine values) from the file object *f* and append them to the end of the array. If less than *n* items are available, `EOFError` is raised, but the items that were available are still inserted into the array. *f* must be a real built-in file object; something else with a `read()` method won't do.

fromlist(*list*)

Append items from the list. This is equivalent to `for x in list: a.append(x)` except that if there is a type error, the array is unchanged.

fromstring(*s*)

Appends items from the string, interpreting the string as an array of machine values (i.e. as if it had been read from a file using the `fromfile()` method).

insert(*i*, *x*)

Insert a new item with value *x* in the array before position *i*.

read(*f*, *n*)

Deprecated since release 1.5.1. Use the `fromfile()` method.

Read *n* items (as machine values) from the file object *f* and append them to the end of the array. If less than *n* items are available, `EOFError` is raised, but the items that were available are still inserted into the array. *f* must be a real built-in file object; something else with a `read()` method won't do.

reverse()

Reverse the order of the items in the array.

tofile(*f*)

Write all items (as machine values) to the file object *f*.

tolist()

Convert the array to an ordinary list with the same items.

tostring()

Convert the array to an array of machine values and return the string representation (the same sequence of bytes that would be written to a file by the `tofile()` method.)

write(*f*)

Deprecated since release 1.5.1. Use the `tofile()` method.

Write all items (as machine values) to the file object *f*.

When an array object is printed or converted to a string, it is represented as `array(typecode, initializer)`. The *initializer* is omitted if the array is empty, otherwise it is a string if the *typecode* is `'c'`, otherwise it is a list of numbers. The string is guaranteed to be able to be converted back to an array with the same type and value using reverse quotes (```), so long as the `array()` function has been imported using `from array import array`. Examples:

```
array('l')
array('c', 'hello world')
array('l', [1, 2, 3, 4, 5])
array('d', [1.0, 2.0, 3.14])
```

See Also:

[Module `struct`](#) (section 4.5):

packing and unpacking of heterogeneous binary data

[Module `xdrlib`](#) (section 12.13):

packing and unpacking of XDR data

The Numeric Python extension (NumPy) defines another array type; see *The Numerical Python Manual* for additional information (available online at <ftp://ftp-icf.llnl.gov/pub/python/numericalpython.pdf>). Further information about NumPy is available at <http://www.python.org/topics/scicomp/numpy.html>.

5.7 ConfigParser — Configuration file parser

This module defines the class `ConfigParser`. The `ConfigParser` class implements a basic configuration file parser language which provides a structure similar to what you would find on Microsoft Windows INI files. You can use this to write Python programs which can be customized by end users easily.

The configuration file consists of sections, lead by a `[section]` header and followed by `'name: value'` entries, with continuations in the style of RFC 822; `'name=value'` is also accepted. Note that leading whitespace is removed from values. The optional values can contain format strings which refer to other values in the same section, or values in a special `DEFAULT` section. Additional defaults can be provided upon initialization and retrieval. Lines beginning with `#` or `;` are ignored and may be used to provide comments.

For example:

```
foodir: %(dir)s/whatever
dir=frob
```

would resolve the `'%(dir)s'` to the value of `'dir'` (`'frob'` in this case). All reference expansions are done on demand.

Default values can be specified by passing them into the `ConfigParser` constructor as a dictionary. Additional defaults may be passed into the `get()` method which will override all others.

ConfigParser([*defaults*])

Return a new instance of the `ConfigParser` class. When *defaults* is given, it is initialized into the dictionary of intrinsic defaults. They keys must be strings, and the values must be appropriate for the `'%()s'` string interpolation. Note that `__name__` is always an intrinsic default; its value is the section name.

NoSectionError

Exception raised when a specified section is not found.

DuplicateSectionError

Exception raised when multiple sections with the same name are found, or if `add_section()` is called with the name of a section that is already present.

NoOptionError

Exception raised when a specified option is not found in the specified section.

InterpolationError

Exception raised when problems occur performing string interpolation.

MissingSectionHeaderError

Exception raised when attempting to parse a file which has no section headers.

ParsingError

Exception raised when errors occur attempting to parse a file.

See Also:

[Module shlex](#) (section 5.11):

Support for a creating UNIX shell-like minilanguages which can be used as an alternate format for application configuration files.

5.7.1 ConfigParser Objects

`ConfigParser` instances have the following methods:

defaults()

Return a dictionary containing the instance-wide defaults.

sections()

Return a list of the sections available; DEFAULT is not included in the list.

add_section(*section*)

Add a section named *section* to the instance. If a section by the given name already exists, `DuplicateSectionError` is raised.

has_section(*section*)

Indicates whether the named section is present in the configuration. The DEFAULT section is not acknowledged.

options(*section*)

Returns a list of options available in the specified *section*.

read(*filenames*)

Read and parse a list of filenames. If *filenames* is a string or Unicode string, it is treated as a single filename.

readfp(*fp*[, *filename*])

Read and parse configuration data from the file or file-like object in *fp* (only the `readline`() method is used). If *filename* is omitted and *fp* has a `name` attribute, that is used for *filename*; the default is '<???'>.

get(*section*, *option*[, *raw*[, *vars*]])

Get an *option* value for the provided *section*. All the '%' interpolations are expanded in the return values, based on the defaults passed into the constructor, as well as the options *vars* provided, unless the *raw* argument is true.

getint(*section*, *option*)

A convenience method which coerces the *option* in the specified *section* to an integer.

getfloat(*section*, *option*)

A convenience method which coerces the *option* in the specified *section* to a floating point number.

getboolean(*section*, *option*)

A convenience method which coerces the *option* in the specified *section* to a boolean value. Note that the only accepted values for the option are '0' and '1', any others will raise `ValueError`.

5.8 fileinput — Iterate over lines from multiple input streams

This module implements a helper class and functions to quickly write a loop over standard input or a list of files.

The typical use is:

```
import fileinput
for line in fileinput.input():
    process(line)
```

This iterates over the lines of all files listed in `sys.argv[1:]`, defaulting to `sys.stdin` if the list is empty. If a filename is '-', it is also replaced by `sys.stdin`. To specify an alternative list of filenames, pass it as the first argument to `input`(). A single file name is also allowed.

All files are opened in text mode. If an I/O error occurs during opening or reading a file, `IOError` is raised.

If `sys.stdin` is used more than once, the second and further use will return no lines, except perhaps for interactive use, or if it has been explicitly reset (e.g. using `sys.stdin.seek(0)`).

Empty files are opened and immediately closed; the only time their presence in the list of filenames is noticeable at all is when the last file opened is empty.

It is possible that the last line of a file does not end in a newline character; lines are returned including the trailing

newline when it is present.

The following function is the primary interface of this module:

input([*files*[, *inplace*[, *backup*]]])

Create an instance of the `FileInput` class. The instance will be used as global state for the functions of this module, and is also returned to use during iteration.

The following functions use the global state created by `input()`; if there is no active state, `RuntimeError` is raised.

filename()

Return the name of the file currently being read. Before the first line has been read, returns `None`.

lineno()

Return the cumulative line number of the line that has just been read. Before the first line has been read, returns 0. After the last line of the last file has been read, returns the line number of that line.

filelineno()

Return the line number in the current file. Before the first line has been read, returns 0. After the last line of the last file has been read, returns the line number of that line within the file.

isfirstline()

Returns true the line just read is the first line of its file, otherwise returns false.

isstdin()

Returns true if the last line was read from `sys.stdin`, otherwise returns false.

nextfile()

Close the current file so that the next iteration will read the first line from the next file (if any); lines not read from the file will not count towards the cumulative line count. The filename is not changed until after the first line of the next file has been read. Before the first line has been read, this function has no effect; it cannot be used to skip the first file. After the last line of the last file has been read, this function has no effect.

close()

Close the sequence.

The class which implements the sequence behavior provided by the module is available for subclassing as well:

FileInput([*files*[, *inplace*[, *backup*]]])

Class `FileInput` is the implementation; its methods `filename()`, `lineno()`, `fileline()`, `isfirstline()`, `isstdin()`, `nextfile()` and `close()` correspond to the functions of the same name in the module. In addition it has a `readline()` method which returns the next input line, and a `__getitem__()` method which implements the sequence behavior. The sequence must be accessed in strictly sequential order; random access and `readline()` cannot be mixed.

Optional in-place filtering: if the keyword argument `inplace=1` is passed to `input()` or to the `FileInput` constructor, the file is moved to a backup file and standard output is directed to the input file. This makes it possible to write a filter that rewrites its input file in place. If the keyword argument `backup='.<some extension>'` is also given, it specifies the extension for the backup file, and the backup file remains around; by default, the extension is `'.bak'` and it is deleted when the output file is closed. In-place filtering is disabled when standard input is read.

Caveat: The current implementation does not work for MS-DOS 8+3 filesystems.

5.9 calendar — General calendar-related functions

This module allows you to output calendars like the UNIX `cal` program, and provides additional useful functions related to the calendar.

isleap(*year*)

Returns true if *year* is a leap year.

leapdays(*year1*, *year2*)

Return the number of leap years in the range [*year1*...*year2*].

weekday(*year*, *month*, *day*)

Returns the day of the week (0 is Monday) for *year* (1970-...), *month* (1-12), *day* (1-31).

monthrange(*year*, *month*)

Returns weekday of first day of the month and number of days in month, for the specified *year* and *month*.

monthcalendar(*year*, *month*)

Returns a matrix representing a month's calendar. Each row represents a week; days outside of the month are represented by zeros.

prmonth(*year*, *month*[, *width*[, *length*]])

Prints a month's calendar. If *width* is provided, it specifies the width of the columns that the numbers are centered in. If *length* is given, it specifies the number of lines that each week will use.

prcal(*year*)

Prints the calendar for the year *year*.

timegm(*tuple*)

An unrelated but handy function that takes a time tuple such as returned by the `gmtime()` function in the `time` module, and returns the corresponding Unix timestamp value, assuming an epoch of 1970, and the POSIX encoding. In fact, `time.gmtime()` and `timegm()` are each others' inverse.

See Also:

[Module `time`](#) (section 6.8):

Low-level time related functions.

5.10 `cmd` — Build line-oriented command interpreters.

The `Cmd` class provides a simple framework for writing line-oriented command interpreters. These are often useful for test harnesses, administrative tools, and prototypes that will later be wrapped in a more sophisticated interface.

Cmd()

A `Cmd` instance or subclass instance is a line-oriented interpreter framework. There is no good reason to instantiate `Cmd` itself; rather, it's useful as a superclass of an interpreter class you define yourself in order to inherit `Cmd`'s methods and encapsulate action methods.

5.10.1 `Cmd` Objects

A `Cmd` instance has the following methods:

cmdloop([*intro*])

Repeatedly issue a prompt, accept input, parse an initial prefix off the received input, and dispatch to action methods, passing them the remainder of the line as argument.

The optional argument is a banner or intro string to be issued before the first prompt (this overrides the `intro` class member).

If the `readline` module is loaded, input will automatically inherit **bash**-like history-list editing (e.g. `Ctrl-P` scrolls back to the last command, `Ctrl-N` forward to the next one, `Ctrl-F` moves the cursor to the right non-destructively, `Ctrl-B` moves the cursor to the left non-destructively, etc.).

An end-of-file on input is passed back as the string 'EOF'.

An interpreter instance will recognize a command name 'foo' if and only if it has a method `do_foo()`. As

a special case, a line containing only the character ‘?’ is dispatched to the method `do_help()`. As another special case, a line containing only the character ‘!’ is dispatched to the method `do_shell()` (if such a method is defined).

All subclasses of `Cmd` inherit a predefined `do_help()`. This method, called with an argument `bar`, invokes the corresponding method `help_bar()`. With no argument, `do_help()` lists all available help topics (that is, all commands with corresponding `help_*` methods), and also lists any undocumented commands.

onecmd(*str*)

Interpret the argument as though it had been typed in in response to the prompt.

emptyline()

Method called when an empty line is entered in response to the prompt. If this method is not overridden, it repeats the last nonempty command entered.

default(*line*)

Method called on an input line when the command prefix is not recognized. If this method is not overridden, it prints an error message and returns.

precmd()

Hook method executed just before the input prompt is issued. This method is a stub in `Cmd`; it exists to be overridden by subclasses.

postcmd()

Hook method executed just after a command dispatch is finished. This method is a stub in `Cmd`; it exists to be overridden by subclasses.

preloop()

Hook method executed once when `cmdloop()` is called. This method is a stub in `Cmd`; it exists to be overridden by subclasses.

postloop()

Hook method executed once when `cmdloop()` is about to return. This method is a stub in `Cmd`; it exists to be overridden by subclasses.

Instances of `Cmd` subclasses have some public instance variables:

prompt

The prompt issued to solicit input.

identchars

The string of characters accepted for the command prefix.

lastcmd

The last nonempty command prefix seen.

intro

A string to issue as an intro or banner. May be overridden by giving the `cmdloop()` method an argument.

doc_header

The header to issue if the help output has a section for documented commands.

misc_header

The header to issue if the help output has a section for miscellaneous help topics (that is, there are `help_*` methods without corresponding `do_*` methods).

undoc_header

The header to issue if the help output has a section for undocumented commands (that is, there are `do_*` methods without corresponding `help_*` methods).

ruler

The character used to draw separator lines under the help-message headers. If empty, no ruler line is drawn. It defaults to ‘=’.

5.11 shlex — Simple lexical analysis

New in version 1.5.2.

The `shlex` class makes it easy to write lexical analyzers for simple syntaxes resembling that of the UNIX shell. This will often be useful for writing minilanguages, e.g. in run control files for Python applications.

shlex([*stream*], [*file*])

A `shlex` instance or subclass instance is a lexical analyzer object. The initialization argument, if present, specifies where to read characters from. It must be a file- or stream-like object with `read()` and `readline()` methods. If no argument is given, input will be taken from `sys.stdin`. The second optional argument is a filename string, which sets the initial value of the `infile` member. If the stream argument is omitted or equal to `sys.stdin`, this second argument defaults to “stdin”.

See Also:

[Module ConfigParser](#) (section 5.7):

Parser for configuration files similar to the Windows ‘.ini’ files.

5.11.1 shlex Objects

A `shlex` instance has the following methods:

get_token()

Return a token. If tokens have been stacked using `push_token()`, pop a token off the stack. Otherwise, read one from the input stream. If reading encounters an immediate end-of-file, an empty string is returned.

push_token(*str*)

Push the argument onto the token stack.

read_token()

Read a raw token. Ignore the pushback stack, and do not interpret source requests. (This is not ordinarily a useful entry point, and is documented here only for the sake of completeness.)

openhook(*filename*)

When `shlex` detects a source request (see `source` below) this method is given the following token as argument, and expected to return a tuple consisting of a filename and an opened stream object.

Normally, this method just strips any quotes off the argument and treats it as a filename, calling `open()` on it. It is exposed so that you can use it to implement directory search paths, addition of file extensions, and other namespace hacks.

There is no corresponding ‘close’ hook, but a `shlex` instance will call the `close()` method of the sourced input stream when it returns EOF.

error_leader([*file*], [*line*])

This method generates an error message leader in the format of a Unix C compiler error label; the format is “`”%s”, line %d: ’`”, where the `%s` is replaced with the name of the current source file and the `%d` with the current input line number (the optional arguments can be used to override these).

This convenience is provided to encourage `shlex` users to generate error messages in the standard, parseable format understood by Emacs and other Unix tools.

Instances of `shlex` subclasses have some public instance variables which either control lexical analysis or can be used for debugging:

commenters

The string of characters that are recognized as comment beginners. All characters from the comment beginner to end of line are ignored. Includes just ‘#’ by default.

wordchars

The string of characters that will accumulate into multi-character tokens. By default, includes all ASCII alphanumerics and underscore.

whitespace

Characters that will be considered whitespace and skipped. Whitespace bounds tokens. By default, includes space, tab, linefeed and carriage-return.

quotes

Characters that will be considered string quotes. The token accumulates until the same quote is encountered again (thus, different quote types protect each other as in the shell.) By default, includes ASCII single and double quotes.

infile

The name of the current input file, as initially set at class instantiation time or stacked by later source requests. It may be useful to examine this when constructing error messages.

instream

The input stream from which this shlex instance is reading characters.

source

This member is None by default. If you assign a string to it, that string will be recognized as a lexical-level inclusion request similar to the 'source' keyword in various shells. That is, the immediately following token will be opened as a filename and input taken from that stream until EOF, at which point the `close()` method of that stream will be called and the input source will again become the original input stream. Source requests may be stacked any number of levels deep.

debug

If this member is numeric and 1 or more, a shlex instance will print verbose progress output on its behavior. If you need to use this, you can read the module source code to learn the details.

Note that any character not declared to be a word character, whitespace, or a quote will be returned as a single-character token.

Quote and comment characters are not recognized within words. Thus, the bare words 'ain't' and 'ain#t' would be returned as single tokens by the default parser.

lineno

Source line number (count of newlines seen so far plus one).

token

The token buffer. It may be useful to examine this when catching exceptions.

Generic Operating System Services

The modules described in this chapter provide interfaces to operating system features that are available on (almost) all operating systems, such as files and a clock. The interfaces are generally modelled after the UNIX or C interfaces, but they are available on most other systems as well. Here's an overview:

<code>os</code>	Miscellaneous OS interfaces.
<code>os.path</code>	Common pathname manipulations.
<code>dircache</code>	Return directory listing, with cache mechanism.
<code>stat</code>	Utilities for interpreting the results of <code>os.stat()</code> , <code>os.lstat()</code> and <code>os.fstat()</code> .
<code>statcache</code>	Stat files, and remember results.
<code>statvfs</code>	Constants for interpreting the result of <code>os.statvfs()</code> .
<code>filecmp</code>	Compare files efficiently.
<code>time</code>	Time access and conversions.
<code>sched</code>	General purpose event scheduler.
<code>getpass</code>	Portable reading of passwords and retrieval of the userid.
<code>curses</code>	An interface to the curses library.
<code>getopt</code>	Parser for command line options.
<code>tempfile</code>	Generate temporary file names.
<code>errno</code>	Standard errno system symbols.
<code>glob</code>	UNIX shell style pathname pattern expansion.
<code>fnmatch</code>	UNIX shell style filename pattern matching.
<code>shutil</code>	High-level file operations, including copying.
<code>locale</code>	Internationalization services.
<code>mutex</code>	Lock and queue for mutual exclusion.

6.1 `os` — Miscellaneous OS interfaces

This module provides a more portable way of using operating system (OS) dependent functionality than importing an OS dependent built-in module like `posix` or `nt`.

This module searches for an OS dependent built-in module like `mac` or `posix` and exports the same functions and data as found there. The design of all Python's built-in OS dependent modules is such that as long as the same functionality is available, it uses the same interface; e.g., the function `os.stat(path)` returns stat information about `path` in the same format (which happens to have originated with the POSIX interface).

Extensions peculiar to a particular OS are also available through the `os` module, but using them is of course a threat to portability!

Note that after the first time `os` is imported, there is *no* performance penalty in using functions from `os` instead of directly from the OS dependent built-in module, so there should be *no* reason not to use `os`!

error

This exception is raised when a function returns a system-related error (e.g., not for illegal argument types). This is also known as the built-in exception `OSError`. The accompanying value is a pair containing the numeric error code from `errno` and the corresponding string, as would be printed by the C function `perror()`. See the module `errno`, which contains names for the error codes defined by the underlying operating system.

When exceptions are classes, this exception carries two attributes, `errno` and `strerror`. The first holds the value of the C `errno` variable, and the latter holds the corresponding error message from `strerror()`. For exceptions that involve a file system path (e.g. `chdir()` or `unlink()`), the exception instance will contain a third attribute, `filename`, which is the file name passed to the function.

When exceptions are strings, the string for the exception is `'OSError'`.

name

The name of the OS dependent module imported. The following names have currently been registered: `'posix'`, `'nt'`, `'dos'`, `'mac'`, `'os2'`, `'ce'`, `'java'`.

path

The corresponding OS dependent standard module for pathname operations, e.g., `posixpath` or `macpath`. Thus, given the proper imports, `os.path.split(file)` is equivalent to but more portable than `posixpath.split(file)`. Note that this is also a valid module: it may be imported directly as `os.path`.

6.1.1 Process Parameters

These functions and data items provide information and operate on the current process and user.

environ

A mapping object representing the string environment. For example, `environ['HOME']` is the pathname of your home directory (on some platforms), and is equivalent to `getenv("HOME")` in C.

If the platform supports the `putenv()` function, this mapping may be used to modify the environment as well as query the environment. `putenv()` will be called automatically when the mapping is modified.

If `putenv()` is not provided, this mapping may be passed to the appropriate process-creation functions to cause child processes to use a modified environment.

chdir(path)

getcwd()

These functions are described in “Files and Directories” (section 6.1.4).

ctermid()

Return the filename corresponding to the controlling terminal of the process. Availability: UNIX.

getegid()

Return the current process' effective group id. Availability: UNIX.

geteuid()

Return the current process' effective user id. Availability: UNIX.

getgid()

Return the current process' group id. Availability: UNIX.

getgroups()

Return list of supplemental group ids associated with the current process. Availability: UNIX.

getlogin()

Return the actual login name for the current process, even if there are multiple login names which map to the same user id. Availability: UNIX.

getpgrp()

Return the current process group id. Availability: UNIX.

getpid()

Return the current process id. Availability: UNIX, Windows.

getppid()

Return the parent's process id. Availability: UNIX.

getuid()

Return the current process' user id. Availability: UNIX.

putenv(varname, value)

Set the environment variable named *varname* to the string *value*. Such changes to the environment affect sub-processes started with `os.system()`, `popen()` or `fork()` and `execv()`. Availability: most flavors of UNIX, Windows.

When `putenv()` is supported, assignments to items in `os.environ` are automatically translated into corresponding calls to `putenv()`; however, calls to `putenv()` don't update `os.environ`, so it is actually preferable to assign to items of `os.environ`.

setgid(gid)

Set the current process' group id. Availability: UNIX.

setpgrp()

Calls the system call `setpgrp()` or `setpgrp(0, 0)` depending on which version is implemented (if any). See the UNIX manual for the semantics. Availability: UNIX.

setpgid(pid, grp)

Calls the system call `setpgid()`. See the UNIX manual for the semantics. Availability: UNIX.

setsid()

Calls the system call `setsid()`. See the UNIX manual for the semantics. Availability: UNIX.

setuid(uid)

Set the current process' user id. Availability: UNIX.

strerror(code)

Return the error message corresponding to the error code in *code*. Availability: UNIX, Windows.

umask(mask)

Set the current numeric umask and returns the previous umask. Availability: UNIX, Windows.

uname()

Return a 5-tuple containing information identifying the current operating system. The tuple contains 5 strings: (*sysname*, *nodename*, *release*, *version*, *machine*). Some systems truncate the *nodename* to 8 characters or to the leading component; a better way to get the hostname is `socket.gethostname()` or even `socket.gethostbyaddr(socket.gethostname())`. Availability: recent flavors of UNIX.

6.1.2 File Object Creation

These functions create new file objects.

fdopen(fd[, mode[, bufsize]])

Return an open file object connected to the file descriptor *fd*. The *mode* and *bufsize* arguments have the same meaning as the corresponding arguments to the built-in `open()` function. Availability: Macintosh, UNIX, Windows.

popen(command[, mode[, bufsize]])

Open a pipe to or from *command*. The return value is an open file object connected to the pipe, which can be read or written depending on whether *mode* is 'r' (default) or 'w'. The *bufsize* argument has the same meaning as the corresponding argument to the built-in `open()` function. The exit status of the command (encoded in the format specified for `wait()`) is available as the return value of the `close()` method of the file object, except that when the exit status is zero (termination without errors), `None` is returned. **Note:** This function behaves unreliably under Windows due to the native implementation of `popen()`. Availability: UNIX, Windows.

tmpfile()

Return a new file object opened in update mode ('w+'). The file has no directory entries associated with it and will be automatically deleted once there are no file descriptors for the file. Availability: UNIX.

6.1.3 File Descriptor Operations

These functions operate on I/O streams referred to using file descriptors.

close(*fd*)

Close file descriptor *fd*. Availability: Macintosh, UNIX, Windows.

Note: this function is intended for low-level I/O and must be applied to a file descriptor as returned by `open()` or `pipe()`. To close a “file object” returned by the built-in function `open()` or by `popen()` or `fdopen()`, use its `close()` method.

dup(*fd*)

Return a duplicate of file descriptor *fd*. Availability: Macintosh, UNIX, Windows.

dup2(*fd*, *fd2*)

Duplicate file descriptor *fd* to *fd2*, closing the latter first if necessary. Availability: UNIX, Windows.

fpathconf(*fd*, *name*)

Return system configuration information relevant to an open file. *name* specifies the configuration value to retrieve; it may be a string which is the name of a defined system value; these names are specified in a number of standards (POSIX.1, Unix95, Unix98, and others). Some platforms define additional names as well. The names known to the host operating system are given in the `pathconf_names` dictionary. For configuration variables not included in that mapping, passing an integer for *name* is also accepted. Availability: UNIX.

If *name* is a string and is not known, `ValueError` is raised. If a specific value for *name* is not supported by the host system, even if it is included in `pathconf_names`, an `OSError` is raised with `errno.EINVAL` for the error number.

fstat(*fd*)

Return status for file descriptor *fd*, like `stat()`. Availability: UNIX, Windows.

fstatvfs(*fd*)

Return information about the filesystem containing the file associated with file descriptor *fd*, like `statvfs()`. Availability: UNIX.

ftruncate(*fd*, *length*)

Truncate the file corresponding to file descriptor *fd*, so that it is at most *length* bytes in size. Availability: UNIX.

lseek(*fd*, *pos*, *how*)

Set the current position of file descriptor *fd* to position *pos*, modified by *how*: 0 to set the position relative to the beginning of the file; 1 to set it relative to the current position; 2 to set it relative to the end of the file. Availability: Macintosh, UNIX, Windows.

open(*file*, *flags*[, *mode*])

Open the file *file* and set various flags according to *flags* and possibly its mode according to *mode*. The default *mode* is 0777 (octal), and the current umask value is first masked out. Return the file descriptor for the newly opened file. Availability: Macintosh, UNIX, Windows.

For a description of the flag and mode values, see the C run-time documentation; flag constants (like `O_RDONLY` and `O_WRONLY`) are defined in this module too (see below).

Note: this function is intended for low-level I/O. For normal usage, use the built-in function `open()`, which returns a “file object” with `read()` and `write()` methods (and many more).

pipe()

Create a pipe. Return a pair of file descriptors (*r*, *w*) usable for reading and writing, respectively. Availability: UNIX, Windows.

read(*fd*, *n*)

Read at most *n* bytes from file descriptor *fd*. Return a string containing the bytes read. Availability: Macintosh, UNIX, Windows.

Note: this function is intended for low-level I/O and must be applied to a file descriptor as returned by `open()` or `pipe()`. To read a “file object” returned by the built-in function `open()` or by `popen()` or `fdopen()`, or `sys.stdin`, use its `read()` or `readline()` methods.

tcgetpgrp(*fd*)

Return the process group associated with the terminal given by *fd* (an open file descriptor as returned by `open()`). Availability: UNIX.

tcsetpgrp(*fd*, *pg*)

Set the process group associated with the terminal given by *fd* (an open file descriptor as returned by `open()`) to *pg*. Availability: UNIX.

ttyname(*fd*)

Return a string which specifies the terminal device associated with file-descriptor *fd*. If *fd* is not associated with a terminal device, an exception is raised. Availability: UNIX.

write(*fd*, *str*)

Write the string *str* to file descriptor *fd*. Return the number of bytes actually written. Availability: Macintosh, UNIX, Windows.

Note: this function is intended for low-level I/O and must be applied to a file descriptor as returned by `open()` or `pipe()`. To write a “file object” returned by the built-in function `open()` or by `popen()` or `fdopen()`, or `sys.stdout` or `sys.stderr`, use its `write()` method.

The following data items are available for use in constructing the *flags* parameter to the `open()` function.

O_RDONLY
O_WRONLY
O_RDWR
O_NDELAY
O_NONBLOCK
O_APPEND
O_DSYNC
O_RSYNC
O_SYNC
O_NOCTTY
O_CREAT
O_EXCL
O_TRUNC

Options for the *flag* argument to the `open()` function. These can be bit-wise OR'd together. Availability: Macintosh, UNIX, Windows.

6.1.4 Files and Directories

access(*path*, *mode*)

Check read/write/execute permissions for this process or existence of file *path*. *mode* should be `F_OK` to test the existence of *path*, or it can be the inclusive OR of one or more of `R_OK`, `W_OK`, and `X_OK` to test permissions. Return 1 if access is allowed, 0 if not. See the UNIX man page `access(2)` for more information. Availability: UNIX.

F_OK

Value to pass as the *mode* parameter of `access()` to test the existence of *path*.

R_OK

Value to include in the *mode* parameter of `access()` to test the readability of *path*.

W_OK

Value to include in the *mode* parameter of `access()` to test the writability of *path*.

X_OK

Value to include in the *mode* parameter of `access()` to determine if *path* can be executed.

chdir(*path*)

Change the current working directory to *path*. Availability: Macintosh, UNIX, Windows.

getcwd()

Return a string representing the current working directory. Availability: Macintosh, UNIX, Windows.

chmod(*path, mode*)

Change the mode of *path* to the numeric *mode*. Availability: UNIX, Windows.

chown(*path, uid, gid*)

Change the owner and group id of *path* to the numeric *uid* and *gid*. Availability: UNIX.

link(*src, dst*)

Create a hard link pointing to *src* named *dst*. Availability: UNIX.

listdir(*path*)

Return a list containing the names of the entries in the directory. The list is in arbitrary order. It does not include the special entries `'.'` and `'..'` even if they are present in the directory. Availability: Macintosh, UNIX, Windows.

lstat(*path*)

Like `stat()`, but do not follow symbolic links. Availability: UNIX.

mkfifo(*path*[, *mode*])

Create a FIFO (a named pipe) named *path* with numeric mode *mode*. The default *mode* is 0666 (octal). The current umask value is first masked out from the mode. Availability: UNIX.

FIFOs are pipes that can be accessed like regular files. FIFOs exist until they are deleted (for example with `os.unlink()`). Generally, FIFOs are used as rendezvous between “client” and “server” type processes: the server opens the FIFO for reading, and the client opens it for writing. Note that `mkfifo()` doesn’t open the FIFO — it just creates the rendezvous point.

mkdir(*path*[, *mode*])

Create a directory named *path* with numeric mode *mode*. The default *mode* is 0777 (octal). On some systems, *mode* is ignored. Where it is used, the current umask value is first masked out. Availability: Macintosh, UNIX, Windows.

makedirs(*path*[, *mode*])

Recursive directory creation function. Like `mkdir()`, but makes all intermediate-level directories needed to contain the leaf directory. Throws an `error` exception if the leaf directory already exists or cannot be created. The default *mode* is 0777 (octal). New in version 1.5.2.

pathconf(*path, name*)

Return system configuration information relevant to a named file. *name* specifies the configuration value to retrieve; it may be a string which is the name of a defined system value; these names are specified in a number of standards (POSIX.1, Unix95, Unix98, and others). Some platforms define additional names as well. The names known to the host operating system are given in the `pathconf_names` dictionary. For configuration variables not included in that mapping, passing an integer for *name* is also accepted. Availability: UNIX.

If *name* is a string and is not known, `ValueError` is raised. If a specific value for *name* is not supported by the host system, even if it is included in `pathconf_names`, an `OSError` is raised with `errno.EINVAL` for the error number.

pathconf_names

Dictionary mapping names accepted by `pathconf()` and `fpathconf()` to the integer values defined for those names by the host operating system. This can be used to determine the set of names known to the system.

Availability: UNIX.

readlink(*path*)

Return a string representing the path to which the symbolic link points. Availability: UNIX.

remove(*path*)

Remove the file *path*. See `rmdir()` below to remove a directory. This is identical to the `unlink()` function documented below. Availability: Macintosh, UNIX, Windows.

removedirs(*path*)

Recursive directory removal function. Works like `rmdir()` except that, if the leaf directory is successfully removed, directories corresponding to rightmost path segments will be pruned way until either the whole path is consumed or an error is raised (which is ignored, because it generally means that a parent directory is not empty). Throws an `error` exception if the leaf directory could not be successfully removed. New in version 1.5.2.

rename(*src*, *dst*)

Rename the file or directory *src* to *dst*. Availability: Macintosh, UNIX, Windows.

renames(*old*, *new*)

Recursive directory or file renaming function. Works like `rename()`, except creation of any intermediate directories needed to make the new pathname good is attempted first. After the rename, directories corresponding to rightmost path segments of the old name will be pruned away using `removedirs()`.

Note: this function can fail with the new directory structure made if you lack permissions needed to remove the leaf directory or file. New in version 1.5.2.

rmdir(*path*)

Remove the directory *path*. Availability: Macintosh, UNIX, Windows.

stat(*path*)

Perform a `stat()` system call on the given path. The return value is a tuple of at least 10 integers giving the most important (and portable) members of the `stat` structure, in the order `st_mode`, `st_ino`, `st_dev`, `st_nlink`, `st_uid`, `st_gid`, `st_size`, `st_atime`, `st_mtime`, `st_ctime`. More items may be added at the end by some implementations. (On MS Windows, some items are filled with dummy values.) Availability: Macintosh, UNIX, Windows.

Note: The standard module `stat` defines functions and constants that are useful for extracting information from a `stat` structure.

statvfs(*path*)

Perform a `statvfs()` system call on the given path. The return value is a tuple of 10 integers giving the most common members of the `statvfs` structure, in the order `f_bsize`, `f_frsize`, `f_blocks`, `f_bfree`, `f_bavail`, `f_files`, `f_ffree`, `f_favail`, `f_flag`, `f_namemax`. Availability: UNIX.

Note: The standard module `statvfs` defines constants that are useful for extracting information from a `statvfs` structure.

symlink(*src*, *dst*)

Create a symbolic link pointing to *src* named *dst*. Availability: UNIX.

tempnam([*dir* [, *prefix*]])

Return a unique path name that is reasonable for creating a temporary file. This will be an absolute path that names a potential directory entry in the directory *dir* or a common location for temporary files if *dir* is omitted or `None`. If given and not `None`, *prefix* is used to provide a short prefix to the filename. Applications are responsible for properly creating and managing files created using paths returned by `tempnam()`; no automatic cleanup is provided.

tmpnam()

Return a unique path name that is reasonable for creating a temporary file. This will be an absolute path that names a potential directory entry in a common location for temporary files. Applications are responsible for properly creating and managing files created using paths returned by `tmpnam()`; no automatic cleanup is

provided.

TMP_MAX

The maximum number of unique names that `tmpnam()` will generate before reusing names.

unlink(*path*)

Remove the file *path*. This is the same function as `remove()`; the `unlink()` name is its traditional UNIX name. Availability: Macintosh, UNIX, Windows.

utime(*path*, *times*)

Set the access and modified times of the file specified by *path*. If *times* is `None`, then the file's access and modified times are set to the current time. Otherwise, *times* must be a 2-tuple of numbers, of the form (*atime*, *mtime*) which is used to set the access and modified times, respectively. Changed in version 1.6: added support for `None` for *times*. Availability: Macintosh, UNIX, Windows.

6.1.5 Process Management

These functions may be used to create and manage processes.

abort()

Generate a SIGABRT signal to the current process. On UNIX, the default behavior is to produce a core dump; on Windows, the process immediately returns an exit code of 3. Be aware that programs which use `signal.signal()` to register a handler for SIGABRT will behave differently. Availability: UNIX, Windows.

execl(*path*, *arg0*, *arg1*, ...)

This is equivalent to `execv(path, (arg0, arg1, ...))`. Availability: UNIX, Windows.

execle(*path*, *arg0*, *arg1*, ..., *env*)

This is equivalent to `execve(path, (arg0, arg1, ...), env)`. Availability: UNIX, Windows.

execlp(*path*, *arg0*, *arg1*, ...)

This is equivalent to `execvp(path, (arg0, arg1, ...))`. Availability: UNIX, Windows.

execv(*path*, *args*)

Execute the executable *path* with argument list *args*, replacing the current process (i.e., the Python interpreter). The argument list may be a tuple or list of strings. Availability: UNIX, Windows.

execve(*path*, *args*, *env*)

Execute the executable *path* with argument list *args*, and environment *env*, replacing the current process (i.e., the Python interpreter). The argument list may be a tuple or list of strings. The environment must be a dictionary mapping strings to strings. Availability: UNIX, Windows.

execvp(*path*, *args*)

This is like `execv(path, args)` but duplicates the shell's actions in searching for an executable file in a list of directories. The directory list is obtained from `environ['PATH']`. Availability: UNIX, Windows.

execvpe(*path*, *args*, *env*)

This is a cross between `execve()` and `execvp()`. The directory list is obtained from `env['PATH']`. Availability: UNIX, Windows.

_exit(*n*)

Exit to the system with status *n*, without calling cleanup handlers, flushing stdio buffers, etc. Availability: UNIX, Windows.

Note: the standard way to exit is `sys.exit(n)`. `_exit()` should normally only be used in the child process after a `fork()`.

fork()

Fork a child process. Return 0 in the child, the child's process id in the parent. Availability: UNIX.

kill(*pid*, *sig*)

Kill the process *pid* with signal *sig*. Availability: UNIX.

nice(*increment*)

Add *increment* to the process's "niceness". Return the new niceness. Availability: UNIX.

plock(*op*)

Lock program segments into memory. The value of *op* (defined in `<sys/lock.h>`) determines which segments are locked. Availability: UNIX.

spawnv(*mode, path, args*)

Execute the program *path* in a new process, passing the arguments specified in *args* as command-line parameters. *args* may be a list or a tuple. *mode* is a magic operational constant. See the Visual C++ Runtime Library documentation for further information; the constants are exposed to the Python programmer as listed below. Availability: UNIX, Windows. New in version 1.5.2.

spawnve(*mode, path, args, env*)

Execute the program *path* in a new process, passing the arguments specified in *args* as command-line parameters and the contents of the mapping *env* as the environment. *args* may be a list or a tuple. *mode* is a magic operational constant. See the Visual C++ Runtime Library documentation for further information; the constants are exposed to the Python programmer as listed below. Availability: UNIX, Windows. New in version 1.5.2.

P_WAIT

P_NOWAIT

P_NOWAITO

Possible values for the *mode* parameter to `spawnv()` and `spawnve()`. Availability: UNIX, Windows. New in version 1.5.2.

P_OVERLAY

P_DETACH

Possible values for the *mode* parameter to `spawnv()` and `spawnve()`. These are less portable than those listed above. Availability: Windows. New in version 1.5.2.

system(*command*)

Execute the command (a string) in a subshell. This is implemented by calling the Standard C function `system()`, and has the same limitations. Changes to `posix.environ`, `sys.stdin`, etc. are not reflected in the environment of the executed command. The return value is the exit status of the process encoded in the format specified for `wait()`, except on Windows 95 and 98, where it is always 0. Note that POSIX does not specify the meaning of the return value of the C `system()` function, so the return value of the Python function is system-dependent. Availability: UNIX, Windows.

times()

Return a 5-tuple of floating point numbers indicating accumulated (CPU or other) times, in seconds. The items are: user time, system time, children's user time, children's system time, and elapsed real time since a fixed point in the past, in that order. See the UNIX manual page `times(2)` or the corresponding Windows Platform API documentation. Availability: UNIX, Windows.

wait()

Wait for completion of a child process, and return a tuple containing its pid and exit status indication: a 16-bit number, whose low byte is the signal number that killed the process, and whose high byte is the exit status (if the signal number is zero); the high bit of the low byte is set if a core file was produced. Availability: UNIX.

waitpid(*pid, options*)

Wait for completion of a child process given by process id *pid*, and return a tuple containing its process id and exit status indication (encoded as for `wait()`). The semantics of the call are affected by the value of the integer *options*, which should be 0 for normal operation. Availability: UNIX.

If *pid* is greater than 0, `waitpid()` requests status information for that specific process. If *pid* is 0, the request is for the status of any child in the process group of the current process. If *pid* is -1, the request pertains to any child of the current process. If *pid* is less than -1, status is requested for any process in the process group `-pid` (the absolute value of *pid*).

WNOHANG

The option for `waitpid()` to avoid hanging if no child process status is available immediately. Availability: UNIX.

The following functions take a process status code as returned by `system()`, `wait()`, or `waitpid()` as a parameter. They may be used to determine the disposition of a process.

WIFSTOPPED(*status*)

Return true if the process has been stopped. Availability: UNIX.

WIFSIGNALED(*status*)

Return true if the process exited due to a signal. Availability: UNIX.

WIFEXITED(*status*)

Return true if the process exited using the `exit(2)` system call. Availability: UNIX.

WEXITSTATUS(*status*)

If `WIFEXITED(status)` is true, return the integer parameter to the `exit(2)` system call. Otherwise, the return value is meaningless. Availability: UNIX.

WSTOPSIG(*status*)

Return the signal which caused the process to stop. Availability: UNIX.

WTERMSIG(*status*)

Return the signal which caused the process to exit. Availability: UNIX.

6.1.6 Miscellanenous System Information

`confstr(name)`

Return string-valued system configuration values. *name* specifies the configuration value to retrieve; it may be a string which is the name of a defined system value; these names are specified in a number of standards (POSIX, Unix95, Unix98, and others). Some platforms define additional names as well. The names known to the host operating system are given in the `confstr_names` dictionary. For configuration variables not included in that mapping, passing an integer for *name* is also accepted. Availability: UNIX.

If the configuration value specified by *name* isn't defined, the empty string is returned.

If *name* is a string and is not known, `ValueError` is raised. If a specific value for *name* is not supported by the host system, even if it is included in `confstr_names`, an `OSError` is raised with `errno.EINVAL` for the error number.

`confstr_names`

Dictionary mapping names accepted by `confstr()` to the integer values defined for those names by the host operating system. This can be used to determine the set of names known to the system. Availability: UNIX.

`sysconf(name)`

Return integer-valued system configuration values. If the configuration value specified by *name* isn't defined, `-1` is returned. The comments regarding the *name* parameter for `confstr()` apply here as well; the dictionary that provides information on the known names is given by `sysconf_names`. Availability: UNIX.

`sysconf_names`

Dictionary mapping names accepted by `sysconf()` to the integer values defined for those names by the host operating system. This can be used to determine the set of names known to the system. Availability: UNIX.

The follow data values are used to support path manipulation operations. These are defined for all platforms.

Higher-level operations on pathnames are defined in the `os.path` module.

`curdir`

The constant string used by the OS to refer to the current directory, e.g. `'.'` for POSIX or `':'` for the Macintosh.

pardir

The constant string used by the OS to refer to the parent directory, e.g. `'..'` for POSIX or `'::'` for the Macintosh.

sep

The character used by the OS to separate pathname components, e.g. `'/'` for POSIX or `':'` for the Macintosh. Note that knowing this is not sufficient to be able to parse or concatenate pathnames — use `os.path.split()` and `os.path.join()` — but it is occasionally useful.

altsep

An alternative character used by the OS to separate pathname components, or `None` if only one separator character exists. This is set to `'/'` on DOS and Windows systems where `sep` is a backslash.

pathsep

The character conventionally used by the OS to separate search path components (as in `$PATH`), e.g. `':'` for POSIX or `';'` for DOS and Windows.

defpath

The default search path used by `exec *p*()` if the environment doesn't have a `'PATH'` key.

linesep

The string used to separate (or, rather, terminate) lines on the current platform. This may be a single character, e.g. `'\n'` for POSIX or `'\r'` for MacOS, or multiple characters, e.g. `'\r\n'` for MS-DOS and MS Windows.

6.2 `os.path` — Common pathname manipulations

This module implements some useful functions on pathnames.

abspath(*path*)

Return a normalized absolutized version of the pathname *path*. On most platforms, this is equivalent to `normpath(join(os.getcwd(), path))`. New in version 1.5.2.

basename(*path*)

Return the base name of pathname *path*. This is the second half of the pair returned by `split(path)`.

commonprefix(*list*)

Return the longest string that is a prefix of all strings in *list*. If *list* is empty, return the empty string (`''`).

dirname(*path*)

Return the directory name of pathname *path*. This is the first half of the pair returned by `split(path)`.

exists(*path*)

Return true if *path* refers to an existing path.

expanduser(*path*)

Return the argument with an initial component of `'~'` or `'~user'` replaced by that *user*'s home directory. An initial `'~'` is replaced by the environment variable `$HOME`; an initial `'~user'` is looked up in the password directory through the built-in module `pwd`. If the expansion fails, or if the path does not begin with a tilde, the path is returned unchanged. On the Macintosh, this always returns *path* unchanged.

expandvars(*path*)

Return the argument with environment variables expanded. Substrings of the form `'$name'` or `'${name}'` are replaced by the value of environment variable *name*. Malformed variable names and references to non-existing variables are left unchanged. On the Macintosh, this always returns *path* unchanged.

getatime(*path*)

Return the time of last access of *filename*. The return value is integer giving the number of seconds since the epoch (see the `time` module). Raise `os.error` if the file does not exist or is inaccessible. New in version 1.5.2.

getmtime(*path*)

Return the time of last modification of *filename*. The return value is integer giving the number of seconds since the epoch (see the `time` module). Raise `os.error` if the file does not exist or is inaccessible. New in version 1.5.2.

getsize(*path*)

Return the size, in bytes, of *filename*. Raise `os.error` if the file does not exist or is inaccessible. New in version 1.5.2.

isabs(*path*)

Return true if *path* is an absolute pathname (begins with a slash).

isfile(*path*)

Return true if *path* is an existing regular file. This follows symbolic links, so both `islink()` and `isfile()` can be true for the same path.

isdir(*path*)

Return true if *path* is an existing directory. This follows symbolic links, so both `islink()` and `isdir()` can be true for the same path.

islink(*path*)

Return true if *path* refers to a directory entry that is a symbolic link. Always false if symbolic links are not supported.

ismount(*path*)

Return true if pathname *path* is a *mount point*: a point in a file system where a different file system has been mounted. The function checks whether *path*'s parent, '*path*..', is on a different device than *path*, or whether '*path*..' and *path* point to the same i-node on the same device — this should detect mount points for all UNIX and POSIX variants.

join(*path1*[, *path2*[, ...]])

Joins one or more path components intelligently. If any component is an absolute path, all previous components are thrown away, and joining continues. The return value is the concatenation of *path1*, and optionally *path2*, etc., with exactly one slash ('/') inserted between components, unless *path* is empty.

normcase(*path*)

Normalize the case of a pathname. On UNIX, this returns the path unchanged; on case-insensitive filesystems, it converts the path to lowercase. On Windows, it also converts forward slashes to backward slashes.

normpath(*path*)

Normalize a pathname. This collapses redundant separators and up-level references, e.g. `A//B`, `A/./B` and `A/fooo/././B` all become `A/B`. It does not normalize the case (use `normcase()` for that). On Windows, it converts forward slashes to backward slashes.

samefile(*path1*, *path2*)

Return true if both pathname arguments refer to the same file or directory (as indicated by device number and i-node number). Raise an exception if a `os.stat()` call on either pathname fails. Availability: Macintosh, UNIX.

sameopenfile(*fp1*, *fp2*)

Return true if the file objects *fp1* and *fp2* refer to the same file. The two file objects may represent different file descriptors. Availability: Macintosh, UNIX.

samestat(*stat1*, *stat2*)

Return true if the stat tuples *stat1* and *stat2* refer to the same file. These structures may have been returned by `fstat()`, `lstat()`, or `stat()`. This function implements the underlying comparison used by `samefile()` and `sameopenfile()`. Availability: Macintosh, UNIX.

split(*path*)

Split the pathname *path* into a pair, (*head*, *tail*) where *tail* is the last pathname component and *head* is everything leading up to that. The *tail* part will never contain a slash; if *path* ends in a slash, *tail* will be empty.

If there is no slash in *path*, *head* will be empty. If *path* is empty, both *head* and *tail* are empty. Trailing slashes are stripped from *head* unless it is the root (one or more slashes only). In nearly all cases, `join(head, tail)` equals *path* (the only exception being when there were multiple slashes separating *head* from *tail*).

splitdrive(*path*)

Split the pathname *path* into a pair (*drive*, *tail*) where *drive* is either a drive specification or the empty string. On systems which do not use drive specifications, *drive* will always be the empty string. In all cases, *drive* + *tail* will be the same as *path*.

splitext(*path*)

Split the pathname *path* into a pair (*root*, *ext*) such that *root* + *ext* == *path*, and *ext* is empty or begins with a period and contains at most one period.

walk(*path*, *visit*, *arg*)

Calls the function *visit* with arguments (*arg*, *dirname*, *names*) for each directory in the directory tree rooted at *path* (including *path* itself, if it is a directory). The argument *dirname* specifies the visited directory, the argument *names* lists the files in the directory (gotten from `os.listdir(dirname)`). The *visit* function may modify *names* to influence the set of directories visited below *dirname*, e.g., to avoid visiting certain parts of the tree. (The object referred to by *names* must be modified in place, using `del` or slice assignment.)

6.3 dircache — Cached directory listings

The `dircache` module defines a function for reading directory listing using a cache, and cache invalidation using the *mtime* of the directory. Additionally, it defines a function to annotate directories by appending a slash.

The `dircache` module defines the following functions:

listdir(*path*)

Return a directory listing of *path*, as gotten from `os.listdir()`. Note that unless *path* changes, further call to `listdir()` will not re-read the directory structure.

Note that the list returned should be regarded as read-only. (Perhaps a future version should change it to return a tuple?)

opendir(*path*)

Same as `listdir()`. Defined for backwards compatibility.

annotate(*head*, *list*)

Assume *list* is a list of paths relative to *head*, and append, in place, a '/' to each path which points to a directory.

```
>>> import dircache
>>> a=dircache.listdir('/')
>>> a=a[:] # Copy the return value so we can change 'a'
>>> a
['bin', 'boot', 'cdrom', 'dev', 'etc', 'floppy', 'home', 'initrd', 'lib', 'lost+
found', 'mnt', 'proc', 'root', 'sbin', 'tmp', 'usr', 'var', 'vmlinuz']
>>> dircache.annotate('/', a)
>>> a
['bin/', 'boot/', 'cdrom/', 'dev/', 'etc/', 'floppy/', 'home/', 'initrd/', 'lib/
', 'lost+found/', 'mnt/', 'proc/', 'root/', 'sbin/', 'tmp/', 'usr/', 'var/', 'vm
linuz']
```

6.4 stat — Interpreting `stat()` results

The `stat` module defines constants and functions for interpreting the results of `os.stat()`, `os.fstat()` and `os.lstat()` (if they exist). For complete details about the `stat()`, `fstat()` and `lstat()` calls, consult the documentation for your system.

The `stat` module defines the following functions to test for specific file types:

S_ISDIR(*mode*)

Return non-zero if the mode is from a directory.

S_ISCHR(*mode*)

Return non-zero if the mode is from a character special device file.

S_ISBLK(*mode*)

Return non-zero if the mode is from a block special device file.

S_ISREG(*mode*)

Return non-zero if the mode is from a regular file.

S_ISFIFO(*mode*)

Return non-zero if the mode is from a FIFO (named pipe).

S_ISLNK(*mode*)

Return non-zero if the mode is from a symbolic link.

S_ISSOCK(*mode*)

Return non-zero if the mode is from a socket.

Two additional functions are defined for more general manipulation of the file's mode:

S_IMODE(*mode*)

Return the portion of the file's mode that can be set by `os.chmod()`—that is, the file's permission bits, plus the sticky bit, set-group-id, and set-user-id bits (on systems that support them).

S_IFMT(*mode*)

Return the portion of the file's mode that describes the file type (used by the `S_IS*()` functions above).

Normally, you would use the `os.path.is*()` functions for testing the type of a file; the functions here are useful when you are doing multiple tests of the same file and wish to avoid the overhead of the `stat()` system call for each test. These are also useful when checking for information about a file that isn't handled by `os.path`, like the tests for block and character devices.

All the variables below are simply symbolic indexes into the 10-tuple returned by `os.stat()`, `os.fstat()` or `os.lstat()`.

ST_MODE

Inode protection mode.

ST_INO

Inode number.

ST_DEV

Device inode resides on.

ST_NLINK

Number of links to the inode.

ST_UID

User id of the owner.

ST_GID

Group id of the owner.

ST_SIZE

File size in bytes.

ST_ATIME

Time of last access.

ST_MTIME

Time of last modification.

ST_CTIME

Time of last status change (see manual pages for details).

Example:

```
import os, sys
from stat import *

def walktree(dir, callback):
    '''recursively descend the directory rooted at dir,
       calling the callback function for each regular file'''

    for f in os.listdir(dir):
        pathname = '%s/%s' % (dir, f)
        mode = os.stat(pathname)[ST_MODE]
        if S_ISDIR(mode):
            # It's a directory, recurse into it
            walktree(pathname, callback)
        elif S_ISREG(mode):
            # It's a file, call the callback function
            callback(pathname)
        else:
            # Unknown file type, print a message
            print 'Skipping %s' % pathname

def visitfile(file):
    print 'visiting', file

if __name__ == '__main__':
    walktree(sys.argv[1], visitfile)
```

6.5 statcache — An optimization of `os.stat()`

The `statcache` module provides a simple optimization to `os.stat()`: remembering the values of previous invocations.

The `statcache` module defines the following functions:

stat(*path*)

This is the main module entry-point. Identical for `os.stat()`, except for remembering the result for future invocations of the function.

The rest of the functions are used to clear the cache, or parts of it.

reset()

Clear the cache: forget all results of previous `stat()` calls.

forget(*path*)

Forget the result of `stat(path)`, if any.

forget_prefix(*prefix*)

Forget all results of `stat(path)` for *path* starting with *prefix*.

forget_dir(*prefix*)

Forget all results of `stat(path)` for *path* a file in the directory *prefix*, including `stat(prefix)`.

forget_except_prefix(*prefix*)

Similar to `forget_prefix()`, but for all *path* values *not* starting with *prefix*.

Example:

```
>>> import os, statcache
>>> statcache.stat('.')
(16893, 2049, 772, 18, 1000, 1000, 2048, 929609777, 929609777, 929609777)
>>> os.stat('.')
(16893, 2049, 772, 18, 1000, 1000, 2048, 929609777, 929609777, 929609777)
```

6.6 statvfs — Constants used with `os.statvfs()`

The `statvfs` module defines constants so interpreting the result of `os.statvfs()`, which returns a tuple, can be made without remembering “magic numbers.” Each of the constants defined in this module is the *index* of the entry in the tuple returned by `os.statvfs()` that contains the specified information.

F_BSIZE

Preferred file system block size.

F_FRSIZE

Fundamental file system block size.

F_BLOCKS

Total number of blocks in the filesystem.

F_BFREE

Total number of free blocks.

F_BAVAIL

Free blocks available to non-super user.

F_FILES

Total number of file nodes.

F_FFREE

Total number of free file nodes.

F_FAVAIL

Free nodes available to non-super user.

F_FLAG

Flags. System dependant: see `statvfs()` man page.

F_NAMEMAX

Maximum file name length.

6.7 filecmp — File Comparisons

The `filecmp` module defines a function to compare files, taking all sort of short-cuts to make it a highly efficient operation.

The `filecmp` module defines the following function:

`cmp(f1, f2[, shallow[, use_statcache]])`

Compare the files named *f1* and *f2*, returning 1 if they seem equal, 0 otherwise.

Unless *shallow* is given and is false, files with identical `os.stat()` signatures are taken to be equal. If *use_statcache* is given and is true, `statcache.stat()` will be called rather than `os.stat()`.

Files that were compared using this function will not be compared again unless their `os.stat()` signature changes. Note that using *use_statcache* true will cause the cache invalidation mechanism to fail — the stale `stat` value will be used from `statcache`'s cache.

Note that no external programs are called from this module giving it portability and efficiency.

Example:

```
>>> import filecmp
>>> filecmp.cmp('libundoc.tex', 'libundoc.tex')
1
>>> filecmp.cmp('libundoc.tex', 'lib.tex')
0
```

6.8 `time` — Time access and conversions

This module provides various time-related functions. It is always available, but not all functions are available on all platforms.

An explanation of some terminology and conventions is in order.

- The *epoch* is the point where the time starts. On January 1st of that year, at 0 hours, the “time since the epoch” is zero. For UNIX, the epoch is 1970. To find out what the epoch is, look at `gmtime(0)`.
- The functions in this module do not handle dates and times before the epoch or far in the future. The cut-off point in the future is determined by the C library; for UNIX, it is typically in 2038.
- **Year 2000 (Y2K) issues:** Python depends on the platform's C library, which generally doesn't have year 2000 issues, since all dates and times are represented internally as seconds since the epoch. Functions accepting a time tuple (see below) generally require a 4-digit year. For backward compatibility, 2-digit years are supported if the module variable `accept2dyear` is a non-zero integer; this variable is initialized to 1 unless the environment variable `$PYTHON2K` is set to a non-empty string, in which case it is initialized to 0. Thus, you can set `$PYTHON2K` to a non-empty string in the environment to require 4-digit years for all year input. When 2-digit years are accepted, they are converted according to the POSIX or X/Open standard: values 69-99 are mapped to 1969-1999, and values 0-68 are mapped to 2000-2068. Values 100-1899 are always illegal. Note that this is new as of Python 1.5.2(a2); earlier versions, up to Python 1.5.1 and 1.5.2a1, would add 1900 to year values below 1900.
- UTC is Coordinated Universal Time (formerly known as Greenwich Mean Time, or GMT). The acronym UTC is not a mistake but a compromise between English and French.
- DST is Daylight Saving Time, an adjustment of the timezone by (usually) one hour during part of the year. DST rules are magic (determined by local law) and can change from year to year. The C library has a table containing the local rules (often it is read from a system file for flexibility) and is the only source of True Wisdom in this respect.
- The precision of the various real-time functions may be less than suggested by the units in which their value or argument is expressed. E.g. on most UNIX systems, the clock “ticks” only 50 or 100 times a second, and on the Mac, times are only accurate to whole seconds.

- On the other hand, the precision of `time()` and `sleep()` is better than their UNIX equivalents: times are expressed as floating point numbers, `time()` returns the most accurate time available (using UNIX `gettimeofday()` where available), and `sleep()` will accept a time with a nonzero fraction (UNIX `select()` is used to implement this, where available).
- The time tuple as returned by `gmtime()`, `localtime()`, and `strptime()`, and accepted by `asctime()`, `mktime()` and `strftime()`, is a tuple of 9 integers:

Index	Field	Values
0	year	(e.g. 1993)
1	month	range [1,12]
2	day	range [1,31]
3	hour	range [0,23]
4	minute	range [0,59]
5	second	range [0,61]; see (1) in <code>strftime()</code> description
6	weekday	range [0,6], monday is 0
7	Julian day	range [1,366]
8	daylight savings flag	0, 1 or -1; see below

Note that unlike the C structure, the month value is a range of 1-12, not 0-11. A year value will be handled as described under “Year 2000 (Y2K) issues” above. A `-1` argument as daylight savings flag, passed to `mktime()` will usually result in the correct daylight savings state to be filled in.

The module defines the following functions and data items:

accept2dyear

Boolean value indicating whether two-digit year values will be accepted. This is true by default, but will be set to false if the environment variable `$PYTHON2K` has been set to a non-empty string. It may also be modified at run time.

altzone

The offset of the local DST timezone, in seconds west of UTC, if one is defined. Negative if the local DST timezone is east of the 0th meridian (as in Western Europe, including the UK). Only use this if `daylight` is nonzero.

asctime(*tuple*)

Convert a tuple representing a time as returned by `gmtime()` or `localtime()` to a 24-character string of the following form: `'Sun Jun 20 23:21:05 1993'`. Note: unlike the C function of the same name, there is no trailing newline.

clock()

Return the current CPU time as a floating point number expressed in seconds. The precision, and in fact the very definition of the meaning of “CPU time”, depends on that of the C function of the same name, but in any case, this is the function to use for benchmarking Python or timing algorithms.

ctime(*secs*)

Convert a time expressed in seconds since the epoch to a string representing local time. `ctime(secs)` is equivalent to `asctime(localtime(secs))`.

daylight

Nonzero if a DST timezone is defined.

gmtime(*secs*)

Convert a time expressed in seconds since the epoch to a time tuple in UTC in which the dst flag is always zero. Fractions of a second are ignored. See above for a description of the tuple lay-out.

localtime(*secs*)

Like `gmtime()` but converts to local time. The dst flag is set to 1 when DST applies to the given time.

mktime(*tuple*)

This is the inverse function of `localtime()`. Its argument is the full 9-tuple (since the `dst` flag is needed — pass `-1` as the `dst` flag if it is unknown) which expresses the time in *local* time, not UTC. It returns a floating point number, for compatibility with `time()`. If the input value cannot be represented as a valid time, `OverflowError` is raised.

sleep(*secs*)

Suspend execution for the given number of seconds. The argument may be a floating point number to indicate a more precise sleep time. The actual suspension time may be less than that requested because any caught signal will terminate the `sleep()` following execution of that signal's catching routine. Also, the suspension time may be longer than requested by an arbitrary amount because of the scheduling of other activity in the system.

strftime(*format, tuple*)

Convert a tuple representing a time as returned by `gmtime()` or `localtime()` to a string as specified by the *format* argument. *format* must be a string.

The following directives can be embedded in the *format* string. They are shown without the optional field width and precision specification, and are replaced by the indicated characters in the `strftime()` result:

Directive	Meaning	Notes
%a	Locale's abbreviated weekday name.	
%A	Locale's full weekday name.	
%b	Locale's abbreviated month name.	
%B	Locale's full month name.	
%c	Locale's appropriate date and time representation.	
%d	Day of the month as a decimal number [01,31].	
%H	Hour (24-hour clock) as a decimal number [00,23].	
%I	Hour (12-hour clock) as a decimal number [01,12].	
%j	Day of the year as a decimal number [001,366].	
%m	Month as a decimal number [01,12].	
%M	Minute as a decimal number [00,59].	
%p	Locale's equivalent of either AM or PM.	
%S	Second as a decimal number [00,61].	(1)
%U	Week number of the year (Sunday as the first day of the week) as a decimal number [00,53]. All days in a new year preceding the first Sunday are considered to be in week 0.	
%w	Weekday as a decimal number [0(Sunday),6].	
%W	Week number of the year (Monday as the first day of the week) as a decimal number [00,53]. All days in a new year preceding the first Sunday are considered to be in week 0.	
%x	Locale's appropriate date representation.	
%X	Locale's appropriate time representation.	
%Y	Year without century as a decimal number [00,99].	
%Y	Year with century as a decimal number.	
%Z	Time zone name (or by no characters if no time zone exists).	
%%	A literal '%' character.	

Notes:

(1)The range really is 0 to 61; this accounts for leap seconds and the (very rare) double leap seconds.

Additional directives may be supported on certain platforms, but only the ones listed here have a meaning standardized by ANSI C.

On some platforms, an optional field width and precision specification can immediately follow the initial '%' of a directive in the following order; this is also not portable. The field width is normally 2 except for %j where it is 3.

strptime(*string*[, *format*])

Parse a string representing a time according to a format. The return value is a tuple as returned by `gmtime()` or `localtime()`. The *format* parameter uses the same directives as those used by `strftime()`; it defaults to "%a %b %d %H:%M:%S %Y" which matches the formatting returned by `ctime()`. The same platform caveats apply; see the local UNIX documentation for restrictions or additional supported directives. If *string* cannot be parsed according to *format*, `ValueError` is raised.

Availability: Most modern UNIX systems.

time()

Return the time as a floating point number expressed in seconds since the epoch, in UTC. Note that even though the time is always returned as a floating point number, not all systems provide time with a better precision than 1 second.

timezone

The offset of the local (non-DST) timezone, in seconds west of UTC (i.e. negative in most of Western Europe, positive in the US, zero in the UK).

tzname

A tuple of two strings: the first is the name of the local non-DST timezone, the second is the name of the local DST timezone. If no DST timezone is defined, the second string should not be used.

See Also:

[Module locale](#) (section 6.18):

Internationalization services. The locale settings can affect the return values for some of the functions in the `time` module.

6.9 sched — Event scheduler

The `sched` module defines a class which implements a general purpose event scheduler:

scheduler(*timefunc*, *delayfunc*)

The `scheduler` class defines a generic interface to scheduling events. It needs two functions to actually deal with the “outside world” — *timefunc* should be callable without arguments, and return a number (the “time”, in any units whatsoever). The *delayfunc* function should be callable with one argument, compatible with the output of *timefunc*, and should delay that many time units. *delayfunc* will also be called with the argument 0 after each event is run to allow other threads an opportunity to run in multi-threaded applications.

Example:

```

>>> import sched, time
>>> s=sched.scheduler(time.time, time.sleep)
>>> def print_time(): print "From print_time", time.time()
...
>>> def print_some_times():
...     print time.time()
...     s.enter(5, 1, print_time, ())
...     s.enter(10, 1, print_time, ())
...     s.run()
...     print time.time()
...
>>> print_some_times()
930343690.257
From print_time 930343695.274
From print_time 930343700.273
930343700.276

```

6.9.1 Scheduler Objects

scheduler instances have the following methods:

enterabs(*time, priority, action, argument*)

Schedule a new event. The *time* argument should be a numeric type compatible with the return value of the *timefunc* function passed to the constructor. Events scheduled for the same *time* will be executed in the order of their *priority*.

Executing the event means executing `apply(action, argument)`. *argument* must be a tuple holding the parameters for *action*.

Return value is an event which may be used for later cancellation of the event (see `cancel()`).

enter(*delay, priority, action, argument*)

Schedule an event for *delay* more time units. Other than the relative time, the other arguments, the effect and the return value are the same as those for `enterabs()`.

cancel(*event*)

Remove the event from the queue. If *event* is not an event currently in the queue, this method will raise a `RuntimeError`.

empty()

Return true if the event queue is empty.

run()

Run all scheduled events. This function will wait (using the `delayfunc` function passed to the constructor) for the next event, then execute it and so on until there are no more scheduled events.

Either *action* or *delayfunc* can raise an exception. In either case, the scheduler will maintain a consistent state and propagate the exception. If an exception is raised by *action*, the event will not be attempted in future calls to `run()`.

If a sequence of events takes longer to run than the time available before the next event, the scheduler will simply fall behind. No events will be dropped; the calling code is responsible for cancelling events which are no longer pertinent.

6.10 getpass — Portable password input

The `getpass` module provides two functions:

getpass([*prompt*])

Prompt the user for a password without echoing. The user is prompted using the string *prompt*, which defaults to 'Password: '. Availability: Macintosh, UNIX, Windows.

getuser()

Return the “login name” of the user. Availability: UNIX, Windows.

This function checks the environment variables `$LOGNAME`, `$USER`, `$LNAME` and `$USERNAME`, in order, and returns the value of the first one which is set to a non-empty string. If none are set, the login name from the password database is returned on systems which support the `pwd` module, otherwise, an exception is raised.

6.11 `curses` — Terminal independant console handling

The `curses` module provides an interface to the `curses` UNIX library, the de-facto standard for portable advanced terminal handling.

While `curses` is most widely used in the UNIX environment, versions are available for DOS, OS/2, and possibly other systems as well. The extension module has not been tested with all available versions of `curses`.

See Also:

Tutorial material on using `curses` with Python is available on the Python Web site as Andrew Kuchling’s *Curses Programming with Python*, at <http://www.python.org/doc/howto/curses/curses.html>.

6.11.1 Constants and Functions

The `curses` module defines the following data members:

version

A string representing the current version of the module.

A_NORMAL

Normal attribute.

A_STANDOUT

Standout mode.

A_UNDERLINE

Underline mode.

A_BLINK

Blink mode.

A_DIM

Dim mode.

A_BOLD

Bold mode.

A_ALTCHARSET

Alternate character set mode.

KEY_*

Names for various keys. The exact names available are system dependant.

ACS_*

Names for various characters: `ACS_ULCORNER`, `ACS_LLCORNER`, `ACS_URCORNER`, `ACS_LRCORNER`, `ACS_RTEE`, `ACS_LTEE`, `ACS_BTEE`, `ACS_TTEE`, `ACS_HLINE`, `ACS_VLINE`, `ACS_PLUS`, `ACS_S1`,

ACS_S9, ACS_DIAMOND, ACS_CKBOARD, ACS_DEGREE, ACS_PLMINUS, ACS_BULLET, ACS_LARROW, ACS_RARROW, ACS_DARROW.

Note: These are available only after `initscr()` has been called.

The module `curses` defines the following exception:

error

Curses function returned an error status.

Note: Whenever *x* or *y* arguments to a function or a method are optional, they default to the current cursor location. Whenever *attr* is optional, it defaults to `A_NORMAL`.

The module `curses` defines the following functions:

initscr()

Initialize the library. Returns a `WindowObject` which represents the whole screen.

endwin()

De-initialize the library, and return terminal to normal status.

isendwin()

Returns true if `endwin()` has been called.

doupdate()

Update the screen.

newwin([*nlines*, *ncols*], *begin_y*, *begin_x*)

Return a new window, whose left-upper corner is at (*begin_y*, *begin_x*), and whose height/width is *nlines/ncols*.

By default, the window will extend from the specified position to the lower right corner of the screen.

beep()

Emit a short sound.

flash()

Flash the screen.

ungetch(*ch*)

Push *ch* so the next `getch()` will return it; *ch* is an integer specifying the character to be pushed. **Note:** only one *ch* can be pushed before `getch()` is called.

flushinp()

Flush all input buffers.

cbreak()

Enter cbreak mode.

nocbreak()

Leave cbreak mode.

echo()

Enter echo mode.

noecho()

Leave echo mode.

nl()

Enter nl mode.

nonl()

Leave nl mode.

raw()

Enter raw mode.

noraw()
Leave raw mode.

meta(*yes*)
If *yes* is 1, allow 8-bit characters. If *yes* is 0, allow only 7-bit chars.

keyname(*k*)
Return the name of the key numbered *k*.

6.11.2 Window Objects

Window objects, as returned by `initscr()` and `newwin()` above, have the following methods:

refresh()
Update the display immediately (sync actual screen with previous drawing/deleting methods).

nooutrefresh()
Mark for refresh but wait.

mvwin(*new_y*, *new_x*)
Move the window so its upper-left corner is at (*new_y*, *new_x*).

move(*new_y*, *new_x*)
Move cursor to (*new_y*, *new_x*).

subwin([*nlines*, *ncols*,] *begin_y*, *begin_x*)
Return a sub-window, whose upper-left corner is at (*begin_y*, *begin_x*), and whose width/height is *ncols/nlines*.
By default, the sub-window will extend from the specified position to the lower right corner of the window.

addch([*y*, *x*,] *ch*[, *attr*])
Note: A *character* means a C character (i.e., an ASCII code), rather than a Python character (a string of length 1). (This note is true whenever the documentation mentions a character.)
Paint character *ch* at (*y*, *x*) with attributes *attr*, overwriting any character previously painter at that location.
By default, the character position and attributes are the current settings for the window object.

insch([*y*, *x*,] *ch*[, *attr*])
Paint character *ch* at (*y*, *x*) with attributes *attr*, moving the line from position *x* right by one character.

delch([*x*, *y*])
Delete any character at (*y*, *x*).

echochar(*ch*[, *attr*])
Add character *ch* with attribute *attr*, and immediately call `refresh`.

addstr([*y*, *x*,] *str*[, *attr*])
Paint string *str* at (*y*, *x*) with attributes *attr*, overwriting anything previously on the display.

attron(*attr*)
Turn on attribute *attr*.

attroff(*attr*)
Turn off attribute *attr*.

setattr(*attr*)
Set the current attributes to *attr*.

standend()
Turn off all attributes.

standout()

Turn on attribute `A_STANDOUT`.

border([*ls*[, *rs*[, *ts*[, *bs*[, *tl*[, *tr*[, *bl*[, *br*]]]]]]])

Draw a border around the edges of the window. Each parameter specifies the character to use for a specific part of the border; see the table below for more details. The characters must be specified as integers; using one-character strings will cause `TypeError` to be raised.

Note: A 0 value for any parameter will cause the default character to be used for that parameter. Keyword parameters can *not* be used. The defaults are listed in this table:

Parameter	Description	Default value
<i>ls</i>	Left side	ACS_VLINE
<i>rs</i>	Right side	ACS_VLINE
<i>ts</i>	Top	ACS_HLINE
<i>bs</i>	Bottom	ACS_HLINE
<i>tl</i>	Upper-left corner	ACS_ULCORNER
<i>tr</i>	Upper-right corner	ACS_URCORNER
<i>bl</i>	Bottom-left corner	ACS_BLCORNER
<i>br</i>	Bottom-right corner	ACS_BRCORNER

box([*vertch*, *horch*])

Similar to `border` (), but both *ls* and *rs* are *vertch* and both *ts* and *bs* are *horch*. The default corner characters are always used by this function.

hline([*y*, *x*,] *ch*, *n*)

Display a horizontal line starting at (*y*, *x*) with length *n* consisting of the character *ch*.

vline([*y*, *x*,] *ch*, *n*)

Display a vertical line starting at (*y*, *x*) with length *n* consisting of the character *ch*.

erase()

Clear the screen.

deleteln()

Delete the line under the cursor. All following lines are moved up by 1 line.

insertln()

Insert a blank line under the cursor. All following lines are moved down by 1 line.

getyx()

Return a tuple (*y*, *x*) of current cursor position.

getbegyx()

Return a tuple (*y*, *x*) of co-ordinates of upper-left corner.

getmaxyx()

Return a tuple (*y*, *x*) of the height and width of the window.

clear()

Like `erase` (), but also causes the whole screen to be repainted upon next call to `refresh` ().

clrtoebot()

Erase from cursor to the end of the screen: all lines below the cursor are deleted, and then the equivalent of `clrtoeol` () is performed.

clrtoeol()

Erase from cursor to the end of the line.

scroll([*lines* = 1])

Scroll the screen upward by *lines* lines.

touchwin()

Pretend the whole window has been changed, for purposes of drawing optimizations.

touchline(*start*, *count*)

Pretend *count* lines have been changed, starting with line *start*.

getch([*x*, *y*])

Get a character. Note that the integer returned does *not* have to be in ASCII range: function keys, keypad keys and so on return numbers higher than 256. In no-delay mode, an exception is raised if there is no input.

getstr([*x*, *y*])

Read a string from the user, with primitive line editing capacity.

inch([*x*, *y*])

Return the character at the given position in the window. The bottom 8 bits are the character proper, and upper bits are the attributes.

clearok(*yes*)

If *yes* is 1, the next call to `refresh()` will clear the screen completely.

idlok(*yes*)

If called with *yes* equal to 1, `curses` will try and use hardware line editing facilities. Otherwise, line insertion/deletion are disabled.

leaveok(*yes*)

If *yes* is 1, cursor is left where it is, instead of being at “cursor position.” This reduces cursor movement where possible. If possible it will be made invisible.

If *yes* is 0, cursor will always be at “cursor position” after an update.

setscrreg(*top*, *bottom*)

Set the scrolling region from line *top* to line *bottom*. All scrolling actions will take place in this region.

keypad(*yes*)

If *yes* is 1, escape sequences generated by some keys (keypad, function keys) will be interpreted by `curses`.

If *yes* is 0, escape sequences will be left as is in the input stream.

nodelay(*yes*)

If *yes* is 1, `getch()` will be non-blocking.

notimeout(*yes*)

If *yes* is 1, escape sequences will not be timed out.

If *yes* is 0, after a few milliseconds, an escape sequence will not be interpreted, and will be left in the input stream as is.

6.12 `getopt` — Parser for command line options.

This module helps scripts to parse the command line arguments in `sys.argv`. It supports the same conventions as the UNIX `getopt()` function (including the special meanings of arguments of the form ‘-’ and ‘--’). Long options similar to those supported by GNU software may be used as well via an optional third argument. This module provides a single function and an exception:

getopt(*args*, *options*[, *long_options*])

Parses command line options and parameter list. *args* is the argument list to be parsed, without the leading reference to the running program. Typically, this means ‘`sys.argv[1:]`’. *options* is the string of option letters that the script wants to recognize, with options that require an argument followed by a colon (i.e., the same format that UNIX `getopt()` uses). If specified, *long_options* is a list of strings with the names of the long options which should be supported. The leading ‘--’ characters should not be included in the option name. Options which require an argument should be followed by an equal sign (‘=’).

The return value consists of two elements: the first is a list of (*option*, *value*) pairs; the second is the list of program arguments left after the option list was stripped (this is a trailing slice of the first argument). Each

option-and-value pair returned has the option as its first element, prefixed with a hyphen for short options (e.g., '-x') or two hyphens for long options (e.g., '--long-option'), and the option argument as its second element, or an empty string if the option has no argument. The options occur in the list in the same order in which they were found, thus allowing multiple occurrences. Long and short options may be mixed.

GetoptError

This is raised when an unrecognized option is found in the argument list or when an option requiring an argument is given none. The argument to the exception is a string indicating the cause of the error. For long options, an argument given to an option which does not require one will also cause this exception to be raised. The attributes `msg` and `opt` give the error message and related option; if there is no specific option to which the exception relates, `opt` is an empty string.

error

Alias for `GetoptError`; for backward compatibility.

An example using only UNIX style options:

```
>>> import getopt, string
>>> args = string.split('-a -b -cfoo -d bar a1 a2')
>>> args
['-a', '-b', '-cfoo', '-d', 'bar', 'a1', 'a2']
>>> optlist, args = getopt.getopt(args, 'abc:d:')
>>> optlist
[('-a', ''), ('-b', ''), ('-c', 'foo'), ('-d', 'bar')]
>>> args
['a1', 'a2']
>>>
```

Using long option names is equally easy:

```
>>> s = '--condition=foo --testing --output-file abc.def -x a1 a2'
>>> args = string.split(s)
>>> args
['--condition=foo', '--testing', '--output-file', 'abc.def', '-x', 'a1', 'a2']
>>> optlist, args = getopt.getopt(args, 'x', [
...     'condition=', 'output-file=', 'testing'])
>>> optlist
[('--condition', 'foo'), ('--testing', ''), ('--output-file', 'abc.def'), ('-x',
'')]
>>> args
['a1', 'a2']
>>>
```

6.13 `tempfile` — Generate temporary file names

This module generates temporary file names. It is not UNIX specific, but it may require some help on non-UNIX systems.

Note: the module does not create temporary files, nor does it automatically remove them when the current process exits or dies.

The module defines a single user-callable function:

mktemp()

Return a unique temporary filename. This is an absolute pathname of a file that does not exist at the time the call is made. No two calls will return the same filename.

The module uses two global variables that tell it how to construct a temporary name. The caller may assign values to them; by default they are initialized at the first call to `mktemp()`.

tempdir

When set to a value other than `None`, this variable defines the directory in which filenames returned by `mktemp()` reside. The default is taken from the environment variable `$TMPDIR`; if this is not set, either `/usr/tmp` is used (on UNIX), or the current working directory (all other systems). No check is made to see whether its value is valid.

template

When set to a value other than `None`, this variable defines the prefix of the final component of the filenames returned by `mktemp()`. A string of decimal digits is added to generate unique filenames. The default is either `'@pid.'` where `pid` is the current process ID (on UNIX), or `'tmp'` (all other systems).

Warning: if a UNIX process uses `mktemp()`, then calls `fork()` and both parent and child continue to use `mktemp()`, the processes will generate conflicting temporary names. To resolve this, the child process should assign `None` to `template`, to force recomputing the default on the next call to `mktemp()`.

6.14 `errno` — Standard `errno` system symbols.

This module makes available standard `errno` system symbols. The value of each symbol is the corresponding integer value. The names and descriptions are borrowed from `'linux/include/errno.h'`, which should be pretty all-inclusive.

errorcode

Dictionary providing a mapping from the `errno` value to the string name in the underlying system. For instance, `errno.errorcode[errno.EPERM]` maps to `'EPERM'`.

To translate a numeric error code to an error message, use `os.strerror()`.

Of the following list, symbols that are not used on the current platform are not defined by the module. Symbols available can include:

EPERM

Operation not permitted

ENOENT

No such file or directory

ESRCH

No such process

EINTR

Interrupted system call

EIO

I/O error

ENXIO

No such device or address

E2BIG

Arg list too long

ENOEXEC

Exec format error

EBADF

Bad file number

ECHILD
No child processes

EAGAIN
Try again

ENOMEM
Out of memory

EACCES
Permission denied

EFAULT
Bad address

ENOTBLK
Block device required

EBUSY
Device or resource busy

EEXIST
File exists

EXDEV
Cross-device link

ENODEV
No such device

ENOTDIR
Not a directory

EISDIR
Is a directory

EINVAL
Invalid argument

ENFILE
File table overflow

EMFILE
Too many open files

ENOTTY
Not a typewriter

ETXTBSY
Text file busy

EFBIG
File too large

ENOSPC
No space left on device

ESPIPE
Illegal seek

EROFS
Read-only file system

EMLINK
Too many links

EPIPE
Broken pipe

EDOM
Math argument out of domain of func

ERANGE
Math result not representable

EDEADLK
Resource deadlock would occur

ENAMETOOLONG
File name too long

ENOLCK
No record locks available

ENOSYS
Function not implemented

ENOTEMPTY
Directory not empty

ELOOP
Too many symbolic links encountered

EWOLDBLOCK
Operation would block

ENOMSG
No message of desired type

EIDRM
Identifier removed

ECHRNG
Channel number out of range

EL2NSYNC
Level 2 not synchronized

EL3HLT
Level 3 halted

EL3RST
Level 3 reset

ELNRNG
Link number out of range

EUNATCH
Protocol driver not attached

ENOSCI
No CSI structure available

EL2HLT
Level 2 halted

EBADE
Invalid exchange

EBADR
Invalid request descriptor

EXFULL
Exchange full

ENOANO
No anode

EBADRQC
Invalid request code

EBADSLT
Invalid slot

EDEADLOCK
File locking deadlock error

EBFONT
Bad font file format

ENOSTR
Device not a stream

ENODATA
No data available

ETIME
Timer expired

ENOSR
Out of streams resources

ENONET
Machine is not on the network

ENOPKG
Package not installed

EREMOTE
Object is remote

ENOLINK
Link has been severed

EADV
Advertise error

ESRMNT
Srmount error

ECOMM
Communication error on send

EPROTO
Protocol error

EMULTIHOP
Multihop attempted

EDOTDOT
RFS specific error

EBADMSG
Not a data message

EOVERFLOW
Value too large for defined data type

ENOTUNIQ
Name not unique on network

EBADFD
File descriptor in bad state

EREMCHG
Remote address changed

ELIBACC
Can not access a needed shared library

ELIBBAD
Accessing a corrupted shared library

ELIBSCN
.lib section in a.out corrupted

ELIBMAX
Attempting to link in too many shared libraries

ELIBEXEC
Cannot exec a shared library directly

EILSEQ
Illegal byte sequence

ERESTART
Interrupted system call should be restarted

ESTRPIPE
Streams pipe error

EUSERS
Too many users

ENOTSOCK
Socket operation on non-socket

EDESTADDRREQ
Destination address required

EMSGSIZE
Message too long

EPROTOTYPE
Protocol wrong type for socket

ENOPROTOOPT
Protocol not available

EPROTONOSUPPORT
Protocol not supported

ESOCKTNOSUPPORT
Socket type not supported

EOPNOTSUPP
Operation not supported on transport endpoint

EPFNOSUPPORT
Protocol family not supported

EAFNOSUPPORT
Address family not supported by protocol

EADDRINUSE
Address already in use

EADDRNOTAVAIL
Cannot assign requested address

ENETDOWN
Network is down

ENETUNREACH
Network is unreachable

ENETRESET
Network dropped connection because of reset

ECONNABORTED
Software caused connection abort

ECONNRESET
Connection reset by peer

ENOBUFS
No buffer space available

EISCONN
Transport endpoint is already connected

ENOTCONN
Transport endpoint is not connected

ESHUTDOWN
Cannot send after transport endpoint shutdown

ETOOMANYREFS
Too many references: cannot splice

ETIMEDOUT
Connection timed out

ECONNREFUSED
Connection refused

EHOSTDOWN
Host is down

EHOSTUNREACH
No route to host

EALREADY
Operation already in progress

EINPROGRESS
Operation now in progress

ESTALE
Stale NFS file handle

EUCLEAN
Structure needs cleaning

ENOTNAM
Not a XENIX named type file

ENAVAIL
No XENIX semaphores available

EISNAM

Is a named type file

EREMOTEIO

Remote I/O error

EDQUOT

Quota exceeded

6.15 glob — UNIX style pathname pattern expansion

The `glob` module finds all the pathnames matching a specified pattern according to the rules used by the UNIX shell. No tilde expansion is done, but `*`, `?`, and character ranges expressed with `[]` will be correctly matched. This is done by using the `os.listdir()` and `fnmatch.fnmatch()` functions in concert, and not by actually invoking a subshell. (For tilde and shell variable expansion, use `os.path.expanduser()` and `os.path.expandvars()`.)

glob(pathname)

Returns a possibly-empty list of path names that match *pathname*, which must be a string containing a path specification. *pathname* can be either absolute (like `/usr/src/Python-1.5/Makefile`) or relative (like `../../Tools/*.gif`), and can contain shell-style wildcards.

For example, consider a directory containing only the following files: `'1.gif'`, `'2.txt'`, and `'card.gif'`. `glob()` will produce the following results. Notice how any leading components of the path are preserved.

```
>>> import glob
>>> glob.glob('./[0-9].*')
['./1.gif', './2.txt']
>>> glob.glob('*.*gif')
['1.gif', 'card.gif']
>>> glob.glob('?.gif')
['1.gif']
```

See Also:

[Module `fnmatch`](#) (section 6.16):

Shell-style filename (not path) expansion

6.16 fnmatch — UNIX filename pattern matching

This module provides support for UNIX shell-style wildcards, which are *not* the same as regular expressions (which are documented in the [`re`](#) module). The special characters used in shell-style wildcards are:

Pattern	Meaning
<code>*</code>	matches everything
<code>?</code>	matches any single character
<code>[seq]</code>	matches any character in <i>seq</i>
<code>[!seq]</code>	matches any character not in <i>seq</i>

Note that the filename separator (`'/'` on UNIX) is *not* special to this module. See module [`glob`](#) for pathname expansion (`glob` uses `fnmatch()` to match pathname segments). Similarly, filenames starting with a period are not special for this module, and are matched by the `*` and `?` patterns.

fnmatch(*filename*, *pattern*)

Test whether the *filename* string matches the *pattern* string, returning true or false. If the operating system is case-insensitive, then both parameters will be normalized to all lower- or upper-case before the comparison is performed. If you require a case-sensitive comparison regardless of whether that's standard for your operating system, use `fnmatchcase()` instead.

fnmatchcase(*filename*, *pattern*)

Test whether *filename* matches *pattern*, returning true or false; the comparison is case-sensitive.

See Also:

Module `glob` (section 6.15):

UNIX shell-style path expansion.

6.17 `shutil` — High-level file operations

The `shutil` module offers a number of high-level operations on files and collections of files. In particular, functions are provided which support file copying and removal.

Caveat: On MacOS, the resource fork and other metadata are not used. For file copies, this means that resources will be lost and file type and creator codes will not be correct.

copyfile(*src*, *dst*)

Copy the contents of *src* to *dst*. If *dst* exists, it will be replaced, otherwise it will be created.

copymode(*src*, *dst*)

Copy the permission bits from *src* to *dst*. The file contents, owner, and group are unaffected.

copystat(*src*, *dst*)

Copy the permission bits, last access time, and last modification time from *src* to *dst*. The file contents, owner, and group are unaffected.

copy(*src*, *dst*)

Copy the file *src* to the file or directory *dst*. If *dst* is a directory, a file with the same basename as *src* is created (or overwritten) in the directory specified. Permission bits are copied.

copy2(*src*, *dst*)

Similar to `copy()`, but last access time and last modification time are copied as well. This is similar to the UNIX command `cp -p`.

copytree(*src*, *dst*[, *symlinks*])

Recursively copy an entire directory tree rooted at *src*. The destination directory, named by *dst*, must not already exist; it will be created. Individual files are copied using `copy2()`. If *symlinks* is true, symbolic links in the source tree are represented as symbolic links in the new tree; if false or omitted, the contents of the linked files are copied to the new tree. Errors are reported to standard output.

The source code for this should be considered an example rather than a tool.

rmtree(*path*[, *ignore_errors*[, *onerror*]])

Delete an entire directory tree. If *ignore_errors* is true, errors will be ignored; if false or omitted, errors are handled by calling a handler specified by *onerror* or raise an exception.

If *onerror* is provided, it must be a callable that accepts three parameters: *function*, *path*, and *excinfo*. The first parameter, *function*, is the function which raised the exception; it will be `os.remove()` or `os.rmdir()`. The second parameter, *path*, will be the path name passed to *function*. The third parameter, *excinfo*, will be the exception information return by `sys.exc_info()`. Exceptions raised by *onerror* will not be caught.

6.17.1 Example

This example is the implementation of the `copytree()` function, described above, with the docstring omitted. It demonstrates many of the other functions provided by this module.

```
def copytree(src, dst, symlinks=0):
    names = os.listdir(src)
    os.mkdir(dst)
    for name in names:
        srcname = os.path.join(src, name)
        dstname = os.path.join(dst, name)
        try:
            if symlinks and os.path.islink(srcname):
                linkto = os.readlink(srcname)
                os.symlink(linkto, dstname)
            elif os.path.isdir(srcname):
                copytree(srcname, dstname)
            else:
                copy2(srcname, dstname)
            # XXX What about devices, sockets etc.?
        except (IOError, os.error), why:
            print "Can't copy %s to %s: %s" % (srcname, dstname, str(why))
```

6.18 locale — Internationalization services

The `locale` module opens access to the POSIX locale database and functionality. The POSIX locale mechanism allows programmers to deal with certain cultural issues in an application, without requiring the programmer to know all the specifics of each country where the software is executed.

The `locale` module is implemented on top of the `_locale` module, which in turn uses an ANSI C locale implementation if available.

The `locale` module defines the following exception and functions:

setlocale(*category*[, *value*])

If *value* is specified, modifies the locale setting for the *category*. The available categories are listed in the data description below. The value is the name of a locale. An empty string specifies the user's default settings. If the modification of the locale fails, the exception `Error` is raised. If successful, the new locale setting is returned.

If no *value* is specified, the current setting for the *category* is returned.

`setlocale()` is not thread safe on most systems. Applications typically start with a call of

```
import locale
locale.setlocale(locale.LC_ALL, "")
```

This sets the locale for all categories to the user's default setting (typically specified in the `$LANG` environment variable). If the locale is not changed thereafter, using multithreading should not cause problems.

Error

Exception raised when `setlocale()` fails.

localeconv()

Returns the database of of the local conventions as a dictionary. This dictionary has the following strings as keys:

- `decimal_point` specifies the decimal point used in floating point number representations for the `LC_NUMERIC` category.
- `grouping` is a sequence of numbers specifying at which relative positions the `thousands_sep` is expected. If the sequence is terminated with `CHAR_MAX`, no further grouping is performed. If the sequence terminates with a 0, the last group size is repeatedly used.
- `thousands_sep` is the character used between groups.
- `int_curr_symbol` specifies the international currency symbol from the `LC_MONETARY` category.
- `currency_symbol` is the local currency symbol.
- `mon_decimal_point` is the decimal point used in monetary values.
- `mon_thousands_sep` is the separator for grouping of monetary values.
- `mon_grouping` has the same format as the `grouping` key; it is used for monetary values.
- `positive_sign` and `negative_sign` gives the sign used for positive and negative monetary quantities.
- `int_frac_digits` and `frac_digits` specify the number of fractional digits used in the international and local formatting of monetary values.
- `p_cs_precedes` and `n_cs_precedes` specifies whether the currency symbol precedes the value for positive or negative values.
- `p_sep_by_space` and `n_sep_by_space` specifies whether there is a space between the positive or negative value and the currency symbol.
- `p_sign_posn` and `n_sign_posn` indicate how the sign should be placed for positive and negative monetary values.

The possible values for `p_sign_posn` and `n_sign_posn` are given below.

Value	Explanation
0	Currency and value are surrounded by parentheses.
1	The sign should precede the value and currency symbol.
2	The sign should follow the value and currency symbol.
3	The sign should immediately precede the value.
4	The sign should immediately follow the value.
<code>LC_MAX</code>	Nothing is specified in this locale.

strcoll (*string1*, *string2*)

Compares two strings according to the current `LC_COLLATE` setting. As any other compare function, returns a negative, or a positive value, or 0, depending on whether *string1* collates before or after *string2* or is equal to it.

strxfrm (*string*)

Transforms a string to one that can be used for the built-in function `cmp()`, and still returns locale-aware results. This function can be used when the same string is compared repeatedly, e.g. when collating a sequence of strings.

format (*format*, *val*, [*grouping* = 0])

Formats a number *val* according to the current `LC_NUMERIC` setting. The format follows the conventions of the `%` operator. For floating point values, the decimal point is modified if appropriate. If *grouping* is true, also takes the grouping into account.

str (*float*)

Formats a floating point number using the same format as the built-in function `str(float)`, but takes the decimal point into account.

atof (*string*)

Converts a string to a floating point number, following the `LC_NUMERIC` settings.

atoi (*string*)

Converts a string to an integer, following the `LC_NUMERIC` conventions.

LC_CTYPE

Locale category for the character type functions. Depending on the settings of this category, the functions of module `string` dealing with case change their behaviour.

LC_COLLATE

Locale category for sorting strings. The functions `strcoll()` and `strxfrm()` of the `locale` module are affected.

LC_TIME

Locale category for the formatting of time. The function `time.strftime()` follows these conventions.

LC_MONETARY

Locale category for formatting of monetary values. The available options are available from the `localeconv()` function.

LC_MESSAGES

Locale category for message display. Python currently does not support application specific locale-aware messages. Messages displayed by the operating system, like those returned by `os.strerror()` might be affected by this category.

LC_NUMERIC

Locale category for formatting numbers. The functions `format()`, `atoi()`, `atof()` and `str()` of the `locale` module are affected by that category. All other numeric formatting operations are not affected.

LC_ALL

Combination of all locale settings. If this flag is used when the locale is changed, setting the locale for all categories is attempted. If that fails for any category, no category is changed at all. When the locale is retrieved using this flag, a string indicating the setting for all categories is returned. This string can be later used to restore the settings.

CHAR_MAX

This is a symbolic constant used for different values returned by `localeconv()`.

Example:

```
>>> import locale
>>> loc = locale.setlocale(locale.LC_ALL) # get current locale
>>> locale.setlocale(locale.LC_ALL, "de") # use German locale
>>> locale.strcoll("f\344n", "foo") # compare a string containing an umlaut
>>> locale.setlocale(locale.LC_ALL, "") # use user's preferred locale
>>> locale.setlocale(locale.LC_ALL, "C") # use default (C) locale
>>> locale.setlocale(locale.LC_ALL, loc) # restore saved locale
```

6.18.1 Background, details, hints, tips and caveats

The C standard defines the locale as a program-wide property that may be relatively expensive to change. On top of that, some implementation are broken in such a way that frequent locale changes may cause core dumps. This makes the locale somewhat painful to use correctly.

Initially, when a program is started, the locale is the 'C' locale, no matter what the user's preferred locale is. The program must explicitly say that it wants the user's preferred locale settings by calling `setlocale(LC_ALL, "")`.

It is generally a bad idea to call `setlocale()` in some library routine, since as a side effect it affects the entire program. Saving and restoring it is almost as bad: it is expensive and affects other threads that happen to run before the settings have been restored.

If, when coding a module for general use, you need a locale independent version of an operation that is affected by the

locale (e.g. `string.lower()`, or certain formats used with `time.strftime()`), you will have to find a way to do it without using the standard library routine. Even better is convincing yourself that using locale settings is okay. Only as a last resort should you document that your module is not compatible with non-‘C’ locale settings.

The case conversion functions in the `string` and `strop` modules are affected by the locale settings. When a call to the `setlocale()` function changes the `LC_CTYPE` settings, the variables `string.lowercase`, `string.uppercase` and `string.letters` (and their counterparts in `strop`) are recalculated. Note that this code that uses these variable through ‘from ... import ...’, e.g. `from string import letters`, is not affected by subsequent `setlocale()` calls.

The only way to perform numeric operations according to the locale is to use the special functions defined by this module: `atof()`, `atoi()`, `format()`, `str()`.

6.18.2 For extension writers and programs that embed Python

Extension modules should never call `setlocale()`, except to find out what the current locale is. But since the return value can only be used portably to restore it, that is not very useful (except perhaps to find out whether or not the locale is ‘C’).

When Python is embedded in an application, if the application sets the locale to something specific before initializing Python, that is generally okay, and Python will use whatever locale is set, *except* that the `LC_NUMERIC` locale should always be ‘C’.

The `setlocale()` function in the `locale` module gives the Python programmer the impression that you can manipulate the `LC_NUMERIC` locale setting, but this not the case at the C level: C code will always find that the `LC_NUMERIC` locale setting is ‘C’. This is because too much would break when the decimal point character is set to something else than a period (e.g. the Python parser would break). Caveat: threads that run without holding Python’s global interpreter lock may occasionally find that the numeric locale setting differs; this is because the only portable way to implement this feature is to set the numeric locale settings to what the user requests, extract the relevant characteristics, and then restore the ‘C’ numeric locale.

When Python code uses the `locale` module to change the locale, this also affects the embedding application. If the embedding application doesn’t want this to happen, it should remove the `_locale` extension module (which does all the work) from the table of built-in modules in the ‘`config.c`’ file, and make sure that the `_locale` module is not accessible as a shared library.

6.19 `mutex` — Mutual exclusion support

The `mutex` defines a class that allows mutual-exclusion via acquiring and releasing locks. It does not require (or imply) threading or multi-tasking, though it could be useful for those purposes.

The `mutex` module defines the following class:

`mutex()`

Create a new (unlocked) mutex.

A mutex has two pieces of state — a “locked” bit and a queue. When the mutex is not locked, the queue is empty. Otherwise, the queue contains 0 or more (*function*, *argument*) pairs representing functions (or methods) waiting to acquire the lock. When the mutex is unlocked while the queue is not empty, the first queue entry is removed and its *function(argument)* pair called, implying it now has the lock.

Of course, no multi-threading is implied – hence the funny interface for lock, where a function is called once the lock is acquired.

6.19.1 Mutex Objects

mutex objects have following methods:

test()

Check whether the mutex is locked.

testandset()

“Atomic” test-and-set, grab the lock if it is not set, and return true, otherwise, return false.

lock(function, argument)

Execute *function(argument)*, unless the mutex is locked. In the case it is locked, place the function and argument on the queue. See `unlock` for explanation of when *function(argument)* is executed in that case.

unlock()

Unlock the mutex if queue is empty, otherwise execute the first element in the queue.

Optional Operating System Services

The modules described in this chapter provide interfaces to operating system features that are available on selected operating systems only. The interfaces are generally modelled after the UNIX or C interfaces but they are available on some other systems as well (e.g. Windows or NT). Here's an overview:

<code>signal</code>	Set handlers for asynchronous events.
<code>socket</code>	Low-level networking interface.
<code>select</code>	Wait for I/O completion on multiple streams.
<code>thread</code>	Create multiple threads of control within one interpreter.
<code>threading</code>	Higher-level threading interface.
<code>Queue</code>	A synchronized queue class.
<code>anydbm</code>	Generic interface to DBM-style database modules.
<code>dumbdbm</code>	Portable implementation of the simple DBM interface.
<code>dbhash</code>	DBM-style interface to the BSD database library.
<code>whichdb</code>	Guess which DBM-style module created a given database.
<code>bsddb</code>	Interface to Berkeley DB database library
<code>zlib</code>	Low-level interface to compression and decompression routines compatible with <code>gzip</code> .
<code>gzip</code>	Interfaces for <code>gzip</code> compression and decompression using file objects. Read and write ZIP-format archive files.
<code>rlcompleter</code>	Python identifier completion in the readline library.

7.1 `signal` — Set handlers for asynchronous events.

This module provides mechanisms to use signal handlers in Python. Some general rules for working with signals and their handlers:

- A handler for a particular signal, once set, remains installed until it is explicitly reset (i.e. Python emulates the BSD style interface regardless of the underlying implementation), with the exception of the handler for `SIGCHLD`, which follows the underlying implementation.
- There is no way to “block” signals temporarily from critical sections (since this is not supported by all UNIX flavors).
- Although Python signal handlers are called asynchronously as far as the Python user is concerned, they can only occur between the “atomic” instructions of the Python interpreter. This means that signals arriving during long calculations implemented purely in C (e.g. regular expression matches on large bodies of text) may be delayed for an arbitrary amount of time.
- When a signal arrives during an I/O operation, it is possible that the I/O operation raises an exception after the signal handler returns. This is dependent on the underlying UNIX system's semantics regarding interrupted system calls.

- Because the C signal handler always returns, it makes little sense to catch synchronous errors like SIGFPE or SIGSEGV.
- Python installs a small number of signal handlers by default: SIGPIPE is ignored (so write errors on pipes and sockets can be reported as ordinary Python exceptions) and SIGINT is translated into a KeyboardInterrupt exception. All of these can be overridden.
- Some care must be taken if both signals and threads are used in the same program. The fundamental thing to remember in using signals and threads simultaneously is: always perform `signal()` operations in the main thread of execution. Any thread can perform an `alarm()`, `getsignal()`, or `pause()`; only the main thread can set a new signal handler, and the main thread will be the only one to receive signals (this is enforced by the Python `signal` module, even if the underlying thread implementation supports sending signals to individual threads). This means that signals can't be used as a means of interthread communication. Use locks instead.

The variables defined in the `signal` module are:

SIG_DFL

This is one of two standard signal handling options; it will simply perform the default function for the signal. For example, on most systems the default action for SIGQUIT is to dump core and exit, while the default action for SIGCLD is to simply ignore it.

SIG_IGN

This is another standard signal handler, which will simply ignore the given signal.

SIG*

All the signal numbers are defined symbolically. For example, the hangup signal is defined as `signal.SIGHUP`; the variable names are identical to the names used in C programs, as found in `<signal.h>`. The UNIX man page for '`signal()`' lists the existing signals (on some systems this is `signal(2)`, on others the list is in `signal(7)`). Note that not all systems define the same set of signal names; only those names defined by the system are defined by this module.

NSIG

One more than the number of the highest signal number.

The `signal` module defines the following functions:

alarm(*time*)

If *time* is non-zero, this function requests that a SIGALRM signal be sent to the process in *time* seconds. Any previously scheduled alarm is canceled (i.e. only one alarm can be scheduled at any time). The returned value is then the number of seconds before any previously set alarm was to have been delivered. If *time* is zero, no alarm is scheduled, and any scheduled alarm is canceled. The return value is the number of seconds remaining before a previously scheduled alarm. If the return value is zero, no alarm is currently scheduled. (See the UNIX man page `alarm(2)`.)

getsignal(*signalnum*)

Return the current signal handler for the signal *signalnum*. The returned value may be a callable Python object, or one of the special values `signal.SIG_IGN`, `signal.SIG_DFL` or `None`. Here, `signal.SIG_IGN` means that the signal was previously ignored, `signal.SIG_DFL` means that the default way of handling the signal was previously in use, and `None` means that the previous signal handler was not installed from Python.

pause()

Cause the process to sleep until a signal is received; the appropriate handler will then be called. Returns nothing. (See the UNIX man page `signal(2)`.)

signal(*signalnum*, *handler*)

Set the handler for signal *signalnum* to the function *handler*. *handler* can be a callable Python object taking two arguments (see below), or one of the special values `signal.SIG_IGN` or `signal.SIG_DFL`. The previous signal handler will be returned (see the description of `getsignal()` above). (See the UNIX man page `signal(2)`.)

When threads are enabled, this function can only be called from the main thread; attempting to call it from other threads will cause a `ValueError` exception to be raised.

The *handler* is called with two arguments: the signal number and the current stack frame (`None` or a frame object; see the reference manual for a description of frame objects).

7.1.1 Example

Here is a minimal example program. It uses the `alarm()` function to limit the time spent waiting to open a file; this is useful if the file is for a serial device that may not be turned on, which would normally cause the `os.open()` to hang indefinitely. The solution is to set a 5-second alarm before opening the file; if the operation takes too long, the alarm signal will be sent, and the handler raises an exception.

```
import signal, os, Fcntl

def handler(signum, frame):
    print 'Signal handler called with signal', signum
    raise IOError, "Couldn't open device!"

# Set the signal handler and a 5-second alarm
signal.signal(signal.SIGALRM, handler)
signal.alarm(5)

# This open() may hang indefinitely
fd = os.open('/dev/ttyS0', Fcntl.O_RDWR)

signal.alarm(0)          # Disable the alarm
```

7.2 socket — Low-level networking interface

This module provides access to the BSD *socket* interface. It is available on all modern UNIX systems, Windows, MacOS, BeOS, OS/2, and probably additional platforms.

For an introduction to socket programming (in C), see the following papers: *An Introductory 4.3BSD Interprocess Communication Tutorial*, by Stuart Sechrest and *An Advanced 4.3BSD Interprocess Communication Tutorial*, by Samuel J. Leffler et al, both in the *UNIX Programmer's Manual, Supplementary Documents 1* (sections PS1:7 and PS1:8). The platform-specific reference material for the various socket-related system calls are also a valuable source of information on the details of socket semantics. For UNIX, refer to the manual pages; for Windows, see the WinSock (or Winsock 2) specification.

The Python interface is a straightforward transliteration of the UNIX system call and library interface for sockets to Python's object-oriented style: the `socket()` function returns a *socket object* whose methods implement the various socket system calls. Parameter types are somewhat higher-level than in the C interface: as with `read()` and `write()` operations on Python files, buffer allocation on receive operations is automatic, and buffer length is implicit on send operations.

Socket addresses are represented as a single string for the `AF_UNIX` address family and as a pair (*host*, *port*) for the `AF_INET` address family, where *host* is a string representing either a hostname in Internet domain notation like `'daring.cwi.nl'` or an IP address like `'100.50.200.5'`, and *port* is an integral port number. Other address families are currently not supported. The address format required by a particular socket object is automatically selected based on the address family specified when the socket object was created.

For IP addresses, two special forms are accepted instead of a host address: the empty string represents `INADDR_ANY`,

and the string '`<broadcast>`' represents `INADDR_BROADCAST`.

All errors raise exceptions. The normal exceptions for invalid argument types and out-of-memory conditions can be raised; errors related to socket or address semantics raise the error `socket.error`.

Non-blocking mode is supported through the `setblocking()` method.

The module `socket` exports the following constants and functions:

error

This exception is raised for socket- or address-related errors. The accompanying value is either a string telling what went wrong or a pair (*errno*, *string*) representing an error returned by a system call, similar to the value accompanying `os.error`. See the module `errno`, which contains names for the error codes defined by the underlying operating system.

AF_UNIX

AF_INET

These constants represent the address (and protocol) families, used for the first argument to `socket()`. If the `AF_UNIX` constant is not defined then this protocol is unsupported.

SOCK_STREAM

SOCK_DGRAM

SOCK_RAW

SOCK_RDM

SOCK_SEQPACKET

These constants represent the socket types, used for the second argument to `socket()`. (Only `SOCK_STREAM` and `SOCK_DGRAM` appear to be generally useful.)

SO_*

SOMAXCONN

MSG_*

SOL_*

IPPROTO_*

IPPORT_*

INADDR_*

IP_*

Many constants of these forms, documented in the UNIX documentation on sockets and/or the IP protocol, are also defined in the `socket` module. They are generally used in arguments to the `setsockopt()` and `getsockopt()` methods of socket objects. In most cases, only those symbols that are defined in the UNIX header files are defined; for a few symbols, default values are provided.

gethostbyname(*hostname*)

Translate a host name to IP address format. The IP address is returned as a string, e.g., '`100.50.200.5`'. If the host name is an IP address itself it is returned unchanged. See `gethostbyname_ex()` for a more complete interface.

gethostbyname_ex(*hostname*)

Translate a host name to IP address format, extended interface. Return a triple (*hostname*, *aliaslist*, *ipaddrlist*) where *hostname* is the primary host name responding to the given *ip_address*, *aliaslist* is a (possibly empty) list of alternative host names for the same address, and *ipaddrlist* is a list of IP addresses for the same interface on the same host (often but not always a single address).

gethostname()

Return a string containing the hostname of the machine where the Python interpreter is currently executing. If you want to know the current machine's IP address, use `gethostbyname(gethostname())`. Note: `gethostname()` doesn't always return the fully qualified domain name; use `gethostbyaddr(gethostname())` (see below).

gethostbyaddr(*ip_address*)

Return a triple (*hostname*, *aliaslist*, *ipaddrlist*) where *hostname* is the primary host name responding to the

given *ip_address*, *aliaslist* is a (possibly empty) list of alternative host names for the same address, and *ipaddrlist* is a list of IP addresses for the same interface on the same host (most likely containing only a single address). To find the fully qualified domain name, check *hostname* and the items of *aliaslist* for an entry containing at least one period.

getprotobyname (*protocolname*)

Translate an Internet protocol name (e.g. 'icmp') to a constant suitable for passing as the (optional) third argument to the `socket()` function. This is usually only needed for sockets opened in “raw” mode (`SOCK_RAW`); for the normal socket modes, the correct protocol is chosen automatically if the protocol is omitted or zero.

getservbyname (*servicename*, *protocolname*)

Translate an Internet service name and protocol name to a port number for that service. The protocol name should be 'tcp' or 'udp'.

socket (*family*, *type* [, *proto*])

Create a new socket using the given address family, socket type and protocol number. The address family should be `AF_INET` or `AF_UNIX`. The socket type should be `SOCK_STREAM`, `SOCK_DGRAM` or perhaps one of the other 'SOCK_' constants. The protocol number is usually zero and may be omitted in that case.

fromfd (*fd*, *family*, *type* [, *proto*])

Build a socket object from an existing file descriptor (an integer as returned by a file object's `fileno()` method). Address family, socket type and protocol number are as for the `socket()` function above. The file descriptor should refer to a socket, but this is not checked — subsequent operations on the object may fail if the file descriptor is invalid. This function is rarely needed, but can be used to get or set socket options on a socket passed to a program as standard input or output (e.g. a server started by the UNIX `inetd` daemon).

ntohl (*x*)

Convert 32-bit integers from network to host byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 4-byte swap operation.

ntohs (*x*)

Convert 16-bit integers from network to host byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 2-byte swap operation.

htonl (*x*)

Convert 32-bit integers from host to network byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 4-byte swap operation.

htons (*x*)

Convert 16-bit integers from host to network byte order. On machines where the host byte order is the same as network byte order, this is a no-op; otherwise, it performs a 2-byte swap operation.

inet_aton (*ip_string*)

Convert an IP address from dotted-quad string format (e.g. '123.45.67.89') to 32-bit packed binary format, as a string four characters in length.

Useful when conversing with a program that uses the standard C library and needs objects of type `struct in_addr`, which is the C type for the 32-bit packed binary this function returns.

If the IP address string passed to this function is invalid, `socket.error` will be raised. Note that exactly what is valid depends on the underlying C implementation of `inet_aton()`.

inet_ntoa (*packed_ip*)

Convert a 32-bit packed IP address (a string four characters in length) to its standard dotted-quad string representation (e.g. '123.45.67.89').

Useful when conversing with a program that uses the standard C library and needs objects of type `struct in_addr`, which is the C type for the 32-bit packed binary this function takes as an argument.

If the string passed to this function is not exactly 4 bytes in length, `socket.error` will be raised.

SocketType

This is a Python type object that represents the socket object type. It is the same as `type(socket(...))`.

7.2.1 Socket Objects

Socket objects have the following methods. Except for `makefile()` these correspond to UNIX system calls applicable to sockets.

`accept()`

Accept a connection. The socket must be bound to an address and listening for connections. The return value is a pair `(conn, address)` where `conn` is a new socket object usable to send and receive data on the connection, and `address` is the address bound to the socket on the other end of the connection.

`bind(address)`

Bind the socket to `address`. The socket must not already be bound. (The format of `address` depends on the address family — see above.) **Note:** This method has historically accepted a pair of parameters for `AF_INET` addresses instead of only a tuple. This was never intentional and will no longer be available in Python 1.7.

`close()`

Close the socket. All future operations on the socket object will fail. The remote end will receive no more data (after queued data is flushed). Sockets are automatically closed when they are garbage-collected.

`connect(address)`

Connect to a remote socket at `address`. (The format of `address` depends on the address family — see above.) **Note:** This method has historically accepted a pair of parameters for `AF_INET` addresses instead of only a tuple. This was never intentional and will no longer be available in Python 1.7.

`connect_ex(address)`

Like `connect(address)`, but return an error indicator instead of raising an exception for errors returned by the C-level `connect()` call (other problems, such as “host not found,” can still raise exceptions). The error indicator is 0 if the operation succeeded, otherwise the value of the `errno` variable. This is useful, e.g., for asynchronous connects. **Note:** This method has historically accepted a pair of parameters for `AF_INET` addresses instead of only a tuple. This was never intentional and will no longer be available in Python 1.7.

`fileno()`

Return the socket’s file descriptor (a small integer). This is useful with `select.select()`.

`getpeername()`

Return the remote address to which the socket is connected. This is useful to find out the port number of a remote IP socket, for instance. (The format of the address returned depends on the address family — see above.) On some systems this function is not supported.

`getsockname()`

Return the socket’s own address. This is useful to find out the port number of an IP socket, for instance. (The format of the address returned depends on the address family — see above.)

`getsockopt(level, optname[, buflen])`

Return the value of the given socket option (see the UNIX man page `getsockopt(2)`). The needed symbolic constants (`SO_*` etc.) are defined in this module. If `buflen` is absent, an integer option is assumed and its integer value is returned by the function. If `buflen` is present, it specifies the maximum length of the buffer used to receive the option in, and this buffer is returned as a string. It is up to the caller to decode the contents of the buffer (see the optional built-in module `struct` for a way to decode C structures encoded as strings).

`listen(backlog)`

Listen for connections made to the socket. The `backlog` argument specifies the maximum number of queued connections and should be at least 1; the maximum value is system-dependent (usually 5).

`makefile([mode[, bufsize]])`

Return a *file object* associated with the socket. (File objects are described in 2.1.7, “File Objects.”) The file object references a `dup()`ped version of the socket file descriptor, so the file object and socket object may be closed or garbage-collected independently. The optional `mode` and `bufsize` arguments are interpreted the same way as by the built-in `open()` function.

recv(*bufsize*[, *flags*])

Receive data from the socket. The return value is a string representing the data received. The maximum amount of data to be received at once is specified by *bufsize*. See the UNIX manual page *recv(2)* for the meaning of the optional argument *flags*; it defaults to zero.

recvfrom(*bufsize*[, *flags*])

Receive data from the socket. The return value is a pair (*string*, *address*) where *string* is a string representing the data received and *address* is the address of the socket sending the data. The optional *flags* argument has the same meaning as for *recv*() above. (The format of *address* depends on the address family — see above.)

send(*string*[, *flags*])

Send data to the socket. The socket must be connected to a remote socket. The optional *flags* argument has the same meaning as for *recv*() above. Returns the number of bytes sent.

sendto(*string*[, *flags*], *address*)

Send data to the socket. The socket should not be connected to a remote socket, since the destination socket is specified by *address*. The optional *flags* argument has the same meaning as for *recv*() above. Return the number of bytes sent. (The format of *address* depends on the address family — see above.)

setblocking(*flag*)

Set blocking or non-blocking mode of the socket: if *flag* is 0, the socket is set to non-blocking, else to blocking mode. Initially all sockets are in blocking mode. In non-blocking mode, if a *recv*() call doesn't find any data, or if a *send*() call can't immediately dispose of the data, a *error* exception is raised; in blocking mode, the calls block until they can proceed.

setsockopt(*level*, *optname*, *value*)

Set the value of the given socket option (see the UNIX man page *setsockopt(2)*). The needed symbolic constants are defined in the `socket` module (`SO_*` etc.). The value can be an integer or a string representing a buffer. In the latter case it is up to the caller to ensure that the string contains the proper bits (see the optional built-in module `struct` for a way to encode C structures as strings).

shutdown(*how*)

Shut down one or both halves of the connection. If *how* is 0, further receives are disallowed. If *how* is 1, further sends are disallowed. If *how* is 2, further sends and receives are disallowed.

Note that there are no methods `read()` or `write()`; use `recv()` and `send()` without *flags* argument instead.

7.2.2 Example

Here are two minimal example programs using the TCP/IP protocol: a server that echoes all data that it receives back (servicing only one client), and a client using it. Note that a server must perform the sequence `socket()`, `bind()`, `listen()`, `accept()` (possibly repeating the `accept()` to service more than one client), while a client only needs the sequence `socket()`, `connect()`. Also note that the server does not `send()/recv()` on the socket it is listening on but on the new socket returned by `accept()`.

```

# Echo server program
from socket import *
HOST = '' # Symbolic name meaning the local host
PORT = 50007 # Arbitrary non-privileged server
s = socket(AF_INET, SOCK_STREAM)
s.bind((HOST, PORT))
s.listen(1)
conn, addr = s.accept()
print 'Connected by', addr
while 1:
    data = conn.recv(1024)
    if not data: break
    conn.send(data)
conn.close()

# Echo client program
from socket import *
HOST = 'daring.cwi.nl' # The remote host
PORT = 50007 # The same port as used by the server
s = socket(AF_INET, SOCK_STREAM)
s.connect((HOST, PORT))
s.send('Hello, world')
data = s.recv(1024)
s.close()
print 'Received', 'data'

```

See Also:

[Module SocketServer](#) (section 11.12):
classes that simplify writing network servers

7.3 select — Waiting for I/O completion

This module provides access to the function `select()` available in most operating systems. Note that on Windows, it only works for sockets; on other operating systems, it also works for other file types (in particular, on UNIX, it works on pipes). It cannot be used on regular files to determine whether a file has grown since it was last read.

The module defines the following:

error

The exception raised when an error occurs. The accompanying value is a pair containing the numeric error code from `errno` and the corresponding string, as would be printed by the C function `perror()`.

select(*iwtd*, *owtd*, *ewtd*[, *timeout*])

This is a straightforward interface to the UNIX `select()` system call. The first three arguments are lists of 'waitable objects': either integers representing UNIX file descriptors or objects with a parameterless method named `fileno()` returning such an integer. The three lists of waitable objects are for input, output and 'exceptional conditions', respectively. Empty lists are allowed. The optional *timeout* argument specifies a time-out as a floating point number in seconds. When the *timeout* argument is omitted the function blocks until at least one file descriptor is ready. A time-out value of zero specifies a poll and never blocks.

The return value is a triple of lists of objects that are ready: subsets of the first three arguments. When the time-out is reached without a file descriptor becoming ready, three empty lists are returned.

Amongst the acceptable object types in the lists are Python file objects (e.g. `sys.stdin`, or objects returned by `open()` or `os.popen()`), socket objects returned by `socket.socket()`, and the module `stdin`

which happens to define a function `fileno()` for just this purpose. You may also define a *wrapper* class yourself, as long as it has an appropriate `fileno()` method (that really returns a UNIX file descriptor, not just a random integer).

7.4 `thread` — Multiple threads of control

This module provides low-level primitives for working with multiple threads (a.k.a. *light-weight processes* or *tasks*) — multiple threads of control sharing their global data space. For synchronization, simple locks (a.k.a. *mutexes* or *binary semaphores*) are provided.

The module is optional. It is supported on Windows NT and '95, SGI IRIX, Solaris 2.x, as well as on systems that have a POSIX thread (a.k.a. “pthread”) implementation.

It defines the following constant and functions:

error

Raised on thread-specific errors.

LockType

This is the type of lock objects.

start_new_thread(*function*, *args*[, *kwargs*])

Start a new thread. The thread executes the function *function* with the argument list *args* (which must be a tuple). The optional *kwargs* argument specifies a dictionary of keyword arguments. When the function returns, the thread silently exits. When the function terminates with an unhandled exception, a stack trace is printed and then the thread exits (but other threads continue to run).

exit()

Raise the `SystemExit` exception. When not caught, this will cause the thread to exit silently.

exit_thread()

Deprecated since release 1.5.2. Use `exit()`.

This is an obsolete synonym for `exit()`.

allocate_lock()

Return a new lock object. Methods of locks are described below. The lock is initially unlocked.

get_ident()

Return the ‘thread identifier’ of the current thread. This is a nonzero integer. Its value has no direct meaning; it is intended as a magic cookie to be used e.g. to index a dictionary of thread-specific data. Thread identifiers may be recycled when a thread exits and another thread is created.

Lock objects have the following methods:

acquire([*waitflag*])

Without the optional argument, this method acquires the lock unconditionally, if necessary waiting until it is released by another thread (only one thread at a time can acquire a lock — that’s their reason for existence), and returns `None`. If the integer *waitflag* argument is present, the action depends on its value: if it is zero, the lock is only acquired if it can be acquired immediately without waiting, while if it is nonzero, the lock is acquired unconditionally as before. If an argument is present, the return value is 1 if the lock is acquired successfully, 0 if not.

release()

Releases the lock. The lock must have been acquired earlier, but not necessarily by the same thread.

locked()

Return the status of the lock: 1 if it has been acquired by some thread, 0 if not.

Caveats:

- Threads interact strangely with interrupts: the `KeyboardInterrupt` exception will be received by an arbitrary thread. (When the `signal` module is available, interrupts always go to the main thread.)
- Calling `sys.exit()` or raising the `SystemExit` exception is equivalent to calling `exit()`.
- Not all built-in functions that may block waiting for I/O allow other threads to run. (The most popular ones (`time.sleep()`, `file.read()`, `select.select()`) work as expected.)
- It is not possible to interrupt the `acquire()` method on a lock — the `KeyboardInterrupt` exception will happen after the lock has been acquired.
- When the main thread exits, it is system defined whether the other threads survive. On SGI IRIX using the native thread implementation, they survive. On most other systems, they are killed without executing `try ... finally` clauses or executing object destructors.
- When the main thread exits, it does not do any of its usual cleanup (except that `try ... finally` clauses are honored), and the standard I/O files are not flushed.

7.5 threading — Higher-level threading interface

This module constructs higher-level threading interfaces on top of the lower level `thread` module.

This module is safe for use with `from threading import *`. It defines the following functions and objects:

`activeCount()`

Return the number of currently active `Thread` objects. The returned count is equal to the length of the list returned by `enumerate()`. A function that returns the number of currently active threads.

`Condition()`

A factory function that returns a new condition variable object. A condition variable allows one or more threads to wait until they are notified by another thread.

`currentThread()`

Return the current `Thread` object, corresponding to the caller's thread of control. If the caller's thread of control was not created through the `threading` module, a dummy thread object with limited functionality is returned.

`enumerate()`

Return a list of all currently active `Thread` objects. The list includes daemonic threads, dummy thread objects created by `currentThread()`, and the main thread. It excludes terminated threads and threads that have not yet been started.

`Event()`

A factory function that returns a new event object. An event manages a flag that can be set to true with the `set()` method and reset to false with the `clear()` method. The `wait()` method blocks until the flag is true.

`Lock()`

A factory function that returns a new primitive lock object. Once a thread has acquired it, subsequent attempts to acquire it block, until it is released; any thread may release it.

`RLock()`

A factory function that returns a new reentrant lock object. A reentrant lock must be released by the thread that acquired it. Once a thread has acquired a reentrant lock, the same thread may acquire it again without blocking; the thread must release it once for each time it has acquired it.

`Semaphore()`

A factory function that returns a new semaphore object. A semaphore manages a counter representing the number of `release()` calls minus the number of `acquire()` calls, plus an initial value. The `acquire()` method blocks if necessary until it can return without making the counter negative.

Thread()

A class that represents a thread of control. This class can be safely subclassed in a limited fashion.

Detailed interfaces for the objects are documented below.

The design of this module is loosely based on Java's threading model. However, where Java makes locks and condition variables basic behavior of every object, they are separate objects in Python. Python's `Thread` class supports a subset of the behavior of Java's `Thread` class; currently, there are no priorities, no thread groups, and threads cannot be destroyed, stopped, suspended, resumed, or interrupted. The static methods of Java's `Thread` class, when implemented, are mapped to module-level functions.

All of the methods described below are executed atomically.

7.5.1 Lock Objects

A primitive lock is a synchronization primitive that is not owned by a particular thread when locked. In Python, it is currently the lowest level synchronization primitive available, implemented directly by the `thread` extension module.

A primitive lock is in one of two states, "locked" or "unlocked". It is created in the unlocked state. It has two basic methods, `acquire()` and `release()`. When the state is unlocked, `acquire()` changes the state to locked and returns immediately. When the state is locked, `acquire()` blocks until a call to `release()` in another thread changes it to unlocked, then the `acquire()` call resets it to locked and returns. The `release()` method should only be called in the locked state; it changes the state to unlocked and returns immediately. When more than one thread is blocked in `acquire()` waiting for the state to turn to unlocked, only one thread proceeds when a `release()` call resets the state to unlocked; which one of the waiting threads proceeds is not defined, and may vary across implementations.

All methods are executed atomically.

acquire() (*blocking* = 1)

Acquire a lock, blocking or non-blocking.

When invoked without arguments, block until the lock is unlocked, then set it to locked, and return. There is no return value in this case.

When invoked with the *blocking* argument set to true, do the same thing as when called without arguments, and return true.

When invoked with the *blocking* argument set to false, do not block. If a call without an argument would block, return false immediately; otherwise, do the same thing as when called without arguments, and return true.

release()

Release a lock.

When the lock is locked, reset it to unlocked, and return. If any other threads are blocked waiting for the lock to become unlocked, allow exactly one of them to proceed.

Do not call this method when the lock is unlocked.

There is no return value.

7.5.2 RLock Objects

A reentrant lock is a synchronization primitive that may be acquired multiple times by the same thread. Internally, it uses the concepts of "owning thread" and "recursion level" in addition to the locked/unlocked state used by primitive locks. In the locked state, some thread owns the lock; in the unlocked state, no thread owns it.

To lock the lock, a thread calls its `acquire()` method; this returns once the thread owns the lock. To unlock the lock, a thread calls its `release()` method. `acquire()/release()` call pairs may be nested; only the final `release()` (i.e. the `release()` of the outermost pair) resets the lock to unlocked and allows another thread blocked in `acquire()` to proceed.

acquire([*blocking* = 1])

Acquire a lock, blocking or non-blocking.

When invoked without arguments: if this thread already owns the lock, increment the recursion level by one, and return immediately. Otherwise, if another thread owns the lock, block until the lock is unlocked. Once the lock is unlocked (not owned by any thread), then grab ownership, set the recursion level to one, and return. If more than one thread is blocked waiting until the lock is unlocked, only one at a time will be able to grab ownership of the lock. There is no return value in this case.

When invoked with the *blocking* argument set to true, do the same thing as when called without arguments, and return true.

When invoked with the *blocking* argument set to false, do not block. If a call without an argument would block, return false immediately; otherwise, do the same thing as when called without arguments, and return true.

release()

Release a lock, decrementing the recursion level. If after the decrement it is zero, reset the lock to unlocked (not owned by any thread), and if any other threads are blocked waiting for the lock to become unlocked, allow exactly one of them to proceed. If after the decrement the recursion level is still nonzero, the lock remains locked and owned by the calling thread.

Only call this method when the calling thread owns the lock. Do not call this method when the lock is unlocked.

There is no return value.

7.5.3 Condition Objects

A condition variable is always associated with some kind of lock; this can be passed in or one will be created by default. (Passing one in is useful when several condition variables must share the same lock.)

A condition variable has `acquire()` and `release()` methods that call the corresponding methods of the associated lock. It also has a `wait()` method, and `notify()` and `notifyAll()` methods. These three must only be called when the calling thread has acquired the lock.

The `wait()` method releases the lock, and then blocks until it is awakened by a `notify()` or `notifyAll()` call for the same condition variable in another thread. Once awakened, it re-acquires the lock and returns. It is also possible to specify a timeout.

The `notify()` method wakes up one of the threads waiting for the condition variable, if any are waiting. The `notifyAll()` method wakes up all threads waiting for the condition variable.

Note: the `notify()` and `notifyAll()` methods don't release the lock; this means that the thread or threads awakened will not return from their `wait()` call immediately, but only when the thread that called `notify()` or `notifyAll()` finally relinquishes ownership of the lock.

Tip: the typical programming style using condition variables uses the lock to synchronize access to some shared state; threads that are interested in a particular change of state call `wait()` repeatedly until they see the desired state, while threads that modify the state call `notify()` or `notifyAll()` when they change the state in such a way that it could possibly be a desired state for one of the waiters. For example, the following code is a generic producer-consumer situation with unlimited buffer capacity:

```

# Consume one item
cv.acquire()
while not an_item_is_available():
    cv.wait()
get_an_available_item()
cv.release()

# Produce one item
cv.acquire()
make_an_item_available()
cv.notify()
cv.release()

```

To choose between `notify()` and `notifyAll()`, consider whether one state change can be interesting for only one or several waiting threads. E.g. in a typical producer-consumer situation, adding one item to the buffer only needs to wake up one consumer thread.

Condition([*lock*])

If the *lock* argument is given and not `None`, it must be a `Lock` or `RLock` object, and it is used as the underlying lock. Otherwise, a new `RLock` object is created and used as the underlying lock.

acquire(**args*)

Acquire the underlying lock. This method calls the corresponding method on the underlying lock; the return value is whatever that method returns.

release()

Release the underlying lock. This method calls the corresponding method on the underlying lock; there is no return value.

wait([*timeout*])

Wait until notified or until a timeout occurs. This must only be called when the calling thread has acquired the lock.

This method releases the underlying lock, and then blocks until it is awakened by a `notify()` or `notifyAll()` call for the same condition variable in another thread, or until the optional timeout occurs. Once awakened or timed out, it re-acquires the lock and returns.

When the *timeout* argument is present and not `None`, it should be a floating point number specifying a timeout for the operation in seconds (or fractions thereof).

When the underlying lock is an `RLock`, it is not released using its `release()` method, since this may not actually unlock the lock when it was acquired multiple times recursively. Instead, an internal interface of the `RLock` class is used, which really unlocks it even when it has been recursively acquired several times. Another internal interface is then used to restore the recursion level when the lock is reacquired.

notify()

Wake up a thread waiting on this condition, if any. This must only be called when the calling thread has acquired the lock.

This method wakes up one of the threads waiting for the condition variable, if any are waiting; it is a no-op if no threads are waiting.

The current implementation wakes up exactly one thread, if any are waiting. However, it's not safe to rely on this behavior. A future, optimized implementation may occasionally wake up more than one thread.

Note: the awakened thread does not actually return from its `wait()` call until it can reacquire the lock. Since `notify()` does not release the lock, its caller should.

notifyAll()

Wake up all threads waiting on this condition. This method acts like `notify()`, but wakes up all waiting threads instead of one.

7.5.4 Semaphore Objects

This is one of the oldest synchronization primitives in the history of computer science, invented by the early Dutch computer scientist Edsger W. Dijkstra (he used `P()` and `V()` instead of `acquire()` and `release()`).

A semaphore manages an internal counter which is decremented by each `acquire()` call and incremented by each `release()` call. The counter can never go below zero; when `acquire()` finds that it is zero, it blocks, waiting until some other thread calls `release()`.

Semaphore([*value*])

The optional argument gives the initial value for the internal counter; it defaults to 1.

acquire([*blocking*])

Acquire a semaphore.

When invoked without arguments: if the internal counter is larger than zero on entry, decrement it by one and return immediately. If it is zero on entry, block, waiting until some other thread has called `release()` to make it larger than zero. This is done with proper interlocking so that if multiple `acquire()` calls are blocked, `release()` will wake exactly one of them up. The implementation may pick one at random, so the order in which blocked threads are awakened should not be relied on. There is no return value in this case.

When invoked with *blocking* set to true, do the same thing as when called without arguments, and return true.

When invoked with *blocking* set to false, do not block. If a call without an argument would block, return false immediately; otherwise, do the same thing as when called without arguments, and return true.

release()

Release a semaphore, incrementing the internal counter by one. When it was zero on entry and another thread is waiting for it to become larger than zero again, wake up that thread.

7.5.5 Event Objects

This is one of the simplest mechanisms for communication between threads: one thread signals an event and one or more other threads are waiting for it.

An event object manages an internal flag that can be set to true with the `set()` method and reset to false with the `clear()` method. The `wait()` method blocks until the flag is true.

Event()

The internal flag is initially false.

isSet()

Return true if and only if the internal flag is true.

set()

Set the internal flag to true. All threads waiting for it to become true are awakened. Threads that call `wait()` once the flag is true will not block at all.

clear()

Reset the internal flag to false. Subsequently, threads calling `wait()` will block until `set()` is called to set the internal flag to true again.

wait([*timeout*])

Block until the internal flag is true. If the internal flag is true on entry, return immediately. Otherwise, block until another thread calls `set()` to set the flag to true, or until the optional timeout occurs.

When the timeout argument is present and not `None`, it should be a floating point number specifying a timeout for the operation in seconds (or fractions thereof).

7.5.6 Thread Objects

This class represents an activity that is run in a separate thread of control. There are two ways to specify the activity: by passing a callable object to the constructor, or by overriding the `run()` method in a subclass. No other methods (except for the constructor) should be overridden in a subclass. In other words, *only* override the `__init__()` and `run()` methods of this class.

Once a thread object is created, its activity must be started by calling the thread's `start()` method. This invokes the `run()` method in a separate thread of control.

Once the thread's activity is started, the thread is considered 'alive' and 'active' (these concepts are almost, but not quite exactly, the same; their definition is intentionally somewhat vague). It stops being alive and active when its `run()` method terminates – either normally, or by raising an unhandled exception. The `isAlive()` method tests whether the thread is alive.

Other threads can call a thread's `join()` method. This blocks the calling thread until the thread whose `join()` method is called is terminated.

A thread has a name. The name can be passed to the constructor, set with the `setName()` method, and retrieved with the `getName()` method.

A thread can be flagged as a “daemon thread”. The significance of this flag is that the entire Python program exits when only daemon threads are left. The initial value is inherited from the creating thread. The flag can be set with the `setDaemon()` method and retrieved with the `getDaemon()` method.

There is a “main thread” object; this corresponds to the initial thread of control in the Python program. It is not a daemon thread.

There is the possibility that “dummy thread objects” are created. These are thread objects corresponding to “alien threads”. These are threads of control started outside the threading module, e.g. directly from C code. Dummy thread objects have limited functionality; they are always considered alive, active, and daemonic, and cannot be `joined`. They are never deleted, since it is impossible to detect the termination of alien threads.

Thread(*group=None, target=None, name=None, args=(), kwargs=--*)

This constructor should always be called with keyword arguments. Arguments are:

group Should be `None`; reserved for future extension when a `ThreadGroup` class is implemented.

target Callable object to be invoked by the `run()` method. Defaults to `None`, meaning nothing is called.

name The thread name. By default, a unique name is constructed of the form “Thread-*N*” where *N* is a small decimal number.

args Argument tuple for the target invocation. Defaults to `()`.

kwargs Keyword argument dictionary for the target invocation. Defaults to `{}`.

If the subclass overrides the constructor, it must make sure to invoke the base class constructor (`Thread.__init__()`) before doing anything else to the thread.

start()

Start the thread's activity.

This must be called at most once per thread object. It arranges for the object's `run()` method to be invoked in a separate thread of control.

run()

Method representing the thread's activity.

You may override this method in a subclass. The standard `run()` method invokes the callable object passed to the object's constructor as the *target* argument, if any, with sequential and keyword arguments taken from the *args* and *kwargs* arguments, respectively.

join([*timeout*])

Wait until the thread terminates. This blocks the calling thread until the thread whose `join()` method is called terminates – either normally or through an unhandled exception – or until the optional timeout occurs.

When the *timeout* argument is present and not `None`, it should be a floating point number specifying a timeout for the operation in seconds (or fractions thereof).

A thread can be `join()`ed many times.

A thread cannot join itself because this would cause a deadlock.

It is an error to attempt to `join()` a thread before it has been started.

getName()

Return the thread's name.

setName(*name*)

Set the thread's name.

The name is a string used for identification purposes only. It has no semantics. Multiple threads may be given the same name. The initial name is set by the constructor.

isAlive()

Return whether the thread is alive.

Roughly, a thread is alive from the moment the `start()` method returns until its `run()` method terminates.

isDaemon()

Return the thread's daemon flag.

setDaemon(*daemonic*)

Set the thread's daemon flag to the Boolean value *daemonic*. This must be called before `start()` is called.

The initial value is inherited from the creating thread.

The entire Python program exits when no active non-daemon threads are left.

7.6 Queue — A synchronized queue class.

The `Queue` module implements a multi-producer, multi-consumer FIFO queue. It is especially useful in threads programming when information must be exchanged safely between multiple threads. The `Queue` class in this module implements all the required locking semantics. It depends on the availability of thread support in Python.

The `Queue` module defines the following class and exception:

Queue(*maxsize*)

Constructor for the class. *maxsize* is an integer that sets the upperbound limit on the number of items that can be placed in the queue. Insertion will block once this size has been reached, until queue items are consumed. If *maxsize* is less than or equal to zero, the queue size is infinite.

Empty

Exception raised when non-blocking `get()` (or `get_nowait()`) is called on a `Queue` object which is empty or locked.

Full

Exception raised when non-blocking `put()` (or `put_nowait()`) is called on a `Queue` object which is full or locked.

7.6.1 Queue Objects

Class `Queue` implements queue objects and has the methods described below. This class can be derived from in order to implement other queue organizations (e.g. `stack`) but the inheritable interface is not described here. See the source code for details. The public methods are:

qsize()

Return the approximate size of the queue. Because of multithreading semantics, this number is not reliable.

empty()

Return 1 if the queue is empty, 0 otherwise. Because of multithreading semantics, this is not reliable.

full()

Return 1 if the queue is full, 0 otherwise. Because of multithreading semantics, this is not reliable.

put(*item*[, *block*])

Put *item* into the queue. If optional argument *block* is 1 (the default), block if necessary until a free slot is available. Otherwise (*block* is 0), put *item* on the queue if a free slot is immediately available, else raise the `Full` exception.

put_nowait(*item*)

Equivalent to `put(item, 0)`.

get([*block*])

Remove and return an item from the queue. If optional argument *block* is 1 (the default), block if necessary until an item is available. Otherwise (*block* is 0), return an item if one is immediately available, else raise the `Empty` exception.

get_nowait()

Equivalent to `get(0)`.

7.7 anydbm — Generic access to DBM-style databases

`anydbm` is a generic interface to variants of the DBM database — `dbhash` (requires `bsddb`), `gdbm`, or `dbm`. If none of these modules is installed, the slow-but-simple implementation in module `dumbdbm` will be used.

open(*filename*[, *flag*[, *mode*]])

Open the database file *filename* and return a corresponding object.

If the database file already exists, the `whichdb` module is used to determine its type and the appropriate module is used; if it does not exist, the first module listed above that can be imported is used.

The optional *flag* argument can be `'r'` to open an existing database for reading only, `'w'` to open an existing database for reading and writing, `'c'` to create the database if it doesn't exist, or `'n'`, which will always create a new empty database. If not specified, the default value is `'r'`.

The optional *mode* argument is the UNIX mode of the file, used only when the database has to be created. It defaults to octal 0666 (and will be modified by the prevailing `umask`).

error

A tuple containing the exceptions that can be raised by each of the supported modules, with a unique exception `anydbm.error` as the first item — the latter is used when `anydbm.error` is raised.

The object returned by `open()` supports most of the same functionality as dictionaries; keys and their corresponding values can be stored, retrieved, and deleted, and the `has_key()` and `keys()` methods are available. Keys and values must always be strings.

See Also:

[Module `anydbm`](#) (section 7.7):

Generic interface to dbm-style databases.

[Module `dbhash`](#) (section 7.9):

BSD db database interface.

[Module `dbm`](#) (section 8.6):

Standard UNIX database interface.

[Module `dumbdbm`](#) (section 7.8):

Portable implementation of the dbm interface.

Module `gdbm` (section 8.7):

GNU database interface, based on the `dbm` interface.

Module `shelve` (section 3.12):

General object persistence built on top of the Python `dbm` interface.

Module `whichdb` (section 7.10):

Utility module used to determine the type of an existing database.

7.8 `dumbdbm` — Portable DBM implementation

A simple and slow database implemented entirely in Python. This should only be used when no other DBM-style database is available.

open(*filename*[, *flag*[, *mode*]])

Open the database file *filename* and return a corresponding object. The optional *flag* argument can be `'r'` to open an existing database for reading only, `'w'` to open an existing database for reading and writing, `'c'` to create the database if it doesn't exist, or `'n'`, which will always create a new empty database. If not specified, the default value is `'r'`.

The optional *mode* argument is the UNIX mode of the file, used only when the database has to be created. It defaults to octal `0666` (and will be modified by the prevailing `umask`).

error

Raised for errors not reported as `KeyError` errors.

See Also:

Module `anydbm` (section 7.7):

Generic interface to `dbm`-style databases.

Module `whichdb` (section 7.10):

Utility module used to determine the type of an existing database.

7.9 `dbhash` — DBM-style interface to the BSD database library

The `dbhash` module provides a function to open databases using the BSD `db` library. This module mirrors the interface of the other Python database modules that provide access to DBM-style databases. The `bsddb` module is required to use `dbhash`.

This module provides an exception and a function:

error

Exception raised on database errors other than `KeyError`. It is a synonym for `bsddb.error`.

open(*path*, *flag*[, *mode*])

Open a `db` database and return the database object. The *path* argument is the name of the database file.

The *flag* argument can be `'r'` (the default), `'w'`, `'c'` (which creates the database if it doesn't exist), or `'n'` (which always creates a new empty database). For platforms on which the BSD `db` library supports locking, an `'l'` can be appended to indicate that locking should be used.

The optional *mode* parameter is used to indicate the UNIX permission bits that should be set if a new database must be created; this will be masked by the current `umask` value for the process.

See Also:

Module `anydbm` (section 7.7):

Generic interface to `dbm`-style databases.

Module `bsddb` (section 7.11):

Lower-level interface to the BSD db library.

Module `whichdb` (section 7.10):

Utility module used to determine the type of an existing database.

7.9.1 Database Objects

The database objects returned by `open()` provide the methods common to all the DBM-style databases. The following methods are available in addition to the standard methods.

first()

It's possible to loop over every key in the database using this method and the `next()` method. The traversal is ordered by the databases internal hash values, and won't be sorted by the key values. This method returns the starting key.

last()

Return the last key in a database traversal. This may be used to begin a reverse-order traversal; see `previous()`.

next(key)

Returns the key that follows *key* in the traversal. The following code prints every key in the database `db`, without having to create a list in memory that contains them all:

```
k = db.first()
while k != None:
    print k
    k = db.next(k)
```

previous(key)

Return the key that comes before *key* in a forward-traversal of the database. In conjunction with `last()`, this may be used to implement a reverse-order traversal.

sync()

This method forces any unwritten data to be written to the disk.

7.10 whichdb — Guess which DBM module created a database

The single function in this module attempts to guess which of the several simple database modules available—`dbm`, `gdbm`, or `dbhash`—should be used to open a given file.

whichdb(filename)

Returns one of the following values: `None` if the file can't be opened because it's unreadable or doesn't exist; the empty string (`' '`) if the file's format can't be guessed; or a string containing the required module name, such as `'dbm'` or `'gdbm'`.

7.11 bsddb — Interface to Berkeley DB library

The `bsddb` module provides an interface to the Berkeley DB library. Users can create hash, btree or record based library files using the appropriate `open` call. `Bsddb` objects behave generally like dictionaries. Keys and values must be strings, however, so to use other objects as keys or to store other kinds of objects the user must serialize them somehow, typically using `marshal.dumps` or `pickle.dumps`.

The `bsddb` module is only available on UNIX systems, so it is not built by default in the standard Python distribution. Also, there are two incompatible versions of the underlying library. Version 1.85 is widely available, but has some

known bugs. Version 2 is not quite as widely used, but does offer some improvements. The `bsddb` module uses the 1.85 interface. Users wishing to use version 2 of the Berkeley DB library will have to modify the source for the module to include `'db_185.h'` instead of `'db.h'` (`'db_185.h'` contains the version 1.85 compatibility interface).

The `bsddb` module defines the following functions that create objects that access the appropriate type of Berkeley DB file. The first two arguments of each function are the same. For ease of portability, only the first two arguments should be used in most instances.

hashopen(*filename* [, *flag* [, *mode* [, *bsize* [, *ffactor* [, *nelem* [, *cachesize* [, *hash* [, *lorder*]]]]]]]])

Open the hash format file named *filename*. The optional *flag* identifies the mode used to open the file. It may be `'r'` (read only), `'w'` (read-write), `'c'` (read-write - create if necessary) or `'n'` (read-write - truncate to zero length). The other arguments are rarely used and are just passed to the low-level `dbopen()` function. Consult the Berkeley DB documentation for their use and interpretation.

btopen(*filename* [, *flag* [, *mode* [, *btflags* [, *cachesize* [, *maxkeypage* [, *minkeypage* [, *psize* [, *lorder*]]]]]]]])

Open the btree format file named *filename*. The optional *flag* identifies the mode used to open the file. It may be `'r'` (read only), `'w'` (read-write), `'c'` (read-write - create if necessary) or `'n'` (read-write - truncate to zero length). The other arguments are rarely used and are just passed to the low-level `dbopen` function. Consult the Berkeley DB documentation for their use and interpretation.

rnopen(*filename* [, *flag* [, *mode* [, *rnflags* [, *cachesize* [, *psize* [, *lorder* [, *reclen* [, *bval* [, *bfname*]]]]]]]])

Open a DB record format file named *filename*. The optional *flag* identifies the mode used to open the file. It may be `'r'` (read only), `'w'` (read-write), `'c'` (read-write - create if necessary) or `'n'` (read-write - truncate to zero length). The other arguments are rarely used and are just passed to the low-level `dbopen` function. Consult the Berkeley DB documentation for their use and interpretation.

See Also:

[Module `dbhash`](#) (section 7.9):

DBM-style interface to the `bsddb`

7.11.1 Hash, BTree and Record Objects

Once instantiated, hash, btree and record objects support the following methods:

close()

Close the underlying file. The object can no longer be accessed. Since there is no `open` method for these objects, to open the file again a new `bsddb` module open function must be called.

keys()

Return the list of keys contained in the DB file. The order of the list is unspecified and should not be relied on. In particular, the order of the list returned is different for different file formats.

has_key(*key*)

Return 1 if the DB file contains the argument as a key.

set_location(*key*)

Set the cursor to the item indicated by the key and return it.

first()

Set the cursor to the first item in the DB file and return it. The order of keys in the file is unspecified, except in the case of B-Tree databases.

next()

Set the cursor to the next item in the DB file and return it. The order of keys in the file is unspecified, except in the case of B-Tree databases.

previous()

Set the cursor to the first item in the DB file and return it. The order of keys in the file is unspecified, except in the case of B-Tree databases. This is not supported on hashtable databases (those opened with `hashopen()`).

last()

Set the cursor to the last item in the DB file and return it. The order of keys in the file is unspecified. This is not supported on hashtable databases (those opened with `hashopen()`).

sync()

Synchronize the database on disk.

Example:

```
>>> import bsddb
>>> db = bsddb.btopen('/tmp/spam.db', 'c')
>>> for i in range(10): db['%d'%i] = '%d' % (i*i)
...
>>> db['3']
'9'
>>> db.keys()
['0', '1', '2', '3', '4', '5', '6', '7', '8', '9']
>>> db.first()
('0', '0')
>>> db.next()
('1', '1')
>>> db.last()
('9', '81')
>>> db.set_location('2')
('2', '4')
>>> db.previous()
('1', '1')
>>> db.sync()
0
```

7.12 zlib — Compression compatible with gzip

For applications that require data compression, the functions in this module allow compression and decompression, using the zlib library. The zlib library has its own home page at <http://www.cdrom.com/pub/infozip/zlib/>. Version 1.1.3 is the most recent version as of April 1999; use a later version if one is available. There are known incompatibilities between the Python module and earlier versions of the zlib library.

The available exception and functions in this module are:

error

Exception raised on compression and decompression errors.

adler32(*string*, [*value*])

Computes a Adler-32 checksum of *string*. (An Adler-32 checksum is almost as reliable as a CRC32 but can be computed much more quickly.) If *value* is present, it is used as the starting value of the checksum; otherwise, a fixed default value is used. This allows computing a running checksum over the concatenation of several input strings. The algorithm is not cryptographically strong, and should not be used for authentication or digital signatures.

compress(*string*, [*level*])

Compresses the data in *string*, returning a string contained compressed data. *level* is an integer from 1 to 9 controlling the level of compression; 1 is fastest and produces the least compression, 9 is slowest and produces the most. The default value is 6. Raises the `error` exception if any error occurs.

compressobj([*level*])

Returns a compression object, to be used for compressing data streams that won't fit into memory at once. *level* is an integer from 1 to 9 controlling the level of compression; 1 is fastest and produces the least compression, 9 is slowest and produces the most. The default value is 6.

crc32(*string*[, *value*])

Computes a CRC (Cyclic Redundancy Check) checksum of *string*. If *value* is present, it is used as the starting value of the checksum; otherwise, a fixed default value is used. This allows computing a running checksum over the concatenation of several input strings. The algorithm is not cryptographically strong, and should not be used for authentication or digital signatures.

decompress(*string*[, *wbits*[, *bufsize*]])

Decompresses the data in *string*, returning a string containing the uncompressed data. The *wbits* parameter controls the size of the window buffer. If *bufsize* is given, it is used as the initial size of the output buffer. Raises the `error` exception if any error occurs.

The absolute value of *wbits* is the base two logarithm of the size of the history buffer (the "window size") used when compressing data. Its absolute value should be between 8 and 15 for the most recent versions of the zlib library, larger values resulting in better compression at the expense of greater memory usage. The default value is 15. When *wbits* is negative, the standard **gzip** header is suppressed; this is an undocumented feature of the zlib library, used for compatibility with **unzip**'s compression file format.

bufsize is the initial size of the buffer used to hold decompressed data. If more space is required, the buffer size will be increased as needed, so you don't have to get this value exactly right; tuning it will only save a few calls to `malloc()`. The default size is 16384.

decompressobj([*wbits*])

Returns a compression object, to be used for decompressing data streams that won't fit into memory at once. The *wbits* parameter controls the size of the window buffer.

Compression objects support the following methods:

compress(*string*)

Compress *string*, returning a string containing compressed data for at least part of the data in *string*. This data should be concatenated to the output produced by any preceding calls to the `compress()` method. Some input may be kept in internal buffers for later processing.

flush([*mode*])

All pending input is processed, and a string containing the remaining compressed output is returned. *mode* can be selected from the constants `Z_SYNC_FLUSH`, `Z_FULL_FLUSH`, or `Z_FINISH`, defaulting to `Z_FINISH`. `Z_SYNC_FLUSH` and `Z_FULL_FLUSH` allow compressing further strings of data and are used to allow partial error recovery on decompression, while `Z_FINISH` finishes the compressed stream and prevents compressing any more data. After calling `flush()` with *mode* set to `Z_FINISH`, the `compress()` method cannot be called again; the only realistic action is to delete the object.

Decompression objects support the following methods, and a single attribute:

unused_data

A string which contains any unused data from the last string fed to this decompression object. If the whole string turned out to contain compressed data, this is "", the empty string.

The only way to determine where a string of compressed data ends is by actually decompressing it. This means that when compressed data is contained part of a larger file, you can only find the end of it by reading data and feeding it into a decompression object's `decompress` method until the `unused_data` attribute is no longer the empty string.

decompress(*string*)

Decompress *string*, returning a string containing the uncompressed data corresponding to at least part of the data in *string*. This data should be concatenated to the output produced by any preceding calls to the `decompress()` method. Some of the input data may be preserved in internal buffers for later processing.

flush()

All pending input is processed, and a string containing the remaining uncompressed output is returned. After calling `flush()`, the `decompress()` method cannot be called again; the only realistic action is to delete the object.

See Also:

[Module `gzip`](#) (section 7.13):

reading and writing **gzip**-format files

The zlib library home page is located at <http://www.cdrom.com/pub/infozip/zlib/>.

7.13 `gzip` — Support for **gzip** files

The data compression provided by the `zlib` module is compatible with that used by the GNU compression program **gzip**. Accordingly, the `gzip` module provides the `GzipFile` class to read and write **gzip**-format files, automatically compressing or decompressing the data so it looks like an ordinary file object. Note that additional file formats which can be decompressed by the **gzip** and **gunzip** programs, such as those produced by **compress** and **pack**, are not supported by this module.

The module defines the following items:

GzipFile([*filename*[, *mode*[, *compresslevel*[, *fileobj*]]]])

Constructor for the `GzipFile` class, which simulates most of the methods of a file object, with the exception of the `seek()` and `tell()` methods. At least one of *fileobj* and *filename* must be given a non-trivial value.

The new class instance is based on *fileobj*, which can be a regular file, a `StringIO` object, or any other object which simulates a file. It defaults to `None`, in which case *filename* is opened to provide a file object.

When *fileobj* is not `None`, the *filename* argument is only used to be included in the **gzip** file header, which may include the original filename of the uncompressed file. It defaults to the filename of *fileobj*, if discernible; otherwise, it defaults to the empty string, and in this case the original filename is not included in the header.

The *mode* argument can be any of `'r'`, `'rb'`, `'a'`, `'ab'`, `'w'`, or `'wb'`, depending on whether the file will be read or written. The default is the mode of *fileobj* if discernible; otherwise, the default is `'rb'`. Be aware that only the `'rb'`, `'ab'`, and `'wb'` values should be used for cross-platform portability.

The *compresslevel* argument is an integer from 1 to 9 controlling the level of compression; 1 is fastest and produces the least compression, and 9 is slowest and produces the most compression. The default is 9.

Calling a `GzipFile` object's `close()` method does not close *fileobj*, since you might wish to append more material after the compressed data. This also allows you to pass a `StringIO` object opened for writing as *fileobj*, and retrieve the resulting memory buffer using the `StringIO` object's `getvalue()` method.

open(*filename*[, *mode*[, *compresslevel*]])

This is a shorthand for `GzipFile(filename, mode, compresslevel)`. The *filename* argument is required; *mode* defaults to `'rb'` and *compresslevel* defaults to 9.

See Also:

[Module `zlib`](#) (section 7.12):

the basic data compression module

7.14 `zipfile` — Work with ZIP archives

The ZIP file format is a common archive and compression standard. This module provides tools to create, read, write, append, and list a ZIP file.

The available attributes of this module are:

error

The error raised for bad ZIP files.

_debug

Level of printing, defaults to 1.

ZipFile(...)

The class for reading and writing ZIP files. See “*ZipFile Objects*” (section 7.14.1) for constructor details.

is_zipfile(path)

Returns true if *path* is a valid ZIP file based on its magic number, otherwise returns false. This module does not currently handle ZIP files which have appended comments.

zip2date(zdate)

Return (*year*, *month*, *day*) for a ZIP date code.

zip2time(ztime)

Return (*hour*, *minute*, *second*) for a ZIP time code.

date2zip(year, month, day)

Return a ZIP date code.

time2zip(hour, minute, second)

Return a ZIP time code.

ZIP_STORED

The numeric constant (0) for an uncompressed archive member.

ZIP_DEFLATED

The numeric constant for the usual ZIP compression method. This requires the zlib module. No other compression methods are currently supported.

See Also:

XXX point to ZIP format definition

XXX point to Info-ZIP home page; mention WiZ

7.14.1 ZipFile Objects

zipFile(filename[, mode[, compression]])

Open a ZIP file named *filename*. The *mode* parameter should be ‘r’ to read an existing file, ‘w’ to truncate and write a new file, or ‘a’ to append to an existing file. For *mode* is ‘a’ and *filename* refers to an existing ZIP file, then additional files are added to it. If *filename* does not refer to a ZIP file, then a new ZIP archive is appended to the file. This is meant for adding a ZIP archive to another file, such as ‘python.exe’. Using

```
cat myzip.zip >> python.exe
```

also works, and at least **WinZip** can read such files. *compression* is the ZIP compression method to use when writing the archive, and should be ZIP_STORED or ZIP_DEFLATED; unrecognized values will cause `ValueError` to be raised. The default is ZIP_STORED.

XXX explain the “extra” string for the ZIP format

TOC

A read-only dictionary whose keys are the names in the archive, and whose values are tuples as follows:

Index	Meaning
0	File data seek offset
1	ZIP file "extra" data as a string
2	ZIP file bit flags
3	ZIP file compression type
4	File modification time in DOS format
5	File modification date in DOS format
6	The CRC-32 of the uncompressed data
7	The compressed size of the file
8	The uncompressed size of the file

The class `ZipFile` has these methods:

listdir()

Return a list of names in the archive. Equivalent to `zipfile.TOC.keys()`.

printdir()

Print a table of contents for the archive to stdout.

read(name)

Return the bytes of the file in the archive. The archive must be open for read or append.

writestr(bytes, arcname, year, month, day, hour, minute, second[, extra])

Write the string *bytes* and the other data to the archive, and give the archive member the name *arcname*. *extra* is the ZIP extra data string. The archive must be opened with mode 'w' or 'a'.

write(filename, arcname[, extra])

Write the file named *filename* to the archive, giving it the archive name *arcname*. *extra* is the ZIP extra data string. The archive must be open with mode 'w' or 'a'.

writepy(pathname[, basename])

Search for files '*.py' and add the corresponding file to the archive. The corresponding file is a '*.pyo' file if available, else a '*.pyc' file, compiling if necessary. If the pathname is a file, the filename must end with '.py', and just the (corresponding '*.py[oc]') file is added at the top level (no path information). If it is a directory, and the directory is not a package directory, then all the files '*.py[oc]' are added at the top level. If the directory is a package directory, then all '*.py[oc]' are added under the package name as a file path, and if any subdirectories are package directories, all of these are added recursively. *basename* is intended for internal use only. The `writepy()` method makes archives with file names like this:

```

string.pyc                                # Top level name
test/__init__.pyc                         # Package directory
test/testall.pyc                          # Module test.testall
test/bogus/__init__.pyc                   # Subpackage directory
test/bogus/myfile.pyc                     # Submodule test.bogus.myfile

```

close()

Close the archive file. You must call `close()` before exiting your program or essential records will not be written.

7.15 rlcompleter — Completion function for readline

The `rlcompleter` module defines a completion function for the `readline` module by completing valid Python identifiers and keyword.

The `rlcompleter` module defines the `Completer` class.

Example:

```

>>> import rlcompleter
>>> import readline
>>> readline.parse_and_bind("tab: complete")
>>> readline. <TAB PRESSED>
readline.__doc__          readline.get_line_buffer  readline.read_init_file
readline.__file__        readline.insert_text      readline.set_completer
readline.__name__        readline.parse_and_bind
>>> readline.

```

The `rlcompleter` module is designed for use with Python's interactive mode. A user can add the following lines to his or her initialization file (identified by the `$PYTHONSTARTUP` environment variable) to get automatic Tab completion:

```

try:
    import readline
except ImportError:
    print "Module readline not available."
else:
    import rlcompleter
    readline.parse_and_bind("tab: complete")

```

7.15.1 Completer Objects

Completer objects have the following method:

complete (*text*, *state*)

Return the *state* completion for *text*.

If called for *text* that doesn't include a period character ('.'), it will complete from names currently defined in `__main__`, `__builtin__` and keywords (as defined by the `keyword` module).

If called for a dotted name, it will try to evaluate anything without obvious side-effects (i.e., functions will not be evaluated, but it can generate calls to `__getattr__()` upto the last part, and find matches for the rest via the `dir()` function.

Unix Specific Services

The modules described in this chapter provide interfaces to features that are unique to the UNIX operating system, or in some cases to some or many variants of it. Here's an overview:

<code>posix</code>	The most common POSIX system calls (normally used via module <code>os</code>).
<code>pwd</code>	The password database (<code>getpwnam()</code> and friends).
<code>grp</code>	The group database (<code>getgrnam()</code> and friends).
<code>crypt</code>	The <code>crypt()</code> function used to check UNIX passwords.
<code>dl</code>	Call C functions in shared objects.
<code>dbm</code>	The standard “database” interface, based on <code>ndbm</code> .
<code>gdbm</code>	GNU's reinterpretation of <code>dbm</code> .
<code>termios</code>	POSIX style tty control.
<code>TERMIOS</code>	Symbolic constants required to use the <code>termios</code> module.
<code>tty</code>	Utility functions that perform common terminal control operations.
<code>pty</code>	Pseudo-Terminal Handling for SGI and Linux.
<code>fcntl</code>	The <code>fcntl()</code> and <code>ioctl()</code> system calls.
<code>pipes</code>	A Python interface to UNIX shell pipelines.
<code>posixfile</code>	A file-like object with support for locking.
<code>resource</code>	An interface to provide resource usage information on the current process.
<code>nis</code>	Interface to Sun's NIS (a.k.a. Yellow Pages) library.
<code>syslog</code>	An interface to the UNIX <code>syslog</code> library routines.
<code>popen2</code>	Subprocesses with accessible standard I/O streams.
<code>commands</code>	Utility functions for running external commands.

8.1 `posix` — The most common POSIX system calls

This module provides access to operating system functionality that is standardized by the C Standard and the POSIX standard (a thinly disguised UNIX interface).

Do not import this module directly. Instead, import the module `os`, which provides a *portable* version of this interface. On UNIX, the `os` module provides a superset of the `posix` interface. On non-UNIX operating systems the `posix` module is not available, but a subset is always available through the `os` interface. Once `os` is imported, there is *no* performance penalty in using it instead of `posix`. In addition, `os` provides some additional functionality, such as automatically calling `putenv()` when an entry in `os.environ` is changed.

The descriptions below are very terse; refer to the corresponding UNIX manual (or POSIX documentation) entry for more information. Arguments called *path* refer to a pathname given as a string.

Errors are reported as exceptions; the usual exceptions are given for type errors, while errors reported by the system calls raise `error` (a synonym for the standard exception `OSError`), described below.

8.1.1 Large File Support

Several operating systems (including AIX, HPUX, Irix and Solaris) provide support for files that are larger than 2 Gb from a C programming model where `int` and `long` are 32-bit values. This is typically accomplished by defining the relevant size and offset types as 64-bit values. Such files are sometimes referred to as *large files*.

Large file support is enabled in Python when the size of an `off_t` is larger than a `long` and the `long long` type is available and is at least as large as an `off_t`. Python longs are then used to represent file sizes, offsets and other values that can exceed the range of a Python `int`. It may be necessary to configure and compile Python with certain compiler flags to enable this mode. For example, it is enabled by default with recent versions of Irix, but with Solaris 2.6 and 2.7 you need to do something like:

```
CFLAGS="'getconf LFS_CFLAGS'" OPT="-g -O2 $CFLAGS" \
    configure
```

8.1.2 Module Contents

Module `posix` defines the following data item:

environ

A dictionary representing the string environment at the time the interpreter was started. For example, `environ['HOME']` is the pathname of your home directory, equivalent to `getenv("HOME")` in C.

Modifying this dictionary does not affect the string environment passed on by `execv()`, `popen()` or `system()`; if you need to change the environment, pass `environ` to `execve()` or add variable assignments and export statements to the command string for `system()` or `popen()`.

Note: The `os` module provides an alternate implementation of `environ` which updates the environment on modification. Note also that updating `os.environ` will render this dictionary obsolete. Use of the `os` for this is recommended over direct access to the `posix` module.

Additional contents of this module should only be accessed via the `os` module; refer to the documentation for that module for further information.

8.2 `pwd` — The password database

This module provides access to the UNIX user account and password database. It is available on all UNIX versions.

Password database entries are reported as 7-tuples containing the following items from the password database (see `<pwd.h>`), in order:

Index	Field	Meaning
0	<code>pw_name</code>	Login name
1	<code>pw_passwd</code>	Optional encrypted password
2	<code>pw_uid</code>	Numerical user ID
3	<code>pw_gid</code>	Numerical group ID
4	<code>pw_gecos</code>	User name or comment field
5	<code>pw_dir</code>	User home directory
6	<code>pw_shell</code>	User command interpreter

The `uid` and `gid` items are integers, all others are strings. `KeyError` is raised if the entry asked for cannot be found.

Note: In traditional UNIX the field `pw_passwd` usually contains a password encrypted with a DES derived algorithm (see module `crypt`). However most modern unices use a so-called *shadow password* system. On those unices the

field `pw_passwd` only contains an asterisk (`'*'`) or the letter `'x'` where the encrypted password is stored in a file `'/etc/shadow'` which is not world readable.

It defines the following items:

getpwuid(*uid*)

Return the password database entry for the given numeric user ID.

getpwnam(*name*)

Return the password database entry for the given user name.

getpwall()

Return a list of all available password database entries, in arbitrary order.

See Also:

[Module `grp`](#) (section 8.3):

An interface to the group database, similar to this.

8.3 `grp` — The group database

This module provides access to the UNIX group database. It is available on all UNIX versions.

Group database entries are reported as 4-tuples containing the following items from the group database (see `<grp.h>`), in order:

Index	Field	Meaning
0	<code>gr_name</code>	the name of the group
1	<code>gr_passwd</code>	the (encrypted) group password; often empty
2	<code>gr_gid</code>	the numerical group ID
3	<code>gr_mem</code>	all the group member's user names

The `gid` is an integer, `name` and `password` are strings, and the member list is a list of strings. (Note that most users are not explicitly listed as members of the group they are in according to the password database.) `KeyError` is raised if the entry asked for cannot be found.

It defines the following items:

getgrgid(*gid*)

Return the group database entry for the given numeric group ID.

getgrnam(*name*)

Return the group database entry for the given group name.

getgrall()

Return a list of all available group entries, in arbitrary order.

See Also:

[Module `pwd`](#) (section 8.2):

An interface to the user database, similar to this.

8.4 `crypt` — Function to check UNIX passwords

This module implements an interface to the `crypt(3)` routine, which is a one-way hash function based upon a modified DES algorithm; see the UNIX man page for further details. Possible uses include allowing Python scripts to accept typed passwords from the user, or attempting to crack UNIX passwords with a dictionary.

crypt(*word*, *salt*)

word will usually be a user's password as typed at a prompt or in a graphical interface. *salt* is usually a random two-character string which will be used to perturb the DES algorithm in one of 4096 ways. The characters in *salt* must be in the set `[./a-zA-Z0-9]`. Returns the hashed password as a string, which will be composed of characters from the same alphabet as the salt (the first two characters represent the salt itself).

A simple example illustrating typical use:

```
import crypt, getpass, pwd

def login():
    username = raw_input('Python login:')
    cryptpasswd = pwd.getpwnam(username)[1]
    if cryptpasswd:
        if cryptpasswd == 'x' or cryptpasswd == '*':
            raise "Sorry, currently no support for shadow passwords"
        cleartext = getpass.getpass()
        return crypt.crypt(cleartext, cryptpasswd[:2]) == cryptpasswd
    else:
        return 1
```

8.5 dl — Call C functions in shared objects

The `dl` module defines an interface to the `dlopen()` function, which is the most common interface on UNIX platforms for handling dynamically linked libraries. It allows the program to call arbitrary functions in such a library.

Note: This module will not work unless

```
sizeof(int) == sizeof(long) == sizeof(char *)
```

If this is not the case, `SystemError` will be raised on import.

The `dl` module defines the following function:

open(*name*[, *mode* = `RTLD_LAZY`])

Open a shared object file, and return a handle. Mode signifies late binding (`RTLD_LAZY`) or immediate binding (`RTLD_NOW`). Default is `RTLD_LAZY`. Note that some systems do not support `RTLD_NOW`.

Return value is a `dlobj`ect.

The `dl` module defines the following constants:

RTLD_LAZY

Useful as an argument to `open()`.

RTLD_NOW

Useful as an argument to `open()`. Note that on systems which do not support immediate binding, this constant will not appear in the module. For maximum portability, use `hasattr()` to determine if the system supports immediate binding.

The `dl` module defines the following exception:

error

Exception raised when an error has occurred inside the dynamic loading and linking routines.

Example:

```
>>> import dl, time
>>> a=dl.open('/lib/libc.so.6')
>>> a.call('time'), time.time()
(929723914, 929723914.498)
```

This example was tried on a Debian GNU/Linux system, and is a good example of the fact that using this module is usually a bad alternative.

8.5.1 Dl Objects

Dl objects, as returned by `open()` above, have the following methods:

close()

Free all resources, except the memory.

sym(name)

Return the pointer for the function named *name*, as a number, if it exists in the referenced shared object, otherwise `None`. This is useful in code like:

```
>>> if a.sym('time'):
...     a.call('time')
... else:
...     time.time()
```

(Note that this function will return a non-zero number, as zero is the `NULL` pointer)

call(name[, arg1[, arg2...]])

Call the function named *name* in the referenced shared object. The arguments must be either Python integers, which will be passed as is, Python strings, to which a pointer will be passed, or `None`, which will be passed as `NULL`. Note that strings should only be passed to functions as `const char*`, as Python will not like its string mutated.

There must be at most 10 arguments, and arguments not given will be treated as `None`. The function's return value must be a `C long`, which is a Python integer.

8.6 dbm — Simple “database” interface

The `dbm` module provides an interface to the UNIX `(n)dbm` library. `Dbm` objects behave like mappings (dictionaries), except that keys and values are always strings. Printing a `dbm` object doesn't print the keys and values, and the `items()` and `values()` methods are not supported.

See also the [gdbm](#) module, which provides a similar interface using the GNU GDBM library.

The module defines the following constant and functions:

error

Raised on `dbm`-specific errors, such as I/O errors. `KeyError` is raised for general mapping errors like specifying an incorrect key.

open(filename, [flag, [mode]])

Open a `dbm` database and return a `dbm` object. The *filename* argument is the name of the database file (without the `.dir` or `.pag` extensions).

The optional *flag* argument can be `'r'` (to open an existing database for reading only — default), `'w'` (to open an existing database for reading and writing), `'c'` (which creates the database if it doesn't exist), or `'n'` (which always creates a new empty database).

The optional *mode* argument is the UNIX mode of the file, used only when the database has to be created. It defaults to octal 0666.

See Also:

Module [anydbm](#) (section 7.7):

Generic interface to dbm-style databases.

Module [whichdb](#) (section 7.10):

Utility module used to determine the type of an existing database.

8.7 `gdbm` — GNU's reinterpretation of `dbm`

This module is quite similar to the `dbm` module, but uses `gdbm` instead to provide some additional functionality. Please note that the file formats created by `gdbm` and `dbm` are incompatible.

The `gdbm` module provides an interface to the GNU DBM library. `gdbm` objects behave like mappings (dictionaries), except that keys and values are always strings. Printing a `gdbm` object doesn't print the keys and values, and the `items()` and `values()` methods are not supported.

The module defines the following constant and functions:

error

Raised on `gdbm`-specific errors, such as I/O errors. `KeyError` is raised for general mapping errors like specifying an incorrect key.

open(*filename*, [*flag*, [*mode*]])

Open a `gdbm` database and return a `gdbm` object. The *filename* argument is the name of the database file.

The optional *flag* argument can be 'r' (to open an existing database for reading only — default), 'w' (to open an existing database for reading and writing), 'c' (which creates the database if it doesn't exist), or 'n' (which always creates a new empty database).

Appending 'f' to the flag opens the database in fast mode; altered data will not automatically be written to the disk after every change. This results in faster writes to the database, but may result in an inconsistent database if the program crashes while the database is still open. Use the `sync()` method to force any unwritten data to be written to the disk.

The optional *mode* argument is the UNIX mode of the file, used only when the database has to be created. It defaults to octal 0666.

In addition to the dictionary-like methods, `gdbm` objects have the following methods:

firstkey()

It's possible to loop over every key in the database using this method and the `nextkey()` method. The traversal is ordered by `gdbm`'s internal hash values, and won't be sorted by the key values. This method returns the starting key.

nextkey(*key*)

Returns the key that follows *key* in the traversal. The following code prints every key in the database `db`, without having to create a list in memory that contains them all:

```
k = db.firstkey()
while k != None:
    print k
    k = db.nextkey(k)
```

reorganize()

If you have carried out a lot of deletions and would like to shrink the space used by the `gdbm` file, this routine will reorganize the database. `gdbm` will not shorten the length of a database file except by using this reorganization; otherwise, deleted file space will be kept and reused as new (key, value) pairs are added.

sync()

When the database has been opened in fast mode, this method forces any unwritten data to be written to the disk.

See Also:

Module [anydbm](#) (section 7.7):

Generic interface to dbm-style databases.

Module [whichdb](#) (section 7.10):

Utility module used to determine the type of an existing database.

8.8 `termios` — POSIX style tty control

This module provides an interface to the POSIX calls for tty I/O control. For a complete description of these calls, see the POSIX or UNIX manual pages. It is only available for those UNIX versions that support POSIX *termios* style tty I/O control (and then only if configured at installation time).

All functions in this module take a file descriptor *fd* as their first argument. This must be an integer file descriptor, such as returned by `sys.stdin.fileno()`.

This module should be used in conjunction with the [TERMIOS](#) module, which defines the relevant symbolic constants (see the next section).

The module defines the following functions:

tcgetattr(*fd*)

Return a list containing the tty attributes for file descriptor *fd*, as follows: [*iflag, oflag, cflag, lflag, ispeed, ospeed, cc*] where *cc* is a list of the tty special characters (each a string of length 1, except the items with indices `TERMIOS.VMIN` and `TERMIOS.VTIME`, which are integers when these fields are defined). The interpretation of the flags and the speeds as well as the indexing in the *cc* array must be done using the symbolic constants defined in the [TERMIOS](#) module.

tcsetattr(*fd, when, attributes*)

Set the tty attributes for file descriptor *fd* from the *attributes*, which is a list like the one returned by `tcgetattr()`. The *when* argument determines when the attributes are changed: `TERMIOS.TCSANOW` to change immediately, `TERMIOS.TCSADRAIN` to change after transmitting all queued output, or `TERMIOS.TCSAFLUSH` to change after transmitting all queued output and discarding all queued input.

tcsendbreak(*fd, duration*)

Send a break on file descriptor *fd*. A zero *duration* sends a break for 0.25–0.5 seconds; a nonzero *duration* has a system dependent meaning.

tcdrain(*fd*)

Wait until all output written to file descriptor *fd* has been transmitted.

tcflush(*fd, queue*)

Discard queued data on file descriptor *fd*. The *queue* selector specifies which queue: `TERMIOS.TCIFLUSH` for the input queue, `TERMIOS.TCOFLUSH` for the output queue, or `TERMIOS.TCIOFLUSH` for both queues.

tcflow(*fd, action*)

Suspend or resume input or output on file descriptor *fd*. The *action* argument can be `TERMIOS.TCOOFF` to suspend output, `TERMIOS.TCOON` to restart output, `TERMIOS.TCIOFF` to suspend input, or `TERMIOS.TCION` to restart input.

See Also:

Module [TERMIOS](#) (section 8.9):

Constants for use with `termios`.

Module `tty` (section 8.10):

Convenience functions for common terminal control operations.

8.8.1 Example

Here's a function that prompts for a password with echoing turned off. Note the technique using a separate `tcgetattr()` call and a `try ... finally` statement to ensure that the old `tty` attributes are restored exactly no matter what happens:

```
def getpass(prompt = "Password: "):
    import termios, TERMIOS, sys
    fd = sys.stdin.fileno()
    old = termios.tcgetattr(fd)
    new = termios.tcgetattr(fd)
    new[3] = new[3] & ~TERMIOS.ECHO          # lflags
    try:
        termios.tcsetattr(fd, TERMIOS.TCSADRAIN, new)
        passwd = raw_input(prompt)
    finally:
        termios.tcsetattr(fd, TERMIOS.TCSADRAIN, old)
    return passwd
```

8.9 TERMIOS — Constants used with the `termios` module

This module defines the symbolic constants required to use the `termios` module (see the previous section). See the POSIX or UNIX manual pages (or the source) for a list of those constants.

Note: this module resides in a system-dependent subdirectory of the Python library directory. You may have to generate it for your particular system using the script `'Tools/scripts/h2py.py'`.

8.10 `tty` — Terminal control functions

The `tty` module defines functions for putting the `tty` into `cbreak` and `raw` modes.

Because it requires the `termios` module, it will work only on UNIX.

The `tty` module defines the following functions:

setraw(*fd*[, *when*])

Change the mode of the file descriptor *fd* to raw. If *when* is omitted, it defaults to `TERMIOS.TCAFLUSH`, and is passed to `termios.tcsetattr()`.

setcbreak(*fd*[, *when*])

Change the mode of file descriptor *fd* to `cbreak`. If *when* is omitted, it defaults to `TERMIOS.TCAFLUSH`, and is passed to `termios.tcsetattr()`.

See Also:

Module `termios` (section 8.8):

Low-level terminal control interface.

Module `TERMIOS` (section 8.9):

Constants useful for terminal control operations.

8.11 pty — Pseudo-terminal utilities

The `pty` module defines operations for handling the pseudo-terminal concept: starting another process and being able to write to and read from its controlling terminal programmatically.

Because pseudo-terminal handling is highly platform dependant, there is code to do it only for SGI and Linux. (The Linux code is supposed to work on other platforms, but hasn't been tested yet.)

The `pty` module defines the following functions:

fork()

Fork. Connect the child's controlling terminal to a pseudo-terminal. Return value is (*pid*, *fd*). Note that the child gets *pid* 0, and the *fd* is *invalid*. The parent's return value is the *pid* of the child, and *fd* is a file descriptor connected to the child's controlling terminal (and also to the child's standard input and output).

spawn(*argv*[, *master_read*[, *stdin_read*]])

Spawn a process, and connect its controlling terminal with the current process's standard io. This is often used to baffle programs which insist on reading from the controlling terminal.

The functions *master_read* and *stdin_read* should be functions which read from a file-descriptor. The defaults try to read 1024 bytes each time they are called.

8.12 fcntl — The `fcntl()` and `ioctl()` system calls

This module performs file control and I/O control on file descriptors. It is an interface to the `fcntl()` and `ioctl()` UNIX routines. File descriptors can be obtained with the `fileno()` method of a file or socket object.

The module defines the following functions:

fcntl(*fd*, *op*[, *arg*])

Perform the requested operation on file descriptor *fd*. The operation is defined by *op* and is operating system dependent. Typically these codes can be retrieved from the library module `FCNTL`. The argument *arg* is optional, and defaults to the integer value 0. When present, it can either be an integer value, or a string. With the argument missing or an integer value, the return value of this function is the integer return value of the C `fcntl()` call. When the argument is a string it represents a binary structure, e.g. created by `struct.pack()`. The binary data is copied to a buffer whose address is passed to the C `fcntl()` call. The return value after a successful call is the contents of the buffer, converted to a string object. In case the `fcntl()` fails, an `IOError` is raised.

ioctl(*fd*, *op*, *arg*)

This function is identical to the `fcntl()` function, except that the operations are typically defined in the library module `IOCTL`.

flock(*fd*, *op*)

Perform the lock operation *op* on file descriptor *fd*. See the UNIX manual *flock(3)* for details. (On some systems, this function is emulated using `fcntl()`.)

lockf(*fd*, *code*, [*len*, [*start*, [*whence*]])

This is a wrapper around the `FCNTL.F_SETLK` and `FCNTL.F_SETLKW` `fcntl()` calls. See the UNIX manual for details.

If the library modules `FCNTL` or `IOCTL` are missing, you can find the opcodes in the C include files `<sys/fcntl.h>` and `<sys/ioctl.h>`. You can create the modules yourself with the **h2py** script, found in the 'Tools/scripts/' directory.

Examples (all on a SVR4 compliant system):

```

import struct, fcntl, FCNTL

file = open(...)
rv = fcntl(file.fileno(), FCNTL.O_NDELAY, 1)

lockdata = struct.pack('hhllhh', FCNTL.F_WRLCK, 0, 0, 0, 0, 0)
rv = fcntl.fcntl(file.fileno(), FCNTL.F_SETLKW, lockdata)

```

Note that in the first example the return value variable `rv` will hold an integer value; in the second example it will hold a string value. The structure lay-out for the `lockdata` variable is system dependent — therefore using the `flock()` call may be better.

8.13 pipes — Interface to shell pipelines

The `pipes` module defines a class to abstract the concept of a *pipeline* — a sequence of converters from one file to another.

Because the module uses `/bin/sh` command lines, a POSIX or compatible shell for `os.system()` and `os.popen()` is required.

The `pipes` module defines the following class:

Template()

An abstraction of a pipeline.

Example:

```

>>> import pipes
>>> t=pipes.Template()
>>> t.append('tr a-z A-Z', '--')
>>> f=t.open('/tmp/1', 'w')
>>> f.write('hello world')
>>> f.close()
>>> open('/tmp/1').read()
'HELLO WORLD'

```

8.13.1 Template Objects

Template objects following methods:

reset()

Restore a pipeline template to its initial state.

clone()

Return a new, equivalent, pipeline template.

debug(flag)

If *flag* is true, turn debugging on. Otherwise, turn debugging off. When debugging is on, commands to be executed are printed, and the shell is given `set -x` command to be more verbose.

append(cmd, kind)

Append a new action at the end. The *cmd* variable must be a valid bourne shell command. The *kind* variable consists of two letters.

The first letter can be either of `'-'` (which means the command reads its standard input), `'f'` (which means

the commands reads a given file on the command line) or `'.'` (which means the commands reads no input, and hence must be first.)

Similarly, the second letter can be either of `'-'` (which means the command writes to standard output), `'f'` (which means the command writes a file on the command line) or `'.'` (which means the command does not write anything, and hence must be last.)

prepend(*cmd, kind*)

Add a new action at the beginning. See `append()` for explanations of the arguments.

open(*file, mode*)

Return a file-like object, open to *file*, but read from or written to by the pipeline. Note that only one of `'r'`, `'w'` may be given.

copy(*infile, outfile*)

Copy *infile* to *outfile* through the pipe.

8.14 `posixfile` — File-like objects with locking support

Note: This module will become obsolete in a future release. The locking operation that it provides is done better and more portably by the `fcntl.lockf()` call.

This module implements some additional functionality over the built-in file objects. In particular, it implements file locking, control over the file flags, and an easy interface to duplicate the file object. The module defines a new file object, the `posixfile` object. It has all the standard file object methods and adds the methods described below. This module only works for certain flavors of UNIX, since it uses `fcntl.fcntl()` for file locking.

To instantiate a `posixfile` object, use the `open()` function in the `posixfile` module. The resulting object looks and feels roughly the same as a standard file object.

The `posixfile` module defines the following constants:

SEEK_SET

Offset is calculated from the start of the file.

SEEK_CUR

Offset is calculated from the current position in the file.

SEEK_END

Offset is calculated from the end of the file.

The `posixfile` module defines the following functions:

open(*filename*[, *mode*[, *bufsize*]])

Create a new `posixfile` object with the given *filename* and *mode*. The *filename*, *mode* and *bufsize* arguments are interpreted the same way as by the built-in `open()` function.

fileopen(*fileobject*)

Create a new `posixfile` object with the given standard file object. The resulting object has the same *filename* and *mode* as the original file object.

The `posixfile` object defines the following additional methods:

lock(*fmt*, [*len*[, *start*[, *whence*]])

Lock the specified section of the file that the file object is referring to. The format is explained below in a table. The *len* argument specifies the length of the section that should be locked. The default is 0. *start* specifies the starting offset of the section, where the default is 0. The *whence* argument specifies where the offset is relative to. It accepts one of the constants `SEEK_SET`, `SEEK_CUR` or `SEEK_END`. The default is `SEEK_SET`. For more information about the arguments refer to the `fcntl(2)` manual page on your system.

flags([*flags*])

Set the specified flags for the file that the file object is referring to. The new flags are ORed with the old flags, unless specified otherwise. The format is explained below in a table. Without the *flags* argument a string indicating the current flags is returned (this is the same as the '?' modifier). For more information about the flags refer to the *fcntl(2)* manual page on your system.

dup()

Duplicate the file object and the underlying file pointer and file descriptor. The resulting object behaves as if it were newly opened.

dup2(*fd*)

Duplicate the file object and the underlying file pointer and file descriptor. The new object will have the given file descriptor. Otherwise the resulting object behaves as if it were newly opened.

file()

Return the standard file object that the posixfile object is based on. This is sometimes necessary for functions that insist on a standard file object.

All methods raise `IOError` when the request fails.

Format characters for the `lock()` method have the following meaning:

Format	Meaning
'u'	unlock the specified region
'r'	request a read lock for the specified section
'w'	request a write lock for the specified section

In addition the following modifiers can be added to the format:

Modifier	Meaning	Notes
' '	wait until the lock has been granted	
'?'	return the first lock conflicting with the requested lock, or <code>None</code> if there is no conflict.	(1)

Note:

- (1) The lock returned is in the format (*mode*, *len*, *start*, *whence*, *pid*) where *mode* is a character representing the type of lock ('r' or 'w'). This modifier prevents a request from being granted; it is for query purposes only.

Format characters for the `flags()` method have the following meanings:

Format	Meaning
'a'	append only flag
'c'	close on exec flag
'n'	no delay flag (also called non-blocking flag)
's'	synchronization flag

In addition the following modifiers can be added to the format:

Modifier	Meaning	Notes
'!'	turn the specified flags 'off', instead of the default 'on'	(1)
'='	replace the flags, instead of the default 'OR' operation	(1)
'?'	return a string in which the characters represent the flags that are set.	(2)

Notes:

- (1) The '!' and '=' modifiers are mutually exclusive.

(2) This string represents the flags after they may have been altered by the same call.

Examples:

```
import posixfile

file = posixfile.open('/tmp/test', 'w')
file.lock('w|')
...
file.lock('u')
file.close()
```

8.15 resource — Resource usage information

This module provides basic mechanisms for measuring and controlling system resources utilized by a program.

Symbolic constants are used to specify particular system resources and to request usage information about either the current process or its children.

A single exception is defined for errors:

error

The functions described below may raise this error if the underlying system call failures unexpectedly.

8.15.1 Resource Limits

Resources usage can be limited using the `setrlimit()` function described below. Each resource is controlled by a pair of limits: a soft limit and a hard limit. The soft limit is the current limit, and may be lowered or raised by a process over time. The soft limit can never exceed the hard limit. The hard limit can be lowered to any value greater than the soft limit, but not raised. (Only processes with the effective UID of the super-user can raise a hard limit.)

The specific resources that can be limited are system dependent. They are described in the `getrlimit(2)` man page. The resources listed below are supported when the underlying operating system supports them; resources which cannot be checked or controlled by the operating system are not defined in this module for those platforms.

getrlimit(*resource*)

Returns a tuple (*soft*, *hard*) with the current soft and hard limits of *resource*. Raises `ValueError` if an invalid resource is specified, or `error` if the underlying system call fails unexpectedly.

setrlimit(*resource*, *limits*)

Sets new limits of consumption of *resource*. The *limits* argument must be a tuple (*soft*, *hard*) of two integers describing the new limits. A value of `-1` can be used to specify the maximum possible upper limit.

Raises `ValueError` if an invalid resource is specified, if the new soft limit exceeds the hard limit, or if a process tries to raise its hard limit (unless the process has an effective UID of super-user). Can also raise `error` if the underlying system call fails.

These symbols define resources whose consumption can be controlled using the `setrlimit()` and `getrlimit()` functions described below. The values of these symbols are exactly the constants used by C programs.

The UNIX man page for `getrlimit(2)` lists the available resources. Note that not all systems use the same symbol or same value to denote the same resource.

RLIMIT_CORE

The maximum size (in bytes) of a core file that the current process can create. This may result in the creation of

a partial core file if a larger core would be required to contain the entire process image.

RLIMIT_CPU

The maximum amount of CPU time (in seconds) that a process can use. If this limit is exceeded, a SIGXCPU signal is sent to the process. (See the [signal](#) module documentation for information about how to catch this signal and do something useful, e.g. flush open files to disk.)

RLIMIT_FSIZE

The maximum size of a file which the process may create. This only affects the stack of the main thread in a multi-threaded process.

RLIMIT_DATA

The maximum size (in bytes) of the process's heap.

RLIMIT_STACK

The maximum size (in bytes) of the call stack for the current process.

RLIMIT_RSS

The maximum resident set size that should be made available to the process.

RLIMIT_NPROC

The maximum number of processes the current process may create.

RLIMIT_NOFILE

The maximum number of open file descriptors for the current process.

RLIMIT_OFILE

The BSD name for RLIMIT_NOFILE.

RLIMIT_MEMLOCK

The maximum address space which may be locked in memory.

RLIMIT_VMEM

The largest area of mapped memory which the process may occupy.

RLIMIT_AS

The maximum area (in bytes) of address space which may be taken by the process.

8.15.2 Resource Usage

These functions are used to retrieve resource usage information:

getrusage(*who*)

This function returns a large tuple that describes the resources consumed by either the current process or its children, as specified by the *who* parameter. The *who* parameter should be specified using one of the RUSAGE_* constants described below.

The elements of the return value each describe how a particular system resource has been used, e.g. amount of time spent running in user mode or number of times the process was swapped out of main memory. Some values are dependent on the clock tick interval, e.g. the amount of memory the process is using.

The first two elements of the return value are floating point values representing the amount of time spent executing in user mode and the amount of time spent executing in system mode, respectively. The remaining values are integers. Consult the *getrusage(2)* man page for detailed information about these values. A brief summary is presented here:

Offset	Resource
0	time in user mode (float)
1	time in system mode (float)
2	maximum resident set size
3	shared memory size
4	unshared memory size
5	unshared stack size
6	page faults not requiring I/O
7	page faults requiring I/O
8	number of swap outs
9	block input operations
10	block output operations
11	messages sent
12	messages received
13	signals received
14	voluntary context switches
15	involuntary context switches

This function will raise a `ValueError` if an invalid *who* parameter is specified. It may also raise error exception in unusual circumstances.

`getpagesize()`

Returns the number of bytes in a system page. (This need not be the same as the hardware page size.) This function is useful for determining the number of bytes of memory a process is using. The third element of the tuple returned by `getrusage()` describes memory usage in pages; multiplying by page size produces number of bytes.

The following `RUSAGE_*` symbols are passed to the `getrusage()` function to specify which processes information should be provided for.

`RUSAGE_SELF`

`RUSAGE_SELF` should be used to request information pertaining only to the process itself.

`RUSAGE_CHILDREN`

Pass to `getrusage()` to request resource information for child processes of the calling process.

`RUSAGE_BOTH`

Pass to `getrusage()` to request resources consumed by both the current process and child processes. May not be available on all systems.

8.16 `nis` — Interface to Sun's NIS (Yellow Pages)

The `nis` module gives a thin wrapper around the NIS library, useful for central administration of several hosts.

Because NIS exists only on UNIX systems, this module is only available for UNIX.

The `nis` module defines the following functions:

`match(key, mapname)`

Return the match for *key* in map *mapname*, or raise an error (`nis.error`) if there is none. Both should be strings, *key* is 8-bit clean. Return value is an arbitrary array of bytes (i.e., may contain NULL and other joys).

Note that *mapname* is first checked if it is an alias to another name.

`cat(mapname)`

Return a dictionary mapping *key* to *value* such that `match(key, mapname) == value`. Note that both keys and values of the dictionary are arbitrary arrays of bytes.

Note that *mapname* is first checked if it is an alias to another name.

maps ()

Return a list of all valid maps.

The `nis` module defines the following exception:

error

An error raised when a NIS function returns an error code.

8.17 `syslog` — UNIX `syslog` library routines

This module provides an interface to the UNIX `syslog` library routines. Refer to the UNIX manual pages for a detailed description of the `syslog` facility.

The module defines the following functions:

syslog ([priority,] message)

Send the string *message* to the system logger. A trailing newline is added if necessary. Each message is tagged with a priority composed of a *facility* and a *level*. The optional *priority* argument, which defaults to `LOG_INFO`, determines the message priority. If the facility is not encoded in *priority* using logical-or (`LOG_INFO | LOG_USER`), the value given in the `openlog ()` call is used.

openlog (ident [, logopt [, facility]])

Logging options other than the defaults can be set by explicitly opening the log file with `openlog ()` prior to calling `syslog ()`. The defaults are (usually) *ident* = `'syslog'`, *logopt* = 0, *facility* = `LOG_USER`. The *ident* argument is a string which is prepended to every message. The optional *logopt* argument is a bit field - see below for possible values to combine. The optional *facility* argument sets the default facility for messages which do not have a facility explicitly encoded.

closelog ()

Close the log file.

setlogmask (maskpri)

Set the priority mask to *maskpri* and return the previous mask value. Calls to `syslog ()` with a priority level not set in *maskpri* are ignored. The default is to log all priorities. The function `LOG_MASK (pri)` calculates the mask for the individual priority *pri*. The function `LOG_UPTO (pri)` calculates the mask for all priorities up to and including *pri*.

The module defines the following constants:

Priority levels (high to low): `LOG_EMERG`, `LOG_ALERT`, `LOG_CRIT`, `LOG_ERR`, `LOG_WARNING`, `LOG_NOTICE`, `LOG_INFO`, `LOG_DEBUG`.

Facilities: `LOG_KERN`, `LOG_USER`, `LOG_MAIL`, `LOG_DAEMON`, `LOG_AUTH`, `LOG_LPR`, `LOG_NEWS`, `LOG_UUCP`, `LOG_CRON` and `LOG_LOCAL0` to `LOG_LOCAL7`.

Log options: `LOG_PID`, `LOG_CONS`, `LOG_NDELAY`, `LOG_NOWAIT` and `LOG_PERROR` if defined in `<syslog.h>`.

8.18 `popen2` — Subprocesses with accessible I/O streams

This module allows you to spawn processes and connect their input/output/error pipes and obtain their return codes under UNIX. Similar functionality exists for Windows platforms using the `win32pipe` module provided as part of Mark Hammond's Windows extensions.

The primary interface offered by this module is a pair of factory functions:

popen2(*cmd* [, *bufsize*])

Executes *cmd* as a sub-process. If *bufsize* is specified, it specifies the buffer size for the I/O pipes. Returns the file objects (*child_stdout*, *child_stdin*).

popen3(*cmd* [, *bufsize*])

Executes *cmd* as a sub-process. If *bufsize* is specified, it specifies the buffer size for the I/O pipes. Returns the file objects (*child_stdout*, *child_stdin*, *child_stderr*).

The class defining the objects returned by the factory functions is also available:

Popen3(*cmd* [, *capturestderr* [, *bufsize*]])

This class represents a child process. Normally, `Popen3` instances are created using the factory functions described above.

If not using one off the helper functions to create `Popen3` objects, the parameter *cmd* is the shell command to execute in a sub-process. The *capturestderr* flag, if true, specifies that the object should capture standard error output of the child process. The default is false. If the *bufsize* parameter is specified, it specifies the size of the I/O buffers to/from the child process.

8.18.1 Popen3 Objects

Instances of the `Popen3` class have the following methods:

poll()

Returns -1 if child process hasn't completed yet, or its return code otherwise.

wait()

Waits for and returns the return code of the child process.

The following attributes of `Popen3` objects are also available:

fromchild

A file object that provides output from the child process.

tochild

A file object that provides input to the child process.

childerr

Where the standard error from the child process goes is *capturestderr* was true for the constructor, or None.

pid

The process ID of the child process.

8.19 `commands` — Utilities for running commands

The `commands` module contains wrapper functions for `os.popen()` which take a system command as a string and return any output generated by the command and, optionally, the exit status.

The `commands` module defines the following functions:

getstatusoutput(*cmd*)

Execute the string *cmd* in a shell with `os.popen()` and return a 2-tuple (*status*, *output*). *cmd* is actually run as `{cmd ; } 2>&1`, so that the returned output will contain output or error messages. A trailing newline is stripped from the output. The exit status for the command can be interpreted according to the rules for the C function `wait()`.

getoutput(*cmd*)

Like `getstatusoutput()`, except the exit status is ignored and the return value is a string containing the command's output.

getstatus (*file*)

Return the output of `'ls -ld file'` as a string. This function uses the `getoutput()` function, and properly escapes backslashes and dollar signs in the argument.

Example:

```
>>> import commands
>>> commands.getstatusoutput('ls /bin/ls')
(0, '/bin/ls')
>>> commands.getstatusoutput('cat /bin/junk')
(256, 'cat: /bin/junk: No such file or directory')
>>> commands.getstatusoutput('/bin/junk')
(256, 'sh: /bin/junk: not found')
>>> commands.getoutput('ls /bin/ls')
'/bin/ls'
>>> commands.getstatus('/bin/ls')
'-rwxr-xr-x 1 root          13352 Oct 14 1994 /bin/ls'
```

The Python Debugger

The module `pdb` defines an interactive source code debugger for Python programs. It supports setting (conditional) breakpoints and single stepping at the source line level, inspection of stack frames, source code listing, and evaluation of arbitrary Python code in the context of any stack frame. It also supports post-mortem debugging and can be called under program control.

The debugger is extensible — it is actually defined as the class `Pdb`. This is currently undocumented but easily understood by reading the source. The extension interface uses the modules `bdb` (undocumented) and `cmd`.

A primitive windowing version of the debugger also exists — this is module `wdb`, which requires `stdwin`.

The debugger's prompt is `(Pdb)` . Typical usage to run a program under control of the debugger is:

```
>>> import pdb
>>> import mymodule
>>> pdb.run('mymodule.test()')
> <string>(0)?()
(Pdb) continue
> <string>(1)?()
(Pdb) continue
NameError: 'spam'
> <string>(1)?()
(Pdb)
```

'`pdb.py`' can also be invoked as a script to debug other scripts. For example:

```
python /usr/local/lib/python1.5/pdb.py myscript.py
```

Typical usage to inspect a crashed program is:

```

>>> import pdb
>>> import mymodule
>>> mymodule.test()
Traceback (innermost last):
  File "<stdin>", line 1, in ?
  File "./mymodule.py", line 4, in test
    test2()
  File "./mymodule.py", line 3, in test2
    print spam
NameError: spam
>>> pdb.pm()
> ./mymodule.py(3)test2()
-> print spam
(Pdb)

```

The module defines the following functions; each enters the debugger in a slightly different way:

run(*statement*[, *globals*[, *locals*]])

Execute the *statement* (given as a string) under debugger control. The debugger prompt appears before any code is executed; you can set breakpoints and type ‘continue’, or you can step through the statement using ‘step’ or ‘next’ (all these commands are explained below). The optional *globals* and *locals* arguments specify the environment in which the code is executed; by default the dictionary of the module `__main__` is used. (See the explanation of the `exec` statement or the `eval()` built-in function.)

runeval(*expression*[, *globals*[, *locals*]])

Evaluate the *expression* (given as a string) under debugger control. When `runeval()` returns, it returns the value of the expression. Otherwise this function is similar to `run()`.

runcall(*function*[, *argument*, ...])

Call the *function* (a function or method object, not a string) with the given arguments. When `runcall()` returns, it returns whatever the function call returned. The debugger prompt appears as soon as the function is entered.

set_trace()

Enter the debugger at the calling stack frame. This is useful to hard-code a breakpoint at a given point in a program, even if the code is not otherwise being debugged (e.g. when an assertion fails).

post_mortem(*traceback*)

Enter post-mortem debugging of the given *traceback* object.

pm()

Enter post-mortem debugging of the traceback found in `sys.last_traceback`.

9.1 Debugger Commands

The debugger recognizes the following commands. Most commands can be abbreviated to one or two letters; e.g. ‘h(elp)’ means that either ‘h’ or ‘help’ can be used to enter the help command (but not ‘he’ or ‘hel’, nor ‘H’ or ‘Help’ or ‘HELP’). Arguments to commands must be separated by whitespace (spaces or tabs). Optional arguments are enclosed in square brackets (‘[]’) in the command syntax; the square brackets must not be typed. Alternatives in the command syntax are separated by a vertical bar (‘|’).

Entering a blank line repeats the last command entered. Exception: if the last command was a ‘list’ command, the next 11 lines are listed.

Commands that the debugger doesn’t recognize are assumed to be Python statements and are executed in the context of the program being debugged. Python statements can also be prefixed with an exclamation point (‘!’). This is a

powerful way to inspect the program being debugged; it is even possible to change a variable or call a function. When an exception occurs in such a statement, the exception name is printed but the debugger's state is not changed.

Multiple commands may be entered on a single line, separated by `;`. (A single `;` is not used as it is the separator for multiple commands in a line that is passed to the Python parser.) No intelligence is applied to separating the commands; the input is split at the first `;` pair, even if it is in the middle of a quoted string.

The debugger supports aliases. Aliases can have parameters which allows one a certain level of adaptability to the context under examination.

If a file `.pdbrc` exists in the user's home directory or in the current directory, it is read in and executed as if it had been typed at the debugger prompt. This is particularly useful for aliases. If both files exist, the one in the home directory is read first and aliases defined there can be overridden by the local file.

h(elp) [*command*] Without argument, print the list of available commands. With a *command* as argument, print help about that command. `help pdb` displays the full documentation file; if the environment variable `$PAGER` is defined, the file is piped through that command instead. Since the *command* argument must be an identifier, `help exec` must be entered to get help on the `!` command.

w(here) Print a stack trace, with the most recent frame at the bottom. An arrow indicates the current frame, which determines the context of most commands.

d(own) Move the current frame one level down in the stack trace (to a newer frame).

u(p) Move the current frame one level up in the stack trace (to a older frame).

b(break) [[*filename:*]*lineno* | *function* [, *condition*]] With a *lineno* argument, set a break there in the current file. With a *function* argument, set a break at the first executable statement within that function. The line number may be prefixed with a filename and a colon, to specify a breakpoint in another file (probably one that hasn't been loaded yet). The file is searched on `sys.path`. Note that each breakpoint is assigned a number to which all the other breakpoint commands refer.

If a second argument is present, it is an expression which must evaluate to true before the breakpoint is honored.

Without argument, list all breaks, including for each breakpoint, the number of times that breakpoint has been hit, the current ignore count, and the associated condition if any.

tbreak [[*filename:*]*lineno* | *function* [, *condition*]] Temporary breakpoint, which is removed automatically when it is first hit. The arguments are the same as `break`.

cl(ear) [*bpnumber* [*bpnumber* ...]] With a space separated list of breakpoint numbers, clear those breakpoints. Without argument, clear all breaks (but first ask confirmation).

disable [*bpnumber* [*bpnumber* ...]] Disables the breakpoints given as a space separated list of breakpoint numbers. Disabling a breakpoint means it cannot cause the program to stop execution, but unlike clearing a breakpoint, it remains in the list of breakpoints and can be (re-)enabled.

enable [*bpnumber* [*bpnumber* ...]] Enables the breakpoints specified.

ignore *bpnumber* [*count*] Sets the ignore count for the given breakpoint number. If *count* is omitted, the ignore count is set to 0. A breakpoint becomes active when the ignore count is zero. When non-zero, the count is decremented each time the breakpoint is reached and the breakpoint is not disabled and any associated condition evaluates to true.

condition *bpnumber* [*condition*] Condition is an expression which must evaluate to true before the breakpoint is honored. If condition is absent, any existing condition is removed; i.e., the breakpoint is made unconditional.

s(tep) Execute the current line, stop at the first possible occasion (either in a function that is called or on the next line in the current function).

n(ext) Continue execution until the next line in the current function is reached or it returns. (The difference between 'next' and 'step' is that 'step' stops inside a called function, while 'next' executes called functions at (nearly) full speed, only stopping at the next line in the current function.)

r(eturn) Continue execution until the current function returns.

c(ontinue) Continue execution, only stop when a breakpoint is encountered.

l(ist) [first, last] List source code for the current file. Without arguments, list 11 lines around the current line or continue the previous listing. With one argument, list 11 lines around at that line. With two arguments, list the given range; if the second argument is less than the first, it is interpreted as a count.

a(rgs) Print the argument list of the current function.

p expression Evaluate the *expression* in the current context and print its value. (Note: 'print' can also be used, but is not a debugger command — this executes the Python print statement.)

alias [name [command]] Creates an alias called *name* that executes *command*. The command must *not* be enclosed in quotes. Replaceable parameters can be indicated by '%1', '%2', and so on, while '*' is replaced by all the parameters. If no command is given, the current alias for *name* is shown. If no arguments are given, all aliases are listed.

Aliases may be nested and can contain anything that can be legally typed at the pdb prompt. Note that internal pdb commands *can* be overridden by aliases. Such a command is then hidden until the alias is removed. Aliasing is recursively applied to the first word of the command line; all other words in the line are left alone.

As an example, here are two useful aliases (especially when placed in the '.pdbrc' file):

```
#Print instance variables (usage "pi classInst")
alias pi for k in %1.__dict__.keys(): print "%1.",k,"=",%1.__dict__[k]
#Print instance variables in self
alias ps pi self
```

unalias name Deletes the specified alias.

[!]statement Execute the (one-line) *statement* in the context of the current stack frame. The exclamation point can be omitted unless the first word of the statement resembles a debugger command. To set a global variable, you can prefix the assignment command with a 'global' command on the same line, e.g.:

```
(Pdb) global list_options; list_options = ['-l']
(Pdb)
```

q(uit) Quit from the debugger. The program being executed is aborted.

9.2 How It Works

Some changes were made to the interpreter:

- `sys.settrace(func)` sets the global trace function
- there can also a local trace function (see later)

Trace functions have three arguments: *frame*, *event*, and *arg*. *frame* is the current stack frame. *event* is a string: 'call', 'line', 'return' or 'exception'. *arg* depends on the event type.

The global trace function is invoked (with *event* set to 'call') whenever a new local scope is entered; it should return a reference to the local trace function to be used that scope, or None if the scope shouldn't be traced.

The local trace function should return a reference to itself (or to another function for further tracing in that scope), or None to turn off tracing in that scope.

Instance methods are accepted (and very useful!) as trace functions.

The events have the following meaning:

'call' A function is called (or some other code block entered). The global trace function is called; *arg* is the argument list to the function; the return value specifies the local trace function.

'line' The interpreter is about to execute a new line of code (sometimes multiple line events on one line exist). The local trace function is called; *arg* is None; the return value specifies the new local trace function.

'return' A function (or other code block) is about to return. The local trace function is called; *arg* is the value that will be returned. The trace function's return value is ignored.

'exception' An exception has occurred. The local trace function is called; *arg* is a triple (exception, value, traceback); the return value specifies the new local trace function

Note that as an exception is propagated down the chain of callers, an 'exception' event is generated at each level.

For more information on code and frame objects, refer to the *Python Reference Manual*.

The Python Profiler

Copyright © 1994, by InfoSeek Corporation, all rights reserved.

Written by James Roskind.¹

Permission to use, copy, modify, and distribute this Python software and its associated documentation for any purpose (subject to the restriction in the following sentence) without fee is hereby granted, provided that the above copyright notice appears in all copies, and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of InfoSeek not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. This permission is explicitly restricted to the copying and modification of the software to remain in Python, compiled Python, or other languages (such as C) wherein the modified or derived code is exclusively imported into a Python module.

INFOSEEK CORPORATION DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INFOSEEK CORPORATION BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The profiler was written after only programming in Python for 3 weeks. As a result, it is probably clumsy code, but I don't know for sure yet 'cause I'm a beginner :-). I did work hard to make the code run fast, so that profiling would be a reasonable thing to do. I tried not to repeat code fragments, but I'm sure I did some stuff in really awkward ways at times. Please send suggestions for improvements to: jar@netscape.com. I won't promise *any* support. ...but I'd appreciate the feedback.

10.1 Introduction to the profiler

A *profiler* is a program that describes the run time performance of a program, providing a variety of statistics. This documentation describes the profiler functionality provided in the modules `profile` and `pstats`. This profiler provides *deterministic profiling* of any Python programs. It also provides a series of report generation tools to allow users to rapidly examine the results of a profile operation.

10.2 How Is This Profiler Different From The Old Profiler?

(This section is of historical importance only; the old profiler discussed here was last seen in Python 1.1.)

The big changes from old profiling module are that you get more information, and you pay less CPU time. It's not a trade-off, it's a trade-up.

¹Updated and converted to L^AT_EX by Guido van Rossum. The references to the old profiler are left in the text, although it no longer exists.

To be specific:

Bugs removed: Local stack frame is no longer molested, execution time is now charged to correct functions.

Accuracy increased: Profiler execution time is no longer charged to user's code, calibration for platform is supported, file reads are not done *by* profiler *during* profiling (and charged to user's code!).

Speed increased: Overhead CPU cost was reduced by more than a factor of two (perhaps a factor of five), lightweight profiler module is all that must be loaded, and the report generating module (`pstats`) is not needed during profiling.

Recursive functions support: Cumulative times in recursive functions are correctly calculated; recursive entries are counted.

Large growth in report generating UI: Distinct profiles runs can be added together forming a comprehensive report; functions that import statistics take arbitrary lists of files; sorting criteria is now based on keywords (instead of 4 integer options); reports shows what functions were profiled as well as what profile file was referenced; output format has been improved.

10.3 Instant Users Manual

This section is provided for users that “don't want to read the manual.” It provides a very brief overview, and allows a user to rapidly perform profiling on an existing application.

To profile an application with a main entry point of `foo()`, you would add the following to your module:

```
import profile
profile.run('foo()')
```

The above action would cause `foo()` to be run, and a series of informative lines (the profile) to be printed. The above approach is most useful when working with the interpreter. If you would like to save the results of a profile into a file for later examination, you can supply a file name as the second argument to the `run()` function:

```
import profile
profile.run('foo()', 'fooprof')
```

The file `profile.py` can also be invoked as a script to profile another script. For example:

```
python /usr/local/lib/python1.5/profile.py myscript.py
```

When you wish to review the profile, you should use the methods in the `pstats` module. Typically you would load the statistics data as follows:

```
import pstats
p = pstats.Stats('fooprof')
```

The class `Stats` (the above code just created an instance of this class) has a variety of methods for manipulating and printing the data that was just read into `p`. When you ran `profile.run()` above, what was printed was the result of three method calls:

```
p.strip_dirs().sort_stats(-1).print_stats()
```

The first method removed the extraneous path from all the module names. The second method sorted all the entries according to the standard module/line/name string that is printed (this is to comply with the semantics of the old profiler). The third method printed out all the statistics. You might try the following sort calls:

```
p.sort_stats('name')
p.print_stats()
```

The first call will actually sort the list by function name, and the second call will print out the statistics. The following are some interesting calls to experiment with:

```
p.sort_stats('cumulative').print_stats(10)
```

This sorts the profile by cumulative time in a function, and then only prints the ten most significant lines. If you want to understand what algorithms are taking time, the above line is what you would use.

If you were looking to see what functions were looping a lot, and taking a lot of time, you would do:

```
p.sort_stats('time').print_stats(10)
```

to sort according to time spent within each function, and then print the statistics for the top ten functions.

You might also try:

```
p.sort_stats('file').print_stats('__init__')
```

This will sort all the statistics by file name, and then print out statistics for only the class init methods ('cause they are spelled with '__init__' in them). As one final example, you could try:

```
p.sort_stats('time', 'cum').print_stats(.5, 'init')
```

This line sorts statistics with a primary key of time, and a secondary key of cumulative time, and then prints out some of the statistics. To be specific, the list is first culled down to 50% (re: '.5') of its original size, then only lines containing `init` are maintained, and that sub-sub-list is printed.

If you wondered what functions called the above functions, you could now ('p' is still sorted according to the last criteria) do:

```
p.print_callers(.5, 'init')
```

and you would get a list of callers for each of the listed functions.

If you want more functionality, you're going to have to read the manual, or guess what the following functions do:

```
p.print_callees()
p.add('fooprof')
```

10.4 What Is Deterministic Profiling?

Deterministic profiling is meant to reflect the fact that all *function call*, *function return*, and *exception* events are monitored, and precise timings are made for the intervals between these events (during which time the user's code is executing). In contrast, *statistical profiling* (which is not done by this module) randomly samples the effective instruction pointer, and deduces where time is being spent. The latter technique traditionally involves less overhead (as the code does not need to be instrumented), but provides only relative indications of where time is being spent.

In Python, since there is an interpreter active during execution, the presence of instrumented code is not required to do deterministic profiling. Python automatically provides a *hook* (optional callback) for each event. In addition, the interpreted nature of Python tends to add so much overhead to execution, that deterministic profiling tends to only add small processing overhead in typical applications. The result is that deterministic profiling is not that expensive, yet provides extensive run time statistics about the execution of a Python program.

Call count statistics can be used to identify bugs in code (surprising counts), and to identify possible inline-expansion points (high call counts). Internal time statistics can be used to identify “hot loops” that should be carefully optimized. Cumulative time statistics should be used to identify high level errors in the selection of algorithms. Note that the unusual handling of cumulative times in this profiler allows statistics for recursive implementations of algorithms to be directly compared to iterative implementations.

10.5 Reference Manual

The primary entry point for the profiler is the global function `profile.run()`. It is typically used to create any profile information. The reports are formatted and printed using methods of the class `pstats.Stats`. The following is a description of all of these standard entry points and functions. For a more in-depth view of some of the code, consider reading the later section on Profiler Extensions, which includes discussion of how to derive “better” profilers from the classes presented, or reading the source code for these modules.

`run(string[, filename[, ...]])`

This function takes a single argument that has can be passed to the `exec` statement, and an optional file name. In all cases this routine attempts to `exec` its first argument, and gather profiling statistics from the execution. If no file name is present, then this function automatically prints a simple profiling report, sorted by the standard name string (file/line/function-name) that is presented in each line. The following is a typical output from such a call:

```
main()
2706 function calls (2004 primitive calls) in 4.504 CPU seconds

Ordered by: standard name

ncalls  tottime  percall  cumtime  percall  filename:lineno(function)
      2    0.006    0.003    0.953    0.477  pobject.py:75(save_objects)
    43/3    0.533    0.012    0.749    0.250  pobject.py:99(evaluate)
...
```

The first line indicates that this profile was generated by the call: `profile.run('main()')`, and hence the `exec`'ed string is `'main()'`. The second line indicates that 2706 calls were monitored. Of those calls, 2004 were *primitive*. We define *primitive* to mean that the call was

not induced via recursion. The next line: `Ordered by: standard name`, indicates that the text string in the far right column was used to sort the output. The column headings include:

ncalls for the number of calls,

tottime for the total time spent in the given function (and excluding time made in calls to sub-functions),

percall is the quotient of `tottime` divided by `ncalls`

cumtime is the total time spent in this and all subfunctions (i.e., from invocation till exit). This figure is accurate *even* for recursive functions.

percall is the quotient of `cumtime` divided by primitive calls

filename:lineno(function) provides the respective data of each function

When there are two numbers in the first column (e.g.: '43/3'), then the latter is the number of primitive calls, and the former is the actual number of calls. Note that when the function does not recurse, these two values are the same, and only the single figure is printed.

Analysis of the profiler data is done using this class from the `pstats` module:

Stats(*filename*[, ...])

This class constructor creates an instance of a “statistics object” from a *filename* (or set of filenames). `Stats` objects are manipulated by methods, in order to print useful reports.

The file selected by the above constructor must have been created by the corresponding version of `profile`. To be specific, there is *no* file compatibility guaranteed with future versions of this profiler, and there is no compatibility with files produced by other profilers (e.g., the old system profiler).

If several files are provided, all the statistics for identical functions will be coalesced, so that an overall view of several processes can be considered in a single report. If additional files need to be combined with data in an existing `Stats` object, the `add()` method can be used.

10.5.1 The `Stats` Class

`Stats` objects have the following methods:

strip_dirs()

This method for the `Stats` class removes all leading path information from file names. It is very useful in reducing the size of the printout to fit within (close to) 80 columns. This method modifies the object, and the stripped information is lost. After performing a strip operation, the object is considered to have its entries in a “random” order, as it was just after object initialization and loading. If `strip_dirs()` causes two function names to be indistinguishable (i.e., they are on the same line of the same filename, and have the same function name), then the statistics for these two entries are accumulated into a single entry.

add(*filename*[, ...])

This method of the `Stats` class accumulates additional profiling information into the current profiling object. Its arguments should refer to filenames created by the corresponding version of `profile.run()`. Statistics for identically named (re: file, line, name) functions are automatically accumulated into single function statistics.

sort_stats(*key*[, ...])

This method modifies the `Stats` object by sorting it according to the supplied criteria. The argument is typically a string identifying the basis of a sort (example: 'time' or 'name').

When more than one key is provided, then additional keys are used as secondary criteria when there is equality in all keys selected before them. For example, `sort_stats('name', 'file')` will sort all the entries according to their function name, and resolve all ties (identical function names) by sorting by file name.

Abbreviations can be used for any key names, as long as the abbreviation is unambiguous. The following are the keys currently defined:

Valid Arg	Meaning
'calls'	call count
'cumulative'	cumulative time
'file'	file name
'module'	file name
'pcalls'	primitive call count
'line'	line number
'name'	function name
'nfl'	name/file/line
'stdname'	standard name
'time'	internal time

Note that all sorts on statistics are in descending order (placing most time consuming items first), where as name, file, and line number searches are in ascending order (i.e., alphabetical). The subtle distinction between 'nfl' and 'stdname' is that the standard name is a sort of the name as printed, which means that the embedded line numbers get compared in an odd way. For example, lines 3, 20, and 40 would (if the file names were the same) appear in the string order 20, 3 and 40. In contrast, 'nfl' does a numeric compare of the line numbers. In fact, `sort_stats('nfl')` is the same as `sort_stats('name', 'file', 'line')`.

For compatibility with the old profiler, the numeric arguments -1, 0, 1, and 2 are permitted. They are interpreted as 'stdname', 'calls', 'time', and 'cumulative' respectively. If this old style format (numeric) is used, only one sort key (the numeric key) will be used, and additional arguments will be silently ignored.

reverse_order()

This method for the `Stats` class reverses the ordering of the basic list within the object. This method is provided primarily for compatibility with the old profiler. Its utility is questionable now that ascending vs descending order is properly selected based on the sort key of choice.

print_stats(restriction[, ...])

This method for the `Stats` class prints out a report as described in the `profile.run()` definition.

The order of the printing is based on the last `sort_stats()` operation done on the object (subject to caveats in `add()` and `strip_dirs()`).

The arguments provided (if any) can be used to limit the list down to the significant entries. Initially, the list is taken to be the complete set of profiled functions. Each restriction is either an integer (to select a count of lines), or a decimal fraction between 0.0 and 1.0 inclusive (to select a percentage of lines), or a regular expression (to pattern match the standard name that is printed; as of Python 1.5b1, this uses the Perl-style regular expression syntax defined by the `re` module). If several restrictions are provided, then they are applied sequentially. For example:

```
print_stats(.1, 'foo:')
```

would first limit the printing to first 10% of list, and then only print functions that were part of filename `.*foo:`. In contrast, the command:

```
print_stats('foo:', .1)
```

would limit the list to all functions having file names `.*foo:`, and then proceed to only print the first 10% of them.

print_callers(restrictions[, ...])

This method for the `Stats` class prints a list of all functions that called each function in the profiled database. The ordering is identical to that provided by `print_stats()`, and the definition of the restricting argument is also identical. For convenience, a number is shown in parentheses after each caller to show how many times this specific call was made. A second non-parenthesized number is the cumulative time spent in the function at the right.

```
print_callees(restrictions[, ...])
```

This method for the `Stats` class prints a list of all function that were called by the indicated function. Aside from this reversal of direction of calls (re: called vs was called by), the arguments and ordering are identical to the `print_callers()` method.

```
ignore()
```

Deprecated since release 1.5.1. This is not needed in modern versions of Python.²

10.6 Limitations

There are two fundamental limitations on this profiler. The first is that it relies on the Python interpreter to dispatch *call*, *return*, and *exception* events. Compiled C code does not get interpreted, and hence is “invisible” to the profiler. All time spent in C code (including built-in functions) will be charged to the Python function that invoked the C code. If the C code calls out to some native Python code, then those calls will be profiled properly.

The second limitation has to do with accuracy of timing information. There is a fundamental problem with deterministic profilers involving accuracy. The most obvious restriction is that the underlying “clock” is only ticking at a rate (typically) of about .001 seconds. Hence no measurements will be more accurate than that underlying clock. If enough measurements are taken, then the “error” will tend to average out. Unfortunately, removing this first error induces a second source of error...

The second problem is that it “takes a while” from when an event is dispatched until the profiler’s call to get the time actually *gets* the state of the clock. Similarly, there is a certain lag when exiting the profiler event handler from the time that the clock’s value was obtained (and then squirreled away), until the user’s code is once again executing. As a result, functions that are called many times, or call many functions, will typically accumulate this error. The error that accumulates in this fashion is typically less than the accuracy of the clock (i.e., less than one clock tick), but it *can* accumulate and become very significant. This profiler provides a means of calibrating itself for a given platform so that this error can be probabilistically (i.e., on the average) removed. After the profiler is calibrated, it will be more accurate (in a least square sense), but it will sometimes produce negative numbers (when call counts are exceptionally low, and the gods of probability work against you :-).) Do *not* be alarmed by negative numbers in the profile. They should *only* appear if you have calibrated your profiler, and the results are actually better than without calibration.

10.7 Calibration

The profiler class has a hard coded constant that is added to each event handling time to compensate for the overhead of calling the time function, and socking away the results. The following procedure can be used to obtain this constant for a given platform (see discussion in section Limitations above).

```
import profile
pr = profile.Profile()
print pr.calibrate(100)
print pr.calibrate(100)
print pr.calibrate(100)
```

The argument to `calibrate()` is the number of times to try to do the sample calls to get the CPU times. If your computer is *very* fast, you might have to do:

```
pr.calibrate(1000)
```

²This was once necessary, when Python would print any unused expression result that was not `None`. The method is still defined for backward compatibility.

or even:

```
pr.calibrate(10000)
```

The object of this exercise is to get a fairly consistent result. When you have a consistent answer, you are ready to use that number in the source code. For a Sun Sparcstation 1000 running Solaris 2.3, the magical number is about .00053. If you have a choice, you are better off with a smaller constant, and your results will “less often” show up as negative in profile statistics.

The following shows how the `trace_dispatch()` method in the Profile class should be modified to install the calibration constant on a Sun Sparcstation 1000:

```
def trace_dispatch(self, frame, event, arg):
    t = self.timer()
    t = t[0] + t[1] - self.t - .00053 # Calibration constant

    if self.dispatch[event](frame,t):
        t = self.timer()
        self.t = t[0] + t[1]
    else:
        r = self.timer()
        self.t = r[0] + r[1] - t # put back unrecorded delta
    return
```

Note that if there is no calibration constant, then the line containing the callibration constant should simply say:

```
t = t[0] + t[1] - self.t # no calibration constant
```

You can also achieve the same results using a derived class (and the profiler will actually run equally fast!!), but the above method is the simplest to use. I could have made the profiler “self calibrating”, but it would have made the initialization of the profiler class slower, and would have required some *very* fancy coding, or else the use of a variable where the constant ‘.00053’ was placed in the code shown. This is a **VERY** critical performance section, and there is no reason to use a variable lookup at this point, when a constant can be used.

10.8 Extensions — Deriving Better Profilers

The Profile class of module `profile` was written so that derived classes could be developed to extend the profiler. Rather than describing all the details of such an effort, I’ll just present the following two examples of derived classes that can be used to do profiling. If the reader is an avid Python programmer, then it should be possible to use these as a model and create similar (and perhance better) profile classes.

If all you want to do is change how the timer is called, or which timer function is used, then the basic class has an option for that in the constructor for the class. Consider passing the name of a function to call into the constructor:

```
pr = profile.Profile(your_time_func)
```

The resulting profiler will call `your_time_func()` instead of `os.times()`. The function should return either a single number or a list of numbers (like what `os.times()` returns). If the function returns a single time number, or the list of returned numbers has length 2, then you will get an especially fast version of the dispatch routine.

Be warned that you *should* calibrate the profiler class for the timer function that you choose. For most machines, a timer that returns a lone integer value will provide the best results in terms of low overhead during profiling. (`os.times()` is *pretty* bad, 'cause it returns a tuple of floating point values, so all arithmetic is floating point in the profiler!). If you want to substitute a better timer in the cleanest fashion, you should derive a class, and simply put in the replacement dispatch method that better handles your timer call, along with the appropriate calibration constant :-).

10.8.1 OldProfile Class

The following derived profiler simulates the old style profiler, providing errant results on recursive functions. The reason for the usefulness of this profiler is that it runs faster (i.e., less overhead) than the old profiler. It still creates all the caller stats, and is quite useful when there is *no* recursion in the user's code. It is also a lot more accurate than the old profiler, as it does not charge all its overhead time to the user's code.

```

class OldProfile(Profile):

    def trace_dispatch_exception(self, frame, t):
        rt, rtt, rct, rfn, rframe, rcur = self.cur
        if rcur and not rframe is frame:
            return self.trace_dispatch_return(rframe, t)
        return 0

    def trace_dispatch_call(self, frame, t):
        fn = `frame.f_code`

        self.cur = (t, 0, 0, fn, frame, self.cur)
        if self.timings.has_key(fn):
            tt, ct, callers = self.timings[fn]
            self.timings[fn] = tt, ct, callers
        else:
            self.timings[fn] = 0, 0, {}
        return 1

    def trace_dispatch_return(self, frame, t):
        rt, rtt, rct, rfn, frame, rcur = self.cur
        rtt = rtt + t
        sft = rtt + rct

        pt, ptt, pct, pfn, pframe, pcur = rcur
        self.cur = pt, ptt+rt, pct+sft, pfn, pframe, pcur

        tt, ct, callers = self.timings[rfn]
        if callers.has_key(pfn):
            callers[pfn] = callers[pfn] + 1
        else:
            callers[pfn] = 1
        self.timings[rfn] = tt+rtt, ct + sft, callers

        return 1

    def snapshot_stats(self):
        self.stats = {}
        for func in self.timings.keys():
            tt, ct, callers = self.timings[func]
            nor_func = self.func_normalize(func)
            nor_callers = {}
            nc = 0
            for func_caller in callers.keys():
                nor_callers[self.func_normalize(func_caller)] = \
                    callers[func_caller]
                nc = nc + callers[func_caller]
            self.stats[nor_func] = nc, nc, tt, ct, nor_callers

```

10.8.2 HotProfile Class

This profiler is the fastest derived profile example. It does not calculate caller-callee relationships, and does not calculate cumulative time under a function. It only calculates time spent in a function, so it runs very quickly (re: very low overhead). In truth, the basic profiler is so fast, that is probably not worth the savings to give up the data, but this

class still provides a nice example.

```
class HotProfile(Profile):

    def trace_dispatch_exception(self, frame, t):
        rt, rtt, rfn, rframe, rcur = self.cur
        if rcur and not rframe is frame:
            return self.trace_dispatch_return(rframe, t)
        return 0

    def trace_dispatch_call(self, frame, t):
        self.cur = (t, 0, frame, self.cur)
        return 1

    def trace_dispatch_return(self, frame, t):
        rt, rtt, frame, rcur = self.cur

        rfn = `frame.f_code`

        pt, ptt, pframe, pcur = rcur
        self.cur = pt, ptt+rt, pframe, pcur

        if self.timings.has_key(rfn):
            nc, tt = self.timings[rfn]
            self.timings[rfn] = nc + 1, rt + rtt + tt
        else:
            self.timings[rfn] = 1, rt + rtt

        return 1

    def snapshot_stats(self):
        self.stats = {}
        for func in self.timings.keys():
            nc, tt = self.timings[func]
            nor_func = self.func_normalize(func)
            self.stats[nor_func] = nc, nc, tt, 0, {}
```


Internet Protocols and Support

The modules described in this chapter implement Internet protocols and support for related technology. They are all implemented in Python. Most of these modules require the presence of the system-dependent module `socket`, which is currently supported on most popular platforms. Here is an overview:

<code>cgi</code>	Common Gateway Interface support, used to interpret forms in server-side scripts.
<code>urllib</code>	Open an arbitrary network resource by URL (requires sockets).
<code>httplib</code>	HTTP protocol client (requires sockets).
<code>ftplib</code>	FTP protocol client (requires sockets).
<code>gopherlib</code>	Gopher protocol client (requires sockets).
<code>poplib</code>	POP3 protocol client (requires sockets).
<code>imaplib</code>	IMAP4 protocol client (requires sockets).
<code>nntplib</code>	NNTP protocol client (requires sockets).
<code>smtplib</code>	SMTP protocol client (requires sockets).
<code>telnetlib</code>	Telnet client class.
<code>urlparse</code>	Parse URLs into components.
<code>SocketServer</code>	A framework for network servers.
<code>BaseHTTPServer</code>	Basic HTTP server (base class for <code>SimpleHTTPServer</code> and <code>CGIHTTPServer</code>).
<code>SimpleHTTPServer</code>	This module provides a request handler for HTTP servers.
<code>CGIHTTPServer</code>	This module provides a request handler for HTTP servers which can run CGI scripts.
<code>asyncore</code>	A base class for developing asynchronous socket handling services.

11.1 `cgi` — Common Gateway Interface support.

Support module for CGI (Common Gateway Interface) scripts.

This module defines a number of utilities for use by CGI scripts written in Python.

11.1.1 Introduction

A CGI script is invoked by an HTTP server, usually to process user input submitted through an HTML `<FORM>` or `<ISINDEX>` element.

Most often, CGI scripts live in the server's special 'cgi-bin' directory. The HTTP server places all sorts of information about the request (such as the client's hostname, the requested URL, the query string, and lots of other goodies) in the script's shell environment, executes the script, and sends the script's output back to the client.

The script's input is connected to the client too, and sometimes the form data is read this way; at other times the form data is passed via the "query string" part of the URL. This module is intended to take care of the different cases and provide a simpler interface to the Python script. It also provides a number of utilities that help in debugging scripts,

and the latest addition is support for file uploads from a form (if your browser supports it — Grail 0.3 and Netscape 2.0 do).

The output of a CGI script should consist of two sections, separated by a blank line. The first section contains a number of headers, telling the client what kind of data is following. Python code to generate a minimal header section looks like this:

```
print "Content-type: text/html"      # HTML is following
print                               # blank line, end of headers
```

The second section is usually HTML, which allows the client software to display nicely formatted text with header, in-line images, etc. Here's Python code that prints a simple piece of HTML:

```
print "<TITLE>CGI script output</TITLE>"
print "<H1>This is my first CGI script</H1>"
print "Hello, world!"
```

(It may not be fully legal HTML according to the letter of the standard, but any browser will understand it.)

11.1.2 Using the cgi module

Begin by writing `import cgi`. Do not use `from cgi import *` — the module defines all sorts of names for its own use or for backward compatibility that you don't want in your namespace.

It's best to use the `FieldStorage` class. The other classes defined in this module are provided mostly for backward compatibility. Instantiate it exactly once, without arguments. This reads the form contents from standard input or the environment (depending on the value of various environment variables set according to the CGI standard). Since it may consume standard input, it should be instantiated only once.

The `FieldStorage` instance can be accessed as if it were a Python dictionary. For instance, the following code (which assumes that the `content-type` header and blank line have already been printed) checks that the fields name and addr are both set to a non-empty string:

```
form = cgi.FieldStorage()
form_ok = 0
if form.has_key("name") and form.has_key("addr"):
    if form["name"].value != "" and form["addr"].value != "":
        form_ok = 1
if not form_ok:
    print "<H1>Error</H1>"
    print "Please fill in the name and addr fields."
    return
...further form processing here...
```

Here the fields, accessed through `form[key]`, are themselves instances of `FieldStorage` (or `MiniFieldStorage`, depending on the form encoding).

If the submitted form data contains more than one field with the same name, the object retrieved by `form[key]` is not a `FieldStorage` or `MiniFieldStorage` instance but a list of such instances. If you expect this possibility (i.e., when your HTML form contains multiple fields with the same name), use the `type()` function to determine whether you have a single instance or a list of instances. For example, here's code that concatenates any number of username fields, separated by commas:

```

username = form["username"]
if type(username) is type([]):
    # Multiple username fields specified
    usernames = ""
    for item in username:
        if usernames:
            # Next item -- insert comma
            usernames = usernames + "," + item.value
        else:
            # First item -- don't insert comma
            usernames = item.value
else:
    # Single username field specified
    usernames = username.value

```

If a field represents an uploaded file, the value attribute reads the entire file in memory as a string. This may not be what you want. You can test for an uploaded file by testing either the filename attribute or the file attribute. You can then read the data at leisure from the file attribute:

```

fileitem = form["userfile"]
if fileitem.file:
    # It's an uploaded file; count lines
    linecount = 0
    while 1:
        line = fileitem.file.readline()
        if not line: break
        linecount = linecount + 1

```

The file upload draft standard entertains the possibility of uploading multiple files from one field (using a recursive `multipart/*` encoding). When this occurs, the item will be a dictionary-like `FieldStorage` item. This can be determined by testing its `type` attribute, which should be `multipart/form-data` (or perhaps another MIME type matching `multipart/*`). In this case, it can be iterated over recursively just like the top-level form object.

When a form is submitted in the “old” format (as the query string or as a single data part of type `application/x-www-form-urlencoded`), the items will actually be instances of the class `MiniFieldStorage`. In this case, the `list`, `file` and `filename` attributes are always `None`.

11.1.3 Old classes

These classes, present in earlier versions of the `cgi` module, are still supported for backward compatibility. New applications should use the `FieldStorage` class.

`SvFormContentDict` stores single value form content as dictionary; it assumes each field name occurs in the form only once.

`FormContentDict` stores multiple value form content as a dictionary (the form items are lists of values). Useful if your form contains multiple fields with the same name.

Other classes (`FormContent`, `InterpFormContentDict`) are present for backwards compatibility with really old applications only. If you still use these and would be inconvenienced when they disappeared from a next version of this module, drop me a note.

11.1.4 Functions

These are useful if you want more control, or if you want to employ some of the algorithms implemented in this module in other circumstances.

parse(*fp*)

Parse a query in the environment or from a file (default `sys.stdin`).

parse_qs(*qs*[, *keep_blank_values*, *strict_parsing*])

Parse a query string given as a string argument (data of type `application/x-www-form-urlencoded`). Data are returned as a dictionary. The dictionary keys are the unique query variable names and the values are lists of values for each name.

The optional argument *keep_blank_values* is a flag indicating whether blank values in URL encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.

The optional argument *strict_parsing* is a flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.

parse_qs1(*qs*[, *keep_blank_values*, *strict_parsing*])

Parse a query string given as a string argument (data of type `application/x-www-form-urlencoded`). Data are returned as a list of name, value pairs.

The optional argument *keep_blank_values* is a flag indicating whether blank values in URL encoded queries should be treated as blank strings. A true value indicates that blanks should be retained as blank strings. The default false value indicates that blank values are to be ignored and treated as if they were not included.

The optional argument *strict_parsing* is a flag indicating what to do with parsing errors. If false (the default), errors are silently ignored. If true, errors raise a `ValueError` exception.

parse_multipart(*fp*, *pdict*)

Parse input of type `multipart/form-data` (for file uploads). Arguments are *fp* for the input file and *pdict* for the dictionary containing other parameters of `content-type` header

Returns a dictionary just like `parse_qs()` keys are the field names, each value is a list of values for that field. This is easy to use but not much good if you are expecting megabytes to be uploaded — in that case, use the `FieldStorage` class instead which is much more flexible. Note that `content-type` is the raw, unparsed contents of the `content-type` header.

Note that this does not parse nested multipart parts — use `FieldStorage` for that.

parse_header(*string*)

Parse a header like `content-type` into a main `content-type` and a dictionary of parameters.

test()

Robust test CGI script, usable as main program. Writes minimal HTTP headers and formats all information provided to the script in HTML form.

print_envIRON()

Format the shell environment in HTML.

print_form(*form*)

Format a form in HTML.

print_directory()

Format the current directory in HTML.

print_envIRON_usage()

Print a list of useful (used by CGI) environment variables in HTML.

escape(*s*[, *quote*])

Convert the characters '&', '<' and '>' in string *s* to HTML-safe sequences. Use this if you need to display text

that might contain such characters in HTML. If the optional flag *quote* is true, the double quote character (“”) is also translated; this helps for inclusion in an HTML attribute value, e.g. in ``.

11.1.5 Caring about security

There’s one important rule: if you invoke an external program (e.g. via the `os.system()` or `os.popen()` functions), make very sure you don’t pass arbitrary strings received from the client to the shell. This is a well-known security hole whereby clever hackers anywhere on the web can exploit a gullible CGI script to invoke arbitrary shell commands. Even parts of the URL or field names cannot be trusted, since the request doesn’t have to come from your form!

To be on the safe side, if you must pass a string gotten from a form to a shell command, you should make sure the string contains only alphanumeric characters, dashes, underscores, and periods.

11.1.6 Installing your CGI script on a Unix system

Read the documentation for your HTTP server and check with your local system administrator to find the directory where CGI scripts should be installed; usually this is in a directory ‘cgi-bin’ in the server tree.

Make sure that your script is readable and executable by “others”; the UNIX file mode should be 0755 octal (use ‘`chmod 0755 filename`’). Make sure that the first line of the script contains `#!` starting in column 1 followed by the pathname of the Python interpreter, for instance:

```
#!/usr/local/bin/python
```

Make sure the Python interpreter exists and is executable by “others”.

Make sure that any files your script needs to read or write are readable or writable, respectively, by “others” — their mode should be 0644 for readable and 0666 for writable. This is because, for security reasons, the HTTP server executes your script as user “nobody”, without any special privileges. It can only read (write, execute) files that everybody can read (write, execute). The current directory at execution time is also different (it is usually the server’s cgi-bin directory) and the set of environment variables is also different from what you get at login. In particular, don’t count on the shell’s search path for executables (`$PATH`) or the Python module search path (`$PYTHONPATH`) to be set to anything interesting.

If you need to load modules from a directory which is not on Python’s default module search path, you can change the path in your script, before importing other modules, e.g.:

```
import sys
sys.path.insert(0, "/usr/home/joe/lib/python")
sys.path.insert(0, "/usr/local/lib/python")
```

(This way, the directory inserted last will be searched first!)

Instructions for non-UNIX systems will vary; check your HTTP server’s documentation (it will usually have a section on CGI scripts).

11.1.7 Testing your CGI script

Unfortunately, a CGI script will generally not run when you try it from the command line, and a script that works perfectly from the command line may fail mysteriously when run from the server. There’s one reason why you should

still test your script from the command line: if it contains a syntax error, the Python interpreter won't execute it at all, and the HTTP server will most likely send a cryptic error to the client.

Assuming your script has no syntax errors, yet it does not work, you have no choice but to read the next section.

11.1.8 Debugging CGI scripts

First of all, check for trivial installation errors — reading the section above on installing your CGI script carefully can save you a lot of time. If you wonder whether you have understood the installation procedure correctly, try installing a copy of this module file ('cgi.py') as a CGI script. When invoked as a script, the file will dump its environment and the contents of the form in HTML form. Give it the right mode etc, and send it a request. If it's installed in the standard 'cgi-bin' directory, it should be possible to send it a request by entering a URL into your browser of the form:

```
http://yourhostname/cgi-bin/cgi.py?name=Joe+Blow&addr=At+Home
```

If this gives an error of type 404, the server cannot find the script — perhaps you need to install it in a different directory. If it gives another error (e.g. 500), there's an installation problem that you should fix before trying to go any further. If you get a nicely formatted listing of the environment and form content (in this example, the fields should be listed as "addr" with value "At Home" and "name" with value "Joe Blow"), the 'cgi.py' script has been installed correctly. If you follow the same procedure for your own script, you should now be able to debug it.

The next step could be to call the `cgi` module's `test()` function from your script: replace its main code with the single statement

```
cgi.test()
```

This should produce the same results as those gotten from installing the 'cgi.py' file itself.

When an ordinary Python script raises an unhandled exception (e.g. because of a typo in a module name, a file that can't be opened, etc.), the Python interpreter prints a nice traceback and exits. While the Python interpreter will still do this when your CGI script raises an exception, most likely the traceback will end up in one of the HTTP server's log file, or be discarded altogether.

Fortunately, once you have managed to get your script to execute *some* code, it is easy to catch exceptions and cause a traceback to be printed. The `test()` function below in this module is an example. Here are the rules:

1. Import the `traceback` module before entering the `try ... except` statement
2. Assign `sys.stderr` to be `sys.stdout`
3. Make sure you finish printing the headers and the blank line early
4. Wrap all remaining code in a `try ... except` statement
5. In the `except` clause, call `traceback.print_exc()`

For example:

```

import sys
import traceback
print "Content-type: text/html"
print
sys.stderr = sys.stdout
try:
    ...your code here...
except:
    print "\n\n<PRE>"
    traceback.print_exc()

```

Notes: The assignment to `sys.stderr` is needed because the traceback prints to `sys.stderr`. The `print "\n\n<PRE>"` statement is necessary to disable the word wrapping in HTML.

If you suspect that there may be a problem in importing the traceback module, you can use an even more robust approach (which only uses built-in modules):

```

import sys
sys.stderr = sys.stdout
print "Content-type: text/plain"
print
...your code here...

```

This relies on the Python interpreter to print the traceback. The content type of the output is set to plain text, which disables all HTML processing. If your script works, the raw HTML will be displayed by your client. If it raises an exception, most likely after the first two lines have been printed, a traceback will be displayed. Because no HTML interpretation is going on, the traceback will be readable.

11.1.9 Common problems and solutions

- Most HTTP servers buffer the output from CGI scripts until the script is completed. This means that it is not possible to display a progress report on the client's display while the script is running.
- Check the installation instructions above.
- Check the HTTP server's log files. (`tail -f logfile` in a separate window may be useful!)
- Always check a script for syntax errors first, by doing something like `python script.py`.
- When using any of the debugging techniques, don't forget to add `import sys` to the top of the script.
- When invoking external programs, make sure they can be found. Usually, this means using absolute path names — `$PATH` is usually not set to a very useful value in a CGI script.
- When reading or writing external files, make sure they can be read or written by every user on the system.
- Don't try to give a CGI script a set-uid mode. This doesn't work on most systems, and is a security liability as well.

11.2 urllib — Open an arbitrary resource by URL

This module provides a high-level interface for fetching data across the World-Wide Web. In particular, the `urlopen()` function is similar to the built-in function `open()`, but accepts Universal Resource Locators (URLs)

instead of filenames. Some restrictions apply — it can only open URLs for reading, and no seek operations are available.

It defines the following public functions:

urlopen(*url*[, *data*])

Open a network object denoted by a URL for reading. If the URL does not have a scheme identifier, or if it has 'file:' as its scheme identifier, this opens a local file; otherwise it opens a socket to a server somewhere on the network. If the connection cannot be made, or if the server returns an error code, the `IOError` exception is raised. If all went well, a file-like object is returned. This supports the following methods: `read()`, `readline()`, `readlines()`, `fileno()`, `close()`, `info()` and `geturl()`.

Except for the `info()` and `geturl()` methods, these methods have the same interface as for file objects — see section 2.1.7 in this manual. (It is not a built-in file object, however, so it can't be used at those few places where a true built-in file object is required.)

The `info()` method returns an instance of the class `mimertools.Message` containing meta-information associated with the URL. When the method is HTTP, these headers are those returned by the server at the head of the retrieved HTML page (including Content-Length and Content-Type). When the method is FTP, a Content-Length header will be present if (as is now usual) the server passed back a file length in response to the FTP retrieval request. When the method is local-file, returned headers will include a Date representing the file's last-modified time, a Content-Length giving file size, and a Content-Type containing a guess at the file's type. See also the description of the `mimertools` module.

The `geturl()` method returns the real URL of the page. In some cases, the HTTP server redirects a client to another URL. The `urlopen()` function handles this transparently, but in some cases the caller needs to know which URL the client was redirected to. The `geturl()` method can be used to get at this redirected URL.

If the *url* uses the 'http:' scheme identifier, the optional *data* argument may be given to specify a POST request (normally the request type is GET). The *data* argument must in standard 'application/x-www-form-urlencoded' format; see the `urlencode()` function below.

The `urlopen()` function works transparently with proxies. In a UNIX or Windows environment, set the `$http_proxy`, `$ftp_proxy` or `$gopher_proxy` environment variables to a URL that identifies the proxy server before starting the Python interpreter. For example (the '%' is the command prompt):

```
% http_proxy="http://www.someproxy.com:3128"  
% export http_proxy  
% python  
...
```

In a Macintosh environment, `urlopen()` will retrieve proxy information from Internet Config.

The `urlopen()` function works transparently with proxies. In a UNIX or Windows environment, set the `$http_proxy`, `$ftp_proxy` or `$gopher_proxy` environment variables to a URL that identifies the proxy server before starting the Python interpreter, e.g.:

```
% http_proxy="http://www.someproxy.com:3128"  
% export http_proxy  
% python  
...
```

In a Macintosh environment, `urlopen()` will retrieve proxy information from Internet Config.

urlretrieve(*url*[, *filename*[, *hook*]])

Copy a network object denoted by a URL to a local file, if necessary. If the URL points to a local file, or a valid cached copy of the object exists, the object is not copied. Return a tuple (*filename*, *headers*) where *filename* is the local file name under which the object can be found, and *headers* is either `None` (for a local object) or whatever the `info()` method of the object returned by `urlopen()` returned (for a remote object, possibly cached). Exceptions are the same as for `urlopen()`.

The second argument, if present, specifies the file location to copy to (if absent, the location will be a tempfile with a generated name). The third argument, if present, is a hook function that will be called once on establishment of the network connection and once after each block read thereafter. The hook will be passed three arguments; a count of blocks transferred so far, a block size in bytes, and the total size of the file. The third argument may be `-1` on older FTP servers which do not return a file size in response to a retrieval request.

urllcleanup()

Clear the cache that may have been built up by previous calls to `urlretrieve()`.

quote(string[, safe])

Replace special characters in *string* using the `'%xx'` escape. Letters, digits, and the characters `'_', '.', '-'` are never quoted. The optional *safe* parameter specifies additional characters that should not be quoted — its default value is `'/'`.

Example: `quote('/~/connolly/')` yields `'/%7econnolly/'`.

quote_plus(string[, safe])

Like `quote()`, but also replaces spaces by plus signs, as required for quoting HTML form values. Plus signs in the original string are escaped unless they are included in *safe*.

unquote(string)

Replace `'%xx'` escapes by their single-character equivalent.

Example: `unquote('/%7Econnolly/')` yields `'/~/connolly/'`.

unquote_plus(string)

Like `unquote()`, but also replaces plus signs by spaces, as required for unquoting HTML form values.

urlencode(dict)

Convert a dictionary to a “url-encoded” string, suitable to pass to `urlopen()` above as the optional *data* argument. This is useful to pass a dictionary of form fields to a POST request. The resulting string is a series of *key=value* pairs separated by `'&'` characters, where both *key* and *value* are quoted using `quote_plus()` above.

The public functions `urlopen()` and `urlretrieve()` create an instance of the `FancyURLopener` class and use it to perform their requested actions. To override this functionality, programmers can create a subclass of `URLopener` or `FancyURLopener`, then assign that class to the `urllib._url opener` variable before calling the desired function. For example, applications may want to specify a different `user-agent` header than `URLopener` defines. This can be accomplished with the following code:

```
class AppURLopener(urllib.FancyURLopener):
    def __init__(self, *args):
        apply(urllib.FancyURLopener.__init__, (self,) + args)
        self.version = "App/1.7"

urllib._url opener = AppURLopener
```

URLopener([proxies[, **x509]])

Base class for opening and reading URLs. Unless you need to support opening objects using schemes other than `'http:'`, `'ftp:'`, `'gopher:'` or `'file:'`, you probably want to use `FancyURLopener`.

By default, the `URLopener` class sends a `user-agent` header of `'urllib/VVV'`, where *VVV* is the `urllib` version number. Applications can define their own `user-agent` header by subclassing `URLopener` or `FancyURLopener` and setting the instance attribute *version* to an appropriate string value before the `open()` method is called.

Additional keyword parameters, collected in *x509*, are used for authentication with the `'https:'` scheme. The keywords *key_file* and *cert_file* are supported; both are needed to actually retrieve a resource at an `'https:'` URL.

FancyURLOpener (...)

FancyURLOpener subclasses URLOpener providing default handling for the following HTTP response codes: 301, 302 or 401. For 301 and 302 response codes, the `location` header is used to fetch the actual URL. For 401 response codes (authentication required), basic HTTP authentication is performed.

The parameters to the constructor are the same as those for URLOpener.

Restrictions:

- Currently, only the following protocols are supported: HTTP, (versions 0.9 and 1.0), Gopher (but not Gopher+), FTP, and local files.
- The caching feature of `urlretrieve()` has been disabled until I find the time to hack proper processing of Expiration time headers.
- There should be a function to query whether a particular URL is in the cache.
- For backward compatibility, if a URL appears to point to a local file but the file can't be opened, the URL is re-interpreted using the FTP protocol. This can sometimes cause confusing error messages.
- The `urlopen()` and `urlretrieve()` functions can cause arbitrarily long delays while waiting for a network connection to be set up. This means that it is difficult to build an interactive web client using these functions without using threads.
- The data returned by `urlopen()` or `urlretrieve()` is the raw data returned by the server. This may be binary data (e.g. an image), plain text or (for example) HTML. The HTTP protocol provides type information in the reply header, which can be inspected by looking at the `content-type` header. For the Gopher protocol, type information is encoded in the URL; there is currently no easy way to extract it. If the returned data is HTML, you can use the module `htmllib` to parse it.
- Although the `urllib` module contains (undocumented) routines to parse and unparse URL strings, the recommended interface for URL manipulation is in module `urlparse`.

11.2.1 URLOpener Objects

URLOpener and FancyURLOpener objects have the following methods:

open(*fullurl*[, *data*])

Open *fullurl* using the appropriate protocol. This method sets up cache and proxy information, then calls the appropriate open method with its input arguments. If the scheme is not recognized, `open_unknown()` is called. The *data* argument has the same meaning as the *data* argument of `urlopen()`.

open_unknown(*fullurl*[, *data*])

Overridable interface to open unknown URL types.

retrieve(*url*[, *filename*[, *reporhook*]])

Retrieves the contents of *url* and places it in *filename*. The return value is a tuple consisting of a local filename and either a `mimertools.Message` object containing the response headers (for remote URLs) or `None` (for local URLs). The caller must then open and read the contents of *filename*. If *filename* is not given and the URL refers to a local file, the input filename is returned. If the URL is non-local and *filename* is not given, the filename is the output of `tempfile.mktemp()` with a suffix that matches the suffix of the last path component of the input URL. If *reporhook* is given, it must be a function accepting three numeric parameters. It will be called after each chunk of data is read from the network. *reporhook* is ignored for local URLs.

11.2.2 Examples

Here is an example session that uses the 'GET' method to retrieve a URL containing parameters:

```

>>> import urllib
>>> params = urllib.urlencode({'spam': 1, 'eggs': 2, 'bacon': 0})
>>> f = urllib.urlopen("http://www.musi-cal.com/cgi-bin/query?%s" % params)
>>> print f.read()

```

The following example uses the ‘POST’ method instead:

```

>>> import urllib
>>> params = urllib.urlencode({'spam': 1, 'eggs': 2, 'bacon': 0})
>>> f = urllib.urlopen("http://www.musi-cal.com/cgi-bin/query", params)
>>> print f.read()

```

11.3 httplib — HTTP protocol client

This module defines a class which implements the client side of the HTTP protocol. It is normally not used directly — the module `urllib` uses it to handle URLs that use HTTP.

The module defines one class, `HTTP`:

HTTP([*host*[, *port*]])

An `HTTP` instance represents one transaction with an HTTP server. It should be instantiated passing it a host and optional port number. If no port number is passed, the port is extracted from the host string if it has the form *host:port*, else the default HTTP port (80) is used. If no host is passed, no connection is made, and the `connect()` method should be used to connect to a server. For example, the following calls all create instances that connect to the server at the same host and port:

```

>>> h1 = httplib.HTTP('www.cwi.nl')
>>> h2 = httplib.HTTP('www.cwi.nl:80')
>>> h3 = httplib.HTTP('www.cwi.nl', 80)

```

Once an `HTTP` instance has been connected to an HTTP server, it should be used as follows:

1. Make exactly one call to the `putrequest()` method.
2. Make zero or more calls to the `putheader()` method.
3. Call the `endheaders()` method (this can be omitted if step 4 makes no calls).
4. Optional calls to the `send()` method.
5. Call the `getreply()` method.
6. Call the `getfile()` method and read the data off the file object that it returns.

11.3.1 HTTP Objects

`HTTP` instances have the following methods:

set_debuglevel(*level*)

Set the debugging level (the amount of debugging output printed). The default debug level is 0, meaning no debugging output is printed.

connect (*host*[, *port*])

Connect to the server given by *host* and *port*. See the intro for the default port. This should be called directly only if the instance was instantiated without passing a host.

send (*data*)

Send data to the server. This should be used directly only after the `endheaders()` method has been called and before `getreply()` has been called.

putrequest (*request*, *selector*)

This should be the first call after the connection to the server has been made. It sends a line to the server consisting of the *request* string, the *selector* string, and the HTTP version (HTTP/1.0).

putheader (*header*, *argument*[, ...])

Send an RFC 822 style header to the server. It sends a line to the server consisting of the header, a colon and a space, and the first argument. If more arguments are given, continuation lines are sent, each consisting of a tab and an argument.

endheaders ()

Send a blank line to the server, signalling the end of the headers.

getreply ()

Complete the request by shutting down the sending end of the socket, read the reply from the server, and return a triple (*replycode*, *message*, *headers*). Here, *replycode* is the integer reply code from the request (e.g., 200 if the request was handled properly); *message* is the message string corresponding to the reply code; and *headers* is an instance of the class `mimetools.Message` containing the headers received from the server. See the description of the `mimetools` module.

getfile ()

Return a file object from which the data returned by the server can be read, using the `read()`, `readline()` or `readlines()` methods.

11.3.2 Example

Here is an example session:

```
>>> import httplib
>>> h = httplib.HTTP('www.cwi.nl')
>>> h.putrequest('GET', '/index.html')
>>> h.putheader('Accept', 'text/html')
>>> h.putheader('Accept', 'text/plain')
>>> h.endheaders()
>>> errcode, errmsg, headers = h.getreply()
>>> print errcode # Should be 200
>>> f = h.getfile()
>>> data = f.read() # Get the raw HTML
>>> f.close()
```

11.4 ftplib — FTP protocol client

This module defines the class `FTP` and a few related items. The `FTP` class implements the client side of the FTP protocol. You can use this to write Python programs that perform a variety of automated FTP jobs, such as mirroring other ftp servers. It is also used by the module `urllib` to handle URLs that use FTP. For more information on FTP (File Transfer Protocol), see Internet RFC 959.

Here's a sample session using the `ftplib` module:

```
>>> from ftplib import FTP
>>> ftp = FTP('ftp.cwi.nl') # connect to host, default port
>>> ftp.login()             # user anonymous, passwd user@hostname
>>> ftp.retrlines('LIST')  # list directory contents
total 24418
drwxrwsr-x   5 ftp-usr  pdmaint      1536 Mar 20 09:48 .
dr-xr-srwt 105 ftp-usr  pdmaint      1536 Mar 21 14:32 ..
-rw-r--r--   1 ftp-usr  pdmaint      5305 Mar 20 09:48 INDEX
.
.
.
>>> ftp.retrbinary('RETR README', open('README', 'wb').write)
'226 Transfer complete.'
>>> ftp.quit()
```

The module defines the following items:

FTP (`[host[, user[, passwd[, acct]]]]`)

Return a new instance of the FTP class. When *host* is given, the method call `connect(host)` is made. When *user* is given, additionally the method call `login(user, passwd, acct)` is made (where *passwd* and *acct* default to the empty string when not given).

all_errors

The set of all exceptions (as a tuple) that methods of FTP instances may raise as a result of problems with the FTP connection (as opposed to programming errors made by the caller). This set includes the four exceptions listed below as well as `socket.error` and `IOError`.

error_reply

Exception raised when an unexpected reply is received from the server.

error_temp

Exception raised when an error code in the range 400–499 is received.

error_perm

Exception raised when an error code in the range 500–599 is received.

error_proto

Exception raised when a reply is received from the server that does not begin with a digit in the range 1–5.

See Also:

[Module `netrc`](#) (section 12.21):

Parser for the `.netrc` file format. The file `.netrc` is typically used by FTP clients to load user authentication information before prompting the user.

The file `Tools/scripts/ftpmirror.py` in the Python source distribution is a script that can mirror FTP sites, or portions thereof, using the `ftplib` module. It can be used as an extended example that applies this module.

11.4.1 FTP Objects

Several methods are available in two flavors: one for handling text files and another for binary files. These are named for the command which is used followed by `'lines'` for the text version or `'binary'` for the binary version.

FTP instances have the following methods:

set_debuglevel (*level*)

Set the instance's debugging level. This controls the amount of debugging output printed. The default, 0,

produces no debugging output. A value of 1 produces a moderate amount of debugging output, generally a single line per request. A value of 2 or higher produces the maximum amount of debugging output, logging each line sent and received on the control connection.

connect(*host*[, *port*])

Connect to the given host and port. The default port number is 21, as specified by the FTP protocol specification. It is rarely needed to specify a different port number. This function should be called only once for each instance; it should not be called at all if a host was given when the instance was created. All other methods can only be used after a connection has been made.

getwelcome()

Return the welcome message sent by the server in reply to the initial connection. (This message sometimes contains disclaimers or help information that may be relevant to the user.)

login([*user*[, *passwd*[, *acct*]]])

Log in as the given *user*. The *passwd* and *acct* parameters are optional and default to the empty string. If no *user* is specified, it defaults to 'anonymous'. If *user* is 'anonymous', the default *passwd* is '*realuser@host*' where *realuser* is the real user name (glanced from the \$LOGNAME or \$USER environment variable) and *host* is the hostname as returned by `socket.gethostname()`. This function should be called only once for each instance, after a connection has been established; it should not be called at all if a host and user were given when the instance was created. Most FTP commands are only allowed after the client has logged in.

abort()

Abort a file transfer that is in progress. Using this does not always work, but it's worth a try.

sendcmd(*command*)

Send a simple command string to the server and return the response string.

voidcmd(*command*)

Send a simple command string to the server and handle the response. Return nothing if a response code in the range 200–299 is received. Raise an exception otherwise.

retrbinary(*command*, *callback*[, *maxblocksize*])

Retrieve a file in binary transfer mode. *command* should be an appropriate 'RETR' command, i.e. 'RETR *filename*'. The *callback* function is called for each block of data received, with a single string argument giving the data block. The optional *maxblocksize* argument specifies the maximum chunk size to read on the low-level socket object created to do the actual transfer (which will also be the largest size of the data blocks passed to *callback*). A reasonable default is chosen.

retrlines(*command*[, *callback*])

Retrieve a file or directory listing in ASCII transfer mode. *command* should be an appropriate 'RETR' command (see `retrbinary()` or a 'LIST' command (usually just the string 'LIST')). The *callback* function is called for each line, with the trailing CRLF stripped. The default *callback* prints the line to `sys.stdout`.

set_pasv(*boolean*)

Enable "passive" mode if *boolean* is true, other disable passive mode.

storbinary(*command*, *file*, *blocksize*)

Store a file in binary transfer mode. *command* should be an appropriate 'STOR' command, i.e. "STOR *filename*". *file* is an open file object which is read until EOF using its `read()` method in blocks of size *blocksize* to provide the data to be stored.

storlines(*command*, *file*)

Store a file in ASCII transfer mode. *command* should be an appropriate 'STOR' command (see `storbinary()`). Lines are read until EOF from the open file object *file* using its `readline()` method to provide the data to be stored.

transfercmd(*cmd*)

Initiate a transfer over the data connection. If the transfer is active, send a 'PORT' command and the transfer command specified by *cmd*, and accept the connection. If the server is passive, send a 'PASV' command,

connect to it, and start the transfer command. Either way, return the socket for the connection.

ntransfercmd(*cmd*)

Like `transfercmd()`, but returns a tuple of the data connection and the expected size of the data. If the expected size could not be computed, `None` will be returned as the expected size.

nlst(*argument*[, ...])

Return a list of files as returned by the ‘NLST’ command. The optional *argument* is a directory to list (default is the current server directory). Multiple arguments can be used to pass non-standard options to the ‘NLST’ command.

dir(*argument*[, ...])

Produce a directory listing as returned by the ‘LIST’ command, printing it to standard output. The optional *argument* is a directory to list (default is the current server directory). Multiple arguments can be used to pass non-standard options to the ‘LIST’ command. If the last argument is a function, it is used as a *callback* function as for `retrlines()`; the default prints to `sys.stdout`. This method returns `None`.

rename(*fromname*, *toname*)

Rename file *fromname* on the server to *toname*.

delete(*filename*)

Remove the file named *filename* from the server. If successful, returns the text of the response, otherwise raises `error_perm` on permission errors or `error_reply` on other errors.

cwd(*pathname*)

Set the current directory on the server.

mkd(*pathname*)

Create a new directory on the server.

pwd()

Return the pathname of the current directory on the server.

rmd(*dirname*)

Remove the directory named *dirname* on the server.

size(*filename*)

Request the size of the file named *filename* on the server. On success, the size of the file is returned as an integer, otherwise `None` is returned. Note that the ‘SIZE’ command is not standardized, but is supported by many common server implementations.

quit()

Send a ‘QUIT’ command to the server and close the connection. This is the “polite” way to close a connection, but it may raise an exception if the server responds with an error to the ‘QUIT’ command. This implies a call to the `close()` method which renders the FTP instance useless for subsequent calls (see below).

close()

Close the connection unilaterally. This should not be applied to an already closed connection (e.g. after a successful call to `quit()`). After this call the FTP instance should not be used any more (i.e., after a call to `close()` or `quit()` you cannot reopen the connection by issuing another `login()` method).

11.5 gopherlib — Gopher protocol client

This module provides a minimal implementation of client side of the the Gopher protocol. It is used by the module `urllib` to handle URLs that use the Gopher protocol.

The module defines the following functions:

send_selector(*selector*, *host*[, *port*])

Send a *selector* string to the gopher server at *host* and *port* (default 70). Returns an open file object from which

the returned document can be read.

send_query(*selector*, *query*, *host*[, *port*])

Send a *selector* string and a *query* string to a gopher server at *host* and *port* (default 70). Returns an open file object from which the returned document can be read.

Note that the data returned by the Gopher server can be of any type, depending on the first character of the selector string. If the data is text (first character of the selector is '0'), lines are terminated by CRLF, and the data is terminated by a line consisting of a single '.', and a leading '.' should be stripped from lines that begin with '..'. Directory listings (first character of the selector is '1') are transferred using the same protocol.

11.6 poplib — POP3 protocol client

This module defines a class, POP3, which encapsulates a connection to an POP3 server and implements protocol as defined in RFC 1725. The POP3 class supports both the minimal and optional command sets.

A single class is provided by the poplib module:

POP3(*host*[, *port*])

This class implements the actual POP3 protocol. The connection is created when the instance is initialized. If *port* is omitted, the standard POP3 port (110) is used.

One exception is defined as an attribute of the poplib module:

error_proto

Exception raised on any errors. The reason for the exception is passed to the constructor as a string.

11.6.1 POP3 Objects

All POP3 commands are represented by methods of the same name, in lower-case; most return the response text sent by the server.

An POP3 instance has the following methods:

getwelcome()

Returns the greeting string sent by the POP3 server.

user(*username*)

Send user command, response should indicate that a password is required.

pass_(*password*)

Send password, response includes message count and mailbox size. Note: the mailbox on the server is locked until `quit()` is called.

apop(*user*, *secret*)

Use the more secure APOP authentication to log into the POP3 server.

rpop(*user*)

Use RPOP authentication (similar to UNIX r-commands) to log into POP3 server.

stat()

Get mailbox status. The result is a tuple of 2 integers: (*message count*, *mailbox size*).

list([*which*])

Request message list, result is in the form (*response*, [*'msg_num octets'*, ...]). If *which* is set, it is the message to list.

retr(*which*)

Retrieve whole message number *which*. Result is in form (*response*, [*'line'*, ...], *octets*).

delete(*which*)
Delete message number *which*.

rset()
Remove any deletion marks for the mailbox.

noop()
Do nothing. Might be used as a keep-alive.

quit()
Signoff: commit changes, unlock mailbox, drop connection.

top(*which*, *howmuch*)
Retrieves the message header plus *howmuch* lines of the message after the header of message number *which*. Result is in form (*response*, [*'line'*, ...], *octets*).

uidl([*which*])
Return message digest (unique id) list. If *which* is specified, result contains the unique id for that message in the form '*response mesgnum uid*', otherwise result is list (*response*, [*'mesgnum uid'*, ...], *octets*).

11.6.2 POP3 Example

Here is a minimal example (without error checking) that opens a mailbox and retrieves and prints all messages:

```
import getpass, poplib

M = poplib.POP3('localhost')
M.user(getpass.getuser())
M.pass_(getpass.getpass())
numMessages = len(M.list()[1])
for i in range(numMessages):
    for j in M.retr(i+1)[1]:
        print j
```

At the end of the module, there is a test section that contains a more extensive example of usage.

11.7 imaplib — IMAP4 protocol client

This module defines a class, `IMAP4`, which encapsulates a connection to an IMAP4 server and implements the IMAP4rev1 client protocol as defined in RFC 2060. It is backward compatible with IMAP4 (RFC 1730) servers, but note that the 'STATUS' command is not supported in IMAP4.

A single class is provided by the `imaplib` module:

IMAP4([*host*[, *port*]])

This class implements the actual IMAP4 protocol. The connection is created and protocol version (IMAP4 or IMAP4rev1) is determined when the instance is initialized. If *host* is not specified, '' (the local host) is used. If *port* is omitted, the standard IMAP4 port (143) is used.

Two exceptions are defined as attributes of the `IMAP4` class:

IMAP4.error

Exception raised on any errors. The reason for the exception is passed to the constructor as a string.

IMAP4.abort

IMAP4 server errors cause this exception to be raised. This is a sub-class of `IMAP4.error`. Note that closing

the instance and instantiating a new one will usually allow recovery from this exception.

IMAP4.readonly

This exception is raised when a writeable mailbox has its status changed by the server. This is a sub-class of `IMAP4.error`. Some other client now has write permission, and the mailbox will need to be re-opened to re-obtain write permission.

The following utility functions are defined:

Internaldate2tuple(*datestr*)

Converts an IMAP4 INTERNALDATE string to Coordinated Universal Time. Returns a `time` module tuple.

Int2AP(*num*)

Converts an integer into a string representation using characters from the set [A .. P].

ParseFlags(*flagstr*)

Converts an IMAP4 'FLAGS' response to a tuple of individual flags.

Time2Internaldate(*date_time*)

Converts a `time` module tuple to an IMAP4 'INTERNALDATE' representation. Returns a string in the form: "DD-Mmm-YYYY HH:MM:SS +HHMM" (including double-quotes).

Note that IMAP4 message numbers change as the mailbox changes, so it is highly advisable to use UIDs instead, with the UID command.

At the end of the module, there is a test section that contains a more extensive example of usage.

See Also:

Documents describing the protocol, and sources and binaries for servers implementing it, can all be found at the University of Washington's *IMAP Information Center* (<http://www.cac.washington.edu/imap/>).

11.7.1 IMAP4 Objects

All IMAP4rev1 commands are represented by methods of the same name, either upper-case or lower-case.

All arguments to commands are converted to strings, except for 'AUTHENTICATE', and the last argument to 'APPEND' which is passed as an IMAP4 literal. If necessary (the string contains IMAP4 protocol-sensitive characters and isn't enclosed with either parentheses or double quotes) each string is quoted. However, the *password* argument to the 'LOGIN' command is always quoted.

Each command returns a tuple: (*type*, [*data*, ...]) where *type* is usually 'OK' or 'NO', and *data* is either the text from the command response, or mandated results from the command.

An IMAP4 instance has the following methods:

append(*mailbox*, *flags*, *date_time*, *message*)

Append message to named mailbox.

authenticate(*func*)

Authenticate command — requires response processing. This is currently unimplemented, and raises an exception.

check()

Checkpoint mailbox on server.

close()

Close currently selected mailbox. Deleted messages are removed from writable mailbox. This is the recommended command before 'LOGOUT'.

copy(*message_set*, *new_mailbox*)

Copy *message_set* messages onto end of *new_mailbox*.

create(*mailbox*)
Create new mailbox named *mailbox*.

delete(*mailbox*)
Delete old mailbox named *mailbox*.

expunge()
Permanently remove deleted items from selected mailbox. Generates an ‘EXPUNGE’ response for each deleted message. Returned data contains a list of ‘EXPUNGE’ message numbers in order received.

fetch(*message_set*, *message_parts*)
Fetch (parts of) messages. Returned data are tuples of message part envelope and data.

list([*directory* [, *pattern*]])
List mailbox names in *directory* matching *pattern*. *directory* defaults to the top-level mail folder, and *pattern* defaults to match anything. Returned data contains a list of ‘LIST’ responses.

login(*user*, *password*)
Identify the client using a plaintext password. The *password* will be quoted.

logout()
Shutdown connection to server. Returns server ‘BYE’ response.

lsub([*directory* [, *pattern*]])
List subscribed mailbox names in *directory* matching *pattern*. *directory* defaults to the top level directory and *pattern* defaults to match any mailbox. Returned data are tuples of message part envelope and data.

noop()
Send ‘NOOP’ to server.

open(*host*, *port*)
Opens socket to *port* at *host*. You may override this method.

partial(*message_num*, *message_part*, *start*, *length*)
Fetch truncated part of a message. Returned data is a tuple of message part envelope and data.

recent()
Prompt server for an update. Returned data is None if no new messages, else value of ‘RECENT’ response.

rename(*oldmailbox*, *newmailbox*)
Rename mailbox named *oldmailbox* to *newmailbox*.

response(*code*)
Return data for response *code* if received, or None. Returns the given code, instead of the usual type.

search(*charset*, *criteria*)
Search mailbox for matching messages. Returned data contains a space separated list of matching message numbers.

select([*mailbox* [, *readonly*]])
Select a mailbox. Returned data is the count of messages in *mailbox* (‘EXISTS’ response). The default *mailbox* is ‘INBOX’. If the *readonly* flag is set, modifications to the mailbox are not allowed.

socket()
Returns socket instance used to connect to server.

status(*mailbox*, *names*)
Request named status conditions for *mailbox*.

store(*message_set*, *command*, *flag_list*)
Alters flag dispositions for messages in mailbox.

subscribe(*mailbox*)
Subscribe to new mailbox.

uid(*command*, *args*)

Execute command *args* with messages identified by UID, rather than message number. Returns response appropriate to command.

unsubscribe(*mailbox*)

Unsubscribe from old mailbox.

xatom(*name*[, *arg1*[, *arg2*]])

Allow simple extension commands notified by server in 'CAPABILITY' response.

The following attributes are defined on instances of IMAP4:

PROTOCOL_VERSION

The most recent supported protocol in the 'CAPABILITY' response from the server.

debug

Integer value to control debugging output. The initialize value is taken from the module variable `Debug`. Values greater than three trace each command.

11.7.2 IMAP4 Example

Here is a minimal example (without error checking) that opens a mailbox and retrieves and prints all messages:

```
import getpass, imaplib, string

M = imaplib.IMAP4()
M.login(getpass.getuser(), getpass.getpass())
M.select()
typ, data = M.search(None, 'ALL')
for num in string.split(data[0]):
    typ, data = M.fetch(num, '(RFC822)')
    print 'Message %s\n%s\n' % (num, data[0][1])
M.logout()
```

11.8 nntplib — NNTP protocol client

This module defines the class `NNTP` which implements the client side of the NNTP protocol. It can be used to implement a news reader or poster, or automated news processors. For more information on NNTP (Network News Transfer Protocol), see Internet RFC 977.

Here are two small examples of how it can be used. To list some statistics about a newsgroup and print the subjects of the last 10 articles:

```

>>> s = NNTP('news.cwi.nl')
>>> resp, count, first, last, name = s.group('comp.lang.python')
>>> print 'Group', name, 'has', count, 'articles, range', first, 'to', last
Group comp.lang.python has 59 articles, range 3742 to 3803
>>> resp, subs = s.xhdr('subject', first + '-' + last)
>>> for id, sub in subs[-10:]: print id, sub
...
3792 Re: Removing elements from a list while iterating...
3793 Re: Who likes Info files?
3794 Emacs and doc strings
3795 a few questions about the Mac implementation
3796 Re: executable python scripts
3797 Re: executable python scripts
3798 Re: a few questions about the Mac implementation
3799 Re: PROPOSAL: A Generic Python Object Interface for Python C Modules
3802 Re: executable python scripts
3803 Re: \POSIX{} wait and SIGCHLD
>>> s.quit()
'205 news.cwi.nl closing connection. Goodbye.'

```

To post an article from a file (this assumes that the article has valid headers):

```

>>> s = NNTP('news.cwi.nl')
>>> f = open('/tmp/article')
>>> s.post(f)
'240 Article posted successfully.'
>>> s.quit()
'205 news.cwi.nl closing connection. Goodbye.'

```

The module itself defines the following items:

NNTP(*host* [, *port* [, *user* [, *password* [, *readermode*]]]])

Return a new instance of the NNTP class, representing a connection to the NNTP server running on host *host*, listening at port *port*. The default *port* is 119. If the optional *user* and *password* are provided, the 'AUTHINFO USER' and 'AUTHINFO PASS' commands are used to identify and authenticate the user to the server. If the optional flag *readermode* is true, then a 'mode reader' command is sent before authentication is performed. Reader mode is sometimes necessary if you are connecting to an NNTP server on the local machine and intend to call reader-specific commands, such as 'group'. If you get unexpected NNTPPermanentErrors, you might need to set *readermode*. *readermode* defaults to None.

NNTPError()

Derived from the standard exception Exception, this is the base class for all exceptions raised by the nntpplib module.

NNTPReplyError()

Exception raised when an unexpected reply is received from the server. For backwards compatibility, the exception *error_reply* is equivalent to this class.

NNTPTemporaryError()

Exception raised when an error code in the range 400–499 is received. For backwards compatibility, the exception *error_temp* is equivalent to this class.

NNTPPermanentError()

Exception raised when an error code in the range 500–599 is received. For backwards compatibility, the exception *error_perm* is equivalent to this class.

NNTPProtocolError ()

Exception raised when a reply is received from the server that does not begin with a digit in the range 1–5. For backwards compatibility, the exception `error_proto` is equivalent to this class.

NNTPDataError ()

Exception raised when there is some error in the response data. For backwards compatibility, the exception `error_data` is equivalent to this class.

11.8.1 NNTP Objects

NNTP instances have the following methods. The *response* that is returned as the first item in the return tuple of almost all methods is the server's response: a string beginning with a three-digit code. If the server's response indicates an error, the method raises one of the above exceptions.

getwelcome ()

Return the welcome message sent by the server in reply to the initial connection. (This message sometimes contains disclaimers or help information that may be relevant to the user.)

set_debuglevel (level)

Set the instance's debugging level. This controls the amount of debugging output printed. The default, 0, produces no debugging output. A value of 1 produces a moderate amount of debugging output, generally a single line per request or response. A value of 2 or higher produces the maximum amount of debugging output, logging each line sent and received on the connection (including message text).

newgroups (date, time)

Send a 'NEWGROUPS' command. The *date* argument should be a string of the form '*yymmdd*' indicating the date, and *time* should be a string of the form '*hhmmss*' indicating the time. Return a pair (*response*, *groups*) where *groups* is a list of group names that are new since the given date and time.

newnews (group, date, time)

Send a 'NEWNEWS' command. Here, *group* is a group name or '*', and *date* and *time* have the same meaning as for `newgroups ()`. Return a pair (*response*, *articles*) where *articles* is a list of article ids.

list ()

Send a 'LIST' command. Return a pair (*response*, *list*) where *list* is a list of tuples. Each tuple has the form (*group*, *last*, *first*, *flag*), where *group* is a group name, *last* and *first* are the last and first article numbers (as strings), and *flag* is 'y' if posting is allowed, 'n' if not, and 'm' if the newsgroup is moderated. (Note the ordering: *last*, *first*.)

group (name)

Send a 'GROUP' command, where *name* is the group name. Return a tuple (*response*, *count*, *first*, *last*, *name*) where *count* is the (estimated) number of articles in the group, *first* is the first article number in the group, *last* is the last article number in the group, and *name* is the group name. The numbers are returned as strings.

help ()

Send a 'HELP' command. Return a pair (*response*, *list*) where *list* is a list of help strings.

stat (id)

Send a 'STAT' command, where *id* is the message id (enclosed in '<' and '>') or an article number (as a string). Return a triple (*response*, *number*, *id*) where *number* is the article number (as a string) and *id* is the article id (enclosed in '<' and '>').

next ()

Send a 'NEXT' command. Return as for `stat ()`.

last ()

Send a 'LAST' command. Return as for `stat ()`.

head(*id*)

Send a 'HEAD' command, where *id* has the same meaning as for `stat()`. Return a tuple (*response*, *number*, *id*, *list*) where the first three are the same as for `stat()`, and *list* is a list of the article's headers (an uninterpreted list of lines, without trailing newlines).

body(*id*)

Send a 'BODY' command, where *id* has the same meaning as for `stat()`. Return as for `head()`.

article(*id*)

Send a 'ARTICLE' command, where *id* has the same meaning as for `stat()`. Return as for `head()`.

slave()

Send a 'SLAVE' command. Return the server's *response*.

xhdr(*header*, *string*)

Send an 'XHDR' command. This command is not defined in the RFC but is a common extension. The *header* argument is a header keyword, e.g. 'subject'. The *string* argument should have the form '*first-last*' where *first* and *last* are the first and last article numbers to search. Return a pair (*response*, *list*), where *list* is a list of pairs (*id*, *text*), where *id* is an article id (as a string) and *text* is the text of the requested header for that article.

post(*file*)

Post an article using the 'POST' command. The *file* argument is an open file object which is read until EOF using its `readline()` method. It should be a well-formed news article, including the required headers. The `post()` method automatically escapes lines beginning with '.'.

ihave(*id*, *file*)

Send an 'IHAVE' command. If the response is not an error, treat *file* exactly as for the `post()` method.

date()

Return a triple (*response*, *date*, *time*), containing the current date and time in a form suitable for the `newnews()` and `newgroups()` methods. This is an optional NNTP extension, and may not be supported by all servers.

xgtitle(*name*)

Process an 'XGTITLE' command, returning a pair (*response*, *list*), where *list* is a list of tuples containing (*name*, *title*). This is an optional NNTP extension, and may not be supported by all servers.

xover(*start*, *end*)

Return a pair (*resp*, *list*). *list* is a list of tuples, one for each article in the range delimited by the *start* and *end* article numbers. Each tuple is of the form (*article number*, *subject*, *poster*, *date*, *id*, *references*, *size*, *lines*). This is an optional NNTP extension, and may not be supported by all servers.

xpath(*id*)

Return a pair (*resp*, *path*), where *path* is the directory path to the article with message ID *id*. This is an optional NNTP extension, and may not be supported by all servers.

quit()

Send a 'QUIT' command and close the connection. Once this method has been called, no other methods of the NNTP object should be called.

11.9 smtpplib — SMTP protocol client

The `smtpplib` module defines an SMTP client session object that can be used to send mail to any Internet machine with an SMTP or ESMTP listener daemon. For details of SMTP and ESMTP operation, consult RFC 821 (*Simple Mail Transfer Protocol*) and RFC 1869 (*SMTP Service Extensions*).

SMTP([*host*[, *port*]])

A SMTP instance encapsulates an SMTP connection. It has methods that support a full repertoire of SMTP and

ESMTP operations. If the optional host and port parameters are given, the SMTP `connect()` method is called with those parameters during initialization. An `SMTPConnectError` is raised if the specified host doesn't respond correctly.

For normal use, you should only require the initialization/connect, `sendmail()`, and `quit()` methods. An example is included below.

A nice selection of exceptions is defined as well:

SMTPException

Base exception class for all exceptions raised by this module.

SMTPServerDisconnected

This exception is raised when the server unexpectedly disconnects, or when an attempt is made to use the SMTP instance before connecting it to a server.

SMTPResponseException

Base class for all exceptions that include an SMTP error code. These exceptions are generated in some instances when the SMTP server returns an error code. The error code is stored in the `smtp_code` attribute of the error, and the `smtp_error` attribute is set to the error message.

SMTPSenderRefused

Sender address refused. In addition to the attributes set by on all `SMTPResponseException` exceptions, this sets 'sender' to the string that the SMTP server refused.

SMTPRecipientsRefused

All recipient addresses refused. The errors for each recipient are accessible through the attribute `recipients`, which is a dictionary of exactly the same sort as `SMTP.sendmail()` returns.

SMTPDataError

The SMTP server refused to accept the message data.

SMTPConnectError

Error occurred during establishment of a connection with the server.

SMTPHeloError

The server refused our 'HELO' message.

See Also:

Internet RFC 821, *Simple Mail Transfer Protocol*. Available online at <http://info.internet.isi.edu/in-notes/rfc/files/rfc821.txt>.

Internet RFC 1869, *SMTP Service Extensions*. Available online at <http://info.internet.isi.edu/in-notes/rfc/files/rfc1869.txt>.

11.9.1 SMTP Objects

An SMTP instance has the following methods:

set_debuglevel(*level*)

Set the debug output level. A true value for *level* results in debug messages for connection and for all messages sent to and received from the server.

connect([*host* [, *port*]])

Connect to a host on a given port. The defaults are to connect to the local host at the standard SMTP port (25).

If the hostname ends with a colon (':') followed by a number, that suffix will be stripped off and the number interpreted as the port number to use.

Note: This method is automatically invoked by the constructor if a host is specified during instantiation.

docmd(*cmd*, [, *argstring*])

Send a command *cmd* to the server. The optional argument *argstring* is simply concatenated to the command,

separated by a space.

This returns a 2-tuple composed of a numeric response code and the actual response line (multiline responses are joined into one long line.)

In normal operation it should not be necessary to call this method explicitly. It is used to implement other methods and may be useful for testing private extensions.

If the connection to the server is lost while waiting for the reply, `SMTPServerDisconnected` will be raised.

hello(*[hostname]*)

Identify yourself to the SMTP server using 'HELO'. The *hostname* argument defaults to the fully qualified domain name of the local host.

In normal operation it should not be necessary to call this method explicitly. It will be implicitly called by the `sendmail()` when necessary.

ehlo(*[hostname]*)

Identify yourself to an ESMTP server using 'EHLO'. The *hostname* argument defaults to the fully qualified domain name of the local host. Examine the response for ESMTP option and store them for use by `has_option()`.

Unless you wish to use `has_option()` before sending mail, it should not be necessary to call this method explicitly. It will be implicitly called by `sendmail()` when necessary.

has_extn(*name*)

Return 1 if *name* is in the set of SMTP service extensions returned by the server, 0 otherwise. Case is ignored.

verify(*address*)

Check the validity of an address on this server using SMTP 'VRFY'. Returns a tuple consisting of code 250 and a full RFC 822 address (including human name) if the user address is valid. Otherwise returns an SMTP error code of 400 or greater and an error string.

Note: many sites disable SMTP 'VRFY' in order to foil spammers.

sendmail(*from_addr, to_addrs, msg*[, *mail_options, rcpt_options*])

Send mail. The required arguments are an RFC 822 from-address string, a list of RFC 822 to-address strings, and a message string. The caller may pass a list of ESMTP options (such as '8bitmime') to be used in 'MAIL FROM' commands as *mail_options*. ESMTP options (such as 'DSN' commands) that should be used with all 'RCPT' commands can be passed as *rcpt_options*. (If you need to use different ESMTP options to different recipients you have to use the low-level methods such as `mail`, `rcpt` and `data` to send the message.)

Note: The *from_addr* and *to_addrs* parameters are used to construct the message envelope used by the transport agents. The SMTP does not modify the message headers in any way.

If there has been no previous 'EHLO' or 'HELO' command this session, this method tries ESMTP 'EHLO' first. If the server does ESMTP, message size and each of the specified options will be passed to it (if the option is in the feature set the server advertises). If 'EHLO' fails, 'HELO' will be tried and ESMTP options suppressed.

This method will return normally if the mail is accepted for at least one recipient. Otherwise it will throw an exception. That is, if this method does not throw an exception, then someone should get your mail. If this method does not throw an exception, it returns a dictionary, with one entry for each recipient that was refused. Each entry contains a tuple of the SMTP error code and the accompanying error message sent by the server.

This method may raise the following exceptions:

SMTPRecipientsRefusedAll recipients were refused. Nobody got the mail. The `recipients` attribute of the exception object is a dictionary with information about the refused recipients (like the one returned when at least one recipient was accepted).

SMTPHelloErrorThe server didn't reply properly to the 'HELO' greeting.

SMTPSenderRefusedThe server didn't accept the *from_addr*.

SMTPDataErrorThe server replied with an unexpected error code (other than a refusal of a recipient).

Unless otherwise noted, the connection will be open even after an exception is raised.

quit()

Terminate the SMTP session and close the connection.

Low-level methods corresponding to the standard SMTP/ESMTP commands ‘HELP’, ‘RSET’, ‘NOOP’, ‘MAIL’, ‘RCPT’, and ‘DATA’ are also supported. Normally these do not need to be called directly, so they are not documented here. For details, consult the module code.

11.9.2 SMTP Example

This example prompts the user for addresses needed in the message envelope (‘To’ and ‘From’ addresses), and the message to be delivered. Note that the headers to be included with the message must be included in the message as entered; this example doesn’t do any processing of the RFC 822 headers. In particular, the ‘To’ and ‘From’ addresses must be included in the message headers explicitly.

```
import smtplib
import string

def prompt(prompt):
    return string.strip(raw_input(prompt))

fromaddr = prompt("From: ")
toaddrs = string.split(prompt("To: "))
print "Enter message, end with ^D:"

# Add the From: and To: headers at the start!
msg = ("From: %s\r\nTo: %s\r\n\r\n"
       % (fromaddr, string.join(toaddrs, ", ")))
while 1:
    line = raw_input()
    if not line:
        break
    msg = msg + line

print "Message length is " + `len(msg)`

server = smtplib.SMTP('localhost')
server.set_debuglevel(1)
server.sendmail(fromaddr, toaddrs, msg)
server.quit()
```

11.10 telnetlib — Telnet client

The `telnetlib` module provides a `Telnet` class that implements the Telnet protocol. See RFC 854 for details about the protocol.

Telnet(*[host*, *port*])

`Telnet` represents a connection to a telnet server. The instance is initially not connected by default; the `open()` method must be used to establish a connection. Alternatively, the host name and optional port number can be passed to the constructor, `to`, in which case the connection to the server will be established before the constructor returns.

Do not reopen an already connected instance.

This class has many `read_*()` methods. Note that some of them raise `EOFError` when the end of the connection is read, because they can return an empty string for other reasons. See the individual descriptions below.

See Also:

RFC 854, “*Telnet Protocol Specification*”
Definition of the Telnet protocol.

11.10.1 Telnet Objects

Telnet instances have the following methods:

read_until(*expected*[, *timeout*])

Read until a given string is encountered or until timeout.

When no match is found, return whatever is available instead, possibly the empty string. Raise `EOFError` if the connection is closed and no cooked data is available.

read_all()

Read all data until EOF; block until connection closed.

read_some()

Read at least one byte of cooked data unless EOF is hit. Return '' if EOF is hit. Block if no data is immediately available.

read_very_eager()

Read everything that can be without blocking in I/O (eager).

Raise `EOFError` if connection closed and no cooked data available. Return '' if no cooked data available otherwise. Do not block unless in the midst of an IAC sequence.

read_eager()

Read readily available data.

Raise `EOFError` if connection closed and no cooked data available. Return '' if no cooked data available otherwise. Do not block unless in the midst of an IAC sequence.

read_lazy()

Process and return data already in the queues (lazy).

Raise `EOFError` if connection closed and no data available. Return '' if no cooked data available otherwise. Do not block unless in the midst of an IAC sequence.

read_very_lazy()

Return any data available in the cooked queue (very lazy).

Raise `EOFError` if connection closed and no data available. Return '' if no cooked data available otherwise. This method never blocks.

open(*host*[, *port*])

Connect to a host. The optional second argument is the port number, which defaults to the standard telnet port (23).

Do not try to reopen an already connected instance.

msg(*msg*[, **args*])

Print a debug message when the debug level is > 0. If extra arguments are present, they are substituted in the message using the standard string formatting operator.

set_debuglevel(*debuglevel*)

Set the debug level. The higher the value of *debuglevel*, the more debug output you get (on `sys.stdout`).

close()
Close the connection.

get_socket()
Return the socket object used internally.

fileno()
Return the file descriptor of the socket object used internally.

write(*buffer*)
Write a string to the socket, doubling any IAC characters. This can block if the connection is blocked. May raise `socket.error` if the connection is closed.

interact()
Interaction function, emulates a very dumb telnet client.

mt_interact()
Multithreaded version of `interact()`.

expect(*list*[, *timeout*])
Read until one from a list of a regular expressions matches.
The first argument is a list of regular expressions, either compiled (`re.RegexObject` instances) or uncompiled (strings). The optional second argument is a timeout, in seconds; the default is to block indefinitely.
Return a tuple of three items: the index in the list of the first regular expression that matches; the match object returned; and the text read up till and including the match.
If end of file is found and no text was read, raise `EOFError`. Otherwise, when nothing matches, return `(-1, None, text)` where `text` is the text received so far (may be the empty string if a timeout happened).
If a regular expression ends with a greedy match (e.g. `[. *]`) or if more than one expression can match the same input, the results are undeterministic, and may depend on the I/O timing.

11.10.2 Telnet Example

A simple example illustrating typical use:

```
import getpass
import sys
import telnetlib

HOST = "localhost"
user = raw_input("Enter your remote account: ")
password = getpass.getpass()

tn = telnetlib.Telnet(HOST)

tn.read_until("login: ")
tn.write(user + "\n")
if password:
    tn.read_until("Password: ")
    tn.write(password + "\n")

tn.write("ls\n")
tn.write("exit\n")

print tn.read_all()
```

11.11 `urlparse` — Parse URLs into components.

This module defines a standard interface to break URL strings up in components (addressing scheme, network location, path etc.), to combine the components back into a URL string, and to convert a “relative URL” to an absolute URL given a “base URL.”

The module has been designed to match the Internet RFC on Relative Uniform Resource Locators (and discovered a bug in an earlier draft!). Refer to RFC 1808 for details on relative URLs and RFC 1738 for information on basic URL syntax.

It defines the following functions:

`urlparse`(*urlstring*[, *default_scheme*[, *allow_fragments*]])

Parse a URL into 6 components, returning a 6-tuple: (addressing scheme, network location, path, parameters, query, fragment identifier). This corresponds to the general structure of a URL: *scheme://netloc/path;parameters?query#fragment*. Each tuple item is a string, possibly empty. The components are not broken up in smaller parts (e.g. the network location is a single string), and % escapes are not expanded. The delimiters as shown above are not part of the tuple items, except for a leading slash in the *path* component, which is retained if present.

Example:

```
urlparse('http://www.cwi.nl:80/%7Eguido/Python.html')
```

yields the tuple

```
('http', 'www.cwi.nl:80', '/%7Eguido/Python.html', '', '', '')
```

If the *default_scheme* argument is specified, it gives the default addressing scheme, to be used only if the URL string does not specify one. The default value for this argument is the empty string.

If the *allow_fragments* argument is zero, fragment identifiers are not allowed, even if the URL’s addressing scheme normally does support them. The default value for this argument is 1.

`urlunparse`(*tuple*)

Construct a URL string from a tuple as returned by `urlparse()`. This may result in a slightly different, but equivalent URL, if the URL that was parsed originally had redundant delimiters, e.g. a ? with an empty query (the draft states that these are equivalent).

`urljoin`(*base*, *url*[, *allow_fragments*])

Construct a full (“absolute”) URL by combining a “base URL” (*base*) with a “relative URL” (*url*). Informally, this uses components of the base URL, in particular the addressing scheme, the network location and (part of) the path, to provide missing components in the relative URL.

Example:

```
urljoin('http://www.cwi.nl/%7Eguido/Python.html', 'FAQ.html')
```

yields the string

```
'http://www.cwi.nl/%7Eguido/FAQ.html'
```

The *allow_fragments* argument has the same meaning as for `urlparse()`.

11.12 `SocketServer` — A framework for network servers.

The `SocketServer` module simplifies the task of writing network servers.

There are four basic server classes: `TCPServer` uses the Internet TCP protocol, which provides for continuous streams of data between the client and server. `UDPServer` uses datagrams, which are discrete packets of information that may arrive out of order or be lost while in transit. The more infrequently used `UnixStreamServer` and `UnixDatagramServer` classes are similar, but use UNIX domain sockets; they're not available on non-UNIX platforms. For more details on network programming, consult a book such as W. Richard Steven's *UNIX Network Programming* or Ralph Davis's *Win32 Network Programming*.

These four classes process requests *synchronously*; each request must be completed before the next request can be started. This isn't suitable if each request takes a long time to complete, because it requires a lot of computation, or because it returns a lot of data which the client is slow to process. The solution is to create a separate process or thread to handle each request; the `ForkingMixin` and `ThreadingMixin` mix-in classes can be used to support asynchronous behaviour.

Creating a server requires several steps. First, you must create a request handler class by subclassing the `BaseRequestHandler` class and overriding its `handle()` method; this method will process incoming requests. Second, you must instantiate one of the server classes, passing it the server's address and the request handler class. Finally, call the `handle_request()` or `serve_forever()` method of the server object to process one or many requests.

Server classes have the same external methods and attributes, no matter what network protocol they use:

`fileno()`

Return an integer file descriptor for the socket on which the server is listening. This function is most commonly passed to `select.select()`, to allow monitoring multiple servers in the same process.

`handle_request()`

Process a single request. This function calls the following methods in order: `get_request()`, `verify_request()`, and `process_request()`. If the user-provided `handle()` method of the handler class raises an exception, the server's `handle_error()` method will be called.

`serve_forever()`

Handle an infinite number of requests. This simply calls `handle_request()` inside an infinite loop.

`address_family`

The family of protocols to which the server's socket belongs. `socket.AF_INET` and `socket.AF_UNIX` are two possible values.

`RequestHandlerClass`

The user-provided request handler class; an instance of this class is created for each request.

`server_address`

The address on which the server is listening. The format of addresses varies depending on the protocol family; see the documentation for the `socket` module for details. For Internet protocols, this is a tuple containing a string giving the address, and an integer port number: `('127.0.0.1', 80)`, for example.

`socket`

The socket object on which the server will listen for incoming requests.

The server classes support the following class variables:

`request_queue_size`

The size of the request queue. If it takes a long time to process a single request, any requests that arrive while the server is busy are placed into a queue, up to `request_queue_size` requests. Once the queue is full, further requests from clients will get a "Connection denied" error. The default value is usually 5, but this can be overridden by subclasses.

`socket_type`

The type of socket used by the server; `socket.SOCK_STREAM` and `socket.SOCK_DGRAM` are two possible values.

There are various server methods that can be overridden by subclasses of base server classes like `TCPServer`; these

methods aren't useful to external users of the server object.

finish_request()

Actually processes the request by instantiating `RequestHandlerClass` and calling its `handle()` method.

get_request()

Must accept a request from the socket, and return a 2-tuple containing the *new* socket object to be used to communicate with the client, and the client's address.

handle_error(request, client_address)

This function is called if the `RequestHandlerClass`'s `handle()` method raises an exception. The default action is to print the traceback to standard output and continue handling further requests.

process_request(request, client_address)

Calls `finish_request()` to create an instance of the `RequestHandlerClass`. If desired, this function can create a new process or thread to handle the request; the `ForkingMixIn` and `ThreadingMixIn` classes do this.

server_activate()

Called by the server's constructor to activate the server. May be overridden.

server_bind()

Called by the server's constructor to bind the socket to the desired address. May be overridden.

verify_request(request, client_address)

Must return a Boolean value; if the value is true, the request will be processed, and if it's false, the request will be denied. This function can be overridden to implement access controls for a server. The default implementation always return true.

The request handler class must define a new `handle()` method, and can override any of the following methods. A new instance is created for each request.

finish()

Called after the `handle()` method to perform any clean-up actions required. The default implementation does nothing. If `setup()` or `handle()` raise an exception, this function will not be called.

handle()

This function must do all the work required to service a request. Several instance attributes are available to it; the request is available as `self.request`; the client address as `self.client_address`; and the server instance as `self.server`, in case it needs access to per-server information.

The type of `self.request` is different for datagram or stream services. For stream services, `self.request` is a socket object; for datagram services, `self.request` is a string. However, this can be hidden by using the mix-in request handler classes `StreamRequestHandler` or `DatagramRequestHandler`, which override the `setup()` and `finish()` methods, and provides `self.rfile` and `self.wfile` attributes. `self.rfile` and `self.wfile` can be read or written, respectively, to get the request data or return data to the client.

setup()

Called before the `handle()` method to perform any initialization actions required. The default implementation does nothing.

11.13 BaseHTTPServer — Basic HTTP server.

This module defines two classes for implementing HTTP servers (web servers). Usually, this module isn't used directly, but is used as a basis for building functioning web servers. See the `SimpleHTTPServer` and `CGI-HTTPServer` modules.

The first class, `HTTPServer`, is a `SocketServer.TCPServer` subclass. It creates and listens at the web socket,

dispatching the requests to a handler. Code to create and run the server looks like this:

```
def run(server_class=BaseHTTPServer.HTTPServer,
        handler_class=BaseHTTPServer.BaseHTTPRequestHandler):
    server_address = ('', 8000)
    httpd = server_class(server_address, handler_class)
    httpd.serve_forever()
```

HTTPServer (*server_address, RequestHandlerClass*)

This class builds on the `TCPServer` class by storing the server address as instance variables named `server_name` and `server_port`. The server is accessible by the handler, typically through the handler's server instance variable.

BaseHTTPRequestHandler (*request, client_address, server*)

This class is used to handle the HTTP requests that arrive at the server. By itself, it cannot respond to any actual HTTP requests; it must be subclassed to handle each request method (e.g. GET or POST). `BaseHTTPRequestHandler` provides a number of class and instance variables, and methods for use by subclasses.

The handler will parse the request and the headers, then call a method specific to the request type. The method name is constructed from the request. For example, for the request method 'SPAM', the `do_SPAM()` method will be called with no arguments. All of the relevant information is stored in instance variables of the handler. Subclasses should not need to override or extend the `__init__()` method.

`BaseHTTPRequestHandler` has the following instance variables:

client_address

Contains a tuple of the form (*host, port*) referring to the client's address.

command

Contains the command (request type). For example, 'GET'.

path

Contains the request path.

request_version

Contains the version string from the request. For example, 'HTTP/1.0'.

headers

Holds an instance of the class specified by the `MessageClass` class variable. This instance parses and manages the headers in the HTTP request.

rfile

Contains an input stream, positioned at the start of the optional input data.

wfile

Contains the output stream for writing a response back to the client. Proper adherence to the HTTP protocol must be used when writing to this stream.

`BaseHTTPRequestHandler` has the following class variables:

server_version

Specifies the server software version. You may want to override this. The format is multiple whitespace-separated strings, where each string is of the form `name[/version]`. For example, 'BaseHTTP/0.2'.

sys_version

Contains the Python system version, in a form usable by the `version_string` method and the `server_version` class variable. For example, 'Python/1.4'.

error_message_format

Specifies a format string for building an error response to the client. It uses parenthesized, keyed format specifiers, so the format operand must be a dictionary. The `code` key should be an integer, specifying the numeric

HTTP error code value. *message* should be a string containing a (detailed) error message of what occurred, and *explain* should be an explanation of the error code number. Default *message* and *explain* values can found in the *responses* class variable.

protocol_version

This specifies the HTTP protocol version used in responses. Typically, this should not be overridden. Defaults to 'HTTP/1.0'.

MessageClass

Specifies a `rfc822.Message`-like class to parse HTTP headers. Typically, this is not overridden, and it defaults to `mimetools.Message`.

responses

This variable contains a mapping of error code integers to two-element tuples containing a short and long message. For example, `{code: (shortmessage, longmessage)}`. The *shortmessage* is usually used as the *message* key in an error response, and *longmessage* as the *explain* key (see the `error_message_format` class variable).

A `BaseHTTPRequestHandler` instance has the following methods:

handle()

Overrides the superclass' `handle()` method to provide the specific handler behavior. This method will parse and dispatch the request to the appropriate `do_*()` method.

send_error(*code*[, *message*])

Sends and logs a complete error reply to the client. The numeric *code* specifies the HTTP error code, with *message* as optional, more specific text. A complete set of headers is sent, followed by text composed using the `error_message_format` class variable.

send_response(*code*[, *message*])

Sends a response header and logs the accepted request. The HTTP response line is sent, followed by *Server* and *Date* headers. The values for these two headers are picked up from the `version_string()` and `date_time_string()` methods, respectively.

send_header(*keyword*, *value*)

Writes a specific MIME header to the output stream. *keyword* should specify the header keyword, with *value* specifying its value.

end_headers()

Sends a blank line, indicating the end of the MIME headers in the response.

log_request([*code*[, *size*]])

Logs an accepted (successful) request. *code* should specify the numeric HTTP code associated with the response. If a size of the response is available, then it should be passed as the *size* parameter.

log_error(...)

Logs an error when a request cannot be fulfilled. By default, it passes the message to `log_message()`, so it takes the same arguments (*format* and additional values).

log_message(*format*, ...)

Logs an arbitrary message to `sys.stderr`. This is typically overridden to create custom error logging mechanisms. The *format* argument is a standard `printf`-style format string, where the additional arguments to `log_message()` are applied as inputs to the formatting. The client address and current date and time are prefixed to every message logged.

version_string()

Returns the server software's version string. This is a combination of the `server_version` and `sys_version` class variables.

date_time_string()

Returns the current date and time, formatted for a message header.

log_data_time_string()

Returns the current date and time, formatted for logging.

address_string()

Returns the client address, formatted for logging. A name lookup is performed on the client's IP address.

See Also:

[Module CGIHTTPServer](#) (section 11.15):

Extended request handler that supports CGI scripts.

[Module SimpleHTTPServer](#) (section 11.14):

Basic request handler that limits response to files actually under the document root.

11.14 SimpleHTTPServer — A Do-Something Request Handler

The `SimpleHTTPServer` module defines a request-handler class, interface compatible with `BaseHTTPServer.BaseHTTPRequestHandler` which serves files only from a base directory.

The `SimpleHTTPServer` module defines the following class:

SimpleHTTPRequestHandler (*request, client_address, server*)

This class is used, to serve files from current directory and below, directly mapping the directory structure to HTTP requests.

A lot of the work is done by the base class `BaseHTTPServer.BaseHTTPRequestHandler`, such as parsing the request. This class implements the `do_GET()` and `do_HEAD()` functions.

The `SimpleHTTPRequestHandler` defines the following member variables:

server_version

This will be `"SimpleHTTP/" + __version__`, where `__version__` is defined in the module.

extensions_map

A dictionary mapping suffixes into MIME types. Default is signified by an empty string, and is considered to be `text/plain`. The mapping is used case-insensitively, and so should contain only lower-cased keys.

The `SimpleHTTPRequestHandler` defines the following methods:

do_HEAD()

This method serves the 'HEAD' request type: it sends the headers it would send for the equivalent GET request. See the `do_GET()` method for more complete explanation of the possible headers.

do_GET()

The request is mapped to a local file by interpreting the request as a path relative to the current working directory.

If the request was mapped to a directory, a 403 respond is output, followed by the explanation 'Directory listing not supported'. Any `IOError` exception in opening the requested file, is mapped to a 404, 'File not found' error. Otherwise, the content type is guessed using the `extensions_map` variable.

A 'Content-type:' with the guessed content type is output, and then a blank line, signifying end of headers, and then the contents of the file. The file is always opened in binary mode.

For example usage, see the implementation of the `test()` function.

See Also:

[Module BaseHTTPServer](#) (section 11.13):

Base class implementation for Web server and request handler.

11.15 CGIHTTPServer — A Do-Something Request Handler

The `CGIHTTPServer` module defines a request-handler class, interface compatible with `BaseHTTPServer.BaseHTTPRequestHandler` and inherits behaviour from `SimpleHTTPServer.SimpleHTTPRequestHandler` but can also run CGI scripts.

Note: This module is UNIX dependent since it creates the CGI process using `os.fork()` and `os.exec()`.

The `CGIHTTPServer` module defines the following class:

CGIHTTPRequestHandler (*request, client_address, server*)

This class is used to serve either files or output of CGI scripts from the current directory and below. Note that mapping HTTP hierarchic structure to local directory structure is exactly as in `SimpleHTTPServer.SimpleHTTPRequestHandler`.

The class will however, run the CGI script, instead of serving it as a file, if it guesses it to be a CGI script. Only directory-based CGI are used — the other common server configuration is to treat special extensions as denoting CGI scripts.

The `do_GET()` and `do_HEAD()` functions are modified to run CGI scripts and serve the output, instead of serving files, if the request leads to somewhere below the `cgi_directories` path.

The `CGIHTTPRequestHandler` defines the following data member:

cgi_directories

This defaults to `['/cgi-bin', '/htbin']` and describes directories to treat as containing CGI scripts.

The `CGIHTTPRequestHandler` defines the following methods:

do_POST()

This method serves the 'POST' request type, only allowed for CGI scripts. Error 501, "Can only POST to CGI scripts", is output when trying to POST to a non-CGI url.

Note that CGI scripts will be run with UID of user nobody, for security reasons. Problems with the CGI script will be translated to error 403.

For example usage, see the implementation of the `test()` function.

See Also:

[Module BaseHTTPServer](#) (section 11.13):

Base class implementation for Web server and request handler.

11.16 `asyncore` — Asynchronous socket handler

This module provides the basic infrastructure for writing asynchronous socket service clients and servers.

There are only two ways to have a program on a single processor do "more than one thing at a time." Multi-threaded programming is the simplest and most popular way to do it, but there is another very different technique, that lets you have nearly all the advantages of multi-threading, without actually using multiple threads. It's really only practical if your program is largely I/O bound. If your program is CPU bound, then pre-emptive scheduled threads are probably what you really need. Network servers are rarely CPU-bound, however.

If your operating system supports the `select()` system call in its I/O library (and nearly all do), then you can use it to juggle multiple communication channels at once; doing other work while your I/O is taking place in the "background." Although this strategy can seem strange and complex, especially at first, it is in many ways easier to understand and control than multi-threaded programming. The module documented here solves many of the difficult problems for you, making the task of building sophisticated high-performance network servers and clients a snap.

dispatcher()

The first class we will introduce is the `dispatcher` class. This is a thin wrapper around a low-level socket

object. To make it more useful, it has a few methods for event-handling on it. Otherwise, it can be treated as a normal non-blocking socket object.

The direct interface between the select loop and the socket object are the `handle_read_event()` and `handle_write_event()` methods. These are called whenever an object ‘fires’ that event.

The firing of these low-level events can tell us whether certain higher-level events have taken place, depending on the timing and the state of the connection. For example, if we have asked for a socket to connect to another host, we know that the connection has been made when the socket fires a write event (at this point you know that you may write to it with the expectation of success). The implied higher-level events are:

Event	Description
<code>handle_connect()</code>	Implied by a write event
<code>handle_close()</code>	Implied by a read event with no data available
<code>handle_accept()</code>	Implied by a read event on a listening socket

This set of user-level events is larger than the basics. The full set of methods that can be overridden in your subclass are:

handle_read()

Called when there is new data to be read from a socket.

handle_write()

Called when there is an attempt to write data to the object. Often this method will implement the necessary buffering for performance. For example:

```
def handle_write(self):
    sent = self.send(self.buffer)
    self.buffer = self.buffer[sent:]
```

handle_expt()

Called when there is out of band (OOB) data for a socket connection. This will almost never happen, as OOB is tenuously supported and rarely used.

handle_connect()

Called when the socket actually makes a connection. This might be used to send a “welcome” banner, or something similar.

handle_close()

Called when the socket is closed.

handle_accept()

Called on listening sockets when they actually accept a new connection.

readable()

Each time through the `select()` loop, the set of sockets is scanned, and this method is called to see if there is any interest in reading. The default method simply returns 1, indicating that by default, all channels will be interested.

writable()

Each time through the `select()` loop, the set of sockets is scanned, and this method is called to see if there is any interest in writing. The default method simply returns 1, indicating that by default, all channels will be interested.

In addition, there are the basic methods needed to construct and manipulate “channels,” which are what we will call the socket connections in this context. Note that most of these are nearly identical to their socket partners.

create_socket(family, type)

This is identical to the creation of a normal socket, and will use the same options for creation. Refer to the [socket](#) documentation for information on creating sockets.

connect(address)

As with the normal socket object, *address* is a tuple with the first element the host to connect to, and the second the port.

send(*data*)

Send *data* out the socket.

recv(*buffer_size*)

Read at most *buffer_size* bytes from the socket.

listen([*backlog*])

Listen for connections made to the socket. The *backlog* argument specifies the maximum number of queued connections and should be at least 1; the maximum value is system-dependent (usually 5).

bind(*address*)

Bind the socket to *address*. The socket must not already be bound. (The format of *address* depends on the address family — see above.)

accept()

Accept a connection. The socket must be bound to an address and listening for connections. The return value is a pair (*conn*, *address*) where *conn* is a *new* socket object usable to send and receive data on the connection, and *address* is the address bound to the socket on the other end of the connection.

close()

Close the socket. All future operations on the socket object will fail. The remote end will receive no more data (after queued data is flushed). Sockets are automatically closed when they are garbage-collected.

11.16.1 Example basic HTTP client

As a basic example, below is a very basic HTTP client that uses the `dispatcher` class to implement its socket handling:

```
class http_client(asyncore.dispatcher):
    def __init__(self, host,path):
        asyncore.dispatcher.__init__(self)
        self.path = path
        self.create_socket(socket.AF_INET, socket.SOCK_STREAM)
        self.connect( (host, 80) )
        self.buffer = 'GET %s HTTP/1.0\r\n\r\n' % self.path

    def handle_connect(self):
        pass

    def handle_read(self):
        data = self.recv(8192)
        print data

    def writeable(self):
        return (len(self.buffer) > 0)

    def handle_write(self):
        sent = self.send(self.buffer)
        self.buffer = self.buffer[sent:]
```


Internet Data Handling

This chapter describes modules which support handling data formats commonly used on the internet. Some, like SGML and XML, may be useful for other applications as well.

<code>sgmlib</code>	Only as much of an SGML parser as needed to parse HTML.
<code>htmlib</code>	A parser for HTML documents.
<code>htmlentitydefs</code>	Definitions of HTML general entities.
<code>xmllib</code>	A parser for XML documents.
<code>formatter</code>	Generic output formatter and device interface.
<code>rfc822</code>	Parse RFC 822 style mail headers.
<code>mimertools</code>	Tools for parsing MIME-style message bodies.
<code>MimeWriter</code>	Generic MIME file writer.
<code>multifile</code>	Support for reading files which contain distinct parts, such as some MIME data.
<code>binhex</code>	Encode and decode files in binhex4 format.
<code>uu</code>	Encode and decode files in uuencode format.
<code>binascii</code>	Tools for converting between binary and various ASCII-encoded binary representations.
<code>xdrlib</code>	Encoders and decoders for the External Data Representation (XDR).
<code>mailcap</code>	Mailcap file handling.
<code>mimetypes</code>	Mapping of filename extensions to MIME types.
<code>base64</code>	Encode and decode files using the MIME base64 data.
<code>quopri</code>	Encode and decode files using the MIME quoted-printable encoding.
<code>mailbox</code>	Read various mailbox formats.
<code>mhlib</code>	Manipulate MH mailboxes from Python.
<code>mimify</code>	Mimification and unmimification of mail messages.
<code>netrc</code>	Loading of '.netrc' files.
<code>robotparser</code>	Accepts as input a list of lines or URL that refers to a robots.txt file, parses the file, then builds a set of rules from

12.1 `sgmlib` — Simple SGML parser

This module defines a class `SGMLParser` which serves as the basis for parsing text files formatted in SGML (Standard Generalized Mark-up Language). In fact, it does not provide a full SGML parser — it only parses SGML insofar as it is used by HTML, and the module only exists as a base for the `htmlib` module.

`SGMLParser`()

The `SGMLParser` class is instantiated without arguments. The parser is hardcoded to recognize the following constructs:

- Opening and closing tags of the form '`<tag attr="value" . . . >`' and '`</tag>`', respectively.
- Numeric character references of the form '`&#name ;`'.
- Entity references of the form '`&name ;`'.

- SGML comments of the form ‘<!--text-->’. Note that spaces, tabs, and newlines are allowed between the trailing ‘>’ and the immediately preceding ‘--’.

SGMLParser instances have the following interface methods:

reset()

Reset the instance. Loses all unprocessed data. This is called implicitly at instantiation time.

setnomoretags()

Stop processing tags. Treat all following input as literal input (CDATA). (This is only provided so the HTML tag <PLAINTEXT> can be implemented.)

setliteral()

Enter literal mode (CDATA mode).

feed(data)

Feed some text to the parser. It is processed insofar as it consists of complete elements; incomplete data is buffered until more data is fed or `close()` is called.

close()

Force processing of all buffered data as if it were followed by an end-of-file mark. This method may be redefined by a derived class to define additional processing at the end of the input, but the redefined version should always call `close()`.

handle_starttag(tag, method, attributes)

This method is called to handle start tags for which either a `start_tag()` or `do_tag()` method has been defined. The *tag* argument is the name of the tag converted to lower case, and the *method* argument is the bound method which should be used to support semantic interpretation of the start tag. The *attributes* argument is a list of (*name*, *value*) pairs containing the attributes found inside the tag’s <> brackets. The *name* has been translated to lower case and double quotes and backslashes in the *value* have been interpreted. For instance, for the tag , this method would be called as ‘unknown_starttag('a', [(‘href’, ‘http://www.cwi.nl/’)])’. The base implementation simply calls *method* with *attributes* as the only argument.

handle_endtag(tag, method)

This method is called to handle endtags for which an `end_tag()` method has been defined. The *tag* argument is the name of the tag converted to lower case, and the *method* argument is the bound method which should be used to support semantic interpretation of the end tag. If no `end_tag()` method is defined for the closing element, this handler is not called. The base implementation simply calls *method*.

handle_data(data)

This method is called to process arbitrary data. It is intended to be overridden by a derived class; the base class implementation does nothing.

handle_charref(ref)

This method is called to process a character reference of the form ‘&#ref;’. In the base implementation, *ref* must be a decimal number in the range 0-255. It translates the character to ASCII and calls the method `handle_data()` with the character as argument. If *ref* is invalid or out of range, the method `unknown_charref(ref)` is called to handle the error. A subclass must override this method to provide support for named character entities.

handle_entityref(ref)

This method is called to process a general entity reference of the form ‘&ref;’ where *ref* is an general entity reference. It looks for *ref* in the instance (or class) variable `entitydefs` which should be a mapping from entity names to corresponding translations. If a translation is found, it calls the method `handle_data()` with the translation; otherwise, it calls the method `unknown_entityref(ref)`. The default `entitydefs` defines translations for `&`, `'`, `>`, `<`, and `"`.

handle_comment(comment)

This method is called when a comment is encountered. The *comment* argument is a string containing the text

between the ‘<!--’ and ‘-->’ delimiters, but not the delimiters themselves. For example, the comment ‘<!--text-->’ will cause this method to be called with the argument ‘text’. The default method does nothing.

report_unbalanced(*tag*)

This method is called when an end tag is found which does not correspond to any open element.

unknown_starttag(*tag*, *attributes*)

This method is called to process an unknown start tag. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_endtag(*tag*)

This method is called to process an unknown end tag. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_charref(*ref*)

This method is called to process unresolvable numeric character references. Refer to `handle_charref()` to determine what is handled by default. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_entityref(*ref*)

This method is called to process an unknown entity reference. It is intended to be overridden by a derived class; the base class implementation does nothing.

Apart from overriding or extending the methods listed above, derived classes may also define methods of the following form to define processing of specific tags. Tag names in the input stream are case independent; the *tag* occurring in method names must be in lower case:

start_tag(*attributes*)

This method is called to process an opening tag *tag*. It has preference over `do_tag()`. The *attributes* argument has the same meaning as described for `handle_starttag()` above.

do_tag(*attributes*)

This method is called to process an opening tag *tag* that does not come with a matching closing tag. The *attributes* argument has the same meaning as described for `handle_starttag()` above.

end_tag()

This method is called to process a closing tag *tag*.

Note that the parser maintains a stack of open elements for which no end tag has been found yet. Only tags processed by `start_tag()` are pushed on this stack. Definition of an `end_tag()` method is optional for these tags. For tags processed by `do_tag()` or by `unknown_tag()`, no `end_tag()` method must be defined; if defined, it will not be used. If both `start_tag()` and `do_tag()` methods exist for a tag, the `start_tag()` method takes precedence.

12.2 `htmllib` — A parser for HTML documents

This module defines a class which can serve as a base for parsing text files formatted in the HyperText Mark-up Language (HTML). The class is not directly concerned with I/O — it must be provided with input in string form via a method, and makes calls to methods of a “formatter” object in order to produce output. The `HTMLParser` class is designed to be used as a base class for other classes in order to add functionality, and allows most of its methods to be extended or overridden. In turn, this class is derived from and extends the `SGMLParser` class defined in module `sgmlib`. The `HTMLParser` implementation supports the HTML 2.0 language as described in RFC 1866. Two implementations of formatter objects are provided in the `formatter` module; refer to the documentation for that module for information on the formatter interface.

The following is a summary of the interface defined by `sgmlib.SGMLParser`:

- The interface to feed data to an instance is through the `feed()` method, which takes a string argument. This can

be called with as little or as much text at a time as desired; `p.feed(a); p.feed(b)` has the same effect as `p.feed(a+b)`. When the data contains complete HTML tags, these are processed immediately; incomplete elements are saved in a buffer. To force processing of all unprocessed data, call the `close()` method.

For example, to parse the entire contents of a file, use:

```
parser.feed(open('myfile.html').read())
parser.close()
```

- The interface to define semantics for HTML tags is very simple: derive a class and define methods called `start_tag()`, `end_tag()`, or `do_tag()`. The parser will call these at appropriate moments: `start_tag` or `do_tag()` is called when an opening tag of the form `<tag . . . >` is encountered; `end_tag()` is called when a closing tag of the form `</tag>` is encountered. If an opening tag requires a corresponding closing tag, like `<H1> . . . </H1>`, the class should define the `start_tag()` method; if a tag requires no closing tag, like `<P>`, the class should define the `do_tag()` method.

The module defines a single class:

HTMLParser (*formatter*)

This is the basic HTML parser class. It supports all entity names required by the HTML 2.0 specification (RFC 1866). It also defines handlers for all HTML 2.0 and many HTML 3.0 and 3.2 elements.

See Also:

Module [htmlentitydefs](#) (section 12.3):

Definition of replacement text for HTML 2.0 entities.

Module [sgmllib](#) (section 12.1):

Base class for HTMLParser.

12.2.1 HTMLParser Objects

In addition to tag methods, the HTMLParser class provides some additional methods and instance variables for use within tag methods.

formatter

This is the formatter instance associated with the parser.

nofill

Boolean flag which should be true when whitespace should not be collapsed, or false when it should be. In general, this should only be true when character data is to be treated as “preformatted” text, as within a `<PRE>` element. The default value is false. This affects the operation of `handle_data()` and `save_end()`.

anchor_bgn (*href, name, type*)

This method is called at the start of an anchor region. The arguments correspond to the attributes of the `<A>` tag with the same names. The default implementation maintains a list of hyperlinks (defined by the `HREF` attribute for `<A>` tags) within the document. The list of hyperlinks is available as the data attribute `anchorlist`.

anchor_end ()

This method is called at the end of an anchor region. The default implementation adds a textual footnote marker using an index into the list of hyperlinks created by `anchor_bgn()`.

handle_image (*source, alt* [, *ismap* [, *align* [, *width* [, *height*]]]])

This method is called to handle images. The default implementation simply passes the `alt` value to the `handle_data()` method.

save_bgn ()

Begins saving character data in a buffer instead of sending it to the formatter object. Retrieve the stored data via

`save_end()`. Use of the `save_bgn()` / `save_end()` pair may not be nested.

save_end()

Ends buffering character data and returns all data saved since the preceding call to `save_bgn()`. If the `nofill` flag is false, whitespace is collapsed to single spaces. A call to this method without a preceding call to `save_bgn()` will raise a `TypeError` exception.

12.3 `htmlentitydefs` — Definitions of HTML general entities

This module defines a single dictionary, `entitydefs`, which is used by the `htmllib` module to provide the `entitydefs` member of the `HTMLParser` class. The definition provided here contains all the entities defined by HTML 2.0 that can be handled using simple textual substitution in the Latin-1 character set (ISO-8859-1).

entitydefs

A dictionary mapping HTML 2.0 entity definitions to their replacement text in ISO Latin-1.

12.4 `xmllib` — A parser for XML documents

Changed in version 1.5.2.

This module defines a class `XMLParser` which serves as the basis for parsing text files formatted in XML (Extensible Markup Language).

XMLParser()

The `XMLParser` class must be instantiated without arguments.¹

This class provides the following interface methods and instance variables:

attributes

A mapping of element names to mappings. The latter mapping maps attribute names that are valid for the element to the default value of the attribute, or if there is no default to `None`. The default value is the empty dictionary. This variable is meant to be overridden, not extended since the default is shared by all instances of `XMLParser`.

elements

A mapping of element names to tuples. The tuples contain a function for handling the start and end tag respectively of the element, or `None` if the method `unknown_starttag()` or `unknown_endtag()` is to be called. The default value is the empty dictionary. This variable is meant to be overridden, not extended since the default is shared by all instances of `XMLParser`.

entitydefs

A mapping of entitynames to their values. The default value contains definitions for `'lt'`, `'gt'`, `'amp'`, `'quot'`, and `'apos'`.

reset()

Reset the instance. Loses all unprocessed data. This is called implicitly at the instantiation time.

setnomoretags()

Stop processing tags. Treat all following input as literal input (CDATA).

¹Actually, a number of keyword arguments are recognized which influence the parser to accept certain non-standard constructs. The following keyword arguments are currently recognized. The defaults for all of these is 0 (false). `accept_unquoted_attributes` (accept certain attribute values without requiring quotes), `accept_missing_endtag_name` (accept end tags that look like `</>`), `map_case` (map upper case to lower case in tags and attributes), `accept_utf8` (allow UTF-8 characters in input; this is required according to the XML standard, but Python does not as yet deal properly with these characters, so this is not the default).

setliteral()

Enter literal mode (CDATA mode). This mode is automatically exited when the close tag matching the last unclosed open tag is encountered.

feed(*data*)

Feed some text to the parser. It is processed insofar as it consists of complete tags; incomplete data is buffered until more data is fed or `close()` is called.

close()

Force processing of all buffered data as if it were followed by an end-of-file mark. This method may be redefined by a derived class to define additional processing at the end of the input, but the redefined version should always call `close()`.

translate_references(*data*)

Translate all entity and character references in *data* and return the translated string.

handle_xml(*encoding, standalone*)

This method is called when the `<?xml . . . ?>` tag is processed. The arguments are the values of the encoding and standalone attributes in the tag. Both encoding and standalone are optional. The values passed to `handle_xml()` default to `None` and the string `'no'` respectively.

handle_doctype(*tag, pubid, syslit, data*)

This method is called when the `<!DOCTYPE . . . >` tag is processed. The arguments are the name of the root element, the Formal Public Identifier (or `None` if not specified), the system identifier, and the uninterpreted contents of the internal DTD subset as a string (or `None` if not present).

handle_starttag(*tag, method, attributes*)

This method is called to handle start tags for which a start tag handler is defined in the instance variable `elements`. The *tag* argument is the name of the tag, and the *method* argument is the function (method) which should be used to support semantic interpretation of the start tag. The *attributes* argument is a dictionary of attributes, the key being the *name* and the value being the *value* of the attribute found inside the tag's `<>` brackets. Character and entity references in the *value* have been interpreted. For instance, for the start tag ``, this method would be called as `handle_starttag('A', self.elements['A'][0], {'HREF': 'http://www.cwi.nl/'})`. The base implementation simply calls *method* with *attributes* as the only argument.

handle_endtag(*tag, method*)

This method is called to handle endtags for which an end tag handler is defined in the instance variable `elements`. The *tag* argument is the name of the tag, and the *method* argument is the function (method) which should be used to support semantic interpretation of the end tag. For instance, for the endtag ``, this method would be called as `handle_endtag('A', self.elements['A'][1])`. The base implementation simply calls *method*.

handle_data(*data*)

This method is called to process arbitrary data. It is intended to be overridden by a derived class; the base class implementation does nothing.

handle_charref(*ref*)

This method is called to process a character reference of the form `'&#ref;'`. *ref* can either be a decimal number, or a hexadecimal number when preceded by an `'x'`. In the base implementation, *ref* must be a number in the range 0-255. It translates the character to ASCII and calls the method `handle_data()` with the character as argument. If *ref* is invalid or out of range, the method `unknown_charref(ref)` is called to handle the error. A subclass must override this method to provide support for character references outside of the ASCII range.

handle_comment(*comment*)

This method is called when a comment is encountered. The *comment* argument is a string containing the text between the `<!--` and `-->` delimiters, but not the delimiters themselves. For example, the comment `<!--text-->` will cause this method to be called with the argument `'text'`. The default method does nothing.

handle_cdata(*data*)

This method is called when a CDATA element is encountered. The *data* argument is a string containing the text between the `<![CDATA[` and `']>` delimiters, but not the delimiters themselves. For example, the entity `<![CDATA[text]]>` will cause this method to be called with the argument `'text'`. The default method does nothing, and is intended to be overridden.

handle_proc(*name*, *data*)

This method is called when a processing instruction (PI) is encountered. The *name* is the PI target, and the *data* argument is a string containing the text between the PI target and the closing delimiter, but not the delimiter itself. For example, the instruction `<?XML text?>` will cause this method to be called with the arguments `'XML'` and `'text'`. The default method does nothing. Note that if a document starts with `<?xml . . .?>`, `handle_xml()` is called to handle it.

handle_special(*data*)

This method is called when a declaration is encountered. The *data* argument is a string containing the text between the `<!` and `>` delimiters, but not the delimiters themselves. For example, the entity `<!ENTITY text>` will cause this method to be called with the argument `'ENTITY text'`. The default method does nothing. Note that `<!DOCTYPE . . .>` is handled separately if it is located at the start of the document.

syntax_error(*message*)

This method is called when a syntax error is encountered. The *message* is a description of what was wrong. The default method raises a `RuntimeError` exception. If this method is overridden, it is permissible for it to return. This method is only called when the error can be recovered from. Unrecoverable errors raise a `RuntimeError` without first calling `syntax_error()`.

unknown_starttag(*tag*, *attributes*)

This method is called to process an unknown start tag. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_endtag(*tag*)

This method is called to process an unknown end tag. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_charref(*ref*)

This method is called to process unresolvable numeric character references. It is intended to be overridden by a derived class; the base class implementation does nothing.

unknown_entityref(*ref*)

This method is called to process an unknown entity reference. It is intended to be overridden by a derived class; the base class implementation calls `syntax_error()` to signal an error.

See Also:

The XML specification, published by the World Wide Web Consortium (W3C), is available online at <http://www.w3.org/TR/REC-xml>. References to additional material on XML are available at <http://www.w3.org/XML/>.

The Python XML Topic Guide provides a great deal of information on using XML from Python and links to other sources of information on XML. It's located on the Web at <http://www.python.org/topics/xml/>.

The Python XML Special Interest Group is developing substantial support for processing XML from Python. See <http://www.python.org/sigs/xml-sig/> for more information.

12.4.1 XML Namespaces

This module has support for XML namespaces as defined in the XML Namespaces proposed recommendation.

Tag and attribute names that are defined in an XML namespace are handled as if the name of the tag or element consisted of the namespace (i.e. the URL that defines the namespace) followed by a space and the name of the tag or attribute. For instance, the tag `<html xmlns='http://www.w3.org/TR/REC-html40'>` is treated as if the tag name was `'http://www.w3.org/TR/REC-html40 html'`, and

the tag `<html:a href='http://frob.com'>` inside the above mentioned element is treated as if the tag name were `'http://www.w3.org/TR/REC-html40 a'` and the attribute name as if it were `'http://www.w3.org/TR/REC-html40 src'`.

An older draft of the XML Namespaces proposal is also recognized, but triggers a warning.

12.5 `formatter` — Generic output formatting

This module supports two interface definitions, each with multiple implementations. The *formatter* interface is used by the `HTMLParser` class of the `htmllib` module, and the *writer* interface is required by the `formatter` interface.

Formatter objects transform an abstract flow of formatting events into specific output events on writer objects. Formatters manage several stack structures to allow various properties of a writer object to be changed and restored; writers need not be able to handle relative changes nor any sort of “change back” operation. Specific writer properties which may be controlled via formatter objects are horizontal alignment, font, and left margin indentations. A mechanism is provided which supports providing arbitrary, non-exclusive style settings to a writer as well. Additional interfaces facilitate formatting events which are not reversible, such as paragraph separation.

Writer objects encapsulate device interfaces. Abstract devices, such as file formats, are supported as well as physical devices. The provided implementations all work with abstract devices. The interface makes available mechanisms for setting the properties which formatter objects manage and inserting data into the output.

12.5.1 The Formatter Interface

Interfaces to create formatters are dependent on the specific formatter class being instantiated. The interfaces described below are the required interfaces which all formatters must support once initialized.

One data element is defined at the module level:

AS_IS

Value which can be used in the font specification passed to the `push_font()` method described below, or as the new value to any other `push_property()` method. Pushing the `AS_IS` value allows the corresponding `pop_property()` method to be called without having to track whether the property was changed.

The following attributes are defined for formatter instance objects:

writer

The writer instance with which the formatter interacts.

end_paragraph(*blanklines*)

Close any open paragraphs and insert at least *blanklines* before the next paragraph.

add_line_break()

Add a hard line break if one does not already exist. This does not break the logical paragraph.

add_hor_rule(*args, **kw)

Insert a horizontal rule in the output. A hard break is inserted if there is data in the current paragraph, but the logical paragraph is not broken. The arguments and keywords are passed on to the writer's `send_line_break()` method.

add_flowling_data(*data*)

Provide data which should be formatted with collapsed whitespaces. Whitespace from preceeding and successive calls to `add_flowling_data()` is considered as well when the whitespace collapse is performed. The data which is passed to this method is expected to be word-wrapped by the output device. Note that any word-wrapping still must be performed by the writer object due to the need to rely on device and font information.

add_literal_data(*data*)

Provide data which should be passed to the writer unchanged. Whitespace, including newline and tab characters,

are considered legal in the value of *data*.

add_label_data(*format, counter*)

Insert a label which should be placed to the left of the current left margin. This should be used for constructing bulleted or numbered lists. If the *format* value is a string, it is interpreted as a format specification for *counter*, which should be an integer. The result of this formatting becomes the value of the label; if *format* is not a string it is used as the label value directly. The label value is passed as the only argument to the writer's `send_label_data()` method. Interpretation of non-string label values is dependent on the associated writer.

Format specifications are strings which, in combination with a counter value, are used to compute label values. Each character in the format string is copied to the label value, with some characters recognized to indicate a transform on the counter value. Specifically, the character '1' represents the counter value formatter as an arabic number, the characters 'A' and 'a' represent alphabetic representations of the counter value in upper and lower case, respectively, and 'I' and 'i' represent the counter value in Roman numerals, in upper and lower case. Note that the alphabetic and roman transforms require that the counter value be greater than zero.

flush_softspace()

Send any pending whitespace buffered from a previous call to `add_flowring_data()` to the associated writer object. This should be called before any direct manipulation of the writer object.

push_alignment(*align*)

Push a new alignment setting onto the alignment stack. This may be `AS_IS` if no change is desired. If the alignment value is changed from the previous setting, the writer's `new_alignment()` method is called with the *align* value.

pop_alignment()

Restore the previous alignment.

push_font((*size, italic, bold, teletype*))

Change some or all font properties of the writer object. Properties which are not set to `AS_IS` are set to the values passed in while others are maintained at their current settings. The writer's `new_font()` method is called with the fully resolved font specification.

pop_font()

Restore the previous font.

push_margin(*margin*)

Increase the number of left margin indentations by one, associating the logical tag *margin* with the new indentation. The initial margin level is 0. Changed values of the logical tag must be true values; false values other than `AS_IS` are not sufficient to change the margin.

pop_margin()

Restore the previous margin.

push_style(**styles*)

Push any number of arbitrary style specifications. All styles are pushed onto the styles stack in order. A tuple representing the entire stack, including `AS_IS` values, is passed to the writer's `new_styles()` method.

pop_style([*n = 1*])

Pop the last *n* style specifications passed to `push_style()`. A tuple representing the revised stack, including `AS_IS` values, is passed to the writer's `new_styles()` method.

set_spacing(*spacing*)

Set the spacing style for the writer.

assert_line_data([*flag = 1*])

Inform the formatter that data has been added to the current paragraph out-of-band. This should be used when the writer has been manipulated directly. The optional *flag* argument can be set to false if the writer manipulations produced a hard line break at the end of the output.

12.5.2 Formatter Implementations

Two implementations of formatter objects are provided by this module. Most applications may use one of these classes without modification or subclassing.

NullFormatter([*writer*])

A formatter which does nothing. If *writer* is omitted, a `NullWriter` instance is created. No methods of the writer are called by `NullFormatter` instances. Implementations should inherit from this class if implementing a writer interface but don't need to inherit any implementation.

AbstractFormatter(*writer*)

The standard formatter. This implementation has demonstrated wide applicability to many writers, and may be used directly in most circumstances. It has been used to implement a full-featured world-wide web browser.

12.5.3 The Writer Interface

Interfaces to create writers are dependent on the specific writer class being instantiated. The interfaces described below are the required interfaces which all writers must support once initialized. Note that while most applications can use the `AbstractFormatter` class as a formatter, the writer must typically be provided by the application.

flush()

Flush any buffered output or device control events.

new_alignment(*align*)

Set the alignment style. The *align* value can be any object, but by convention is a string or `None`, where `None` indicates that the writer's "preferred" alignment should be used. Conventional *align* values are `'left'`, `'center'`, `'right'`, and `'justify'`.

new_font(*font*)

Set the font style. The value of *font* will be `None`, indicating that the device's default font should be used, or a tuple of the form `(size, italic, bold, teletype)`. *Size* will be a string indicating the size of font that should be used; specific strings and their interpretation must be defined by the application. The *italic*, *bold*, and *teletype* values are boolean indicators specifying which of those font attributes should be used.

new_margin(*margin, level*)

Set the margin level to the integer *level* and the logical tag to *margin*. Interpretation of the logical tag is at the writer's discretion; the only restriction on the value of the logical tag is that it not be a false value for non-zero values of *level*.

new_spacing(*spacing*)

Set the spacing style to *spacing*.

new_styles(*styles*)

Set additional styles. The *styles* value is a tuple of arbitrary values; the value `AS_IS` should be ignored. The *styles* tuple may be interpreted either as a set or as a stack depending on the requirements of the application and writer implementation.

send_line_break()

Break the current line.

send_paragraph(*blankline*)

Produce a paragraph separation of at least *blankline* blank lines, or the equivalent. The *blankline* value will be an integer. Note that the implementation will receive a call to `send_line_break()` before this call if a line break is needed; this method should not include ending the last line of the paragraph. It is only responsible for vertical spacing between paragraphs.

send_hor_rule(**args, **kw*)

Display a horizontal rule on the output device. The arguments to this method are entirely application- and writer-specific, and should be interpreted with care. The method implementation may assume that a line break

has already been issued via `send_line_break()`.

send_flow_data(*data*)

Output character data which may be word-wrapped and re-flowed as needed. Within any sequence of calls to this method, the writer may assume that spans of multiple whitespace characters have been collapsed to single space characters.

send_literal_data(*data*)

Output character data which has already been formatted for display. Generally, this should be interpreted to mean that line breaks indicated by newline characters should be preserved and no new line breaks should be introduced. The data may contain embedded newline and tab characters, unlike data provided to the `send_formatted_data()` interface.

send_label_data(*data*)

Set *data* to the left of the current left margin, if possible. The value of *data* is not restricted; treatment of non-string values is entirely application- and writer-dependent. This method will only be called at the beginning of a line.

12.5.4 Writer Implementations

Three implementations of the writer object interface are provided as examples by this module. Most applications will need to derive new writer classes from the `NullWriter` class.

NullWriter()

A writer which only provides the interface definition; no actions are taken on any methods. This should be the base class for all writers which do not need to inherit any implementation methods.

AbstractWriter()

A writer which can be used in debugging formatters, but not much else. Each method simply announces itself by printing its name and arguments on standard output.

DumbWriter([*file*[, *maxcol* = 72]])

Simple writer class which writes output on the file object passed in as *file* or, if *file* is omitted, on standard output. The output is simply word-wrapped to the number of columns specified by *maxcol*. This class is suitable for reflowing a sequence of paragraphs.

12.6 rfc822 — Parse RFC 822 mail headers

This module defines a class, `Message`, which represents a collection of “email headers” as defined by the Internet standard RFC 822. It is used in various contexts, usually to read such headers from a file. This module also defines a helper class `AddressList` for parsing RFC 822 addresses. Please refer to the RFC for information on the specific syntax of RFC 822 headers.

The `mailbox` module provides classes to read mailboxes produced by various end-user mail programs.

Message(*file*[, *seekable*])

A `Message` instance is instantiated with an input object as parameter. `Message` relies only on the input object having a `readline()` method; in particular, ordinary file objects qualify. Instantiation reads headers from the input object up to a delimiter line (normally a blank line) and stores them in the instance.

This class can work with any input object that supports a `readline()` method. If the input object has `seek` and `tell` capability, the `rewindbody()` method will work; also, illegal lines will be pushed back onto the input stream. If the input object lacks `seek` but has an `unread()` method that can push back a line of input, `Message` will use that to push back illegal lines. Thus this class can be used to parse messages coming from a buffered stream.

The optional *seekable* argument is provided as a workaround for certain stdio libraries in which `tell()` dis-

cards buffered data before discovering that the `lseek()` system call doesn't work. For maximum portability, you should set the `seekable` argument to zero to prevent that initial `tell()` when passing in an unseekable object such as a file object created from a socket object.

Input lines as read from the file may either be terminated by CR-LF or by a single linefeed; a terminating CR-LF is replaced by a single linefeed before the line is stored.

All header matching is done independent of upper or lower case; e.g. `m['From']`, `m['from']` and `m['FROM']` all yield the same result.

AddressList (*field*)

You may instantiate the `AddressList` helper class using a single string parameter, a comma-separated list of RFC 822 addresses to be parsed. (The parameter `None` yields an empty list.)

parsedate (*date*)

Attempts to parse a date according to the rules in RFC 822. However, some mailers don't follow that format as specified, so `parsedate()` tries to guess correctly in such cases. *date* is a string containing an RFC 822 date, such as `'Mon, 20 Nov 1995 19:12:08 -0500'`. If it succeeds in parsing the date, `parsedate()` returns a 9-tuple that can be passed directly to `time.mktime()`; otherwise `None` will be returned. Note that fields 6, 7, and 8 of the result tuple are not usable.

parsedate_tz (*date*)

Performs the same function as `parsedate()`, but returns either `None` or a 10-tuple; the first 9 elements make up a tuple that can be passed directly to `time.mktime()`, and the tenth is the offset of the date's timezone from UTC (which is the official term for Greenwich Mean Time). (Note that the sign of the timezone offset is the opposite of the sign of the `time.timezone` variable for the same timezone; the latter variable follows the POSIX standard while this module follows RFC 822.) If the input string has no timezone, the last element of the tuple returned is `None`. Note that fields 6, 7, and 8 of the result tuple are not usable.

mktime_tz (*tuple*)

Turn a 10-tuple as returned by `parsedate_tz()` into a UTC timestamp. If the `timezone` item in the tuple is `None`, assume local time. Minor deficiency: this first interprets the first 8 elements as a local time and then compensates for the timezone difference; this may yield a slight error around daylight savings time switch dates. Not enough to worry about for common use.

See Also:

Module [mailbox](#) (section 12.18):

Classes to read various mailbox formats produced by end-user mail programs.

12.6.1 Message Objects

A `Message` instance has the following methods:

rewindbody ()

Seek to the start of the message body. This only works if the file object is seekable.

isheader (*line*)

Returns a line's canonicalized fieldname (the dictionary key that will be used to index it) if the line is a legal RFC 822 header; otherwise returns `None` (implying that parsing should stop here and the line be pushed back on the input stream). It is sometimes useful to override this method in a subclass.

islast (*line*)

Return true if the given line is a delimiter on which `Message` should stop. The delimiter line is consumed, and the file object's read location positioned immediately after it. By default this method just checks that the line is blank, but you can override it in a subclass.

iscomment (*line*)

Return true if the given line should be ignored entirely, just skipped. By default this is a stub that always returns false, but you can override it in a subclass.

getallmatchingheaders(*name*)

Return a list of lines consisting of all headers matching *name*, if any. Each physical line, whether it is a continuation line or not, is a separate list item. Return the empty list if no header matches *name*.

getfirstmatchingheader(*name*)

Return a list of lines comprising the first header matching *name*, and its continuation line(s), if any. Return None if there is no header matching *name*.

getrawheader(*name*)

Return a single string consisting of the text after the colon in the first header matching *name*. This includes leading whitespace, the trailing linefeed, and internal linefeeds and whitespace if there any continuation line(s) were present. Return None if there is no header matching *name*.

getheader(*name*[, *default*])

Like `getrawheader(name)`, but strip leading and trailing whitespace. Internal whitespace is not stripped. The optional *default* argument can be used to specify a different default to be returned when there is no header matching *name*.

get(*name*[, *default*])

An alias for `getheader()`, to make the interface more compatible with regular dictionaries.

getaddr(*name*)

Return a pair (*full name*, *email address*) parsed from the string returned by `getheader(name)`. If no header matching *name* exists, return (None, None); otherwise both the full name and the address are (possibly empty) strings.

Example: If *m*'s first From header contains the string 'jack@cwi.nl (Jack Jansen)', then `m.getaddr('From')` will yield the pair ('Jack Jansen', 'jack@cwi.nl'). If the header contained 'Jack Jansen <jack@cwi.nl>' instead, it would yield the exact same result.

getaddrlist(*name*)

This is similar to `getaddr(list)`, but parses a header containing a list of email addresses (e.g. a To header) and returns a list of (*full name*, *email address*) pairs (even if there was only one address in the header). If there is no header matching *name*, return an empty list.

If multiple headers exist that match the named header (e.g. if there are several Cc headers), all are parsed for addresses. Any continuation lines the named headers contain are also parsed.

getdate(*name*)

Retrieve a header using `getheader()` and parse it into a 9-tuple compatible with `time.mktime()`; note that fields 6, 7, and 8 are not usable. If there is no header matching *name*, or it is unparseable, return None.

Date parsing appears to be a black art, and not all mailers adhere to the standard. While it has been tested and found correct on a large collection of email from many sources, it is still possible that this function may occasionally yield an incorrect result.

getdate_tz(*name*)

Retrieve a header using `getheader()` and parse it into a 10-tuple; the first 9 elements will make a tuple compatible with `time.mktime()`, and the 10th is a number giving the offset of the date's timezone from UTC. Note that fields 6, 7, and 8 are not usable. Similarly to `getdate()`, if there is no header matching *name*, or it is unparseable, return None.

Message instances also support a read-only mapping interface. In particular: `m[name]` is like `m.getheader(name)` but raises `KeyError` if there is no matching header; and `len(m)`, `m.has_key(name)`, `m.keys()`, `m.values()` and `m.items()` act as expected (and consistently).

Finally, Message instances have two public instance variables:

headers

A list containing the entire set of header lines, in the order in which they were read (except that `setitem` calls may disturb this order). Each line contains a trailing newline. The blank line terminating the headers is not contained in the list.

fp

The file or file-like object passed at instantiation time. This can be used to read the message content.

12.6.2 AddressList Objects

An `AddressList` instance has the following methods:

__len__(*name*)

Return the number of addresses in the address list.

__str__(*name*)

Return a canonicalized string representation of the address list. Addresses are rendered in "name" ;host@domain; form, comma-separated.

__add__(*name*)

Return an `AddressList` instance that contains all addresses in both `AddressList` operands, with duplicates removed (set union).

__sub__(*name*)

Return an `AddressList` instance that contains every address in the left-hand `AddressList` operand that is not present in the right-hand address operand (set difference).

Finally, `AddressList` instances have one public instance variable:

addresslist

A list of tuple string pairs, one per address. In each member, the first is the canonicalized name part of the address, the second is the route-address (@-separated host-domain pair).

12.7 `mimertools` — Tools for parsing MIME messages

This module defines a subclass of the `rfc822` module's `Message` class and a number of utility functions that are useful for the manipulation for MIME multipart or encoded message.

It defines the following items:

Message(*fp*[, *seekable*])

Return a new instance of the `Message` class. This is a subclass of the `rfc822.Message` class, with some additional methods (see below). The *seekable* argument has the same meaning as for `rfc822.Message`.

choose_boundary()

Return a unique string that has a high likelihood of being usable as a part boundary. The string has the form '*hostipaddr.uid.pid.timestamp.random*'.

decode(*input*, *output*, *encoding*)

Read data encoded using the allowed MIME *encoding* from open file object *input* and write the decoded data to open file object *output*. Valid values for *encoding* include 'base64', 'quoted-printable' and 'uencode'.

encode(*input*, *output*, *encoding*)

Read data from open file object *input* and write it encoded using the allowed MIME *encoding* to open file object *output*. Valid values for *encoding* are the same as for `decode`().

copyliteral(*input*, *output*)

Read lines from open file *input* until EOF and write them to open file *output*.

copybinary(*input*, *output*)

Read blocks until EOF from open file *input* and write them to open file *output*. The block size is currently fixed at 8192.

See Also:

Module `rfc822` (section 12.6):

Provides the base class for `mimertools.Message`.

Module `multifile` (section 12.9):

Support for reading files which contain distinct parts, such as MIME data.

<http://www.cs.uu.nl/wais/html/na-dir/mail/mime-faq.html>

The MIME Frequently Asked Questions document. For an overview of MIME, see the answer to question 1.1 in Part 1 of this document.

12.7.1 Additional Methods of Message objects

The `Message` class defines the following methods in addition to the `rfc822.Message` methods:

getplist()

Return the parameter list of the `content-type` header. This is a list of strings. For parameters of the form `'key=value'`, `key` is converted to lower case but `value` is not. For example, if the message contains the header `'Content-type: text/html; spam=1; Spam=2; Spam'` then `getplist()` will return the Python list `['spam=1', 'spam=2', 'Spam']`.

getparam(name)

Return the *value* of the first parameter (as returned by `getplist()` of the form `'name=value'` for the given *name*. If *value* is surrounded by quotes of the form `'<...>'` or `"..."`, these are removed.

getencoding()

Return the encoding specified in the `content-transfer-encoding` message header. If no such header exists, return `'7bit'`. The encoding is converted to lower case.

gettype()

Return the message type (of the form `'type/subtype'`) as specified in the `content-type` header. If no such header exists, return `'text/plain'`. The type is converted to lower case.

getmaintype()

Return the main type as specified in the `content-type` header. If no such header exists, return `'text'`. The main type is converted to lower case.

getsubtype()

Return the subtype as specified in the `content-type` header. If no such header exists, return `'plain'`. The subtype is converted to lower case.

12.8 MimeWriter — Generic MIME file writer

This module defines the class `MimeWriter`. The `MimeWriter` class implements a basic formatter for creating MIME multi-part files. It doesn't seek around the output file nor does it use large amounts of buffer space. You must write the parts out in the order that they should occur in the final file. `MimeWriter` does buffer the headers you add, allowing you to rearrange their order.

MimeWriter(fp)

Return a new instance of the `MimeWriter` class. The only argument passed, *fp*, is a file object to be used for writing. Note that a `StringIO` object could also be used.

12.8.1 MimeWriter Objects

`MimeWriter` instances have the following methods:

addheader(*key*, *value*[, *prefix*])

Add a header line to the MIME message. The *key* is the name of the header, where the *value* obviously provides the value of the header. The optional argument *prefix* determines where the header is inserted; '0' means append at the end, '1' is insert at the start. The default is to append.

flushheaders()

Causes all headers accumulated so far to be written out (and forgotten). This is useful if you don't need a body part at all, e.g. for a subpart of type `message/rfc822` that's (mis)used to store some header-like information.

startbody(*ctype*[, *plist*[, *prefix*]])

Returns a file-like object which can be used to write to the body of the message. The content-type is set to the provided *ctype*, and the optional parameter *plist* provides additional parameters for the content-type declaration. *prefix* functions as in `addheader()` except that the default is to insert at the start.

startmultipartbody(*subtype*[, *boundary*[, *plist*[, *prefix*]]])

Returns a file-like object which can be used to write to the body of the message. Additionally, this method initializes the multi-part code, where *subtype* provides the multipart subtype, *boundary* may provide a user-defined boundary specification, and *plist* provides optional parameters for the subtype. *prefix* functions as in `startbody()`. Subparts should be created using `nextpart()`.

nextpart()

Returns a new instance of `MimeWriter` which represents an individual part in a multipart message. This may be used to write the part as well as used for creating recursively complex multipart messages. The message must first be initialized with `startmultipartbody()` before using `nextpart()`.

lastpart()

This is used to designate the last part of a multipart message, and should *always* be used when writing multipart messages.

12.9 `MultiFile` — Support for files containing distinct parts

The `MultiFile` object enables you to treat sections of a text file as file-like input objects, with '' being returned by `readline()` when a given delimiter pattern is encountered. The defaults of this class are designed to make it useful for parsing MIME multipart messages, but by subclassing it and overriding methods it can be easily adapted for more general use.

MultiFile(*fp*[, *seekable*])

Create a multi-file. You must instantiate this class with an input object argument for the `MultiFile` instance to get lines from, such as a file object returned by `open()`.

`MultiFile` only ever looks at the input object's `readline()`, `seek()` and `tell()` methods, and the latter two are only needed if you want random access to the individual MIME parts. To use `MultiFile` on a non-seekable stream object, set the optional *seekable* argument to false; this will prevent using the input object's `seek()` and `tell()` methods.

It will be useful to know that in `MultiFile`'s view of the world, text is composed of three kinds of lines: data, section-dividers, and end-markers. `MultiFile` is designed to support parsing of messages that may have multiple nested message parts, each with its own pattern for section-divider and end-marker lines.

12.9.1 `MultiFile` Objects

A `MultiFile` instance has the following methods:

push(*str*)

Push a boundary string. When an appropriately decorated version of this boundary is found as an input line, it will be interpreted as a section-divider or end-marker. All subsequent reads will return the empty string to

indicate end-of-file, until a call to `pop()` removes the boundary a or `next()` call reenables it.

It is possible to push more than one boundary. Encountering the most-recently-pushed boundary will return EOF; encountering any other boundary will raise an error.

readline(*str*)

Read a line. If the line is data (not a section-divider or end-marker or real EOF) return it. If the line matches the most-recently-stacked boundary, return `''` and set `self.last` to 1 or 0 according as the match is or is not an end-marker. If the line matches any other stacked boundary, raise an error. On encountering end-of-file on the underlying stream object, the method raises `ERROR` unless all boundaries have been popped.

readlines(*str*)

Return all lines remaining in this part as a list of strings.

read()

Read all lines, up to the next section. Return them as a single (multiline) string. Note that this doesn't take a size argument!

next()

Skip lines to the next section (that is, read lines until a section-divider or end-marker has been consumed). Return true if there is such a section, false if an end-marker is seen. Re-enable the most-recently-pushed boundary.

pop()

Pop a section boundary. This boundary will no longer be interpreted as EOF.

seek(*pos*[, *whence*])

Seek. Seek indices are relative to the start of the current section. The *pos* and *whence* arguments are interpreted as for a file seek.

tell()

Return the file position relative to the start of the current section.

is_data(*str*)

Return true if *str* is data and false if it might be a section boundary. As written, it tests for a prefix other than `'--'` at start of line (which all MIME boundaries have) but it is declared so it can be overridden in derived classes.

Note that this test is used intended as a fast guard for the real boundary tests; if it always returns false it will merely slow processing, not cause it to fail.

section_divider(*str*)

Turn a boundary into a section-divider line. By default, this method prepends `'--'` (which MIME section boundaries have) but it is declared so it can be overridden in derived classes. This method need not append LF or CR-LF, as comparison with the result ignores trailing whitespace.

end_marker(*str*)

Turn a boundary string into an end-marker line. By default, this method prepends `'--'` and appends `'--'` (like a MIME-multipart end-of-message marker) but it is declared so it can be overridden in derived classes. This method need not append LF or CR-LF, as comparison with the result ignores trailing whitespace.

Finally, `MultiFile` instances have two public instance variables:

level

Nesting depth of the current part.

last

True if the last end-of-file was for an end-of-message marker.

12.9.2 MultiFile Example

```
import mimetools
import MultiFile
import StringIO

def extract_mime_part_matching(stream, mimetype):
    """Return the first element in a multipart MIME message on stream
    matching mimetype."""

    msg = mimetools.Message(stream)
    msgtype = msg.gettype()
    params = msg.getplist()

    data = StringIO.StringIO()
    if msgtype[:10] == "multipart/":

        file = multifile.MultiFile(stream)
        file.push(msg.getparam("boundary"))
        while file.next():
            submsg = mimetools.Message(file)
            try:
                data = StringIO.StringIO()
                mimetools.decode(file, data, submsg.getencoding())
            except ValueError:
                continue
            if submsg.gettype() == mimetype:
                break
        file.pop()
    return data.getvalue()
```

12.10 binhex — Encode and decode binhex4 files

This module encodes and decodes files in binhex4 format, a format allowing representation of Macintosh files in ASCII. On the Macintosh, both forks of a file and the finder information are encoded (or decoded), on other platforms only the data fork is handled.

The binhex module defines the following functions:

binhex(*input*, *output*)

Convert a binary file with filename *input* to binhex file *output*. The *output* parameter can either be a filename or a file-like object (any object supporting a `write()` and `close()` method).

hexbin(*input*[, *output*])

Decode a binhex file *input*. *input* may be a filename or a file-like object supporting `read()` and `close()` methods. The resulting file is written to a file named *output*, unless the argument is omitted in which case the output filename is read from the binhex file.

See Also:

[Module binascii](#) (section 12.12):

support module containing ASCII-to-binary and binary-to-ASCII conversions

12.10.1 Notes

There is an alternative, more powerful interface to the coder and decoder, see the source for details.

If you code or decode textfiles on non-Macintosh platforms they will still use the Macintosh newline convention (carriage-return as end of line).

As of this writing, `hexbin()` appears to not work in all cases.

12.11 uu — Encode and decode uuencode files

This module encodes and decodes files in uuencode format, allowing arbitrary binary data to be transferred over ascii-only connections. Wherever a file argument is expected, the methods accept a file-like object. For backwards compatibility, a string containing a pathname is also accepted, and the corresponding file will be opened for reading and writing; the pathname `'-'` is understood to mean the standard input or output. However, this interface is deprecated; it's better for the caller to open the file itself, and be sure that, when required, the mode is `'rb'` or `'wb'` on Windows or DOS.

This code was contributed by Lance Ellinghouse, and modified by Jack Jansen.

The `uu` module defines the following functions:

encode(*in_file*, *out_file*[, *name*[, *mode*]])

Uuencode file *in_file* into file *out_file*. The uuencoded file will have the header specifying *name* and *mode* as the defaults for the results of decoding the file. The default defaults are taken from *in_file*, or `'-'` and `0666` respectively.

decode(*in_file*[, *out_file*[, *mode*]])

This call decodes uuencoded file *in_file* placing the result on file *out_file*. If *out_file* is a pathname, *mode* is used to set the permission bits if the file must be created. Defaults for *out_file* and *mode* are taken from the uuencode header.

See Also:

[Module `binascii`](#) (section 12.12):

support module containing ASCII-to-binary and binary-to-ASCII conversions

12.12 binascii — Convert between binary and ASCII

The `binascii` module contains a number of methods to convert between binary and various ASCII-encoded binary representations. Normally, you will not use these functions directly but use wrapper modules like `uu` or `binhex` instead, this module solely exists because bit-manipulation of large amounts of data is slow in Python.

The `binascii` module defines the following functions:

a2b_uu(*string*)

Convert a single line of uuencoded data back to binary and return the binary data. Lines normally contain 45 (binary) bytes, except for the last line. Line data may be followed by whitespace.

b2a_uu(*data*)

Convert binary data to a line of ASCII characters, the return value is the converted line, including a newline char. The length of *data* should be at most 45.

a2b_base64(*string*)

Convert a block of base64 data back to binary and return the binary data. More than one line may be passed at a time.

b2a_base64(*data*)

Convert binary data to a line of ASCII characters in base64 coding. The return value is the converted line, including a newline char. The length of *data* should be at most 57 to adhere to the base64 standard.

a2b_hqx(*string*)

Convert binhex4 formatted ASCII data to binary, without doing RLE-decompression. The string should contain a complete number of binary bytes, or (in case of the last portion of the binhex4 data) have the remaining bits zero.

rledecode_hqx(*data*)

Perform RLE-decompression on the data, as per the binhex4 standard. The algorithm uses 0x90 after a byte as a repeat indicator, followed by a count. A count of 0 specifies a byte value of 0x90. The routine returns the decompressed data, unless data input data ends in an orphaned repeat indicator, in which case the `Incomplete` exception is raised.

rlecode_hqx(*data*)

Perform binhex4 style RLE-compression on *data* and return the result.

b2a_hqx(*data*)

Perform hexbin4 binary-to-ASCII translation and return the resulting string. The argument should already be RLE-coded, and have a length divisible by 3 (except possibly the last fragment).

crc_hqx(*data*, *crc*)

Compute the binhex4 crc value of *data*, starting with an initial *crc* and returning the result.

crc32(*data*[, *crc*])

Compute CRC-32, the 32-bit checksum of data, starting with an initial *crc*. This is consistent with the ZIP file checksum. Use as follows:

```
print binascii.crc32("hello world")
# Or, in two pieces:
crc = binascii.crc32("hello")
crc = binascii.crc32(" world", crc)
print crc
```

Error

Exception raised on errors. These are usually programming errors.

Incomplete

Exception raised on incomplete data. These are usually not programming errors, but may be handled by reading a little more data and trying again.

See Also:

[Module base64](#) (section 12.16):

support for base64 encoding used in MIME email messages

[Module binhex](#) (section 12.10):

support for the binhex format used on the Macintosh

[Module uu](#) (section 12.11):

support for UU encoding used on UNIX

12.13 `xdrlib` — Encode and decode XDR data.

The `xdrlib` module supports the External Data Representation Standard as described in RFC 1014, written by Sun Microsystems, Inc. June 1987. It supports most of the data types described in the RFC.

The `xdrlib` module defines two classes, one for packing variables into XDR representation, and another for unpacking from XDR representation. There are also two exception classes.

Packer()

`Packer` is the class for packing data into XDR representation. The `Packer` class is instantiated with no arguments.

Unpacker(data)

`Unpacker` is the complementary class which unpacks XDR data values from a string buffer. The input buffer is given as *data*.

12.13.1 Packer Objects

`Packer` instances have the following methods:

get_buffer()

Returns the current pack buffer as a string.

reset()

Resets the pack buffer to the empty string.

In general, you can pack any of the most common XDR data types by calling the appropriate `pack_type()` method. Each method takes a single argument, the value to pack. The following simple data type packing methods are supported: `pack_uint()`, `pack_int()`, `pack_enum()`, `pack_bool()`, `pack_uhyper()`, and `pack_hyper()`.

pack_float(value)

Packs the single-precision floating point number *value*.

pack_double(value)

Packs the double-precision floating point number *value*.

The following methods support packing strings, bytes, and opaque data:

pack_fstring(n, s)

Packs a fixed length string, *s*. *n* is the length of the string but it is *not* packed into the data buffer. The string is padded with null bytes if necessary to guaranteed 4 byte alignment.

pack_fopaque(n, data)

Packs a fixed length opaque data stream, similarly to `pack_fstring()`.

pack_string(s)

Packs a variable length string, *s*. The length of the string is first packed as an unsigned integer, then the string data is packed with `pack_fstring()`.

pack_opaque(data)

Packs a variable length opaque data string, similarly to `pack_string()`.

pack_bytes(bytes)

Packs a variable length byte stream, similarly to `pack_string()`.

The following methods support packing arrays and lists:

pack_list(list, pack_item)

Packs a *list* of homogeneous items. This method is useful for lists with an indeterminate size; i.e. the size is not available until the entire list has been walked. For each item in the list, an unsigned integer 1 is packed first, followed by the data value from the list. *pack_item* is the function that is called to pack the individual item. At the end of the list, an unsigned integer 0 is packed.

For example, to pack a list of integers, the code might appear like this:

```
import xdrlib
p = xdrlib.Packer()
p.pack_list([1, 2, 3], p.pack_int)
```

pack_farray(*n*, *array*, *pack_item*)

Packs a fixed length list (*array*) of homogeneous items. *n* is the length of the list; it is *not* packed into the buffer, but a `ValueError` exception is raised if `len(array)` is not equal to *n*. As above, *pack_item* is the function used to pack each element.

pack_array(*list*, *pack_item*)

Packs a variable length *list* of homogeneous items. First, the length of the list is packed as an unsigned integer, then each element is packed as in `pack_farray()` above.

12.13.2 Unpacker Objects

The `Unpacker` class offers the following methods:

reset(*data*)

Resets the string buffer with the given *data*.

get_position()

Returns the current unpack position in the data buffer.

set_position(*position*)

Sets the data buffer unpack position to *position*. You should be careful about using `get_position()` and `set_position()`.

get_buffer()

Returns the current unpack data buffer as a string.

done()

Indicates unpack completion. Raises an `Error` exception if all of the data has not been unpacked.

In addition, every data type that can be packed with a `Packer`, can be unpacked with an `Unpacker`. Unpacking methods are of the form `unpack_type()`, and take no arguments. They return the unpacked object.

unpack_float()

Unpacks a single-precision floating point number.

unpack_double()

Unpacks a double-precision floating point number, similarly to `unpack_float()`.

In addition, the following methods unpack strings, bytes, and opaque data:

unpack_fstring(*n*)

Unpacks and returns a fixed length string. *n* is the number of characters expected. Padding with null bytes to guaranteed 4 byte alignment is assumed.

unpack_fopaque(*n*)

Unpacks and returns a fixed length opaque data stream, similarly to `unpack_fstring()`.

unpack_string()

Unpacks and returns a variable length string. The length of the string is first unpacked as an unsigned integer, then the string data is unpacked with `unpack_fstring()`.

unpack_opaque()

Unpacks and returns a variable length opaque data string, similarly to `unpack_string()`.

unpack_bytes()

Unpacks and returns a variable length byte stream, similarly to `unpack_string()`.

The following methods support unpacking arrays and lists:

unpack_list(*unpack_item*)

Unpacks and returns a list of homogeneous items. The list is unpacked one element at a time by first unpacking an unsigned integer flag. If the flag is 1, then the item is unpacked and appended to the list. A flag of 0 indicates

the end of the list. *unpack_item* is the function that is called to unpack the items.

unpack_farray(*n*, *unpack_item*)

Unpacks and returns (as a list) a fixed length array of homogeneous items. *n* is number of list elements to expect in the buffer. As above, *unpack_item* is the function used to unpack each element.

unpack_array(*unpack_item*)

Unpacks and returns a variable length *list* of homogeneous items. First, the length of the list is unpacked as an unsigned integer, then each element is unpacked as in `unpack_farray()` above.

12.13.3 Exceptions

Exceptions in this module are coded as class instances:

Error

The base exception class. `Error` has a single public data member `msg` containing the description of the error.

ConversionError

Class derived from `Error`. Contains no additional instance variables.

Here is an example of how you would catch one of these exceptions:

```
import xdrlib
p = xdrlib.Packer()
try:
    p.pack_double(8.01)
except xdrlib.ConversionError, instance:
    print 'packing the double failed:', instance.msg
```

12.14 mailcap — Mailcap file handling.

Mailcap files are used to configure how MIME-aware applications such as mail readers and Web browsers react to files with different MIME types. (The name “mailcap” is derived from the phrase “mail capability”.) For example, a mailcap file might contain a line like `video/mpeg; xmpeg %s`. Then, if the user encounters an email message or Web document with the MIME type `video/mpeg`, `%s` will be replaced by a filename (usually one belonging to a temporary file) and the `xmpeg` program can be automatically started to view the file.

The mailcap format is documented in RFC 1524, “A User Agent Configuration Mechanism For Multimedia Mail Format Information,” but is not an Internet standard. However, mailcap files are supported on most UNIX systems.

findmatch(*caps*, *MIMEtype*[, *key*[, *filename*[, *plist*]]])

Return a 2-tuple; the first element is a string containing the command line to be executed (which can be passed to `os.system()`), and the second element is the mailcap entry for a given MIME type. If no matching MIME type can be found, `(None, None)` is returned.

key is the name of the field desired, which represents the type of activity to be performed; the default value is `'view'`, since in the most common case you simply want to view the body of the MIME-typed data. Other possible values might be `'compose'` and `'edit'`, if you wanted to create a new body of the given MIME type or alter the existing body data. See RFC 1524 for a complete list of these fields.

filename is the filename to be substituted for `%s` in the command line; the default value is `'/dev/null'` which is almost certainly not what you want, so usually you'll override it by specifying a filename.

plist can be a list containing named parameters; the default value is simply an empty list. Each entry in the list must be a string containing the parameter name, an equals sign (`=`), and the parameter's value. Mailcap entries can contain named parameters like `%{foo}`, which will be replaced by the value of the parameter named `'foo'`.

For example, if the command line `'showpartial %{id} %{number} %{total}'` was in a mailcap file, and `plist` was set to `['id=1', 'number=2', 'total=3']`, the resulting command line would be `"showpartial 1 2 3"`.

In a mailcap file, the `"test"` field can optionally be specified to test some external condition (e.g., the machine architecture, or the window system in use) to determine whether or not the mailcap line applies. `findmatch()` will automatically check such conditions and skip the entry if the check fails.

getcaps()

Returns a dictionary mapping MIME types to a list of mailcap file entries. This dictionary must be passed to the `findmatch()` function. An entry is stored as a list of dictionaries, but it shouldn't be necessary to know the details of this representation.

The information is derived from all of the mailcap files found on the system. Settings in the user's mailcap file `'$HOME/.mailcap'` will override settings in the system mailcap files `'/etc/mailcap'`, `'/usr/etc/mailcap'`, and `'/usr/local/etc/mailcap'`.

An example usage:

```
>>> import mailcap
>>> d=mailcap.getcaps()
>>> mailcap.findmatch(d, 'video/mpeg', filename='/tmp/tmp1223')
('xmpeg /tmp/tmp1223', {'view': 'xmpeg %s'})
```

12.15 `mimetypes` — Map filenames to MIME types

The `mimetypes` converts between a filename or URL and the MIME type associated with the filename extension. Conversions are provided from filename to MIME type and from MIME type to filename extension; encodings are not supported for the later conversion.

The functions described below provide the primary interface for this module. If the module has not been initialized, they will call `init()`.

guess_type(filename)

Guess the type of a file based on its filename or URL, given by *filename*. The return value is a tuple (*type*, *encoding*) where *type* is `None` if the type can't be guessed (no or unknown suffix) or a string of the form `'type/subtype'`, usable for a MIME `content-type` header; and *encoding* is `None` for no encoding or the name of the program used to encode (e.g. **compress** or **gzip**). The encoding is suitable for use as a `content-encoding` header, *not* as a `content-transfer-encoding` header. The mappings are table driven. Encoding suffixes are case sensitive; type suffixes are first tried case sensitive, then case insensitive.

guess_extension(type)

Guess the extension for a file based on its MIME type, given by *type*. The return value is a string giving a filename extension, including the leading dot (`'.'`). The extension is not guaranteed to have been associated with any particular data stream, but would be mapped to the MIME type *type* by `guess_type()`. If no extension can be guessed for *type*, `None` is returned.

Some additional functions and data items are available for controlling the behavior of the module.

init([files])

Initialize the internal data structures. If given, *files* must be a sequence of file names which should be used to augment the default type map. If omitted, the file names to use are taken from `knownfiles`. Each file named in *files* or `knownfiles` takes precedence over those named before it. Calling `init()` repeatedly is allowed.

read_mime_types(filename)

Load the type map given in the file *filename*, if it exists. The type map is returned as a dictionary mapping

filename extensions, including the leading dot ('.'), to strings of the form '*type/subtype*'. If the file *filename* does not exist or cannot be read, None is returned.

inited

Flag indicating whether or not the global data structures have been initialized. This is set to true by `init()`.

knownfiles

List of type map file names commonly installed. These files are typically named 'mime.types' and are installed in different locations by different packages.

suffix_map

Dictionary mapping suffixes to suffixes. This is used to allow recognition of encoded files for which the encoding and the type are indicated by the same extension. For example, the '.tgz' extension is mapped to '.tar.gz' to allow the encoding and type to be recognized separately.

encodings_map

Dictionary mapping filename extensions to encoding types.

types_map

Dictionary mapping filename extensions to MIME types.

12.16 `base64` — Encode and decode MIME base64 data

This module performs base64 encoding and decoding of arbitrary binary strings into text strings that can be safely emailed or posted. The encoding scheme is defined in RFC 1521 (*MIME (Multipurpose Internet Mail Extensions) Part One: Mechanisms for Specifying and Describing the Format of Internet Message Bodies*, section 5.2, “Base64 Content-Transfer-Encoding”) and is used for MIME email and various other Internet-related applications; it is not the same as the output produced by the `uuencode` program. For example, the string '`www.python.org`' is encoded as the string '`d3d3LnB5dGhvbi5vcmc=\n`'.

decode(*input*, *output*)

Decode the contents of the *input* file and write the resulting binary data to the *output* file. *input* and *output* must either be file objects or objects that mimic the file object interface. *input* will be read until `input.read()` returns an empty string.

decodestring(*s*)

Decode the string *s*, which must contain one or more lines of base64 encoded data, and return a string containing the resulting binary data.

encode(*input*, *output*)

Encode the contents of the *input* file and write the resulting base64 encoded data to the *output* file. *input* and *output* must either be file objects or objects that mimic the file object interface. *input* will be read until `input.read()` returns an empty string.

encodestring(*s*)

Encode the string *s*, which can contain arbitrary binary data, and return a string containing one or more lines of base64 encoded data.

See Also:

[Module `binascii`](#) (section 12.12):

support module containing ASCII-to-binary and binary-to-ASCII conversions

Internet RFC 1521, *MIME (Multipurpose Internet Mail Extensions) Part One: Mechanisms for Specifying and Describing the Format of Internet Message Bodies*, section 5.2, “Base64 Content-Transfer-Encoding,” provides the definition of the base64 encoding.

12.17 `quopri` — Encode and decode MIME quoted-printable data

This module performs quoted-printable transport encoding and decoding, as defined in RFC 1521: “MIME (Multipurpose Internet Mail Extensions) Part One”. The quoted-printable encoding is designed for data where there are relatively few nonprintable characters; the base64 encoding scheme available via the `base64` module is more compact if there are many such characters, as when sending a graphics file.

`decode`(*input*, *output*)

Decode the contents of the *input* file and write the resulting decoded binary data to the *output* file. *input* and *output* must either be file objects or objects that mimic the file object interface. *input* will be read until *input*.`read()` returns an empty string.

`encode`(*input*, *output*, *quotetabs*)

Encode the contents of the *input* file and write the resulting quoted-printable data to the *output* file. *input* and *output* must either be file objects or objects that mimic the file object interface. *input* will be read until *input*.`read()` returns an empty string.

See Also:

Module `mimify` (section 12.20):

General utilities for processing of MIME messages.

12.18 `mailbox` — Read various mailbox formats

This module defines a number of classes that allow easy and uniform access to mail messages in a (UNIX) mailbox.

`UnixMailbox`(*fp*)

Access a classic UNIX-style mailbox, where all messages are contained in a single file and separated by “From name time” lines. The file object *fp* points to the mailbox file.

`MmdfMailbox`(*fp*)

Access an MMDF-style mailbox, where all messages are contained in a single file and separated by lines consisting of 4 control-A characters. The file object *fp* points to the mailbox file.

`MHMailbox`(*dirname*)

Access an MH mailbox, a directory with each message in a separate file with a numeric name. The name of the mailbox directory is passed in *dirname*.

`Maildir`(*dirname*)

Access a Qmail mail directory. All new and current mail for the mailbox specified by *dirname* is made available.

`BabylMailbox`(*fp*)

Access a Babyl mailbox, which is similar to an MMDF mailbox. Mail messages start with a line containing only ‘*** EOOH ***’ and end with a line containing only ‘\037\014’.

12.18.1 Mailbox Objects

All implementations of Mailbox objects have one externally visible method:

`next`()

Return the next message in the mailbox, as a `rfc822.Message` object (see the `rfc822` module). Depending on the mailbox implementation the *fp* attribute of this object may be a true file object or a class instance simulating a file object, taking care of things like message boundaries if multiple mail messages are contained in a single file, etc.

12.19 `mhlib` — Access to MH mailboxes

The `mhlib` module provides a Python interface to MH folders and their contents.

The module contains three basic classes, `MH`, which represents a particular collection of folders, `Folder`, which represents a single folder, and `Message`, which represents a single message.

`MH`([*path*[, *profile*]])

MH represents a collection of MH folders.

`Folder`(*mh*, *name*)

The `Folder` class represents a single folder and its messages.

`Message`(*folder*, *number*[, *name*])

Message objects represent individual messages in a folder. The `Message` class is derived from `mime-tools.Message`.

12.19.1 MH Objects

MH instances have the following methods:

`error`(*format*[, ...])

Print an error message – can be overridden.

`getprofile`(*key*)

Return a profile entry (None if not set).

`getpath`()

Return the mailbox pathname.

`getcontext`()

Return the current folder name.

`setcontext`(*name*)

Set the current folder name.

`listfolders`()

Return a list of top-level folders.

`listallfolders`()

Return a list of all folders.

`listsubfolders`(*name*)

Return a list of direct subfolders of the given folder.

`listallsubfolders`(*name*)

Return a list of all subfolders of the given folder.

`makefolder`(*name*)

Create a new folder.

`deletefolder`(*name*)

Delete a folder – must have no subfolders.

`openfolder`(*name*)

Return a new open folder object.

12.19.2 Folder Objects

`Folder` instances represent open folders and have the following methods:

error (*format* [, ...])
 Print an error message – can be overridden.

getfullname ()
 Return the folder's full pathname.

getsequencesfilename ()
 Return the full pathname of the folder's sequences file.

getmessagefilename (*n*)
 Return the full pathname of message *n* of the folder.

listmessages ()
 Return a list of messages in the folder (as numbers).

getcurrent ()
 Return the current message number.

setcurrent (*n*)
 Set the current message number to *n*.

parsesequence (*seq*)
 Parse msgs syntax into list of messages.

getlast ()
 Get last message, or 0 if no messages are in the folder.

setlast (*n*)
 Set last message (internal use only).

getsequences ()
 Return dictionary of sequences in folder. The sequence names are used as keys, and the values are the lists of message numbers in the sequences.

putsequences (*dict*)
 Return dictionary of sequences in folder name: list.

removemessages (*list*)
 Remove messages in list from folder.

refilemessages (*list, tofolder*)
 Move messages in list to other folder.

movemessage (*n, tofolder, ton*)
 Move one message to a given destination in another folder.

copymessage (*n, tofolder, ton*)
 Copy one message to a given destination in another folder.

12.19.3 Message Objects

The Message class adds one method to those of `mimertools.Message`:

openmessage (*n*)
 Return a new open message object (costs a file descriptor).

12.20 mimify — MIME processing of mail messages

The `mimify` module defines two functions to convert mail messages to and from MIME format. The mail message can be either a simple message or a so-called multipart message. Each part is treated separately. Mimifying (a part

of) a message entails encoding the message as quoted-printable if it contains any characters that cannot be represented using 7-bit ASCII. Unmimifying (a part of) a message entails undoing the quoted-printable encoding. Mimify and unmimify are especially useful when a message has to be edited before being sent. Typical use would be:

```
unmimify message
edit message
mimify message
send message
```

The module defines the following user-callable functions and user-settable variables:

mimify(*infile*, *outfile*)

Copy the message in *infile* to *outfile*, converting parts to quoted-printable and adding MIME mail headers when necessary. *infile* and *outfile* can be file objects (actually, any object that has a `readline()` method (for *infile*) or a `write()` method (for *outfile*)) or strings naming the files. If *infile* and *outfile* are both strings, they may have the same value.

unmimify(*infile*, *outfile*[, *decode_base64*])

Copy the message in *infile* to *outfile*, decoding all quoted-printable parts. *infile* and *outfile* can be file objects (actually, any object that has a `readline()` method (for *infile*) or a `write()` method (for *outfile*)) or strings naming the files. If *infile* and *outfile* are both strings, they may have the same value. If the *decode_base64* argument is provided and tests true, any parts that are coded in the base64 encoding are decoded as well.

mime_decode_header(*line*)

Return a decoded version of the encoded header line in *line*.

mime_encode_header(*line*)

Return a MIME-encoded version of the header line in *line*.

MAXLEN

By default, a part will be encoded as quoted-printable when it contains any non-ASCII characters (i.e., characters with the 8th bit set), or if there are any lines longer than MAXLEN characters (default value 200).

CHARSET

When not specified in the mail headers, a character set must be filled in. The string used is stored in CHARSET, and the default value is ISO-8859-1 (also known as Latin1 (latin-one)).

This module can also be used from the command line. Usage is as follows:

```
mimify.py -e [-l length] [infile [outfile]]
mimify.py -d [-b] [infile [outfile]]
```

to encode (mimify) and decode (unmimify) respectively. *infile* defaults to standard input, *outfile* defaults to standard output. The same file can be specified for input and output.

If the **-l** option is given when encoding, if there are any lines longer than the specified *length*, the containing part will be encoded.

If the **-b** option is given when decoding, any base64 parts will be decoded as well.

See Also:

[Module `quopri`](#) (section 12.17):

Encode and decode MIME quoted-printable files.

12.21 netrc — netrc file processing

New in version 1.5.2.

The `netrc` class parses and encapsulates the `netrc` file format used by the UNIX **ftp** program and other FTP clients.

netrc([*file*])

A `netrc` instance or subclass instance encapsulates data from a `netrc` file. The initialization argument, if present, specifies the file to parse. If no argument is given, the file `‘.netrc’` in the user’s home directory will be read. Parse errors will raise `SyntaxError` with diagnostic information including the file name, line number, and terminating token.

12.21.1 netrc Objects

A `netrc` instance has the following methods:

authenticators(*host*)

Return a 3-tuple (*login*, *account*, *password*) of authenticators for *host*. If the `netrc` file did not contain an entry for the given host, return the tuple associated with the `‘default’` entry. If neither matching host nor default entry is available, return `None`.

__repr__()

Dump the class data as a string in the format of a `netrc` file. (This discards comments and may reorder the entries.)

Instances of `netrc` have public instance variables:

hosts

Dictionary mapping host names to (*login*, *account*, *password*) tuples. The `‘default’` entry, if any, is represented as a pseudo-host by that name.

macros

Dictionary mapping macro names to string lists.

12.22 robotparser — Parser for robots.txt

This module provides a single class, `RobotFileParser`, which answers questions about whether or not a particular user agent can fetch a URL on the web site that published the `‘robots.txt’` file. For more details on the structure of `‘robots.txt’` files, see <http://info.webcrawler.com/mak/projects/robots/norobots.html>.

RobotFileParser()

This class provides a set of methods to read, parse and answer questions about a single `‘robots.txt’` file.

set_url(*url*)

Sets the URL referring to a `‘robots.txt’` file.

read()

Reads the `‘robots.txt’` URL and feeds it to the parser.

parse(*lines*)

Parses the *lines* argument.

can_fetch(*useragent*, *url*)

Returns true if the *useragent* is allowed to fetch the *url* according to the rules contained in the parsed `‘robots.txt’` file.

mtime()

Returns the time the `robots.txt` file was last fetched. This is useful for long-running web spiders that need to check for new `robots.txt` files periodically.

modified()

Sets the time the `robots.txt` file was last fetched to the current time.

The following example demonstrates basic use of the RobotFileParser class.

```
>>> import robotparser
>>> rp = robotparser.RobotFileParser()
>>> rp.set_url("http://www.musi-cal.com/robots.txt")
>>> rp.read()
>>> rp.can_fetch("*", "http://www.musi-cal.com/cgi-bin/search?city=San+Francisco")
0
>>> rp.can_fetch("*", "http://www.musi-cal.com/")
1
```


Restricted Execution

In general, Python programs have complete access to the underlying operating system through the various functions and classes. For example, a Python program can open any file for reading and writing by using the `open()` built-in function (provided the underlying OS gives you permission!). This is exactly what you want for most applications.

There exists a class of applications for which this “openness” is inappropriate. Take Grail: a web browser that accepts “applets,” snippets of Python code, from anywhere on the Internet for execution on the local system. This can be used to improve the user interface of forms, for instance. Since the originator of the code is unknown, it is obvious that it cannot be trusted with the full resources of the local machine.

Restricted execution is the basic framework in Python that allows for the segregation of trusted and untrusted code. It is based on the notion that trusted Python code (a *supervisor*) can create a “padded cell” (or environment) with limited permissions, and run the untrusted code within this cell. The untrusted code cannot break out of its cell, and can only interact with sensitive system resources through interfaces defined and managed by the trusted code. The term “restricted execution” is favored over “safe-Python” since true safety is hard to define, and is determined by the way the restricted environment is created. Note that the restricted environments can be nested, with inner cells creating subcells of lesser, but never greater, privilege.

An interesting aspect of Python’s restricted execution model is that the interfaces presented to untrusted code usually have the same names as those presented to trusted code. Therefore no special interfaces need to be learned to write code designed to run in a restricted environment. And because the exact nature of the padded cell is determined by the supervisor, different restrictions can be imposed, depending on the application. For example, it might be deemed “safe” for untrusted code to read any file within a specified directory, but never to write a file. In this case, the supervisor may redefine the built-in `open()` function so that it raises an exception whenever the *mode* parameter is `'w'`. It might also perform a `chroot()`-like operation on the *filename* parameter, such that root is always relative to some safe “sandbox” area of the filesystem. In this case, the untrusted code would still see an built-in `open()` function in its environment, with the same calling interface. The semantics would be identical too, with `IOErrors` being raised when the supervisor determined that an unallowable parameter is being used.

The Python run-time determines whether a particular code block is executing in restricted execution mode based on the identity of the `__builtins__` object in its global variables: if this is (the dictionary of) the standard `__builtin__` module, the code is deemed to be unrestricted, else it is deemed to be restricted.

Python code executing in restricted mode faces a number of limitations that are designed to prevent it from escaping from the padded cell. For instance, the function object attribute `func_globals` and the class and instance object attribute `__dict__` are unavailable.

Two modules provide the framework for setting up restricted execution environments:

- `rexec` Basic restricted execution framework.
- `Bastion` Providing restricted access to objects.

See Also:

Andrew Kuchling, “Restricted Execution HOWTO.” Available online at <http://www.python.org/doc/howto/rexec/>.

Grail, an Internet browser written in Python, is available at <http://grail.cnri.reston.va.us/grail/>. More information on the use of Python's restricted execution mode in Grail is available on the Web site.

13.1 `rexec` — Restricted execution framework

This module contains the `RExec` class, which supports `r_eval()`, `r_execfile()`, `r_exec()`, and `r_import()` methods, which are restricted versions of the standard Python functions `eval()`, `execfile()` and the `exec` and `import` statements. Code executed in this restricted environment will only have access to modules and functions that are deemed safe; you can subclass `RExec` to add or remove capabilities as desired.

Note: The `RExec` class can prevent code from performing unsafe operations like reading or writing disk files, or using TCP/IP sockets. However, it does not protect against code using extremely large amounts of memory or CPU time.

`RExec`([`hooks` [, `verbose`]])

Returns an instance of the `RExec` class.

`hooks` is an instance of the `RHooks` class or a subclass of it. If it is omitted or `None`, the default `RHooks` class is instantiated. Whenever the `rexec` module searches for a module (even a built-in one) or reads a module's code, it doesn't actually go out to the file system itself. Rather, it calls methods of an `RHooks` instance that was passed to or created by its constructor. (Actually, the `RExec` object doesn't make these calls — they are made by a module loader object that's part of the `RExec` object. This allows another level of flexibility, e.g. using packages.)

By providing an alternate `RHooks` object, we can control the file system accesses made to import a module, without changing the actual algorithm that controls the order in which those accesses are made. For instance, we could substitute an `RHooks` object that passes all filesystem requests to a file server elsewhere, via some RPC mechanism such as ILU. Grail's applet loader uses this to support importing applets from a URL for a directory.

If `verbose` is true, additional debugging output may be sent to standard output.

The `RExec` class has the following class attributes, which are used by the `__init__()` method. Changing them on an existing instance won't have any effect; instead, create a subclass of `RExec` and assign them new values in the class definition. Instances of the new class will then use those new values. All these attributes are tuples of strings.

`nok_builtin_names`

Contains the names of built-in functions which will *not* be available to programs running in the restricted environment. The value for `RExec` is ('open', 'reload', '__import__'). (This gives the exceptions, because by far the majority of built-in functions are harmless. A subclass that wants to override this variable should probably start with the value from the base class and concatenate additional forbidden functions — when new dangerous built-in functions are added to Python, they will also be added to this module.)

`ok_builtin_modules`

Contains the names of built-in modules which can be safely imported. The value for `RExec` is ('audioop', 'array', 'binascii', 'cmath', 'errno', 'imageop', 'marshal', 'math', 'md5', 'operator', 'parser', 'regex', 'rotor', 'select', 'strop', 'struct', 'time'). A similar remark about overriding this variable applies — use the value from the base class as a starting point.

`ok_path`

Contains the directories which will be searched when an `import` is performed in the restricted environment. The value for `RExec` is the same as `sys.path` (at the time the module is loaded) for unrestricted code.

`ok_posix_names`

Contains the names of the functions in the `os` module which will be available to programs running in the restricted environment. The value for `RExec` is ('error', 'fstat', 'listdir', 'lstat', 'readlink', 'stat', 'times', 'uname', 'getpid', 'getppid', 'getcwd', 'getuid', 'getgid', 'geteuid', 'getegid').

`ok_sys_names`

Contains the names of the functions and variables in the `sys` module which will be available to programs

running in the restricted environment. The value for `RExec` is (`'ps1'`, `'ps2'`, `'copyright'`, `'version'`, `'platform'`, `'exit'`, `'maxint'`).

`RExec` instances support the following methods:

`r_eval`(*code*)

code must either be a string containing a Python expression, or a compiled code object, which will be evaluated in the restricted environment's `__main__` module. The value of the expression or code object will be returned.

`r_exec`(*code*)

code must either be a string containing one or more lines of Python code, or a compiled code object, which will be executed in the restricted environment's `__main__` module.

`r_execfile`(*filename*)

Execute the Python code contained in the file *filename* in the restricted environment's `__main__` module.

Methods whose names begin with `'s_'` are similar to the functions beginning with `'r_'`, but the code will be granted access to restricted versions of the standard I/O streams `sys.stdin`, `sys.stderr`, and `sys.stdout`.

`s_eval`(*code*)

code must be a string containing a Python expression, which will be evaluated in the restricted environment.

`s_exec`(*code*)

code must be a string containing one or more lines of Python code, which will be executed in the restricted environment.

`s_execfile`(*code*)

Execute the Python code contained in the file *filename* in the restricted environment.

`RExec` objects must also support various methods which will be implicitly called by code executing in the restricted environment. Overriding these methods in a subclass is used to change the policies enforced by a restricted environment.

`r_import`(*modulename*[, *globals*[, *locals*[, *fromlist*]])

Import the module *modulename*, raising an `ImportError` exception if the module is considered unsafe.

`r_open`(*filename*[, *mode*[, *bufsize*]])

Method called when `open()` is called in the restricted environment. The arguments are identical to those of `open()`, and a file object (or a class instance compatible with file objects) should be returned. `RExec`'s default behaviour is allow opening any file for reading, but forbidding any attempt to write a file. See the example below for an implementation of a less restrictive `r_open()`.

`r_reload`(*module*)

Reload the module object *module*, re-parsing and re-initializing it.

`r_unload`(*module*)

Unload the module object *module* (i.e., remove it from the restricted environment's `sys.modules` dictionary).

And their equivalents with access to restricted standard I/O streams:

`s_import`(*modulename*[, *globals*[, *locals*[, *fromlist*]])

Import the module *modulename*, raising an `ImportError` exception if the module is considered unsafe.

`s_reload`(*module*)

Reload the module object *module*, re-parsing and re-initializing it.

`s_unload`(*module*)

Unload the module object *module*.

13.1.1 An example

Let us say that we want a slightly more relaxed policy than the standard `RExec` class. For example, if we're willing to allow files in `/tmp` to be written, we can subclass the `RExec` class:

```
class TmpWriterRExec(rexec.RExec):
    def r_open(self, file, mode='r', buf=-1):
        if mode in ('r', 'rb'):
            pass
        elif mode in ('w', 'wb', 'a', 'ab'):
            # check filename : must begin with /tmp/
            if file[:5] != '/tmp/':
                raise IOError, "can't write outside /tmp"
            elif (string.find(file, '/../') >= 0 or
                  file[:3] == '../' or file[-3:] == '/../'):
                raise IOError, "'..' in filename forbidden"
        else: raise IOError, "Illegal open() mode"
        return open(file, mode, buf)
```

Notice that the above code will occasionally forbid a perfectly valid filename; for example, code in the restricted environment won't be able to open a file called `/tmp/foo/./bar`. To fix this, the `r_open()` method would have to simplify the filename to `/tmp/bar`, which would require splitting apart the filename and performing various operations on it. In cases where security is at stake, it may be preferable to write simple code which is sometimes overly restrictive, instead of more general code that is also more complex and may harbor a subtle security hole.

13.2 Bastion — Restricting access to objects

According to the dictionary, a bastion is “a fortified area or position”, or “something that is considered a stronghold.” It's a suitable name for this module, which provides a way to forbid access to certain attributes of an object. It must always be used with the `rexec` module, in order to allow restricted-mode programs access to certain safe attributes of an object, while denying access to other, unsafe attributes.

Bastion(*object*[, *filter*[, *name*[, *class*]]])

Protect the object *object*, returning a bastion for the object. Any attempt to access one of the object's attributes will have to be approved by the *filter* function; if the access is denied an `AttributeError` exception will be raised.

If present, *filter* must be a function that accepts a string containing an attribute name, and returns true if access to that attribute will be permitted; if *filter* returns false, the access is denied. The default filter denies access to any function beginning with an underscore ('_'). The bastion's string representation will be `<Bastion for name>` if a value for *name* is provided; otherwise, `repr(object)` will be used.

class, if present, should be a subclass of `BastionClass`; see the code in `'bastion.py'` for the details. Overriding the default `BastionClass` will rarely be required.

BastionClass(*getfunc*, *name*)

Class which actually implements bastion objects. This is the default class used by `Bastion()`. The *getfunc* parameter is a function which returns the value of an attribute which should be exposed to the restricted execution environment when called with the name of the attribute as the only parameter. *name* is used to construct the `repr()` of the `BastionClass` instance.

Multimedia Services

The modules described in this chapter implement various algorithms or interfaces that are mainly useful for multimedia applications. They are available at the discretion of the installation. Here's an overview:

audioop	Manipulate raw audio data.
imageop	Manipulate raw image data.
aifc	Read and write audio files in AIFF or AIFC format.
sunau	Provide an interface to the Sun AU sound format.
wave	Provide an interface to the WAV sound format.
chunk	Module to read IFF chunks.
colorsys	Conversion functions between RGB and other color systems.
rgbimg	Read and write image files in "SGI RGB" format (the module is <i>not</i> SGI specific though!).
imghdr	Determine the type of image contained in a file or byte stream.
sndhdr	Determine type of a sound file.

14.1 `audioop` — Manipulate raw audio data

The `audioop` module contains some useful operations on sound fragments. It operates on sound fragments consisting of signed integer samples 8, 16 or 32 bits wide, stored in Python strings. This is the same format as used by the `al` and `sunaudiodev` modules. All scalar items are integers, unless specified otherwise.

This module provides support for u-LAW and Intel/DVI ADPCM encodings.

A few of the more complicated operations only take 16-bit samples, otherwise the sample size (in bytes) is always a parameter of the operation.

The module defines the following variables and functions:

error

This exception is raised on all errors, such as unknown number of bytes per sample, etc.

add(*fragment1*, *fragment2*, *width*)

Return a fragment which is the addition of the two samples passed as parameters. *width* is the sample width in bytes, either 1, 2 or 4. Both fragments should have the same length.

adpcm2lin(*adpcmfragment*, *width*, *state*)

Decode an Intel/DVI ADPCM coded fragment to a linear fragment. See the description of `lin2adpcm()` for details on ADPCM coding. Return a tuple (*sample*, *newstate*) where the sample has the width specified in *width*.

adpcm32lin(*adpcmfragment*, *width*, *state*)

Decode an alternative 3-bit ADPCM code. See `lin2adpcm3()` for details.

avg(*fragment*, *width*)

Return the average over all samples in the fragment.

avgpp(*fragment*, *width*)

Return the average peak-peak value over all samples in the fragment. No filtering is done, so the usefulness of this routine is questionable.

bias(*fragment*, *width*, *bias*)

Return a fragment that is the original fragment with a bias added to each sample.

cross(*fragment*, *width*)

Return the number of zero crossings in the fragment passed as an argument.

findfactor(*fragment*, *reference*)

Return a factor F such that `rms(add(fragment, mul(reference, -F)))` is minimal, i.e., return the factor with which you should multiply *reference* to make it match as well as possible to *fragment*. The fragments should both contain 2-byte samples.

The time taken by this routine is proportional to `len(fragment)`.

findfit(*fragment*, *reference*)

Try to match *reference* as well as possible to a portion of *fragment* (which should be the longer fragment). This is (conceptually) done by taking slices out of *fragment*, using `findfactor()` to compute the best match, and minimizing the result. The fragments should both contain 2-byte samples. Return a tuple (*offset*, *factor*) where *offset* is the (integer) offset into *fragment* where the optimal match started and *factor* is the (floating-point) factor as per `findfactor()`.

findmax(*fragment*, *length*)

Search *fragment* for a slice of length *length* samples (not bytes!) with maximum energy, i.e., return *i* for which `rms(fragment[i*2:(i+length)*2])` is maximal. The fragments should both contain 2-byte samples.

The routine takes time proportional to `len(fragment)`.

getsample(*fragment*, *width*, *index*)

Return the value of sample *index* from the fragment.

lin2lin(*fragment*, *width*, *newwidth*)

Convert samples between 1-, 2- and 4-byte formats.

lin2adpcm(*fragment*, *width*, *state*)

Convert samples to 4 bit Intel/DVI ADPCM encoding. ADPCM coding is an adaptive coding scheme, whereby each 4 bit number is the difference between one sample and the next, divided by a (varying) step. The Intel/DVI ADPCM algorithm has been selected for use by the IMA, so it may well become a standard.

state is a tuple containing the state of the coder. The coder returns a tuple (*adpcmfrag*, *newstate*), and the *newstate* should be passed to the next call of `lin2adpcm()`. In the initial call, `None` can be passed as the state. *adpcmfrag* is the ADPCM coded fragment packed 2 4-bit values per byte.

lin2adpcm3(*fragment*, *width*, *state*)

This is an alternative ADPCM coder that uses only 3 bits per sample. It is not compatible with the Intel/DVI ADPCM coder and its output is not packed (due to laziness on the side of the author). Its use is discouraged.

lin2ulaw(*fragment*, *width*)

Convert samples in the audio fragment to u-LAW encoding and return this as a Python string. u-LAW is an audio encoding format whereby you get a dynamic range of about 14 bits using only 8 bit samples. It is used by the Sun audio hardware, among others.

minmax(*fragment*, *width*)

Return a tuple consisting of the minimum and maximum values of all samples in the sound fragment.

max(*fragment*, *width*)

Return the maximum of the *absolute value* of all samples in a fragment.

maxpp(*fragment*, *width*)

Return the maximum peak-peak value in the sound fragment.

mul(*fragment*, *width*, *factor*)

Return a fragment that has all samples in the original fragment multiplied by the floating-point value *factor*. Overflow is silently ignored.

ratecv(*fragment*, *width*, *nchannels*, *inrate*, *outrate*, *state*[, *weightA*[, *weightB*]])

Convert the frame rate of the input fragment.

state is a tuple containing the state of the converter. The converter returns a tuple (*newfragment*, *newstate*), and *newstate* should be passed to the next call of `ratecv()`.

The *weightA* and *weightB* arguments are parameters for a simple digital filter and default to 1 and 0 respectively.

reverse(*fragment*, *width*)

Reverse the samples in a fragment and returns the modified fragment.

rms(*fragment*, *width*)

Return the root-mean-square of the fragment, i.e.

$$\sqrt{\frac{\sum S_i^2}{n}}$$

This is a measure of the power in an audio signal.

tomono(*fragment*, *width*, *lfactor*, *rfactor*)

Convert a stereo fragment to a mono fragment. The left channel is multiplied by *lfactor* and the right channel by *rfactor* before adding the two channels to give a mono signal.

tostereo(*fragment*, *width*, *lfactor*, *rfactor*)

Generate a stereo fragment from a mono fragment. Each pair of samples in the stereo fragment are computed from the mono sample, whereby left channel samples are multiplied by *lfactor* and right channel samples by *rfactor*.

ulaw2lin(*fragment*, *width*)

Convert sound fragments in u-LAW encoding to linearly encoded sound fragments. u-LAW encoding always uses 8 bits samples, so *width* refers only to the sample width of the output fragment here.

Note that operations such as `mul()` or `max()` make no distinction between mono and stereo fragments, i.e. all samples are treated equal. If this is a problem the stereo fragment should be split into two mono fragments first and recombined later. Here is an example of how to do that:

```
def mul_stereo(sample, width, lfactor, rfactor):
    lsample = audioop.tomono(sample, width, 1, 0)
    rsample = audioop.tomono(sample, width, 0, 1)
    lsample = audioop.mul(lsample, width, lfactor)
    rsample = audioop.mul(rsample, width, rfactor)
    lsample = audioop.tostereo(lsample, width, 1, 0)
    rsample = audioop.tostereo(rsample, width, 0, 1)
    return audioop.add(lsample, rsample, width)
```

If you use the ADPCM coder to build network packets and you want your protocol to be stateless (i.e. to be able to tolerate packet loss) you should not only transmit the data but also the state. Note that you should send the *initial* state (the one you passed to `lin2adpcm()`) along to the decoder, not the final state (as returned by the coder). If you want to use `struct.struct()` to store the state in binary you can code the first element (the predicted value) in 16 bits and the second (the delta index) in 8.

The ADPCM coders have never been tried against other ADPCM coders, only against themselves. It could well be that I misinterpreted the standards in which case they will not be interoperable with the respective standards.

The `find*()` routines might look a bit funny at first sight. They are primarily meant to do echo cancellation. A reasonably fast way to do this is to pick the most energetic piece of the output sample, locate that in the input sample

and subtract the whole output sample from the input sample:

```
def echocancel(outputdata, inputdata):
    pos = audioop.findmax(outputdata, 800)    # one tenth second
    out_test = outputdata[pos*2:]
    in_test = inputdata[pos*2:]
    ipos, factor = audioop.findfit(in_test, out_test)
    # Optional (for better cancellation):
    # factor = audioop.findfactor(in_test[ipos*2:ipos*2+len(out_test)],
    #                             out_test)
    prefill = '\0'*(pos+ipos)*2
    postfill = '\0'*(len(inputdata)-len(prefill)-len(outputdata))
    outputdata = prefill + audioop.mul(outputdata,2,-factor) + postfill
    return audioop.add(inputdata, outputdata, 2)
```

14.2 imageop — Manipulate raw image data

The `imageop` module contains some useful operations on images. It operates on images consisting of 8 or 32 bit pixels stored in Python strings. This is the same format as used by `gl.rectwrite()` and the `imgfile` module.

The module defines the following variables and functions:

error

This exception is raised on all errors, such as unknown number of bits per pixel, etc.

crop(*image*, *psize*, *width*, *height*, *x0*, *y0*, *x1*, *y1*)

Return the selected part of *image*, which should be *width* by *height* in size and consist of pixels of *psize* bytes. *x0*, *y0*, *x1* and *y1* are like the `gl.rectread()` parameters, i.e. the boundary is included in the new image. The new boundaries need not be inside the picture. Pixels that fall outside the old image will have their value set to zero. If *x0* is bigger than *x1* the new image is mirrored. The same holds for the y coordinates.

scale(*image*, *psize*, *width*, *height*, *newwidth*, *newheight*)

Return *image* scaled to size *newwidth* by *newheight*. No interpolation is done, scaling is done by simple-minded pixel duplication or removal. Therefore, computer-generated images or dithered images will not look nice after scaling.

tovideo(*image*, *psize*, *width*, *height*)

Run a vertical low-pass filter over an image. It does so by computing each destination pixel as the average of two vertically-aligned source pixels. The main use of this routine is to forestall excessive flicker if the image is displayed on a video device that uses interlacing, hence the name.

grey2mono(*image*, *width*, *height*, *threshold*)

Convert a 8-bit deep greyscale image to a 1-bit deep image by thresholding all the pixels. The resulting image is tightly packed and is probably only useful as an argument to `mono2grey()`.

dither2mono(*image*, *width*, *height*)

Convert an 8-bit greyscale image to a 1-bit monochrome image using a (simple-minded) dithering algorithm.

mono2grey(*image*, *width*, *height*, *p0*, *p1*)

Convert a 1-bit monochrome image to an 8 bit greyscale or color image. All pixels that are zero-valued on input get value *p0* on output and all one-value input pixels get value *p1* on output. To convert a monochrome black-and-white image to greyscale pass the values 0 and 255 respectively.

grey2grey4(*image*, *width*, *height*)

Convert an 8-bit greyscale image to a 4-bit greyscale image without dithering.

grey2grey2(*image*, *width*, *height*)

Convert an 8-bit greyscale image to a 2-bit greyscale image without dithering.

dither2grey2(*image*, *width*, *height*)

Convert an 8-bit greyscale image to a 2-bit greyscale image with dithering. As for `dither2mono()`, the dithering algorithm is currently very simple.

grey42grey(*image*, *width*, *height*)

Convert a 4-bit greyscale image to an 8-bit greyscale image.

grey22grey(*image*, *width*, *height*)

Convert a 2-bit greyscale image to an 8-bit greyscale image.

14.3 aifc — Read and write AIFF and AIFC files

This module provides support for reading and writing AIFF and AIFF-C files. AIFF is Audio Interchange File Format, a format for storing digital audio samples in a file. AIFF-C is a newer version of the format that includes the ability to compress the audio data.

Caveat: Some operations may only work under IRIX; these will raise `ImportError` when attempting to import the `c1` module, which is only available on IRIX.

Audio files have a number of parameters that describe the audio data. The sampling rate or frame rate is the number of times per second the sound is sampled. The number of channels indicate if the audio is mono, stereo, or quadro. Each frame consists of one sample per channel. The sample size is the size in bytes of each sample. Thus a frame consists of $nchannels * samplesize$ bytes, and a second's worth of audio consists of $nchannels * samplesize * framerate$ bytes.

For example, CD quality audio has a sample size of two bytes (16 bits), uses two channels (stereo) and has a frame rate of 44,100 frames/second. This gives a frame size of 4 bytes ($2 * 2$), and a second's worth occupies $2 * 2 * 44100$ bytes, i.e. 176,400 bytes.

Module `aifc` defines the following function:

open(*file*[, *mode*])

Open an AIFF or AIFF-C file and return an object instance with methods that are described below. The argument *file* is either a string naming a file or a file object. *mode* must be `'r'` or `'rb'` when the file must be opened for reading, or `'w'` or `'wb'` when the file must be opened for writing. If omitted, *file.mode* is used if it exists, otherwise `'rb'` is used. When used for writing, the file object should be seekable, unless you know ahead of time how many samples you are going to write in total and use `writeframesraw()` and `setnframes()`.

Objects returned by `open()` when a file is opened for reading have the following methods:

getnchannels()

Return the number of audio channels (1 for mono, 2 for stereo).

getsampwidth()

Return the size in bytes of individual samples.

getframerate()

Return the sampling rate (number of audio frames per second).

getnframes()

Return the number of audio frames in the file.

getcomptype()

Return a four-character string describing the type of compression used in the audio file. For AIFF files, the returned value is `'NONE'`.

getcompname()

Return a human-readable description of the type of compression used in the audio file. For AIFF files, the

returned value is 'not compressed'.

getparams()

Return a tuple consisting of all of the above values in the above order.

getmarkers()

Return a list of markers in the audio file. A marker consists of a tuple of three elements. The first is the mark ID (an integer), the second is the mark position in frames from the beginning of the data (an integer), the third is the name of the mark (a string).

getmark(*id*)

Return the tuple as described in `getmarkers()` for the mark with the given *id*.

readframes(*nframes*)

Read and return the next *nframes* frames from the audio file. The returned data is a string containing for each frame the uncompressed samples of all channels.

rewind()

Rewind the read pointer. The next `readframes()` will start from the beginning.

setpos(*pos*)

Seek to the specified frame number.

tell()

Return the current frame number.

close()

Close the AIFF file. After calling this method, the object can no longer be used.

Objects returned by `open()` when a file is opened for writing have all the above methods, except for `readframes()` and `setpos()`. In addition the following methods exist. The `get*()` methods can only be called after the corresponding `set*()` methods have been called. Before the first `writeframes()` or `writewframesraw()`, all parameters except for the number of frames must be filled in.

aiff()

Create an AIFF file. The default is that an AIFF-C file is created, unless the name of the file ends in '.aiff' in which case the default is an AIFF file.

aifc()

Create an AIFF-C file. The default is that an AIFF-C file is created, unless the name of the file ends in '.aiff' in which case the default is an AIFF file.

setnchannels(*nchannels*)

Specify the number of channels in the audio file.

setsampwidth(*width*)

Specify the size in bytes of audio samples.

setframerate(*rate*)

Specify the sampling frequency in frames per second.

setnframes(*nframes*)

Specify the number of frames that are to be written to the audio file. If this parameter is not set, or not set correctly, the file needs to support seeking.

setcomptype(*type, name*)

Specify the compression type. If not specified, the audio data will not be compressed. In AIFF files, compression is not possible. The name parameter should be a human-readable description of the compression type, the type parameter should be a four-character string. Currently the following compression types are supported: NONE, ULAW, ALAW, G722.

setparams(*nchannels, sampwidth, framerate, comptype, compname*)

Set all the above parameters at once. The argument is a tuple consisting of the various parameters. This means

that it is possible to use the result of a `getparams()` call as argument to `setparams()`.

setmark(*id, pos, name*)

Add a mark with the given *id* (larger than 0), and the given *name* at the given position. This method can be called at any time before `close()`.

tell()

Return the current write position in the output file. Useful in combination with `setmark()`.

writeframes(*data*)

Write *data* to the output file. This method can only be called after the audio file parameters have been set.

writeframesraw(*data*)

Like `writeframes()`, except that the header of the audio file is not updated.

close()

Close the AIFF file. The header of the file is updated to reflect the actual size of the audio data. After calling this method, the object can no longer be used.

14.4 sunau — Read and write Sun AU files

The `sunau` module provides a convenient interface to the Sun AU sound format. Note that this module is interface-compatible with the modules `aifc` and `wave`.

The `sunau` module defines the following functions:

open(*file, mode*)

If *file* is a string, open the file by that name, otherwise treat it as a seekable file-like object. *mode* can be any of

'r' Read only mode.

'w' Write only mode.

Note that it does not allow read/write files.

A *mode* of **'r'** returns a `AU_read` object, while a *mode* of **'w'** or **'wb'** returns a `AU_write` object.

openfp(*file, mode*)

A synonym for `open`, maintained for backwards compatibility.

The `sunau` module defines the following exception:

Error

An error raised when something is impossible because of Sun AU specs or implementation deficiency.

The `sunau` module defines the following data item:

AUDIO_FILE_MAGIC

An integer every valid Sun AU file begins with a big-endian encoding of.

14.4.1 AU_read Objects

`AU_read` objects, as returned by `open()` above, have the following methods:

close()

Close the stream, and make the instance unusable. (This is called automatically on deletion.)

getnchannels()

Returns number of audio channels (1 for mono, 2 for stereo).

getsampwidth()

Returns sample width in bytes.

getframerate()

Returns sampling frequency.

getnframes()

Returns number of audio frames.

getcomptype()

Returns compression type. Supported compression types are 'ULAW', 'ALAW' and 'NONE'.

getcompname()

Human-readable version of `getcomptype()`. The supported types have the respective names 'CCITT G.711 u-law', 'CCITT G.711 A-law' and 'not compressed'.

getparams()

Returns a tuple (*nchannels*, *sampwidth*, *framerate*, *nframes*, *comptype*, *compname*), equivalent to output of the `get*()` methods.

readframes(*n*)

Reads and returns at most *n* frames of audio, as a string of bytes.

rewind()

Rewind the file pointer to the beginning of the audio stream.

The following two methods define a term “position” which is compatible between them, and is otherwise implementation dependant.

setpos(*pos*)

Set the file pointer to the specified position.

tell()

Return current file pointer position.

The following two functions are defined for compatibility with the `aifc`, and don't do anything interesting.

getmarkers()

Returns None.

getmark(*id*)

Raise an error.

14.4.2 AU_write Objects

AU_write objects, as returned by `open()` above, have the following methods:

setnchannels(*n*)

Set the number of channels.

setsampwidth(*n*)

Set the sample width (in bytes.)

setframerate(*n*)

Set the frame rate.

setnframes(*n*)

Set the number of frames. This can be later changed, when and if more frames are written.

setcomptype(*type*, *name*)

Set the compression type and description. Only 'NONE' and 'ULAW' are supported on output.

setparams(*tuple*)

The *tuple* should be (*nchannels*, *sampwidth*, *framerate*, *nframes*, *comptype*, *compname*), with values valid for the `set*()` methods. Set all parameters.

tell()

Return current position in the file, with the same disclaimer for the `AU_read.tell()` and `AU_read.setpos()` methods.

writeframesraw(*data*)

Write audio frames, without correcting *nframes*.

writeframes(*data*)

Write audio frames and make sure *nframes* is correct.

close()

Make sure *nframes* is correct, and close the file.

This method is called upon deletion.

Note that it is invalid to set any parameters after calling `writeframes()` or `writeframesraw()`.

14.5 wave — Read and write WAV files

The `wave` module provides a convenient interface to the WAV sound format. It does not support compression/decompression, but it does support mono/stereo.

The `wave` module defines the following function and exception:

open(*file*[, *mode*])

If *file* is a string, open the file by that name, other treat it as a seekable file-like object. *mode* can be any of

'r', 'rb' Read only mode.

'w', 'wb' Write only mode.

Note that it does not allow read/write WAV files.

A *mode* of `'r'` or `'rb'` returns a `Wave_read` object, while a *mode* of `'w'` or `'wb'` returns a `Wave_write` object. If *mode* is omitted and a file-like object is passed as *file*, *file*.*mode* is used as the default value for *mode* (the `'b'` flag is still added if necessary).

openfp(*file*, *mode*)

A synonym for `open()`, maintained for backwards compatibility.

Error

An error raised when something is impossible because it violates the WAV specification or hits an implementation deficiency.

14.5.1 Wave_read Objects

`Wave_read` objects, as returned by `open()`, have the following methods:

close()

Close the stream, and make the instance unusable. This is called automatically on object collection.

getnchannels()

Returns number of audio channels (1 for mono, 2 for stereo).

getsampwidth()

Returns sample width in bytes.

getframerate()

Returns sampling frequency.

getnframes()

Returns number of audio frames.

getcomptype()

Returns compression type ('NONE' is the only supported type).

getcompname()

Human-readable version of `getcomptype()`. Usually 'not compressed' parallels 'NONE'.

getparams()

Returns a tuple (*nchannels*, *sampwidth*, *framerate*, *nframes*, *comptype*, *compname*), equivalent to output of the `get*()` methods.

readframes(*n*)

Reads and returns at most *n* frames of audio, as a string of bytes.

rewind()

Rewind the file pointer to the beginning of the audio stream.

The following two methods are defined for compatibility with the `aifc` module, and don't do anything interesting.

getmarkers()

Returns None.

getmark(*id*)

Raise an error.

The following two methods define a term "position" which is compatible between them, and is otherwise implementation dependant.

setpos(*pos*)

Set the file pointer to the specified position.

tell()

Return current file pointer position.

14.5.2 Wave_write Objects

Wave_write objects, as returned by `open()`, have the following methods:

close()

Make sure *nframes* is correct, and close the file. This method is called upon deletion.

setnchannels(*n*)

Set the number of channels.

setsampwidth(*n*)

Set the sample width to *n* bytes.

setframerate(*n*)

Set the frame rate to *n*.

setnframes(*n*)

Set the number of frames to *n*. This will be changed later if more frames are written.

setcomptype(*type*, *name*)

Set the compression type and description.

setparams(*tuple*)

The *tuple* should be (*nchannels*, *sampwidth*, *framerate*, *nframes*, *comptype*, *compname*), with values valid for the `set*()` methods. Sets all parameters.

tell()

Return current position in the file, with the same disclaimer for the `Wave_read.tell()` and `Wave_read.setpos()` methods.

writeframesraw(*data*)

Write audio frames, without correcting *nframes*.

writeframes(*data*)

Write audio frames and make sure *nframes* is correct.

Note that it is invalid to set any parameters after calling `writeframes()` or `writeframesraw()`, and any attempt to do so will raise `wave.Error`.

14.6 chunk — Read IFF chunked data

This module provides an interface for reading files that use EA IFF 85 chunks.¹ This format is used in at least the Audio Interchange File Format (AIFF/AIFF-C) and the Real Media File Format (RMFF). The WAVE audio file format is closely related and can also be read using this module.

A chunk has the following structure:

Offset	Length	Contents
0	4	Chunk ID
4	4	Size of chunk in big-endian byte order, not including the header
8	<i>n</i>	Data bytes, where <i>n</i> is the size given in the preceding field
8 + <i>n</i>	0 or 1	Pad byte needed if <i>n</i> is odd and chunk alignment is used

The ID is a 4-byte string which identifies the type of chunk.

The size field (a 32-bit value, encoded using big-endian byte order) gives the size of the chunk data, not including the 8-byte header.

Usually an IFF-type file consists of one or more chunks. The proposed usage of the `Chunk` class defined here is to instantiate an instance at the start of each chunk and read from the instance until it reaches the end, after which a new instance can be instantiated. At the end of the file, creating a new instance will fail with a `EOFError` exception.

Chunk(*file*[, *align*, *bigendian*, *inclheader*])

Class which represents a chunk. The *file* argument is expected to be a file-like object. An instance of this class is specifically allowed. The only method that is needed is `read()`. If the methods `seek()` and `tell()` are present and don't raise an exception, they are also used. If these methods are present and raise an exception, they are expected to not have altered the object. If the optional argument *align* is true, chunks are assumed to be aligned on 2-byte boundaries. If *align* is false, no alignment is assumed. The default value is true. If the optional argument *bigendian* is false, the chunk size is assumed to be in little-endian order. This is needed for WAVE audio files. The default value is true. If the optional argument *inclheader* is true, the size given in the chunk header includes the size of the header. The default value is false.

A `Chunk` object supports the following methods:

getname()

Returns the name (ID) of the chunk. This is the first 4 bytes of the chunk.

getsize()

Returns the size of the chunk.

close()

Close and skip to the end of the chunk. This does not close the underlying file.

The remaining methods will raise `IOError` if called after the `close()` method has been called.

isatty()

Returns 0.

¹“EA IFF 85” Standard for Interchange Format Files, Jerry Morrison, Electronic Arts, January 1985.

seek(*pos*[, *whence*])

Set the chunk's current position. The *whence* argument is optional and defaults to 0 (absolute file positioning); other values are 1 (seek relative to the current position) and 2 (seek relative to the file's end). There is no return value. If the underlying file does not allow seek, only forward seeks are allowed.

tell()

Return the current position into the chunk.

read([*size*])

Read at most *size* bytes from the chunk (less if the read hits the end of the chunk before obtaining *size* bytes). If the *size* argument is negative or omitted, read all data until the end of the chunk. The bytes are returned as a string object. An empty string is returned when the end of the chunk is encountered immediately.

skip()

Skip to the end of the chunk. All further calls to `read()` for the chunk will return ''. If you are not interested in the contents of the chunk, this method should be called so that the file points to the start of the next chunk.

14.7 colorsys — Conversions between color systems

The `colorsys` module defines bidirectional conversions of color values between colors expressed in the RGB (Red Green Blue) color space used in computer monitors and three other coordinate systems: YIQ, HLS (Hue Lightness Saturation) and HSV (Hue Saturation Value). Coordinates in all of these color spaces are floating point values. In the YIQ space, the Y coordinate is between 0 and 1, but the I and Q coordinates can be positive or negative. In all other spaces, the coordinates are all between 0 and 1.

More information about color spaces can be found at <http://www.inforamp.net/%7epoynton/ColorFAQ.html>.

The `colorsys` module defines the following functions:

rgb_to_yiq(*r*, *g*, *b*)

Convert the color from RGB coordinates to YIQ coordinates.

yiq_to_rgb(*y*, *i*, *q*)

Convert the color from YIQ coordinates to RGB coordinates.

rgb_to_hls(*r*, *g*, *b*)

Convert the color from RGB coordinates to HLS coordinates.

hls_to_rgb(*h*, *l*, *s*)

Convert the color from HLS coordinates to RGB coordinates.

rgb_to_hsv(*r*, *g*, *b*)

Convert the color from RGB coordinates to HSV coordinates.

hsv_to_rgb(*h*, *s*, *v*)

Convert the color from HSV coordinates to RGB coordinates.

Example:

```
>>> import colorsys
>>> colorsys.rgb_to_hsv(.3, .4, .2)
(0.25, 0.5, 0.4)
>>> colorsys.hsv_to_rgb(0.25, 0.5, 0.4)
(0.3, 0.4, 0.2)
```

14.8 `rgbimg` — Read and write “SGI RGB” files

The `rgbimg` module allows Python programs to access SGI `imglib` image files (also known as ‘.rgb’ files). The module is far from complete, but is provided anyway since the functionality that there is enough in some cases. Currently, colormap files are not supported.

The module defines the following variables and functions:

error

This exception is raised on all errors, such as unsupported file type, etc.

sizeofimage(*file*)

This function returns a tuple (*x*, *y*) where *x* and *y* are the size of the image in pixels. Only 4 byte RGBA pixels, 3 byte RGB pixels, and 1 byte greyscale pixels are currently supported.

longimagedata(*file*)

This function reads and decodes the image on the specified file, and returns it as a Python string. The string has 4 byte RGBA pixels. The bottom left pixel is the first in the string. This format is suitable to pass to `gl.glRectwrite()`, for instance.

longstoimage(*data*, *x*, *y*, *z*, *file*)

This function writes the RGBA data in *data* to image file *file*. *x* and *y* give the size of the image. *z* is 1 if the saved image should be 1 byte greyscale, 3 if the saved image should be 3 byte RGB data, or 4 if the saved images should be 4 byte RGBA data. The input data always contains 4 bytes per pixel. These are the formats returned by `gl.glRectread()`.

ttob(*flag*)

This function sets a global flag which defines whether the scan lines of the image are read or written from bottom to top (*flag* is zero, compatible with SGI GL) or from top to bottom (*flag* is one, compatible with X). The default is zero.

14.9 `imghdr` — Determine the type of an image.

The `imghdr` module determines the type of image contained in a file or byte stream.

The `imghdr` module defines the following function:

what(*filename*[, *h*])

Tests the image data contained in the file named by *filename*, and returns a string describing the image type. If optional *h* is provided, the *filename* is ignored and *h* is assumed to contain the byte stream to test.

The following image types are recognized, as listed below with the return value from `what()`:

Value	Image format
'rgb'	SGI ImgLib Files
'gif'	GIF 87a and 89a Files
'pbm'	Portable Bitmap Files
'pgm'	Portable Graymap Files
'ppm'	Portable Pixmap Files
'tiff'	TIFF Files
'rast'	Sun Raster Files
'xbm'	X Bitmap Files
'jpeg'	JPEG data in JFIF format
'bmp'	BMP files
'png'	Portable Network Graphics

You can extend the list of file types `imghdr` can recognize by appending to this variable:

tests

A list of functions performing the individual tests. Each function takes two arguments: the byte-stream and an open file-like object. When `what()` is called with a byte-stream, the file-like object will be `None`.

The test function should return a string describing the image type if the test succeeded, or `None` if it failed.

Example:

```
>>> import imghdr
>>> imghdr.what('/tmp/bass.gif')
'gif'
```

14.10 sndhdr — Determine type of sound file.

The `sndhdr` provides utility functions which attempt to determine the type of sound data which is in a file. When these functions are able to determine what type of sound data is stored in a file, they return a tuple (*type*, *sampling_rate*, *channels*, *frames*, *bits_per_sample*). The value for *type* indicates the data type and will be one of the strings 'aifc', 'aiff', 'au', 'hcom', 'sndr', 'sndt', 'voc', 'wav', '8svx', 'sb', 'ub', or 'ul'. The *sampling_rate* will be either the actual value or 0 if unknown or difficult to decode. Similarly, *channels* will be either the number of channels or 0 if it cannot be determined or if the value is difficult to decode. The value for *frames* will be either the number of frames or -1. The last item in the tuple, *bits_per_sample*, will either be the sample size in bits or 'A' for A-LAW or 'U' for u-LAW.

what(*filename*)

Determines the type of sound data stored in the file *filename* using `whathdr()`. If it succeeds, returns a tuple as described above, otherwise `None` is returned.

whathdr(*filename*)

Determines the type of sound data stored in a file based on the file header. The name of the file is given by *filename*. This function returns a tuple as described above on success, or `None`.

Cryptographic Services

The modules described in this chapter implement various algorithms of a cryptographic nature. They are available at the discretion of the installation. Here's an overview:

- md5** RSA's MD5 message digest algorithm.
- sha** NIST's secure hash algorithm, SHA.
- mpz** Interface to the GNU MP library for arbitrary precision arithmetic.
- rotor** Enigma-like encryption and decryption.

Hardcore cypherpunks will probably find the cryptographic modules written by Andrew Kuchling of further interest; the package adds built-in modules for DES and IDEA encryption, provides a Python module for reading and decrypting PGP files, and then some. These modules are not distributed with Python but available separately. See the URL <http://starship.python.net/crew/amk/python/crypto.html> or send email to akuchlin@acm.org for more information.

15.1 md5 — MD5 message digest algorithm

This module implements the interface to RSA's MD5 message digest algorithm (see also Internet RFC 1321). Its use is quite straightforward: use the `new()` to create an `md5` object. You can now feed this object with arbitrary strings using the `update()` method, and at any point you can ask it for the *digest* (a strong kind of 128-bit checksum, a.k.a. "fingerprint") of the concatenation of the strings fed to it so far using the `digest()` method.

For example, to obtain the digest of the string 'Nobody inspects the spammish repetition':

```
>>> import md5
>>> m = md5.new()
>>> m.update("Nobody inspects")
>>> m.update(" the spammish repetition")
>>> m.digest()
'\273d\234\203\335\036\245\311\331\336\311\241\215\360\377\351'
```

More condensed:

```
>>> md5.new("Nobody inspects the spammish repetition").digest()
'\273d\234\203\335\036\245\311\331\336\311\241\215\360\377\351'
```

new(`[arg]`)

Return a new `md5` object. If `arg` is present, the method call `update(arg)` is made.

md5(`[arg]`)

For backward compatibility reasons, this is an alternative name for the `new()` function.

An `md5` object has the following methods:

update(*arg*)

Update the `md5` object with the string *arg*. Repeated calls are equivalent to a single call with the concatenation of all the arguments, i.e. `m.update(a)`; `m.update(b)` is equivalent to `m.update(a+b)`.

digest()

Return the digest of the strings passed to the `update()` method so far. This is an 16-byte string which may contain non-ASCII characters, including null bytes.

copy()

Return a copy (“clone”) of the `md5` object. This can be used to efficiently compute the digests of strings that share a common initial substring.

15.2 sha — SHA message digest algorithm

This module implements the interface to NIST’s secure hash algorithm, known as SHA. It is used in the same way as the `md5` module: use the `new()` to create an `sha` object, then feed this object with arbitrary strings using the `update()` method, and at any point you can ask it for the *digest* of the contatenation of the strings fed to it so far. SHA digests are 160 bits instead of 128 bits.

new([*string*])

Return a new `sha` object. If *string* is present, the method call `update(string)` is made.

The following values are provided as constants in the module and as attributes of the `sha` objects returned by `new()`:

blocksize

Size of the blocks fed into the hash function; this is always 1. This size is used to allow an arbitrary string to be hashed.

digestsize

The size of the resulting digest in bytes. This is always 20.

A `sha` object has all the methods the `md5` objects have, plus one:

hexdigest()

Return the digest value as a string of hexadecimal digits. This may be used to exchange the value safely in email or other non-binary environments.

See Also:

The Secure Hash Algorithm is defined by NIST document FIPS PUB 180-1: *Secure Hash Standard*, published in April of 1995. It is available online as plain text at <http://csrc.nist.gov/fips/fip180-1.txt> (at least one diagram was omitted) and as PostScript at <http://csrc.nist.gov/fips/fip180-1.ps>.

15.3 mpz — GNU arbitrary magnitude integers

This is an optional module. It is only available when Python is configured to include it, which requires that the GNU MP software is installed.

This module implements the interface to part of the GNU MP library, which defines arbitrary precision integer and rational number arithmetic routines. Only the interfaces to the *integer* (`mpz_*()`) routines are provided. If not stated otherwise, the description in the GNU MP documentation can be applied.

Support for rational numbers can be implemented in Python. For an example, see the `Rat` module, provided as ‘Demos/classes/Rat.py’ in the Python source distribution.

In general, *mpz*-numbers can be used just like other standard Python numbers, e.g., you can use the built-in operators like `+`, `*`, etc., as well as the standard built-in functions like `abs()`, `int()`, ..., `divmod()`, `pow()`. **Please note:** the *bitwise-xor* operation has been implemented as a bunch of *ands*, *inverts* and *ors*, because the library lacks an `mpz_xor()` function, and I didn't need one.

You create an *mpz*-number by calling the function `mpz()` (see below for an exact description). An *mpz*-number is printed like this: `mpz(value)`.

mpz(value)

Create a new *mpz*-number. *value* can be an integer, a long, another *mpz*-number, or even a string. If it is a string, it is interpreted as an array of radix-256 digits, least significant digit first, resulting in a positive number. See also the `binary()` method, described below.

MPZType

The type of the objects returned by `mpz()` and most other functions in this module.

A number of *extra* functions are defined in this module. Non *mpz*-arguments are converted to *mpz*-values first, and the functions return *mpz*-numbers.

powm(base, exponent, modulus)

Return `pow(base, exponent) % modulus`. If *exponent* == 0, return `mpz(1)`. In contrast to the C library function, this version can handle negative exponents.

gcd(op1, op2)

Return the greatest common divisor of *op1* and *op2*.

gcdext(a, b)

Return a tuple (g, s, t) , such that $a*s + b*t == g == \text{gcd}(a, b)$.

sqrt(op)

Return the square root of *op*. The result is rounded towards zero.

sqrrem(op)

Return a tuple $(root, remainder)$, such that $root*root + remainder == op$.

divm(numerator, denominator, modulus)

Returns a number *q* such that $q * denominator \% modulus == numerator$. One could also implement this function in Python, using `gcdext()`.

An *mpz*-number has one method:

binary()

Convert this *mpz*-number to a binary string, where the number has been stored as an array of radix-256 digits, least significant digit first.

The *mpz*-number must have a value greater than or equal to zero, otherwise `ValueError` will be raised.

15.4 rotor — Enigma-like encryption and decryption.

This module implements a rotor-based encryption algorithm, contributed by Lance Ellinghouse. The design is derived from the Enigma device, a machine used during World War II to encipher messages. A rotor is simply a permutation. For example, if the character 'A' is the origin of the rotor, then a given rotor might map 'A' to 'L', 'B' to 'Z', 'C' to 'G', and so on. To encrypt, we choose several different rotors, and set the origins of the rotors to known positions; their initial position is the ciphering key. To encipher a character, we permute the original character by the first rotor, and then apply the second rotor's permutation to the result. We continue until we've applied all the rotors; the resulting character is our ciphertext. We then change the origin of the final rotor by one position, from 'A' to 'B'; if the final rotor has made a complete revolution, then we rotate the next-to-last rotor by one position, and apply the same procedure recursively. In other words, after enciphering one character, we advance the rotors in the same fashion as a car's odometer. Decoding works in the same way, except we reverse the permutations and apply them in the opposite order.

The available functions in this module are:

newrotor (*key*[, *numrotors*])

Return a rotor object. *key* is a string containing the encryption key for the object; it can contain arbitrary binary data. The key will be used to randomly generate the rotor permutations and their initial positions. *numrotors* is the number of rotor permutations in the returned object; if it is omitted, a default value of 6 will be used.

Rotor objects have the following methods:

setkey (*key*)

Sets the rotor's key to *key*.

encrypt (*plaintext*)

Reset the rotor object to its initial state and encrypt *plaintext*, returning a string containing the ciphertext. The ciphertext is always the same length as the original plaintext.

encryptmore (*plaintext*)

Encrypt *plaintext* without resetting the rotor object, and return a string containing the ciphertext.

decrypt (*ciphertext*)

Reset the rotor object to its initial state and decrypt *ciphertext*, returning a string containing the ciphertext. The plaintext string will always be the same length as the ciphertext.

decryptmore (*ciphertext*)

Decrypt *ciphertext* without resetting the rotor object, and return a string containing the ciphertext.

An example usage:

```
>>> import rotor
>>> rt = rotor.newrotor('key', 12)
>>> rt.encrypt('bar')
'\2534\363'
>>> rt.encryptmore('bar')
'\357\375$'
>>> rt.encrypt('bar')
'\2534\363'
>>> rt.decrypt('\2534\363')
'bar'
>>> rt.decryptmore('\357\375$')
'bar'
>>> rt.decrypt('\357\375$')
'l(\315'
>>> del rt
```

The module's code is not an exact simulation of the original Enigma device; it implements the rotor encryption scheme differently from the original. The most important difference is that in the original Enigma, there were only 5 or 6 different rotors in existence, and they were applied twice to each character; the cipher key was the order in which they were placed in the machine. The Python `rotor` module uses the supplied key to initialize a random number generator; the rotor permutations and their initial positions are then randomly generated. The original device only enciphered the letters of the alphabet, while this module can handle any 8-bit binary data; it also produces binary output. This module can also operate with an arbitrary number of rotors.

The original Enigma cipher was broken in 1944. The version implemented here is probably a good deal more difficult to crack (especially if you use many rotors), but it won't be impossible for a truly skilful and determined attacker to break the cipher. So if you want to keep the NSA out of your files, this rotor cipher may well be unsafe, but for discouraging casual snooping through your files, it will probably be just fine, and may be somewhat safer than using the UNIX **crypt** command.

SGI IRIX Specific Services

The modules described in this chapter provide interfaces to features that are unique to SGI's IRIX operating system (versions 4 and 5).

a1	Audio functions on the SGI.
AL	Constants used with the <code>a1</code> module.
cd	Interface to the CD-ROM on Silicon Graphics systems.
fl	FORMS library interface for GUI applications.
FL	Constants used with the <code>fl</code> module.
flp	Functions for loading stored FORMS designs.
fm	<i>Font Manager</i> interface for SGI workstations.
gl	Functions from the Silicon Graphics <i>Graphics Library</i> .
DEVICE	Constants used with the <code>gl</code> module.
GL	Constants used with the <code>gl</code> module.
imgfile	Support for SGI <code>imglib</code> files.
jpeg	Read and write image files in compressed JPEG format.

16.1 a1 — Audio functions on the SGI

This module provides access to the audio facilities of the SGI Indy and Indigo workstations. See section 3A of the IRIX man pages for details. You'll need to read those man pages to understand what these functions do! Some of the functions are not available in IRIX releases before 4.0.5. Again, see the manual to check whether a specific function is available on your platform.

All functions and methods defined in this module are equivalent to the C functions with 'AL' prefixed to their name.

Symbolic constants from the C header file `<audio.h>` are defined in the standard module `AL`, see below.

Warning: the current version of the audio library may dump core when bad argument values are passed rather than returning an error status. Unfortunately, since the precise circumstances under which this may happen are undocumented and hard to check, the Python interface can provide no protection against this kind of problems. (One example is specifying an excessive queue size — there is no documented upper limit.)

The module defines the following functions:

openport (*name*, *direction*[, *config*])

The name and direction arguments are strings. The optional *config* argument is a configuration object as returned by `newconfig()`. The return value is an *audio port object*; methods of audio port objects are described below.

newconfig ()

The return value is a new *audio configuration object*; methods of audio configuration objects are described below.

queryparams (*device*)

The *device* argument is an integer. The return value is a list of integers containing the data returned by `ALqueryparams()`.

getparams(*device, list*)

The *device* argument is an integer. The *list* argument is a list such as returned by `queryparams()`; it is modified in place (!).

setparams(*device, list*)

The *device* argument is an integer. The *list* argument is a list such as returned by `queryparams()`.

16.1.1 Configuration Objects

Configuration objects (returned by `newconfig()`) have the following methods:

getqueuesize()

Return the queue size.

setqueuesize(*size*)

Set the queue size.

getwidth()

Get the sample width.

setwidth(*width*)

Set the sample width.

getchannels()

Get the channel count.

setchannels(*nchannels*)

Set the channel count.

getsampfmt()

Get the sample format.

setsampfmt(*sampfmt*)

Set the sample format.

getfloatmax()

Get the maximum value for floating sample formats.

setfloatmax(*floatmax*)

Set the maximum value for floating sample formats.

16.1.2 Port Objects

Port objects, as returned by `openport()`, have the following methods:

closeport()

Close the port.

getfd()

Return the file descriptor as an int.

getfilled()

Return the number of filled samples.

getfillable()

Return the number of fillable samples.

readsamps(*nsamples*)

Read a number of samples from the queue, blocking if necessary. Return the data as a string containing the raw data, (e.g., 2 bytes per sample in big-endian byte order (high byte, low byte) if you have set the sample width to 2 bytes).

writesamps(*samples*)

Write samples into the queue, blocking if necessary. The samples are encoded as described for the `readsamps()` return value.

getfillpoint()

Return the 'fill point'.

setfillpoint(*fillpoint*)

Set the 'fill point'.

getconfig()

Return a configuration object containing the current configuration of the port.

setconfig(*config*)

Set the configuration from the argument, a configuration object.

getstatus(*list*)

Get status information on last error.

16.2 AL — Constants used with the `al` module

This module defines symbolic constants needed to use the built-in module `al` (see above); they are equivalent to those defined in the C header file `<audio.h>` except that the name prefix 'AL_' is omitted. Read the module source for a complete list of the defined names. Suggested use:

```
import al
from AL import *
```

16.3 `cd` — CD-ROM access on SGI systems

This module provides an interface to the Silicon Graphics CD library. It is available only on Silicon Graphics systems.

The way the library works is as follows. A program opens the CD-ROM device with `open()` and creates a parser to parse the data from the CD with `createparser()`. The object returned by `open()` can be used to read data from the CD, but also to get status information for the CD-ROM device, and to get information about the CD, such as the table of contents. Data from the CD is passed to the parser, which parses the frames, and calls any callback functions that have previously been added.

An audio CD is divided into *tracks* or *programs* (the terms are used interchangeably). Tracks can be subdivided into *indices*. An audio CD contains a *table of contents* which gives the starts of the tracks on the CD. Index 0 is usually the pause before the start of a track. The start of the track as given by the table of contents is normally the start of index 1.

Positions on a CD can be represented in two ways. Either a frame number or a tuple of three values, minutes, seconds and frames. Most functions use the latter representation. Positions can be both relative to the beginning of the CD, and to the beginning of the track.

Module `cd` defines the following functions and constants:

createparser()

Create and return an opaque parser object. The methods of the parser object are described below.

msftoframe (*minutes, seconds, frames*)

Converts a (*minutes, seconds, frames*) triple representing time in absolute time code into the corresponding CD frame number.

open ([*device* [, *mode*]])

Open the CD-ROM device. The return value is an opaque player object; methods of the player object are described below. The device is the name of the SCSI device file, e.g. `'/dev/scsi/sc0d410'`, or `None`. If omitted or `None`, the hardware inventory is consulted to locate a CD-ROM drive. The *mode*, if not omitted, should be the string `'r'`.

The module defines the following variables:

error

Exception raised on various errors.

DATASIZE

The size of one frame's worth of audio data. This is the size of the audio data as passed to the callback of type `audio`.

BLOCKSIZE

The size of one uninterpreted frame of audio data.

The following variables are states as returned by `getstatus()`:

READY

The drive is ready for operation loaded with an audio CD.

NODISC

The drive does not have a CD loaded.

CDROM

The drive is loaded with a CD-ROM. Subsequent play or read operations will return I/O errors.

ERROR

An error occurred while trying to read the disc or its table of contents.

PLAYING

The drive is in CD player mode playing an audio CD through its audio jacks.

PAUSED

The drive is in CD layer mode with play paused.

STILL

The equivalent of `PAUSED` on older (non 3301) model Toshiba CD-ROM drives. Such drives have never been shipped by SGI.

audio

pnum

index

ptime

atime

catalog

ident

control

Integer constants describing the various types of parser callbacks that can be set by the `addcallback()` method of CD parser objects (see below).

16.3.1 Player Objects

Player objects (returned by `open()`) have the following methods:

allowremoval()

Unlocks the eject button on the CD-ROM drive permitting the user to eject the caddy if desired.

bestreadsize()

Returns the best value to use for the *num_frames* parameter of the `reada()` method. Best is defined as the value that permits a continuous flow of data from the CD-ROM drive.

close()

Frees the resources associated with the player object. After calling `close()`, the methods of the object should no longer be used.

eject()

Ejects the caddy from the CD-ROM drive.

getstatus()

Returns information pertaining to the current state of the CD-ROM drive. The returned information is a tuple with the following values: *state*, *track*, *rtime*, *atime*, *ttime*, *first*, *last*, *scsi_audio*, *cur_block*. *rtime* is the time relative to the start of the current track; *atime* is the time relative to the beginning of the disc; *ttime* is the total time on the disc. For more information on the meaning of the values, see the man page `CDgetstatus(3dm)`. The value of *state* is one of the following: `ERROR`, `NODISC`, `READY`, `PLAYING`, `PAUSED`, `STILL`, or `CDROM`.

gettrackinfo(track)

Returns information about the specified track. The returned information is a tuple consisting of two elements, the start time of the track and the duration of the track.

msftoblock(min, sec, frame)

Converts a minutes, seconds, frames triple representing a time in absolute time code into the corresponding logical block number for the given CD-ROM drive. You should use `msftoframe()` rather than `msftoblock()` for comparing times. The logical block number differs from the frame number by an offset required by certain CD-ROM drives.

play(start, play)

Starts playback of an audio CD in the CD-ROM drive at the specified track. The audio output appears on the CD-ROM drive's headphone and audio jacks (if fitted). Play stops at the end of the disc. *start* is the number of the track at which to start playing the CD; if *play* is 0, the CD will be set to an initial paused state. The method `togglepause()` can then be used to commence play.

playabs(minutes, seconds, frames, play)

Like `play()`, except that the start is given in minutes, seconds, and frames instead of a track number.

playtrack(start, play)

Like `play()`, except that playing stops at the end of the track.

playtrackabs(track, minutes, seconds, frames, play)

Like `play()`, except that playing begins at the specified absolute time and ends at the end of the specified track.

preventremoval()

Locks the eject button on the CD-ROM drive thus preventing the user from arbitrarily ejecting the caddy.

reada(num_frames)

Reads the specified number of frames from an audio CD mounted in the CD-ROM drive. The return value is a string representing the audio frames. This string can be passed unaltered to the `parseframe()` method of the parser object.

seek(minutes, seconds, frames)

Sets the pointer that indicates the starting point of the next read of digital audio data from a CD-ROM. The pointer is set to an absolute time code location specified in *minutes*, *seconds*, and *frames*. The return value is the logical block number to which the pointer has been set.

seekblock(block)

Sets the pointer that indicates the starting point of the next read of digital audio data from a CD-ROM. The

pointer is set to the specified logical block number. The return value is the logical block number to which the pointer has been set.

seektrack(*track*)

Sets the pointer that indicates the starting point of the next read of digital audio data from a CD-ROM. The pointer is set to the specified track. The return value is the logical block number to which the pointer has been set.

stop()

Stops the current playing operation.

togglepause()

Pauses the CD if it is playing, and makes it play if it is paused.

16.3.2 Parser Objects

Parser objects (returned by `createparser()`) have the following methods:

addcallback(*type, func, arg*)

Adds a callback for the parser. The parser has callbacks for eight different types of data in the digital audio data stream. Constants for these types are defined at the `cd` module level (see above). The callback is called as follows: `func(arg, type, data)`, where *arg* is the user supplied argument, *type* is the particular type of callback, and *data* is the data returned for this *type* of callback. The type of the data depends on the *type* of callback as follows:

Type	Value
audio	String which can be passed unmodified to <code>al.writesamps()</code> .
pnum	Integer giving the program (track) number.
index	Integer giving the index number.
ptime	Tuple consisting of the program time in minutes, seconds, and frames.
atime	Tuple consisting of the absolute time in minutes, seconds, and frames.
catalog	String of 13 characters, giving the catalog number of the CD.
ident	String of 12 characters, giving the ISRC identification number of the recording. The string consists of two characters country code, three characters owner code, two characters giving the year, and five characters giving a serial number.
control	Integer giving the control bits from the CD subcode data

deleteparser()

Deletes the parser and frees the memory it was using. The object should not be used after this call. This call is done automatically when the last reference to the object is removed.

parseframe(*frame*)

Parses one or more frames of digital audio data from a CD such as returned by `readdata()`. It determines which subcodes are present in the data. If these subcodes have changed since the last frame, then `parseframe()` executes a callback of the appropriate type passing to it the subcode data found in the frame. Unlike the `C` function, more than one frame of digital audio data can be passed to this method.

removecallback(*type*)

Removes the callback for the given *type*.

resetparser()

Resets the fields of the parser used for tracking subcodes to an initial state. `resetparser()` should be called after the disc has been changed.

16.4 fl — FORMS library interface for GUI applications

This module provides an interface to the FORMS Library by Mark Overmars. The source for the library can be retrieved by anonymous ftp from host 'ftp.cs.ruu.nl', directory 'SGI/FORMS'. It was last tested with version 2.0b.

Most functions are literal translations of their C equivalents, dropping the initial 'fl_' from their name. Constants used by the library are defined in module `FL` described below.

The creation of objects is a little different in Python than in C: instead of the 'current form' maintained by the library to which new FORMS objects are added, all functions that add a FORMS object to a form are methods of the Python object representing the form. Consequently, there are no Python equivalents for the C functions `fl_addto_form()` and `fl_end_form()`, and the equivalent of `fl_bgn_form()` is called `fl.make_form()`.

Watch out for the somewhat confusing terminology: FORMS uses the word *object* for the buttons, sliders etc. that you can place in a form. In Python, 'object' means any value. The Python interface to FORMS introduces two new Python object types: form objects (representing an entire form) and FORMS objects (representing one button, slider etc.). Hopefully this isn't too confusing.

There are no 'free objects' in the Python interface to FORMS, nor is there an easy way to add object classes written in Python. The FORMS interface to GL event handling is available, though, so you can mix FORMS with pure GL windows.

Please note: importing `fl` implies a call to the GL function `foreground()` and to the FORMS routine `fl_init()`.

16.4.1 Functions Defined in Module `fl`

Module `fl` defines the following functions. For more information about what they do, see the description of the equivalent C function in the FORMS documentation:

make_form(*type, width, height*)

Create a form with given type, width and height. This returns a *form* object, whose methods are described below.

do_forms()

The standard FORMS main loop. Returns a Python object representing the FORMS object needing interaction, or the special value `FL.EVENT`.

check_forms()

Check for FORMS events. Returns what `do_forms()` above returns, or `None` if there is no event that immediately needs interaction.

set_event_callback(*function*)

Set the event callback function.

set_graphics_mode(*rgbmode, doublebuffering*)

Set the graphics modes.

get_rgbmode()

Return the current rgb mode. This is the value of the C global variable `fl_rgbmode`.

show_message(*str1, str2, str3*)

Show a dialog box with a three-line message and an OK button.

show_question(*str1, str2, str3*)

Show a dialog box with a three-line message and YES and NO buttons. It returns 1 if the user pressed YES, 0 if NO.

show_choice(*str1, str2, str3, but1[, but2[, but3]]*)

Show a dialog box with a three-line message and up to three buttons. It returns the number of the button clicked by the user (1, 2 or 3).

show_input(*prompt, default*)

Show a dialog box with a one-line prompt message and text field in which the user can enter a string. The second argument is the default input string. It returns the string value as edited by the user.

show_file_selector(*message, directory, pattern, default*)

Show a dialog box in which the user can select a file. It returns the absolute filename selected by the user, or None if the user presses Cancel.

get_directory()

get_pattern()

get_filename()

These functions return the directory, pattern and filename (the tail part only) selected by the user in the last `show_file_selector()` call.

qdevice(*dev*)

unqdevice(*dev*)

isqueued(*dev*)

qtest()

qread()

qreset()

qenter(*dev, val*)

get_mouse()

tie(*button, valuator1, valuator2*)

These functions are the FORMS interfaces to the corresponding GL functions. Use these if you want to handle some GL events yourself when using `fl.do_events()`. When a GL event is detected that FORMS cannot handle, `fl.do_forms()` returns the special value `FL.EVENT` and you should call `fl.qread()` to read the event from the queue. Don't use the equivalent GL functions!

color()

mapcolor()

getmcolor()

See the description in the FORMS documentation of `fl_color()`, `fl_mapcolor()` and `fl_getmcolor()`.

16.4.2 Form Objects

Form objects (returned by `make_form()` above) have the following methods. Each method corresponds to a C function whose name is prefixed with 'fl_'; and whose first argument is a form pointer; please refer to the official FORMS documentation for descriptions.

All the `add_*()` methods return a Python object representing the FORMS object. Methods of FORMS objects are described below. Most kinds of FORMS object also have some methods specific to that kind; these methods are listed here.

show_form(*placement, bordertype, name*)

Show the form.

hide_form()

Hide the form.

redraw_form()

Redraw the form.

set_form_position(*x, y*)

Set the form's position.

freeze_form()

Freeze the form.

unfreeze_form()
Unfreeze the form.

activate_form()
Activate the form.

deactivate_form()
Deactivate the form.

bgn_group()
Begin a new group of objects; return a group object.

end_group()
End the current group of objects.

find_first()
Find the first object in the form.

find_last()
Find the last object in the form.

add_box(*type, x, y, w, h, name*)
Add a box object to the form. No extra methods.

add_text(*type, x, y, w, h, name*)
Add a text object to the form. No extra methods.

add_clock(*type, x, y, w, h, name*)
Add a clock object to the form.
Method: `get_clock()`.

add_button(*type, x, y, w, h, name*)
Add a button object to the form.
Methods: `get_button()`, `set_button()`.

add_lightbutton(*type, x, y, w, h, name*)
Add a lightbutton object to the form.
Methods: `get_button()`, `set_button()`.

add_roundbutton(*type, x, y, w, h, name*)
Add a roundbutton object to the form.
Methods: `get_button()`, `set_button()`.

add_slider(*type, x, y, w, h, name*)
Add a slider object to the form.
Methods: `set_slider_value()`, `get_slider_value()`, `set_slider_bounds()`,
`get_slider_bounds()`, `set_slider_return()`, `set_slider_size()`,
`set_slider_precision()`, `set_slider_step()`.

add_valslider(*type, x, y, w, h, name*)
Add a valslider object to the form.
Methods: `set_slider_value()`, `get_slider_value()`, `set_slider_bounds()`,
`get_slider_bounds()`, `set_slider_return()`, `set_slider_size()`,
`set_slider_precision()`, `set_slider_step()`.

add_dial(*type, x, y, w, h, name*)
Add a dial object to the form.
Methods: `set_dial_value()`, `get_dial_value()`, `set_dial_bounds()`,
`get_dial_bounds()`.

add_positioner(*type, x, y, w, h, name*)
Add a positioner object to the form.

Methods: `set_positioner_xvalue()`, `set_positioner_yvalue()`,
`set_positioner_xbounds()`, `set_positioner_ybounds()`, `get_positioner_xvalue()`,
`get_positioner_yvalue()`, `get_positioner_xbounds()`, `get_positioner_ybounds()`.

add_counter (*type, x, y, w, h, name*)

Add a counter object to the form.

Methods: `set_counter_value()`, `get_counter_value()`, `set_counter_bounds()`,
`set_counter_step()`, `set_counter_precision()`, `set_counter_return()`.

add_input (*type, x, y, w, h, name*)

Add an input object to the form.

Methods: `set_input()`, `get_input()`, `set_input_color()`, `set_input_return()`.

add_menu (*type, x, y, w, h, name*)

Add a menu object to the form.

Methods: `set_menu()`, `get_menu()`, `addto_menu()`.

add_choice (*type, x, y, w, h, name*)

Add a choice object to the form.

Methods: `set_choice()`, `get_choice()`, `clear_choice()`, `addto_choice()`,
`replace_choice()`, `delete_choice()`, `get_choice_text()`, `set_choice_fontsize()`,
`set_choice_fontstyle()`.

add_browser (*type, x, y, w, h, name*)

Add a browser object to the form.

Methods: `set_browser_topline()`, `clear_browser()`, `add_browser_line()`,
`addto_browser()`, `insert_browser_line()`, `delete_browser_line()`,
`replace_browser_line()`, `get_browser_line()`, `load_browser()`,
`get_browser_maxline()`, `select_browser_line()`, `deselect_browser_line()`,
`deselect_browser()`, `isselected_browser_line()`, `get_browser()`,
`set_browser_fontsize()`, `set_browser_fontstyle()`, `set_browser_specialkey()`.

add_timer (*type, x, y, w, h, name*)

Add a timer object to the form.

Methods: `set_timer()`, `get_timer()`.

Form objects have the following data attributes; see the FORMS documentation:

Name	C Type	Meaning
window	int (read-only)	GL window id
w	float	form width
h	float	form height
x	float	form x origin
y	float	form y origin
deactivated	int	nonzero if form is deactivated
visible	int	nonzero if form is visible
frozen	int	nonzero if form is frozen
doublebuf	int	nonzero if double buffering on

16.4.3 FORMS Objects

Besides methods specific to particular kinds of FORMS objects, all FORMS objects also have the following methods:

set_callback (*function, argument*)

Set the object's callback function and argument. When the object needs interaction, the callback function will be called with two arguments: the object, and the callback argument. (FORMS objects without a callback function

are returned by `fl.do_forms()` or `fl.check_forms()` when they need interaction.) Call this method without arguments to remove the callback function.

delete_object()
Delete the object.

show_object()
Show the object.

hide_object()
Hide the object.

redraw_object()
Redraw the object.

freeze_object()
Freeze the object.

unfreeze_object()
Unfreeze the object.

FORMS objects have these data attributes; see the FORMS documentation:

Name	C Type	Meaning
objclass	int (read-only)	object class
type	int (read-only)	object type
boxtype	int	box type
x	float	x origin
y	float	y origin
w	float	width
h	float	height
col1	int	primary color
col2	int	secondary color
align	int	alignment
lcol	int	label color
lsize	float	label font size
label	string	label string
lstyle	int	label style
pushed	int (read-only)	(see FORMS docs)
focus	int (read-only)	(see FORMS docs)
belowmouse	int (read-only)	(see FORMS docs)
frozen	int (read-only)	(see FORMS docs)
active	int (read-only)	(see FORMS docs)
input	int (read-only)	(see FORMS docs)
visible	int (read-only)	(see FORMS docs)
radio	int (read-only)	(see FORMS docs)
automatic	int (read-only)	(see FORMS docs)

16.5 FL — Constants used with the fl module

This module defines symbolic constants needed to use the built-in module `fl` (see above); they are equivalent to those defined in the C header file `<forms.h>` except that the name prefix 'FL_' is omitted. Read the module source for a complete list of the defined names. Suggested use:

```
import fl
from FL import *
```

16.6 flp — Functions for loading stored FORMS designs

This module defines functions that can read form definitions created by the ‘form designer’ (**fdesign**) program that comes with the FORMS library (see module [fl](#) above).

For now, see the file ‘flp.doc’ in the Python library source directory for a description.

XXX A complete description should be inserted here!

16.7 fm — *Font Manager* interface

This module provides access to the IRIS *Font Manager* library. It is available only on Silicon Graphics machines. See also: *4Sight User’s Guide*, section 1, chapter 5: “Using the IRIS Font Manager.”

This is not yet a full interface to the IRIS Font Manager. Among the unsupported features are: matrix operations; cache operations; character operations (use string operations instead); some details of font info; individual glyph metrics; and printer matching.

It supports the following operations:

init()

Initialization function. Calls `fm_init()`. It is normally not necessary to call this function, since it is called automatically the first time the `fm` module is imported.

findfont(fontname)

Return a font handle object. Calls `fm_findfont(fontname)`.

enumerate()

Returns a list of available font names. This is an interface to `fm_enumerate()`.

prstr(string)

Render a string using the current font (see the `setfont()` font handle method below). Calls `fm_prstr(string)`.

setpath(string)

Sets the font search path. Calls `fm_setpath(string)`. (XXX Does not work!?)

fontpath()

Returns the current font search path.

Font handle objects support the following operations:

scalefont(factor)

Returns a handle for a scaled version of this font. Calls `fm_scalefont(fh, factor)`.

setfont()

Makes this font the current font. Note: the effect is undone silently when the font handle object is deleted. Calls `fm_setfont(fh)`.

getfontname()

Returns this font’s name. Calls `fm_getfontname(fh)`.

getcomment()

Returns the comment string associated with this font. Raises an exception if there is none. Calls `fm_getcom-`

ment(*fh*).

getfontinfo()

Returns a tuple giving some pertinent data about this font. This is an interface to `fmgetfontinfo()`. The returned tuple contains the following numbers: (*printermatched*, *fixed_width*, *xorig*, *yorig*, *xsize*, *ysize*, *height*, *nglyphs*).

getstrwidth(*string*)

Returns the width, in pixels, of *string* when drawn in this font. Calls `fmgetstrwidth(fh, string)`.

16.8 gl — *Graphics Library* interface

This module provides access to the Silicon Graphics *Graphics Library*. It is available only on Silicon Graphics machines.

Warning: Some illegal calls to the GL library cause the Python interpreter to dump core. In particular, the use of most GL calls is unsafe before the first window is opened.

The module is too large to document here in its entirety, but the following should help you to get started. The parameter conventions for the C functions are translated to Python as follows:

- All (short, long, unsigned) int values are represented by Python integers.
- All float and double values are represented by Python floating point numbers. In most cases, Python integers are also allowed.
- All arrays are represented by one-dimensional Python lists. In most cases, tuples are also allowed.
- All string and character arguments are represented by Python strings, for instance, `winopen('Hi There!')` and `rotate(900, 'z')`.
- All (short, long, unsigned) integer arguments or return values that are only used to specify the length of an array argument are omitted. For example, the C call

```
lndef(deftype, index, np, props)
```

is translated to Python as

```
lndef(deftype, index, props)
```

- Output arguments are omitted from the argument list; they are transmitted as function return values instead. If more than one value must be returned, the return value is a tuple. If the C function has both a regular return value (that is not omitted because of the previous rule) and an output argument, the return value comes first in the tuple. Examples: the C call

```
getmcolor(i, &red, &green, &blue)
```

is translated to Python as

```
red, green, blue = getmcolor(i)
```

The following functions are non-standard or have special argument conventions:

varray(*argument*)

Equivalent to but faster than a number of `v3d()` calls. The *argument* is a list (or tuple) of points. Each point must be a tuple of coordinates (*x*, *y*, *z*) or (*x*, *y*). The points may be 2- or 3-dimensional but must all have the same dimension. Float and int values may be mixed however. The points are always converted to 3D double precision points by assuming *z* = 0.0 if necessary (as indicated in the man page), and for each point `v3d()` is called.

nvarray()

Equivalent to but faster than a number of `n3f` and `v3f` calls. The argument is an array (list or tuple) of pairs of normals and points. Each pair is a tuple of a point and a normal for that point. Each point or normal must be a tuple of coordinates (*x*, *y*, *z*). Three coordinates must be given. Float and int values may be mixed. For each pair, `n3f()` is called for the normal, and then `v3f()` is called for the point.

vnarray()

Similar to `nvarray()` but the pairs have the point first and the normal second.

nurbssurface(*s_k*, *t_k*, *ctl*, *s_ord*, *t_ord*, *type*)

Defines a nurbs surface. The dimensions of `ctl[][]` are computed as follows: `[len(s_k) - s_ord], [len(t_k) - t_ord]`.

nurbscurve(*knots*, *ctlpoints*, *order*, *type*)

Defines a nurbs curve. The length of `ctlpoints` is `len(knots) - order`.

pwlcurve(*points*, *type*)

Defines a piecewise-linear curve. *points* is a list of points. *type* must be `N_ST`.

pick(*n*)

select(*n*)

The only argument to these functions specifies the desired size of the pick or select buffer.

endpick()

endselect()

These functions have no arguments. They return a list of integers representing the used part of the pick/select buffer. No method is provided to detect buffer overrun.

Here is a tiny but complete example GL program in Python:

```

import gl, GL, time

def main():
    gl.foreground()
    gl.prefposition(500, 900, 500, 900)
    w = gl.winopen('CrissCross')
    gl.ortho2(0.0, 400.0, 0.0, 400.0)
    gl.color(GL.WHITE)
    gl.clear()
    gl.color(GL.RED)
    gl.bgnline()
    gl.v2f(0.0, 0.0)
    gl.v2f(400.0, 400.0)
    gl.endline()
    gl.bgnline()
    gl.v2f(400.0, 0.0)
    gl.v2f(0.0, 400.0)
    gl.endline()
    time.sleep(5)

main()

```

See Also:

An interface to OpenGL is also available; see information about David Ascher's **PyOpenGL** online at <http://starship.python.net/crew/da/PyOpenGL/>. This may be a better option if support for SGI hardware from before about 1996 is not required.

16.9 DEVICE — Constants used with the `gl` module

This module defines the constants used by the Silicon Graphics *Graphics Library* that C programmers find in the header file `<gl/device.h>`. Read the module source file for details.

16.10 GL — Constants used with the `gl` module

This module contains constants used by the Silicon Graphics *Graphics Library* from the C header file `<gl/gl.h>`. Read the module source file for details.

16.11 `imgfile` — Support for SGI `imglib` files

The `imgfile` module allows Python programs to access SGI `imglib` image files (also known as `'rgb'` files). The module is far from complete, but is provided anyway since the functionality that there is is enough in some cases. Currently, colormap files are not supported.

The module defines the following variables and functions:

error

This exception is raised on all errors, such as unsupported file type, etc.

getsizes(*file*)

This function returns a tuple (x, y, z) where x and y are the size of the image in pixels and z is the number

of bytes per pixel. Only 3 byte RGB pixels and 1 byte greyscale pixels are currently supported.

read(*file*)

This function reads and decodes the image on the specified file, and returns it as a Python string. The string has either 1 byte greyscale pixels or 4 byte RGBA pixels. The bottom left pixel is the first in the string. This format is suitable to pass to `gl.rectwrite()`, for instance.

readscaled(*file*, *x*, *y*, *filter*[, *blur*])

This function is identical to `read` but it returns an image that is scaled to the given *x* and *y* sizes. If the *filter* and *blur* parameters are omitted scaling is done by simply dropping or duplicating pixels, so the result will be less than perfect, especially for computer-generated images.

Alternatively, you can specify a filter to use to smoothen the image after scaling. The filter forms supported are 'impulse', 'box', 'triangle', 'quadratic' and 'gaussian'. If a filter is specified *blur* is an optional parameter specifying the blurriness of the filter. It defaults to 1.0.

`readscaled()` makes no attempt to keep the aspect ratio correct, so that is the users' responsibility.

ttob(*flag*)

This function sets a global flag which defines whether the scan lines of the image are read or written from bottom to top (*flag* is zero, compatible with SGI GL) or from top to bottom (*flag* is one, compatible with X). The default is zero.

write(*file*, *data*, *x*, *y*, *z*)

This function writes the RGB or greyscale data in *data* to image file *file*. *x* and *y* give the size of the image, *z* is 1 for 1 byte greyscale images or 3 for RGB images (which are stored as 4 byte values of which only the lower three bytes are used). These are the formats returned by `gl.rectread()`.

16.12 jpeg — Read and write JPEG files

The module `jpeg` provides access to the jpeg compressor and decompressor written by the Independent JPEG Group (IJG). JPEG is a standard for compressing pictures; it is defined in ISO 10918. For details on JPEG or the Independent JPEG Group software refer to the JPEG standard or the documentation provided with the software.

A portable interface to JPEG image files is available with the Python Imaging Library (PIL) by Fredrik Lundh. Information on PIL is available at <http://www.pythonware.com/products/pil/>.

The `jpeg` module defines an exception and some functions.

error

Exception raised by `compress()` and `decompress()` in case of errors.

compress(*data*, *w*, *h*, *b*)

Treat data as a pixmap of width *w* and height *h*, with *b* bytes per pixel. The data is in SGI GL order, so the first pixel is in the lower-left corner. This means that `gl.rectread()` return data can immediately be passed to `compress()`. Currently only 1 byte and 4 byte pixels are allowed, the former being treated as greyscale and the latter as RGB color. `compress()` returns a string that contains the compressed picture, in JFIF format.

decompress(*data*)

Data is a string containing a picture in JFIF format. It returns a tuple (*data*, *width*, *height*, *bytesperpixel*). Again, the data is suitable to pass to `gl.rectwrite()`.

setoption(*name*, *value*)

Set various options. Subsequent `compress()` and `decompress()` calls will use these options. The following options are available:

Option	Effect
'forcegray'	Force output to be grayscale, even if input is RGB.
'quality'	Set the quality of the compressed image to a value between 0 and 100 (default is 75). This only affects compression.
'optimize'	Perform Huffman table optimization. Takes longer, but results in smaller compressed image. This only affects compression.
'smooth'	Perform inter-block smoothing on uncompressed image. Only useful for low-quality images. This only affects decompression.

See Also:

JPEG Still Image Data Compression Standard, by Pennebaker and Mitchell, is the canonical reference for the JPEG image format.

The ISO standard for JPEG is also published as ITU T.81. This is available in PDF form at <http://www.w3.org/Graphics/JPEG/itu-t81.pdf>.

SunOS Specific Services

The modules described in this chapter provide interfaces to features that are unique to the SunOS operating system (versions 4 and 5; the latter is also known as Solaris version 2).

17.1 `sunaudiodev` — Access to Sun audio hardware

This module allows you to access the Sun audio interface. The Sun audio hardware is capable of recording and playing back audio data in u-LAW format with a sample rate of 8K per second. A full description can be found in the *audio(7I)* manual page.

The module `SUNAUDIODEV` defines constants which may be used with this module.

This module defines the following variables and functions:

error

This exception is raised on all errors. The argument is a string describing what went wrong.

open(mode)

This function opens the audio device and returns a Sun audio device object. This object can then be used to do I/O on. The *mode* parameter is one of `'r'` for record-only access, `'w'` for play-only access, `'rw'` for both and `'control'` for access to the control device. Since only one process is allowed to have the recorder or player open at the same time it is a good idea to open the device only for the activity needed. See *audio(7I)* for details.

As per the manpage, this module first looks in the environment variable `AUDIODEV` for the base audio device filename. If not found, it falls back to `'/dev/audio'`. The control device is calculated by appending `"ctl"` to the base audio device.

17.1.1 Audio Device Objects

The audio device objects are returned by `open()` define the following methods (except `control` objects which only provide `getinfo()`, `setinfo()`, `fileno()`, and `drain()`):

close()

This method explicitly closes the device. It is useful in situations where deleting the object does not immediately close it since there are other references to it. A closed device should not be used again.

fileno()

Returns the file descriptor associated with the device. This can be used to set up `SIGPOLL` notification, as described below.

drain()

This method waits until all pending output is processed and then returns. Calling this method is often not necessary: destroying the object will automatically close the audio device and this will do an implicit drain.

flush()

This method discards all pending output. It can be used avoid the slow response to a user's stop request (due to buffering of up to one second of sound).

getinfo()

This method retrieves status information like input and output volume, etc. and returns it in the form of an audio status object. This object has no methods but it contains a number of attributes describing the current device status. The names and meanings of the attributes are described in `<sun/audioio.h>` and in the *audio(7I)* manual page. Member names are slightly different from their C counterparts: a status object is only a single structure. Members of the `play` substructure have `'o_'` prepended to their name and members of the `record` structure have `'i_'`. So, the C member `play.sample_rate` is accessed as `o_sample_rate`, `record.gain` as `i_gain` and `monitor_gain` plainly as `monitor_gain`.

ibufcount()

This method returns the number of samples that are buffered on the recording side, i.e. the program will not block on a `read()` call of so many samples.

obufcount()

This method returns the number of samples buffered on the playback side. Unfortunately, this number cannot be used to determine a number of samples that can be written without blocking since the kernel output queue length seems to be variable.

read(size)

This method reads *size* samples from the audio input and returns them as a Python string. The function blocks until enough data is available.

setinfo(status)

This method sets the audio device status parameters. The *status* parameter is an device status object as returned by `getinfo()` and possibly modified by the program.

write(samples)

Write is passed a Python string containing audio samples to be played. If there is enough buffer space free it will immediately return, otherwise it will block.

The audio device supports asynchronous notification of various events, through the SIGPOLL signal. Here's an example of how you might enable this in Python:

```
def handle_sigpoll(signum, frame):
    print 'I got a SIGPOLL update'

import fcntl, signal, STROPTS

signal.signal(signal.SIGPOLL, handle_sigpoll)
fcntl.ioctl(audio_obj.fileno(), STROPTS.I_SETSIG, STROPTS.S_MSG)
```

17.2 SUNAUDIODEV — Constants used with sunaudiodev

This is a companion module to `sunaudiodev` which defines useful symbolic constants like `MIN_GAIN`, `MAX_GAIN`, `SPEAKER`, etc. The names of the constants are the same names as used in the C include file `<sun/audioio.h>`, with the leading string `'AUDIO_'` stripped.

MS Windows Specific Services

This chapter describes modules that are only available on MS Windows platforms.

msvcrt Miscellaneous useful routines from the MS VC++ runtime.
winsound Access to the sound-playing machinery for Windows.

18.1 `msvcrt` – Useful routines from the MS VC++ runtime

These functions provide access to some useful capabilities on Windows platforms. Some higher-level modules use these functions to build the Windows implementations of their services. For example, the `getpass` module uses this in the implementation of the `getpass()` function.

Further documentation on these functions can be found in the Platform API documentation.

18.1.1 File Operations

locking(*fd, mode, nbytes*)

Lock part of a file based on a file descriptor from the C runtime. Raises `IOError` on failure.

setmode(*fd, flags*)

Set the line-end translation mode for the file descriptor *fd*. To set it to text mode, *flags* should be `os.O_TEXT`; for binary, it should be `os.O_BINARY`.

open_osfhandle(*handle, flags*)

Create a C runtime file descriptor from the file handle *handle*. The *flags* parameter should be a bit-wise OR of `os.O_APPEND`, `os.O_RDONLY`, and `os.O_TEXT`. The returned file descriptor may be used as a parameter to `os.fdopen()` to create a file object.

get_osfhandle(*fd*)

Return the file handle for the file descriptor *fd*. Raises `IOError` if *fd* is not recognized.

18.1.2 Console I/O

kbhit()

Return true if a keypress is waiting to be read.

getch()

Read a keypress and return the resulting character. Nothing is echoed to the console. This call will block if a keypress is not already available, but will not wait for `Enter` to be pressed. If the pressed key was a special function key, this will return `'\000'` or `'\xe0'`; the next call will return the keycode. The `Control-C` keypress cannot be read with this function.

getche()

Similar to `getch()`, but the keypress will be echoed if it represents a printable character.

putch(char)

Print the character *char* to the console without buffering.

ungetch(char)

Cause the character *char* to be “pushed back” into the console buffer; it will be the next character read by `getch()` or `getche()`.

18.1.3 Other Functions

heapmin()

Force the `malloc()` heap to clean itself up and return unused blocks to the operating system. This only works on Windows NT. On failure, this raises `IOError`.

18.2 winsound — Sound-playing interface for Windows

New in version 1.5.2.

The `winsound` module provides access to the basic sound-playing machinery provided by Windows platforms. It includes two functions and several constants.

Beep(frequency, duration)

Beep the PC’s speaker. The *frequency* parameter specifies frequency, in hertz, of the sound, and must be in the range 37 through 32,767 (0x25 through 0x7fff). The *duration* parameter specifies the number of milliseconds the sound should last. If the system is not able to beep the speaker, `RuntimeError` is raised. New in version 1.5.3.

PlaySound(sound, flags)

Call the underlying `PlaySound()` function from the Platform API. The *sound* parameter may be a filename, audio data as a string, or `None`. Its interpretation depends on the value of *flags*, which can be a bit-wise ORED combination of the constants described below. If the system indicates an error, `RuntimeError` is raised.

SND_FILENAME

The *sound* parameter is the name of a WAV file.

SND_ALIAS

The *sound* parameter should be interpreted as a control panel sound association name.

SND_LOOP

Play the sound repeatedly. The `SND_ASYNC` flag must also be used to avoid blocking.

SND_MEMORY

The *sound* parameter to `PlaySound()` is a memory image of a WAV file.

Note: This module does not support playing from a memory image asynchronously, so a combination of this flag and `SND_ASYNC` will raise a `RuntimeError`.

SND_PURGE

Stop playing all instances of the specified sound.

SND_ASYNC

Return immediately, allowing sounds to play asynchronously.

SND_NODEFAULT

If the specified sound cannot be found, do not play a default beep.

SND_NOSTOP

Do not interrupt sounds currently playing.

SND_NOWAIT

Return immediately if the sound driver is busy.

Undocumented Modules

Here's a quick listing of modules that are currently undocumented, but that should be documented. Feel free to contribute documentation for them! (The idea and original contents for this chapter were taken from a posting by Fredrik Lundh; I have revised some modules' status.)

19.1 Frameworks

Frameworks tend to be harder to document, but are well worth the effort spent.

Tkinter — Interface to Tcl/Tk for graphical user interfaces; Fredrik Lundh is working on this one! See *An Introduction to Tkinter* at <http://www.pythonware.com/library.htm> for on-line reference material.

Tkdnd — Drag-and-drop support for Tkinter.

turtle — Turtle graphics in a Tk window.

test — Regression testing framework. This is used for the Python regression test, but is useful for other Python libraries as well. This is a package rather than a module.

19.2 Miscellaneous useful utilities

Some of these are very old and/or not very robust; marked with “hmm.”

dircmp — Class to build directory diff tools on (may become a demo or tool). **Deprecated since release 1.6.** The `filecmp` module will replace `dircmp`.

bdb — A generic Python debugger base class (used by `pdb`)

ihooks — Import hook support (for `rexec`; may become obsolete)

tzparse — Parse a timezone specification (unfinished; may disappear in the future)

19.3 Platform specific modules

These modules are used to implement the `os.path` module, and are not documented beyond this mention. There's little need to document these.

dospath — implementation of `os.path` on MS-DOS

ntpath — implementation on `os.path` on 32-bit Windows

posixpath — implementation on `os.path` on POSIX

19.4 Multimedia

audiodev — Platform-independent API for playing audio data

sunaudio — Interpret Sun audio headers (may become obsolete or a tool/demo)

toaiff — Convert "arbitrary" sound files to AIFF files; should probably become a tool or demo. Requires the external program **sox**.

19.5 Obsolete

These modules are not normally available for import; additional work must be done to make them available.

Those which are written in Python will be installed into the directory 'lib-old/' installed as part of the standard library. To use these, the directory must be added to `sys.path`, possibly using `$PYTHONPATH`.

Obsolete extension modules written in C are not built by default. Under UNIX, these must be enabled by uncommenting the appropriate lines in 'Modules/Setup' in the build tree and either rebuilding Python if the modules are statically linked, or building and installing the shared object if using dynamically-loaded extensions.

addpack — alternate approach to packages

cmp — File comparison function. Use the newer [filecmp](#) instead.

cmpcache — Caching version of the obsolete `cmp` module. Use the newer [filecmp](#) instead.

codehack — Extract function name or line number from a function code object (these are now accessible as attributes: `co.co_name`, `func.func_name`, `co.co_firstlineno`).

dircmp — class to build directory diff tools on (may become a demo or tool)

dump — Print python code that reconstructs a variable

fmt — text formatting abstractions (too slow)

lockfile — wrapper around FCNTL file locking (use `fcntl.lockf()`/`flock()` instead; see [fcntl](#))

newdir — New `dir()` function (the standard `dir()` is now just as good)

Para — helper for `fmt.py`

poly — Polynomials

tb — Print tracebacks, with a dump of local variables (use `pdb.pm()` or [traceback](#) instead)

timing — Measure time intervals to high resolution (use `time.clock()` instead). (This is an extension module.)

util — Useful functions that don't fit elsewhere.

wdb — A primitive windowing debugger based on STDWIN.

whatsound — Recognize sound files; use [sndhdr](#) instead.

zmod — Compute properties of mathematical "fields"

The following modules are obsolete, but are likely re-surface as tools or scripts.

find — find files matching pattern in directory tree

grep — grep

packmail — create a self-unpacking UNIX shell archive

The following modules were documented in previous versions of this manual, but are now considered obsolete. The source for the documentation is still available as part of the documentation source archive.

ni — Import modules in “packages.” Basic package support is now built in.

rand — Old interface to the random number generator.

soundex — Algorithm for collapsing names which sound similar to a shared key. (This is an extension module.)

19.6 Extension modules

stdwin — Interface to STDWIN (an old, unsupported platform-independent GUI package). Obsolete; use `Tkinter` for a platform-independent GUI instead.

The following are SGI specific, and may be out of touch with the current version of reality.

c1 — Interface to the SGI compression library.

sv — Interface to the “simple video” board on SGI Indigo (obsolete hardware).

MODULE INDEX

Symbols

`__builtin__`, 74
`__main__`, 74

A

`aifc`, 291
`AL`, 307
`al`, 305
`anydbm`, 167
`array`, 100
`asyncore`, 247
`audioop`, 287

B

`base64`, 275
`BaseHTTPServer`, 243
`Bastion`, 286
`binascii`, 269
`binhex`, 268
`bisect`, 100
`bsddb`, 169

C

`calendar`, 105
`cd`, 307
`cgi`, 213
`CGIHTTPServer`, 247
`chunk`, 297
`cmath`, 97
`cmd`, 106
`code`, 59
`codecs`, 93
`codeop`, 61
`colorsys`, 298
`commands`, 193
`compileall`, 65
`ConfigParser`, 103
`copy`, 42
`copy_reg`, 41
`cPickle`, 41
`crypt`, 179

`cStringIO`, 93
`curses`, 132

D

`dbhash`, 168
`dbm`, 181
`DEVICE`, 319
`dircache`, 123
`dis`, 66
`dl`, 180
`dumbdbm`, 168

E

`errno`, 138
`exceptions`, 12

F

`fcntl`, 185
`filecmp`, 126
`fileinput`, 104
`FL`, 315
`fl`, 310
`flp`, 316
`fm`, 316
`fnmatch`, 144
`formatter`, 258
`fpformat`, 92
`ftplib`, 224

G

`gdbm`, 182
`getopt`, 136
`getpass`, 131
`GL`, 319
`gl`, 317
`glob`, 144
`gopherlib`, 227
`grp`, 179
`gzip`, 173

H

`htmlentitydefs`, 255

htmllib, 253
httplib, 223

I

imageop, 290
imaplib, 229
imgfile, 319
imghdr, 299
imp, 44

J

jpeg, 320

K

keyword, 57

L

linecache, 36
locale, 146

M

mailbox, 276
mailcap, 273
marshal, 43
math, 95
md5, 301
mhlib, 277
mimetools, 264
mimetypes, 274
MimeWriter, 265
mimify, 278
mpz, 302
msvcrt, 325
multifile, 266
mutex, 149

N

netrc, 279
new, 71
nis, 191
nntplib, 232

O

operator, 32
os, 111
os.path, 121

P

parser, 47
pdb, 195
pickle, 36
pipes, 186
popen2, 192
poplib, 228

posix, 177
posixfile, 187
pprint, 61
profile, 204
pstats, 205
pty, 185
pwd, 178
py_compile, 65
pyclbr, 58

Q

Queue, 166
quopri, 276

R

random, 98
re, 78
regex, 85
regsub, 89
repr, 63
resource, 189
rexec, 284
rfc822, 261
rgbing, 299
rlcompleter, 175
robotparser, 280
rotor, 303

S

sched, 130
select, 158
sgmlib, 251
sha, 302
shelve, 41
shlex, 108
shutil, 145
signal, 151
SimpleHTTPServer, 246
site, 72
smtplib, 235
sndhdr, 300
socket, 153
SocketServer, 241
stat, 123
statcache, 125
statvfs, 126
string, 75
StringIO, 93
struct, 90
sunau, 293
SUNAUDIODEV, 324
sunaudiodev, 323
symbol, 56
sys, 25

syslog, 192

T

tabnanny, 58
telnetlib, 238
tempfile, 137
TERMIOS, 184
termios, 183
thread, 159
threading, 160
time, 127
token, 57
tokenize, 57
traceback, 34
tty, 184
types, 29

U

urllib, 219
urlparse, 241
user, 73
UserDict, 31
UserList, 31
UserString, 31
uu, 269

W

wave, 295
whichdb, 169
whrandom, 99
winsound, 326

X

xdrlib, 270
xmllib, 255

Z

zlib, 171

INDEX

Symbols

`.ini`
file, 103

`.pdbrc`
file, 197

`.pythonrc.py`
file, 73

`==`
operator, 4

`__abs__()` (in module operator), 32

`__add__()` (in module operator), 32

`__add__()` (in module rfc822), 264

`__and__()` (in module operator), 33

`__builtin__` (built-in module), **74**

`__cmp__()`, 4

`__concat__()` (in module operator), 33

`__copy__()` (in module copy), 43

`__deepcopy__()` (in module copy), 43

`__delitem__()` (in module operator), 33

`__delslice__()` (in module operator), 34

`__dict__` (pickle protocol), 38

`__div__()` (in module operator), 32

`__getinitargs__()` (in module copy), 43

`__getinitargs__()` (pickle protocol), 38

`__getitem__()` (in module operator), 33

`__getslice__()` (in module operator), 34

`__getstate__()` (in module copy), 43

`__getstate__()` (pickle protocol), 38

`__import__()` (built-in function), 16

`__init__()` (pickle protocol), 38

`__inv__()` (in module operator), 33

`__len__()` (in module rfc822), 264

`__lshift__()` (in module operator), 33

`__main__` (built-in module), **74**

`__mod__()` (in module operator), 32

`__mul__()` (in module operator), 32

`__neg__()` (in module operator), 32

`__not__()` (in module operator), 33

`__or__()` (in module operator), 33

`__pos__()` (in module operator), 32

`__repeat__()` (in module operator), 33

`__repr__()` (in module netrc), 280

`__rshift__()` (in module operator), 33

`__setitem__()` (in module operator), 33

`__setslice__()` (in module operator), 34

`__setstate__()` (in module copy), 43

`__setstate__()` (pickle protocol), 38

`__stderr__` (in module sys), 28

`__stdin__` (in module sys), 28

`__stdout__` (in module sys), 28

`__str__()` (in module rfc822), 264

`__sub__()` (in module operator), 32

`__sub__()` (in module rfc822), 264

`__xor__()` (in module operator), 33

`_debug`, 174

`_exit()` (in module os), 118

`_locale` (built-in module), 146

A

A-LAW, 292, 300

`a2b_base64()` (in module binascii), 269

`a2b_hqx()` (in module binascii), 270

`a2b_uu()` (in module binascii), 269

`A_ALTCHARSET` (in module curses), 132

`A_BLINK` (in module curses), 132

`A_BOLD` (in module curses), 132

`A_DIM` (in module curses), 132

`A_NORMAL` (in module curses), 132

`A_STANDOUT` (in module curses), 132

`A_UNDERLINE` (in module curses), 132

ABC language, 4

`abort()` (in module ftplib), 226

`abort()` (in module os), 118

`abs()` (built-in function), 16

`abs()` (in module operator), 32

`abspath()` (in module os.path), 121

`AbstractFormatter` (in module formatter), 260

`AbstractWriter` (in module formatter), 261

`accept()` (in module asyncore), 249

`accept()` (in module socket), 156

`accept2dyear` (in module time), 128

`access()` (in module os), 115

`acos()` (in module cmath), 97

`acos()` (in module `math`), 95
`acosh()` (in module `cmath`), 97
`acquire()` (in module `thread`), 159
`acquire()` (in module `threading`), 161–164
`ACS_*` (in module `curses`), 132
`activate_form()` (in module `fl`), 313
`activeCount()` (in module `threading`), 160
`add()` (in module `audioop`), 287
`add()` (in module `operator`), 32
`add()` (in module `pstats`), 205
`add_box()` (in module `fl`), 313
`add_browser()` (in module `fl`), 314
`add_button()` (in module `fl`), 313
`add_choice()` (in module `fl`), 314
`add_clock()` (in module `fl`), 313
`add_counter()` (in module `fl`), 314
`add_dial()` (in module `fl`), 313
`add_flow_data()` (in module `formatter`), 258
`add_hor_rule()` (in module `formatter`), 258
`add_input()` (in module `fl`), 314
`add_label_data()` (in module `formatter`), 259
`add_lightbutton()` (in module `fl`), 313
`add_line_break()` (in module `formatter`), 258
`add_literal_data()` (in module `formatter`), 258
`add_menu()` (in module `fl`), 314
`add_positioner()` (in module `fl`), 313
`add_roundbutton()` (in module `fl`), 313
`add_section()` (in module `ConfigParser`), 104
`add_slider()` (in module `fl`), 313
`add_text()` (in module `fl`), 313
`add_timer()` (in module `fl`), 314
`add_valslider()` (in module `fl`), 313
`addcallback()` (in module `cd`), 310
`addch()` (in module `curses`), 134
`addheader()` (in module `MimeWriter`), 266
`address_family` (`SocketServer` protocol), 242
`address_string()` (in module `Base-HTTPServer`), 246
`AddressList` (in module `rfc822`), 262
`addresslist` (in module `rfc822`), 264
`addstr()` (in module `curses`), 134
`adler32()` (in module `zlib`), 171
`ADPCM`, Intel/DVI, 287
`adpcm2lin()` (in module `audioop`), 287
`adpcm32lin()` (in module `audioop`), 287
`AF_INET` (in module `socket`), 154
`AF_UNIX` (in module `socket`), 154
`aifc` (standard module), **291**
`aifc()` (in module `aifc`), 292
`AIFF`, 291, 297
`aiff()` (in module `aifc`), 292
`AIFF-C`, 291, 297
`AL` (standard module), 305, **307**
`al` (built-in module), **305**
`alarm()` (in module `signal`), 152
`all_errors` (in module `ftplib`), 225
`allocate_lock()` (in module `thread`), 159
`allowremoval()` (in module `cd`), 309
`altsep` (in module `os`), 121
`altzone` (in module `time`), 128
`anchor_bgn()` (in module `htmlib`), 254
`anchor_end()` (in module `htmlib`), 254
`and`
 operator, 3, 4
`and_()` (in module `operator`), 33
`annotate()` (in module `dircache`), 123
`anydbm` (standard module), **167**
`apop()` (in module `poplib`), 228
`append()`, 8
`append()` (in module `array`), 101
`append()` (in module `imaplib`), 230
`append()` (in module `pipes`), 186
`apply()` (built-in function), 16
arbitrary precision integers, 302
`aRepr` (in module `repr`), 63
`argv` (in module `sys`), 26
arithmetic, 5
`ArithmeticError` (built-in exception base class), 13
`array` (built-in module), **100**
`array()` (in module `array`), 101
arrays, 101
`ArrayType` (in module `array`), 101
`article()` (in module `nntplib`), 235
`AS_IS` (in module `formatter`), 258
Ascher, David, 319
`asctime()` (in module `time`), 128
`asin()` (in module `cmath`), 97
`asin()` (in module `math`), 95
`asinh()` (in module `cmath`), 97
`assert`
 statement, 14
`assert_line_data()` (in module `formatter`), 259
`AssertionError` (built-in exception), 14
assignment
 slice, 8
 subscript, 8
`ast2list()` (in module `parser`), 49
`ast2tuple()` (in module `parser`), 49
`ASTType` (in module `parser`), 50
`asyncore` (built-in module), **247**
`atan()` (in module `cmath`), 97
`atan()` (in module `math`), 95
`atan2()` (in module `math`), 95
`atanh()` (in module `cmath`), 97
`atime` (in module `cd`), 308
`atof()` (in module `locale`), 147
`atof()` (in module `string`), 76

atoi() (in module locale), 147
 atoi() (in module string), 76
 atol() (in module string), 76
 AttributeError (built-in exception), 14
 attributes (in module xmllib), 255
 attroff() (in module curses), 134
 attron() (in module curses), 134
 audio (in module cd), 308
 Audio Interchange File Format, 291, 297
 AUDIO_FILE_MAGIC (in module sunau), 293
 audioop (built-in module), **287**
 authenticate() (in module imaplib), 230
 authenticators() (in module netrc), 280
 avg() (in module audioop), 287
 avgpp() (in module audioop), 288

B

b2a_base64() (in module binascii), 269
 b2a_hqx() (in module binascii), 270
 b2a_uu() (in module binascii), 269
 BabylMailbox (in module mailbox), 276
 base64
 encoding, 275
 base64 (standard module), **275**
 BaseHTTPRequestHandler (in module Base-
 HTTPServer), 244
 BaseHTTPServer (standard module), **243**
 basename() (in module os.path), 121
 Bastion (standard module), **286**
 Bastion() (in module Bastion), 286
 BastionClass (in module Bastion), 286
 bdb (standard module), 195
 Beep() (in module winsound), 326
 beep() (in module curses), 133
 benchmarking, 128
 bestreadsize() (in module cd), 309
 betavariate() (in module random), 98
 bgn_group() (in module fl), 313
 bias() (in module audioop), 288
 binary
 data, packing, 90
 binary semaphores, 159
 binary() (in module mpz), 303
 binascii (built-in module), **269**
 bind() (in module asyncore), 249
 bind() (in module socket), 156
 binhex (standard module), **268**, 269
 binhex() (in module binhex), 268
 bisect (standard module), **100**
 bisect() (in module bisect), 100
 bit-string
 operations, 6
 BLOCKSIZE (in module cd), 308
 blocksize (in module sha), 302

body() (in module nntplib), 235
 BOM (in module codecs), 94
 BOM32_BE (in module codecs), 94
 BOM32_LE (in module codecs), 94
 BOM64_BE (in module codecs), 94
 BOM64_LE (in module codecs), 94
 BOM_BE (in module codecs), 94
 BOM_LE (in module codecs), 94
 Boolean
 operations, 3, 4
 type, 3
 border() (in module curses), 135
 box() (in module curses), 135
 bsddb (built-in module), 167, 168
 bsddb (extension module), **169**
 btopen() (in module bsddb), 170
 buffer size, I/O, 20
 buffer() (built-in function), 17
 buffer() (in module types), 31
 buffer_info() (in module array), 101
 BufferType (in module types), 31
 built-in
 exceptions, 3
 functions, 3
 types, 3
 builtin_module_names (in module sys), 26
 BuiltinFunctionType (in module types), 30
 BuiltinMethodType (in module types), 30
 byte-code
 file, 44, 46, 65
 byteswap() (in module array), 101

C

C
 language, 5
 structures, 90
 C
 language, 4, 5
 C_BUILTIN (in module imp), 46
 C_EXTENSION (in module imp), 45
 calctime() (in module struct), 90
 calendar (standard module), **105**
 call() (in module dl), 181
 callable() (built-in function), 17
 can_fetch() (in module robotparser), 280
 cancel() (in module sched), 131
 capitalize() (in module string), 76
 capwords() (in module re.sub), 90
 capwords() (in module string), 76
 casefold (in module regex), 88
 cat() (in module nis), 191
 catalog (in module cd), 308
 cbreak() (in module curses), 133
 cd (built-in module), **307**

CDROM (in module cd), 308
 ceil(), 5
 ceil() (in module math), 95
 center() (in module string), 77
 CGI
 protocol, 213
 cgi (standard module), **213**
 cgi_directories (in module CGIHTTPServer), 247
 CGIHTTPRequestHandler (in module CGIHTTPServer), 247
 CGIHTTPServer (standard module), 243, **247**
 chaining
 comparisons, 4
 CHAR_MAX (in module locale), 148
 CHARSET (in module mimify), 279
 chdir() (in module os), 116
 check() (in module imaplib), 230
 check() (in module tabnanny), 58
 check_forms() (in module fl), 311
 checkcache() (in module linecache), 36
 checksum
 Cyclic Redundancy Check, 172
 MD5, 301
 SHA, 302
 childerr (in module popen2), 193
 chmod() (in module os), 116
 choice() (in module random), 99
 choice() (in module whrandom), 99
 choose_boundary() (in module mimetools), 264
 chown() (in module os), 116
 chr() (built-in function), 17
 Chunk (in module chunk), 297
 chunk (standard module), **297**
 cipher
 DES, 179, 301
 Enigma, 304
 IDEA, 301
 classobj() (in module new), 72
 ClassType (in module types), 30
 clear(), 8
 clear() (in module curses), 135
 clear() (in module threading), 164
 clear_cache() (in module regsub), 90
 clearcache() (in module linecache), 36
 clearok() (in module curses), 136
 client_address (in module BaseHTTPServer), 244
 clock() (in module time), 128
 clone() (in module pipes), 186
 close(), 11, 175
 close() (in module StringIO), 93
 close() (in module aifc), 292, 293
 close() (in module asyncore), 249
 close() (in module bsddb), 170
 close() (in module cd), 309
 close() (in module chunk), 297
 close() (in module dl), 181
 close() (in module fileinput), 105
 close() (in module ftplib), 227
 close() (in module imaplib), 230
 close() (in module os), 114
 close() (in module sgmlib), 252
 close() (in module socket), 156
 close() (in module sunau), 293, 295
 close() (in module sunaudiodev), 323
 close() (in module telnetlib), 240
 close() (in module wave), 295, 296
 close() (in module xmllib), 256
 closed, 12
 closelog() (in module syslog), 192
 closeport() (in module al), 306
 clrtoobot() (in module curses), 135
 clrtoeol() (in module curses), 135
 cmath (built-in module), **97**
 Cmd (in module cmd), 106
 cmd (standard module), **106**, 195
 cmdloop() (in module cmd), 106
 cmp() (built-in function), 17
 cmp() (in module filecmp), 127
 cmp() (in module locale), 147
 cmp_op (in module dis), 67
 code
 object, 10, 44
 code (standard module), **59**
 code() (in module new), 72
 Codecs, 93
 decode, 93
 encode, 93
 codecs (standard module), **93**
 codeop (standard module), **61**
 CodeType (in module types), 30
 coerce() (built-in function), 17
 color() (in module fl), 312
 colorsys (standard module), **298**
 command (in module BaseHTTPServer), 244
 commands (standard module), **193**
 COMMENT (in module tokenize), 58
 commenters (in module shlex), 108
 Common Gateway Interface, 213
 commonprefix() (in module os.path), 121
 comparing
 objects, 4
 comparison
 operator, 4
 comparisons
 chaining, 4
 compile(), 10

`compile()` (built-in function), 17
`compile()` (in module `parser`), 49, 50
`compile()` (in module `py_compile`), 65
`compile()` (in module `re`), 81
`compile()` (in module `regex`), 87
`compile()` (in module `types`), 30
`compile_command()` (in module `code`), 59
`compile_command()` (in module `codeop`), 61
`compile_dir()` (in module `compileall`), 65
`compile_path()` (in module `compileall`), 65
`compileall` (standard module), **65**
`compileast()` (in module `parser`), 49
`complete()` (in module `rlcompleter`), 176
complex number
 literals, 5
 type, 5
`complex()`, 5
`complex()` (built-in function), 17
`ComplexType` (in module `types`), 30
`compress()` (in module `jpeg`), 320
`compress()` (in module `zlib`), 171, 172
`compressobj()` (in module `zlib`), 171
`concat()` (in module `operator`), 33
concatenation
 operation, 6
`Condition` (in module `threading`), 163
`Condition()` (in module `threading`), 160
`ConfigParser` (in module `ConfigParser`), 103
`ConfigParser` (standard module), **103**
configuration
 file, 103
 file, debugger, 197
 file, path, 72
 file, user, 73
`confstr()` (in module `os`), 120
`confstr_names` (in module `os`), 120
`conjugate()`, 5
`connect()` (in module `asyncore`), 248
`connect()` (in module `ftplib`), 226
`connect()` (in module `httplib`), 224
`connect()` (in module `smtplib`), 236
`connect()` (in module `socket`), 156
`connect_ex()` (in module `socket`), 156
`constructor()` (in module `copy_reg`), 41
`contains()` (in module `operator`), 33
content type
 MIME, 274
`control` (in module `cd`), 308
`ConversionError` (in module `xdrlib`), 273
conversions
 numeric, 5
Coordinated Universal Time, 127
`copy` (standard module), 38, 41, **42**
`copy()`, 8
`copy()` (in module `copy`), 43
`copy()` (in module `imaplib`), 230
`copy()` (in module `md5`), 302
`copy()` (in module `pipes`), 187
`copy()` (in module `shutil`), 145
`copy2()` (in module `shutil`), 145
`copy_reg` (standard module), **41**
`copybinary()` (in module `mimertools`), 264
`copyfile()` (in module `shutil`), 145
copying files, 145
`copyliteral()` (in module `mimertools`), 264
`copymessage()` (in module `mhlib`), 278
`copymode()` (in module `shutil`), 145
copyright (in module `sys`), 26
`copystat()` (in module `shutil`), 145
`copytree()` (in module `shutil`), 145
`cos()` (in module `cmath`), 97
`cos()` (in module `math`), 96
`cosh()` (in module `cmath`), 97
`cosh()` (in module `math`), 96
`count()`, 8
`count()` (in module `string`), 76
`countOf()` (in module `operator`), 33
`cPickle` (built-in module), 37, 41, **41**
CPU time, 128
`crc32()` (in module `binascii`), 270
`crc32()` (in module `zlib`), 172
`crc_hqx()` (in module `binascii`), 270
`create()` (in module `imaplib`), 231
`create_socket()` (in module `asyncore`), 248
`createparser()` (in module `cd`), 307
`crop()` (in module `imageop`), 290
`cross()` (in module `audioop`), 288
`crypt` (built-in module), 178, **179**
`crypt()` (in module `crypt`), 180
`crypt(3)`, 179
cryptology, 301
`cStringIO` (built-in module), **93**
`ctermid()` (in module `os`), 112
`ctime()` (in module `time`), 128
`cunifvariate()` (in module `random`), 98
`curdir` (in module `os`), 120
`currentThread()` (in module `threading`), 160
curses (extension module), **132**
`cwd()` (in module `ftplib`), 227
Cyclic Redundancy Check, 172

D

data

 packing binary, 90

`data` (in module `UserDict`), 31

`data` (in module `UserList`), 31

`data` (in module `UserString`), 32

`DATASIZE` (in module `cd`), 308

`date()` (in module `ntplib`), 235
`date2zip()`, 174
`date_time_string()` (in module `Base-HTTPServer`), 245
`daylight` (in module `time`), 128
Daylight Saving Time, 127
`dbhash` (standard module), 167, **168**
`dbm` (built-in module), 42, 167, **181**, 182
`deactivate_form()` (in module `fl`), 313
`debug` (in module `imaplib`), 232
`debug` (in module `shlex`), 109
`debug()` (in module `pipes`), 186
`debugger`, 28
 configuration file, 197
`debugging`, 195
`decode`
 Codecs, 93
`decode()` (in module `base64`), 275
`decode()` (in module `mimetools`), 264
`decode()` (in module `quopri`), 276
`decode()` (in module `uu`), 269
`decodestring()` (in module `base64`), 275
`decompress()` (in module `jpeg`), 320
`decompress()` (in module `zlib`), 172
`decompressobj()` (in module `zlib`), 172
`decrypt()` (in module `rotor`), 304
`decryptmore()` (in module `rotor`), 304
`deepcopy()` (in module `copy`), 43
`default()` (in module `cmd`), 107
`defaults()` (in module `ConfigParser`), 103
`defpath` (in module `os`), 121
`del`
 statement, 8
`delattr()` (built-in function), 17
`delch()` (in module `curses`), 134
`dele()` (in module `poplib`), 229
`delete()` (in module `ftplib`), 227
`delete()` (in module `imaplib`), 231
`delete_object()` (in module `fl`), 315
`deletefolder()` (in module `mhlib`), 277
`deletparser()` (in module `cd`), 310
`deleteln()` (in module `curses`), 135
`delitem()` (in module `operator`), 33
`delslice()` (in module `operator`), 34
DES
 cipher, 179, 301
deterministic profiling, 201
`DEVICE` (standard module), **319**
`device`
 Enigma, 303
dictionary
 type, 8
 type, operations on, 8
`DictionaryType` (in module `types`), 30
`DictType` (in module `types`), 30
`digest()` (in module `md5`), 302
`digestsize` (in module `sha`), 302
`digits` (in module `string`), 75
`dir()` (built-in function), 17
`dir()` (in module `ftplib`), 227
`dircache` (standard module), **123**
`directory`
 changing, 116
 creating, 116
 deleting, 117, 145
 site-packages, 72
 site-python, 72
`dirname()` (in module `os.path`), 121
`dis` (standard module), **66**
`dis()` (in module `dis`), 66
`disassemble()` (in module `dis`), 66
`disco()` (in module `dis`), 67
`dispatcher` (in module `asyncore`), 247
`distb()` (in module `dis`), 66
`dither2grey2()` (in module `imageop`), 291
`dither2mono()` (in module `imageop`), 290
`div()` (in module `operator`), 32
`division`
 integer, 5
 long integer, 5
`divm()` (in module `mpz`), 303
`divmod()` (built-in function), 18
`dl` (extension module), **180**
`dllhandle` (in module `sys`), 26
`do_forms()` (in module `fl`), 311
`do_GET()` (in module `SimpleHTTPServer`), 246
`do_HEAD()` (in module `SimpleHTTPServer`), 246
`do_POST()` (in module `CGIHTTPServer`), 247
`doc_header` (in module `cmd`), 107
`docmd()` (in module `smtplib`), 236
`docstrings`, 51
`done()` (in module `xdrlib`), 272
`DOTALL` (in module `re`), 82
`doupdate()` (in module `curses`), 133
`drain()` (in module `sunaudiodev`), 323
`dumbdbm` (standard module), 167, **168**
`DumbWriter` (in module `formatter`), 261
`dump()` (in module `marshal`), 44
`dump()` (in module `pickle`), 39
`dumps()` (in module `marshal`), 44
`dumps()` (in module `pickle`), 39
`dup()` (in module `os`), 114
`dup()` (`posixfile` method), 188
`dup2()` (in module `os`), 114
`dup2()` (`posixfile` method), 188
`DuplicateSectionError` (in module `ConfigParser`), 103

E

- e (in module cmath), 98
- e (in module math), 96
- E2BIG (in module errno), 138
- EACCES (in module errno), 139
- EADDRINUSE (in module errno), 142
- EADDRNOTAVAIL (in module errno), 143
- EADV (in module errno), 141
- EAFNOSUPPORT (in module errno), 142
- EAGAIN (in module errno), 139
- EALREADY (in module errno), 143
- EBADE (in module errno), 140
- EBADF (in module errno), 138
- EBADFD (in module errno), 142
- EBADMSG (in module errno), 141
- EBADR (in module errno), 140
- EBADRQC (in module errno), 141
- EBADSLT (in module errno), 141
- EBFONT (in module errno), 141
- EBUSY (in module errno), 139
- ECHILD (in module errno), 139
- echo () (in module curses), 133
- echochar () (in module curses), 134
- ECHRNG (in module errno), 140
- ECOMM (in module errno), 141
- ECONNABORTED (in module errno), 143
- ECONNREFUSED (in module errno), 143
- ECONNRESET (in module errno), 143
- EDEADLK (in module errno), 140
- EDEADLOCK (in module errno), 141
- EDESTADDRREQ (in module errno), 142
- EDOM (in module errno), 140
- EDOTDOT (in module errno), 141
- EDQUOT (in module errno), 144
- EEXIST (in module errno), 139
- EFAULT (in module errno), 139
- EFBIG (in module errno), 139
- ehlo () (in module smtplib), 237
- EHOSTDOWN (in module errno), 143
- EHOSTUNREACH (in module errno), 143
- EIDRM (in module errno), 140
- EILSEQ (in module errno), 142
- EINPROGRESS (in module errno), 143
- EINTR (in module errno), 138
- EINVAL (in module errno), 139
- EIO (in module errno), 138
- EISCONN (in module errno), 143
- EISDIR (in module errno), 139
- EISNAM (in module errno), 143
- eject () (in module cd), 309
- EL2HLT (in module errno), 140
- EL2NSYNC (in module errno), 140
- EL3HLT (in module errno), 140
- EL3RST (in module errno), 140
- elements (in module xmllib), 255
- ELIBACC (in module errno), 142
- ELIBBAD (in module errno), 142
- ELIBEXEC (in module errno), 142
- ELIBMAX (in module errno), 142
- ELIBSCN (in module errno), 142
- Ellinghouse, Lance, 269, 303
- EllipsisType (in module types), 30
- ELNRNG (in module errno), 140
- ELOOP (in module errno), 140
- EMFILE (in module errno), 139
- EMLINK (in module errno), 139
- Empty (in module Queue), 166
- empty () (in module Queue), 167
- empty () (in module sched), 131
- emptyline () (in module cmd), 107
- EMSGSIZE (in module errno), 142
- EMULTIHOP (in module errno), 141
- ENAMETOOLONG (in module errno), 140
- ENAVAIL (in module errno), 143
- encode
 - Codecs, 93
- encode () (in module base64), 275
- encode () (in module mimetools), 264
- encode () (in module quopri), 276
- encode () (in module uu), 269
- EncodedFile () (in module codecs), 94
- encodestring () (in module base64), 275
- encoding
 - base64, 275
 - quoted-printable, 276
- encodings_map (in module mimetypes), 275
- encrypt () (in module rotor), 304
- encryptmore () (in module rotor), 304
- end () (in module re), 85
- end_group () (in module fl), 313
- end_headers () (in module BaseHTTPServer), 245
- end_marker () (in module multifile), 267
- end_paragraph () (in module formatter), 258
- endheaders () (in module httplib), 224
- endpick () (in module gl), 318
- endpos (in module re), 85
- endselect () (in module gl), 318
- endwin () (in module curses), 133
- ENETDOWN (in module errno), 143
- ENETRESET (in module errno), 143
- ENETUNREACH (in module errno), 143
- ENFILE (in module errno), 139
- Enigma
 - cipher, 304
 - device, 303
- ENOANO (in module errno), 141
- ENOBUFS (in module errno), 143

ENOCSI (in module errno), 140
 ENODATA (in module errno), 141
 ENODEV (in module errno), 139
 ENOENT (in module errno), 138
 ENOEXEC (in module errno), 138
 ENOLCK (in module errno), 140
 ENOLINK (in module errno), 141
 ENOMEM (in module errno), 139
 ENOMSG (in module errno), 140
 ENONET (in module errno), 141
 ENOPKG (in module errno), 141
 ENOPROTOOPT (in module errno), 142
 ENOSPC (in module errno), 139
 ENOSR (in module errno), 141
 ENOSTR (in module errno), 141
 ENOSYS (in module errno), 140
 ENOTBLK (in module errno), 139
 ENOTCONN (in module errno), 143
 ENOTDIR (in module errno), 139
 ENOTEMPTY (in module errno), 140
 ENOTNAM (in module errno), 143
 ENOTSOCK (in module errno), 142
 ENOTTY (in module errno), 139
 ENOTUNIQ (in module errno), 141
 enter() (in module sched), 131
 enterabs() (in module sched), 131
 entitydefs (in module htmlentitydefs), 255
 entitydefs (in module xmllib), 255
 enumerate() (in module fm), 316
 enumerate() (in module threading), 160
 environ (in module os), 112
 environ (in module posix), 178
 environment variables
 \$HOME, 73, 121
 \$LANG, 146
 \$LNAM, 132
 \$LOGNAME, 132, 226
 \$PAGER, 197
 \$PATH, 121, 217, 219
 \$PYTHONPATH, 28, 217, 330
 \$PYTHONSTARTUP, 73, 176
 \$PYTHON2K, 127, 128
 \$TMPDIR, 138
 \$USERNAME, 132
 \$USER, 132, 226
 \$ftp_proxy, 220
 \$gopher_proxy, 220
 \$http_proxy, 220
 setting, 113
 EnvironmentError (built-in exception base class), 13
 ENXIO (in module errno), 138
 EOFError (built-in exception), 14
 EOPNOTSUPP (in module errno), 142
 EOVERFLOW (in module errno), 141
 EPERM (in module errno), 138
 EPNOSUPPORT (in module errno), 142
 EPIPE (in module errno), 139
 epoch, 127
 EPROTO (in module errno), 141
 EPROTONOSUPPORT (in module errno), 142
 EPROTOTYPE (in module errno), 142
 ERANGE (in module errno), 140
 erase() (in module curses), 135
 EREMCHG (in module errno), 142
 EREMOTE (in module errno), 141
 EREMOTEIO (in module errno), 144
 ERESTART (in module errno), 142
 EROFS (in module errno), 139
 errno (built-in module), 112, 154
 errno (standard module), **138**
 ERROR (in module cd), 308
 Error (in module binascii), 270
 Error (in module locale), 146
 Error (in module sunau), 293
 Error (in module wave), 295
 Error (in module xdrlib), 273
 error, 174
 error (in module anydbm), 167
 error (in module audioop), 287
 error (in module cd), 308
 error (in module curses), 133
 error (in module dbhash), 168
 error (in module dbm), 181
 error (in module dl), 180
 error (in module dumbdbm), 168
 error (in module gdbm), 182
 error (in module getopt), 137
 error (in module imageop), 290
 error (in module imgfile), 319
 error (in module jpeg), 320
 error (in module nis), 192
 error (in module os), 111
 error (in module re), 83
 error (in module regex), 88
 error (in module resource), 189
 error (in module rgbimg), 299
 error (in module select), 158
 error (in module socket), 154
 error (in module struct), 90
 error (in module sunaudiodev), 323
 error (in module thread), 159
 error (in module zlib), 171
 error() (in module mhlib), 277, 278
 error_leader() (in module shlex), 108
 error_message_format (in module Base-HTTPServer), 244
 error_perm (in module ftplib), 225

error_proto (in module ftplib), 225
 error_proto (in module poplib), 228
 error_reply (in module ftplib), 225
 error_temp (in module ftplib), 225
 errorcode (in module errno), 138
 escape() (in module cgi), 216
 escape() (in module re), 83
 ESHUTDOWN (in module errno), 143
 ESOCKTNOSUPPORT (in module errno), 142
 ESPIPE (in module errno), 139
 ESRCH (in module errno), 138
 ESRMNT (in module errno), 141
 ESTALE (in module errno), 143
 ESTRPIPE (in module errno), 142
 ETIME (in module errno), 141
 ETIMEDOUT (in module errno), 143
 ETOOMANYREFS (in module errno), 143
 ETXTBSY (in module errno), 139
 EUCLEAN (in module errno), 143
 EUNATCH (in module errno), 140
 EUSERS (in module errno), 142
 eval(), 10
 eval() (built-in function), 18
 eval() (in module parser), 49
 eval() (in module pprint), 62, 63
 eval() (in module string), 76
 Event (in module threading), 164
 event scheduling, 130
 Event() (in module threading), 160
 EWOULDBLOCK (in module errno), 140
 exc_info() (in module sys), 26
 exc_traceback (in module sys), 26
 exc_type (in module sys), 26
 exc_value (in module sys), 26
 except
 statement, 13
 Exception (built-in exception base class), 13
 exceptions
 built-in, 3
 exceptions (standard module), **12**
 EXDEV (in module errno), 139
 exec
 statement, 10
 exec_prefix (in module sys), 26
 execfile() (built-in function), 18
 execfile() (in module user), 73
 execl() (in module os), 118
 execl() (in module os), 118
 execlp() (in module os), 118
 executable (in module sys), 26
 execv() (in module os), 118
 execve() (in module os), 118
 execvp() (in module os), 118
 execvpe() (in module os), 118

EXFULL (in module errno), 140
 exists() (in module os.path), 121
 exit() (in module sys), 26
 exit() (in module thread), 159
 exit_thread() (in module thread), 159
 exitfunc (in module sys), 27
 exp() (in module cmath), 97
 exp() (in module math), 96
 expandtabs() (in module string), 76
 expanduser() (in module os.path), 121
 expandvars() (in module os.path), 121
 expect() (in module telnetlib), 240
 expovariate() (in module random), 98
 expr() (in module parser), 48
 expunge() (in module imaplib), 231
 extend(), 8
 Extensible Markup Language, 255
 extensions_map (in module SimpleHTTPServer),
 246
 External Data Representation, 37, 270
 extract_stack() (in module traceback), 35
 extract_tb() (in module traceback), 35

F

F_BAVAIL (in module statvfs), 126
 F_BFREE (in module statvfs), 126
 F_BLOCKS (in module statvfs), 126
 F_BSIZE (in module statvfs), 126
 F_FAVAIL (in module statvfs), 126
 F_FFEE (in module statvfs), 126
 F_FILES (in module statvfs), 126
 F_FLAG (in module statvfs), 126
 F_FRSIZE (in module statvfs), 126
 F_NAMEMAX (in module statvfs), 126
 F_OK (in module os), 115
 fabs() (in module math), 96
 false, 3
 FancyURLopener (in module urllib), 222
 FCNTL (standard module), 185
 fcntl (built-in module), 11, **185**
 fcntl() (in module fcntl), 185
 fcntl() (in module posixfile), 187
 fdopen() (in module os), 113
 feed() (in module sgmlib), 252
 feed() (in module xmllib), 256
 fetch() (in module imaplib), 231
 file
 .ini, 103
 .pdbrc, 197
 .pythonrc.py, 73
 byte-code, 44, 46, 65
 configuration, 103
 copying, 145
 debugger configuration, 197

- large files, 178
 - mime.types, 275
 - object, 11
 - path configuration, 72
 - temporary, 137
 - user configuration, 73
- file (in module pycbr), 59
- file control
 - UNIX, 185
- file name
 - temporary, 137
- file object
 - POSIX, 187
- file() (posixfile method), 188
- filecmp (standard module), **126**
- FileInput (in module fileinput), 105
- fileinput (standard module), **104**
- filelineno() (in module fileinput), 105
- filename() (in module fileinput), 105
- filename_only (in module tabnanny), 58
- filenames
 - pathname expansion, 144
 - wildcard expansion, 144
- fileno(), 11
- fileno() (SocketServer protocol), 242
- fileno() (in module select), 159
- fileno() (in module socket), 156
- fileno() (in module sunaudiodev), 323
- fileno() (in module telnetlib), 240
- fileopen() (in module posixfile), 187
- FileType (in module types), 30
- filter() (built-in function), 18
- find() (in module string), 76
- find_first() (in module fl), 313
- find_last() (in module fl), 313
- find_module() (in module imp), 45
- findall() (in module re), 82, 84
- findfactor() (in module audioop), 288
- findfit() (in module audioop), 288
- findfont() (in module fm), 316
- findmatch() (in module mailcap), 273
- findmax() (in module audioop), 288
- finish() (SocketServer protocol), 243
- finish_request() (SocketServer protocol), 243
- first() (in module bsddb), 170
- first() (in module dbhash), 169
- firstkey() (in module gdbm), 182
- fix() (in module fpformat), 92
- FL (standard module), **315**
- fl (built-in module), **310**
- flags (in module re), 84
- flags() (posixfile method), 187
- flash() (in module curses), 133
- flattening
 - objects, 36
- float(), 5
- float() (built-in function), 18
- float() (in module string), 76
- floating point
 - literals, 5
 - type, 5
- FloatingPointError (built-in exception), 14
- FloatType (in module types), 30
- flock() (in module fcntl), 185
- floor(), 5
- floor() (in module math), 96
- flp (standard module), **316**
- flush(), 11
- flush() (in module formatter), 260
- flush() (in module sunaudiodev), 324
- flush() (in module zlib), 172
- flush_softspace() (in module formatter), 259
- flushheaders() (in module MimeWriter), 266
- flushinp() (in module curses), 133
- fm (built-in module), **316**
- fmod() (in module math), 96
- fnmatch (standard module), **144**
- fnmatch() (in module fnmatch), 145
- fnmatchcase() (in module fnmatch), 145
- Folder (in module mhlib), 277
- Font Manager, IRIS, 316
- fontpath() (in module fm), 316
- forget() (in module statcache), 125
- forget_dir() (in module statcache), 126
- forget_except_prefix() (in module statcache), 126
- forget_prefix() (in module statcache), 125
- fork() (in module os), 118
- fork() (in module pty), 185
- format() (in module locale), 147
- format_exception() (in module traceback), 35
- format_exception_only() (in module traceback), 35
- format_list() (in module traceback), 35
- format_stack() (in module traceback), 35
- format_tb() (in module traceback), 35
- formatter (in module htmllib), 254
- formatter (standard module), 253, **258**
- FORMS Library, 311
- fp (in module rfc822), 264
- fpathconf() (in module os), 114
- fpformat (standard module), **92**
- frame
 - object, 153
- FrameType (in module types), 31
- freeze_form() (in module fl), 312
- freeze_object() (in module fl), 315
- frexp() (in module math), 96

fromchild (in module popen2), 193
 fromfd() (in module socket), 155
 fromfile() (in module array), 101
 fromlist() (in module array), 102
 fromstring() (in module array), 102
 fstat() (in module os), 114
 fstatvfs() (in module os), 114
 FTP
 protocol, 222, 224
 FTP (in module ftplib), 225
 \$ftp_proxy, 220
 ftplib (standard module), **224**
 ftpmirror.py, 225
 ftruncate() (in module os), 114
 Full (in module Queue), 166
 full() (in module Queue), 167
 func_code, 10
 function() (in module new), 71
 functions
 built-in, 3
 FunctionType (in module types), 30

G

G.722, 292
 gamma() (in module random), 98
 gauss() (in module random), 98
 gcd() (in module mpz), 303
 gcdext() (in module mpz), 303
 gdbm (built-in module), 42, 167, 181, **182**
 get(), 8
 get() (in module ConfigParser), 104
 get() (in module Queue), 167
 get() (in module rfc822), 263
 get_buffer() (in module xdrlib), 271, 272
 get_directory() (in module fl), 312
 get_filename() (in module fl), 312
 get_ident() (in module thread), 159
 get_magic() (in module imp), 44
 get_mouse() (in module fl), 312
 get_nowait() (in module Queue), 167
 get_osfhandle() (in module msvcrt), 325
 get_pattern() (in module fl), 312
 get_position() (in module xdrlib), 272
 get_request() (SocketServer protocol), 243
 get_rgbmode() (in module fl), 311
 get_socket() (in module telnetlib), 240
 get_suffixes() (in module imp), 45
 get_syntax() (in module regex), 88
 get_token() (in module shlex), 108
 getaddr() (in module rfc822), 263
 getaddrlist() (in module rfc822), 263
 getallmatchingheaders() (in module rfc822),
 263
 getatime() (in module os.path), 121

getattr() (built-in function), 19
 getbegyx() (in module curses), 135
 getboolean() (in module ConfigParser), 104
 getcaps() (in module mailcap), 274
 getch() (in module curses), 136
 getch() (in module msvcrt), 325
 getchannels() (in module al), 306
 getche() (in module msvcrt), 326
 getcomment() (font handle method), 316
 getcompname() (in module aifc), 291
 getcompname() (in module sunau), 294
 getcompname() (in module wave), 296
 getcomptype() (in module aifc), 291
 getcomptype() (in module sunau), 294
 getcomptype() (in module wave), 296
 getconfig() (in module al), 307
 getcontext() (in module mhlib), 277
 getcurrent() (in module mhlib), 278
 getcwd() (in module os), 116
 getdate() (in module rfc822), 263
 getdate_tz() (in module rfc822), 263
 getegid() (in module os), 112
 getencoding() (in module mimetools), 265
 geteuid() (in module os), 112
 getfd() (in module al), 306
 getfile() (in module httplib), 224
 getfillable() (in module al), 306
 getfilled() (in module al), 306
 getfillpoint() (in module al), 307
 getfirstmatchingheader() (in module
 rfc822), 263
 getfloat() (in module ConfigParser), 104
 getfloatmax() (in module al), 306
 getfontinfo() (font handle method), 317
 getfontname() (font handle method), 316
 getframerate() (in module aifc), 291
 getframerate() (in module sunau), 294
 getframerate() (in module wave), 295
 getfullname() (in module mhlib), 278
 getgid() (in module os), 112
 getgrall() (in module grp), 179
 getgrgid() (in module grp), 179
 getgrnam() (in module grp), 179
 getgroups() (in module os), 112
 getheader() (in module rfc822), 263
 gethostbyaddr() (in module os), 113
 gethostbyaddr() (in module socket), 154
 gethostbyname() (in module socket), 154
 gethostbyname_ex() (in module socket), 154
 gethostname() (in module os), 113
 gethostname() (in module socket), 154
 getinfo() (in module sunaudiodev), 324
 getint() (in module ConfigParser), 104
 getitem() (in module operator), 33

`getlast()` (in module `mhlib`), 278
`getline()` (in module `linecache`), 36
`getlogin()` (in module `os`), 112
`getmaintype()` (in module `mimertools`), 265
`getmark()` (in module `aifc`), 292
`getmark()` (in module `sunau`), 294
`getmark()` (in module `wave`), 296
`getmarkers()` (in module `aifc`), 292
`getmarkers()` (in module `sunau`), 294
`getmarkers()` (in module `wave`), 296
`getmaxyx()` (in module `curses`), 135
`getmcolor()` (in module `fl`), 312
`getmessagefilename()` (in module `mhlib`), 278
`getmtime()` (in module `os.path`), 122
`getName()` (in module `threading`), 166
`getname()` (in module `chunk`), 297
`getnchannels()` (in module `aifc`), 291
`getnchannels()` (in module `sunau`), 293
`getnchannels()` (in module `wave`), 295
`getnframes()` (in module `aifc`), 291
`getnframes()` (in module `sunau`), 294
`getnframes()` (in module `wave`), 295
`getopt` (standard module), **136**
`getopt()` (in module `getopt`), 136
`GetoptError` (in module `getopt`), 137
`getoutput()` (in module `commands`), 193
`getpagesize()` (in module `resource`), 191
`getparam()` (in module `mimertools`), 265
`getparams()` (in module `aifc`), 292
`getparams()` (in module `al`), 306
`getparams()` (in module `sunau`), 294
`getparams()` (in module `wave`), 296
`getpass` (standard module), **131**
`getpass()` (in module `getpass`), 132
`getpath()` (in module `mhlib`), 277
`getpeername()` (in module `socket`), 156
`getpgrp()` (in module `os`), 112
`getpid()` (in module `os`), 112
`getplist()` (in module `mimertools`), 265
`getppid()` (in module `os`), 113
`getprofile()` (in module `mhlib`), 277
`getprotobyname()` (in module `socket`), 155
`getpwall()` (in module `pwd`), 179
`getpwnam()` (in module `pwd`), 179
`getpwuid()` (in module `pwd`), 179
`getqueuesize()` (in module `al`), 306
`getrawheader()` (in module `rfc822`), 263
`getrefcount()` (in module `sys`), 27
`getreply()` (in module `httplib`), 224
`getrlimit()` (in module `resource`), 189
`getrusage()` (in module `resource`), 190
`getsampfmt()` (in module `al`), 306
`getsample()` (in module `audioop`), 288
`getsampwidth()` (in module `aifc`), 291
`getsampwidth()` (in module `sunau`), 293
`getsampwidth()` (in module `wave`), 295
`getsequences()` (in module `mhlib`), 278
`getsequencesfilename()` (in module `mhlib`), 278
`getservbyname()` (in module `socket`), 155
`getsignal()` (in module `signal`), 152
`getsize()` (in module `chunk`), 297
`getsize()` (in module `os.path`), 122
`getsizes()` (in module `imgfile`), 319
`getslice()` (in module `operator`), 33
`getsockname()` (in module `socket`), 156
`getsockopt()` (in module `socket`), 156
`getstatus()` (in module `al`), 307
`getstatus()` (in module `cd`), 309
`getstatus()` (in module `commands`), 194
`getstatusoutput()` (in module `commands`), 193
`getstr()` (in module `curses`), 136
`getstrwidth()` (font handle method), 317
`getsubtype()` (in module `mimertools`), 265
`gettrackinfo()` (in module `cd`), 309
`gettype()` (in module `mimertools`), 265
`getuid()` (in module `os`), 113
`getuser()` (in module `getpass`), 132
`getvalue()` (in module `StringIO`), 93
`getwelcome()` (in module `ftplib`), 226
`getwelcome()` (in module `nntplib`), 234
`getwelcome()` (in module `poplib`), 228
`getwidth()` (in module `al`), 306
`getyx()` (in module `curses`), 135
`givenpat` (regex attribute), 89
`GL` (standard module), **319**
`gl` (built-in module), **317**
`glob` (standard module), 144, **144**
`glob()` (in module `glob`), 144
`globals()` (built-in function), 19
`gmtime()` (in module `time`), 128
`Gopher`
 protocol, 222, 227
`$gopher_proxy`, 220
`gopherlib` (standard module), **227**
`Greenwich Mean Time`, 127
`grey22grey()` (in module `imageop`), 291
`grey2grey2()` (in module `imageop`), 291
`grey2grey4()` (in module `imageop`), 290
`grey2mono()` (in module `imageop`), 290
`grey42grey()` (in module `imageop`), 291
`group()` (in module `nntplib`), 234
`group()` (in module `re`), 84
`group()` (regex method), 88
`groupdict()` (in module `re`), 84
`groupindex` (in module `re`), 84
`groupindex` (regex attribute), 89
`groups()` (in module `re`), 84

grp (built-in module), **179**
gsub() (in module re), 89
guess_extension() (in module mimetypes), 274
guess_type() (in module mimetypes), 274
gzip (standard module), **173**
GzipFile (in module gzip), 173

H

handle() (SocketServer protocol), 243
handle() (in module BaseHTTPServer), 245
handle_accept() (in module asyncore), 248
handle_cdata() (in module xmllib), 256
handle_charref() (in module sgmlib), 252
handle_charref() (in module xmllib), 256
handle_close() (in module asyncore), 248
handle_comment() (in module sgmlib), 252
handle_comment() (in module xmllib), 256
handle_connect() (in module asyncore), 248
handle_data() (in module sgmlib), 252
handle_data() (in module xmllib), 256
handle_doctype() (in module xmllib), 256
handle_endtag() (in module sgmlib), 252
handle_endtag() (in module xmllib), 256
handle_entityref() (in module sgmlib), 252
handle_error() (SocketServer protocol), 243
handle_expt() (in module asyncore), 248
handle_image() (in module htmlib), 254
handle_proc() (in module xmllib), 257
handle_read() (in module asyncore), 248
handle_request() (SocketServer protocol), 242
handle_special() (in module xmllib), 257
handle_starttag() (in module sgmlib), 252
handle_starttag() (in module xmllib), 256
handle_write() (in module asyncore), 248
handle_xml() (in module xmllib), 256
has_extn() (in module smtplib), 237
has_key(), 8
has_key() (in module bsddb), 170
has_section() (in module ConfigParser), 104
hasattr() (built-in function), 19
hascompare (in module dis), 67
hasconst (in module dis), 67
hash() (built-in function), 19
hashopen() (in module bsddb), 170
hasjabs (in module dis), 67
hasjrel (in module dis), 67
haslocal (in module dis), 67
hasname (in module dis), 67
head() (in module nntplib), 235
headers
 MIME, 213, 274
headers (in module BaseHTTPServer), 244
headers (in module rfc822), 263
heapmin() (in module msvcrt), 326

hello() (in module smtplib), 237
help() (in module nntplib), 234
hex() (built-in function), 19
hexadecimal
 literals, 5
hexbin() (in module binhex), 268
hexdigest() (in module sha), 302
hexdigits (in module string), 75
hexversion (in module sys), 27
hide_form() (in module fl), 312
hide_object() (in module fl), 315
hline() (in module curses), 135
hls_to_rgb() (in module colorsys), 298
\$HOME, 73, 121
hosts (in module netrc), 280
hsv_to_rgb() (in module colorsys), 298
HTML, 222, 253
htmlentitydefs (standard module), **255**
htmlib (standard module), 222, 251, **253**
HTMLParser (in module formatter), 258
HTMLParser (in module htmlib), 254
htonl() (in module socket), 155
htons() (in module socket), 155
HTTP
 protocol, 213, 222, 223, 243
HTTP (in module httplib), 223
\$http_proxy, 220
httpd, 243
httplib (standard module), **223**
HTTPServer (in module BaseHTTPServer), 244
hypertext, 253
hypot() (in module math), 96

I

I (in module re), 81
I/O control
 buffering, 20, 113, 156
 POSIX, 183, 184
 tty, 183, 184
 UNIX, 185
ibufcount() (in module sunaudiodev), 324
id() (built-in function), 19
IDEA
 cipher, 301
ident (in module cd), 308
identchars (in module cmd), 107
idllok() (in module curses), 136
if
 statement, 3
ignore() (in module pstats), 207
IGNORECASE (in module re), 81
ihave() (in module nntplib), 235
ihooks (standard module), 16
imageop (built-in module), **290**

IMAP4
 protocol, 229
IMAP4 (in module `imaplib`), 229
IMAP4.abort (in module `imaplib`), 229
IMAP4.error (in module `imaplib`), 229
IMAP4.readonly (in module `imaplib`), 230
imaplib (standard module), **229**
imgfile (built-in module), **319**
imghdr (standard module), **299**
imp (built-in module), 16, **44**
import
 statement, 16, 44
ImportError (built-in exception), 14
in
 operator, 4, 6
INADDR_* (in module `socket`), 154
inch() (in module `curses`), 136
Incomplete (in module `binascii`), 270
Independent JPEG Group, 320
index (in module `cd`), 308
index(), 8
index() (in module `string`), 76
IndexError (built-in exception), 14
indexOf() (in module `operator`), 33
inet_aton() (in module `socket`), 155
inet_ntoa() (in module `socket`), 155
infile (in module `shlex`), 109
Infinity, 18, 76
InfoSeek Corporation, 201
ini file, 103
init() (in module `fm`), 316
init() (in module `mimetypes`), 274
init_builtin() (in module `imp`), 46
init_frozen() (in module `imp`), 46
inited (in module `mimetypes`), 275
initscr() (in module `curses`), 133
input() (built-in function), 19
input() (in module `fileinput`), 105
input() (in module `sys`), 28
InputType (in module `cStringIO`), 93
insch() (in module `curses`), 134
insert(), 8
insert() (in module `array`), 102
insertln() (in module `curses`), 135
insort() (in module `bisect`), 100
instance() (in module `new`), 71
instancemethod() (in module `new`), 71
InstanceType (in module `types`), 30
instream (in module `shlex`), 109
int(), 5
int() (built-in function), 19
Int2AP() (in module `imaplib`), 230
integer
 arbitrary precision, 302
 division, 5
 division, long, 5
 literals, 5
 literals, long, 5
 type, 5
 type, long, 5
 types, 5
 types, operations on, 6
Intel/DVI ADPCM, 287
interact() (in module `code`), 59, 60
interact() (in module `telnetlib`), 240
InteractiveConsole (in module `code`), 59
InteractiveInterpreter (in module `code`), 59
intern() (built-in function), 19
Internaldate2tuple() (in module `imaplib`),
 230
Internet, 213
Internet Config, 220
InterpolationError (in module `ConfigParser`),
 103
interpreter prompts, 28
intro (in module `cmd`), 107
IntType (in module `types`), 29
inv() (in module `operator`), 33
IOCTL (standard module), 185
ioctl() (in module `fcntl`), 185
IOError (built-in exception), 14
IP_* (in module `socket`), 154
IPPORT_* (in module `socket`), 154
IPPROTO_* (in module `socket`), 154
IRIS Font Manager, 316
IRIX
 threads, 160
is
 operator, 4
is not
 operator, 4
is_builtin() (in module `imp`), 46
is_data() (in module `multifile`), 267
is_frozen() (in module `imp`), 46
is_zipfile(), 174
isabs() (in module `os.path`), 122
isAlive() (in module `threading`), 166
isatty(), 11
isatty() (in module `chunk`), 297
iscomment() (in module `rfc822`), 262
isDaemon() (in module `threading`), 166
isdir() (in module `os.path`), 122
isendwin() (in module `curses`), 133
ISEOF() (in module `token`), 57
isexpr() (in module `parser`), 49, 50
isfile() (in module `os.path`), 122
isfirstline() (in module `fileinput`), 105
isheader() (in module `rfc822`), 262

isinstance() (built-in function), 19
 iskeyword() (in module keyword), 57
 islast() (in module rfc822), 262
 isleap() (in module calendar), 105
 islink() (in module os.path), 122
 ismount() (in module os.path), 122
 ISNONTERMINAL() (in module token), 57
 isqueued() (in module fl), 312
 isreadable() (in module pprint), 62, 63
 isrecursive() (in module pprint), 63
 isSet() (in module threading), 164
 isstdin() (in module fileinput), 105
 issubclass() (built-in function), 20
 issuite() (in module parser), 49, 50
 ISTERMINAL() (in module token), 57
 items(), 8
 itemsize (in module array), 101

J

Jansen, Jack, 269
 JFIF, 320
 join() (in module os.path), 122
 join() (in module string), 77
 join() (in module threading), 165
 joinfields() (in module string), 77
 jpeg (built-in module), **320**

K

kbhit() (in module msvcrt), 325
 KEY_* (in module curses), 132
 KeyboardInterrupt (built-in exception), 14
 KeyError (built-in exception), 14
 keyname() (in module curses), 134
 keypad() (in module curses), 136
 keys(), 8
 keys() (in module bsddb), 170
 keyword (standard module), **57**
 kill() (in module os), 118
 knee (standard module), 47
 knownfiles (in module mimetypes), 275
 Kuchling, Andrew, 85, 89, 301

L

L (in module re), 81
 LambdaType (in module types), 30
 \$LANG, 146
 language

- ABC, 4
- C, 5
- C, 4, 5

 large files, 178
 last (in module multifile), 267
 last (regex attribute), 89
 last() (in module bsddb), 171

last() (in module dbhash), 169
 last() (in module nntplib), 234
 last_traceback (in module sys), 27
 last_type (in module sys), 27
 last_value (in module sys), 27
 lastcmd (in module cmd), 107
 lastpart() (in module MimeWriter), 266
 LC_ALL (in module locale), 148
 LC_COLLATE (in module locale), 148
 LC_CTYPE (in module locale), 148
 LC_MESSAGES (in module locale), 148
 LC_MONETARY (in module locale), 148
 LC_NUMERIC (in module locale), 148
 LC_TIME (in module locale), 148
 ldexp() (in module math), 96
 leapdays() (in module calendar), 106
 leaveok() (in module curses), 136
 len(), 6, 8
 len() (built-in function), 20
 letters (in module string), 75
 level (in module multifile), 267
 light-weight processes, 159
 lin2adpcm() (in module audioop), 288
 lin2adpcm3() (in module audioop), 288
 lin2lin() (in module audioop), 288
 lin2ulaw() (in module audioop), 288
 line-buffered I/O, 20
 linecache (standard module), **36**
 lineno (in module pycbr), 59
 lineno (in module shlex), 109
 lineno() (in module fileinput), 105
 linesep (in module os), 121
 link() (in module os), 116
 list

- type, 6, 7
- type, operations on, 8

 list() (built-in function), 20
 list() (in module imaplib), 231
 list() (in module nntplib), 234
 list() (in module poplib), 228
 listallfolders() (in module mhlib), 277
 listallsubfolders() (in module mhlib), 277
 listdir(), 175
 listdir() (in module dircache), 123
 listdir() (in module os), 116
 listen() (in module asyncore), 249
 listen() (in module socket), 156
 listfolders() (in module mhlib), 277
 listmessages() (in module mhlib), 278
 listsubfolders() (in module mhlib), 277
 ListType (in module types), 30
 literals

- complex number, 5
- floating point, 5

- hexadecimal, 5
- integer, 5
- long integer, 5
- numeric, 5
- octal, 5
- ljust() (in module string), 77
- \$LNAME, 132
- load() (in module marshal), 44
- load() (in module pickle), 39
- load_compiled() (in module imp), 46
- load_dynamic() (in module imp), 46
- load_module() (in module imp), 45
- load_source() (in module imp), 46
- loads() (in module marshal), 44
- loads() (in module pickle), 39
- LOCALE (in module re), 82
- locale (standard module), **146**
- localeconv() (in module locale), 146
- locals() (built-in function), 20
- localtime() (in module time), 128
- Lock() (in module threading), 160
- lock() (in module mutex), 150
- lock() (posixfile method), 187
- locked() (in module thread), 159
- lockf() (in modulefcntl), 185
- lockf() (in module posixfile), 187
- locking() (in module msvcrt), 325
- LockType (in module thread), 159
- log() (in module cmath), 97
- log() (in module math), 96
- log10() (in module cmath), 97
- log10() (in module math), 96
- log_data_time_string() (in module Base-
HTTPServer), 245
- log_error() (in module BaseHTTPServer), 245
- log_message() (in module BaseHTTPServer),
245
- log_request() (in module BaseHTTPServer),
245
- login() (in module ftplib), 226
- login() (in module imaplib), 231
- \$LOGNAME, 132, 226
- lognormvariate() (in module random), 98
- logout() (in module imaplib), 231
- long
 - integer division, 5
 - integer literals, 5
 - integer type, 5
- long(), 5
- long() (built-in function), 20
- long() (in module string), 76
- longimagedata() (in module rgbimg), 299
- longstoimage() (in module rgbimg), 299
- LongType (in module types), 29

- lookup() (in module codecs), 94
- LookupError (built-in exception base class), 13
- lower() (in module string), 76
- lowercase (in module string), 75
- lseek() (in module os), 114
- lshift() (in module operator), 33
- lstat() (in module os), 116
- rstrip() (in module string), 77
- lsub() (in module imaplib), 231
- Lundh, Fredrik, 320

M

- M (in module re), 82
- macros (in module netrc), 280
- mailbox (standard module), 261, **276**
- mailcap (standard module), **273**
- Maildir (in module mailbox), 276
- make_form() (in module fl), 311
- makedirs() (in module os), 116
- makefile() (in module socket), 156
- makefolder() (in module mhlib), 277
- maketrans() (in module string), 76
- map() (built-in function), 20
- mapcolor() (in module fl), 312
- mapping
 - types, 8
 - types, operations on, 8
- maps() (in module nis), 192
- marshal (built-in module), 37, **43**
- marshalling
 - objects, 36
- masking
 - operations, 6
- match() (in module nis), 191
- match() (in module re), 82, 83
- match() (in module regex), 87
- match() (regex method), 88
- math (built-in module), 5, **95**, 98
- max(), 6
- max() (built-in function), 20
- max() (in module audioop), 288
- maxdict (in module repr), 64
- maxint (in module sys), 27
- MAXLEN (in module mimify), 279
- maxlevel (in module repr), 64
- maxlist (in module repr), 64
- maxlength (in module repr), 64
- maxother (in module repr), 64
- maxpp() (in module audioop), 288
- maxstring (in module repr), 64
- maxtuple (in module repr), 64
- md5 (built-in module), **301**
- md5() (in module md5), 301
- MemoryError (built-in exception), 14

Message (in module BaseHTTPServer), 245
 Message (in module mhlib), 277
 Message (in module mimetools), 264
 Message (in module rfc822), 261
 message digest, MD5, 301
 MessageClass (in module BaseHTTPServer), 245
 meta() (in module curses), 134
 method
 object, 10
 methods (in module pycbr), 59
 MethodType (in module types), 30
 MH (in module mhlib), 277
 mhlib (standard module), **277**
 MHMailbox (in module mailbox), 276
 MIME
 base64 encoding, 275
 content type, 274
 headers, 213, 274
 quoted-printable encoding, 276
 mime_decode_header() (in module mimify),
 279
 mime_encode_header() (in module mimify),
 279
 mimetools (standard module), 220, 224, **264**
 mimetypes (standard module), **274**
 MimeWriter (in module MimeWriter), 265
 MimeWriter (standard module), **265**
 mimify (standard module), **278**
 mimify() (in module mimify), 279
 min(), 6
 min() (built-in function), 20
 minmax() (in module audioop), 288
 misc_header (in module cmd), 107
 MissingSectionHeaderError (in module Con-
 figParser), 103
 mkd() (in module ftplib), 227
 mkdir() (in module os), 116
 mkfifo() (in module os), 116
 mktemp() (in module tempfile), 137
 mktime() (in module time), 129
 mktime_tz() (in module rfc822), 262
 MmdfMailbox (in module mailbox), 276
 mod() (in module operator), 32
 mode, 12
 modf() (in module math), 96
 modified() (in module robotparser), 280
 module
 search path, 27, 36, 72
 module (in module pycbr), 59
 module() (in module new), 72
 modules (in module sys), 27
 ModuleType (in module types), 30
 mono2grey() (in module imageop), 290
 monthcalendar() (in module calendar), 106
 monthrange() (in module calendar), 106
 move() (in module curses), 134
 movemessage() (in module mhlib), 278
 MP, GNU library, 302
 mpz (built-in module), **302**
 mpz() (in module mpz), 303
 MPZType (in module mpz), 303
 msftoblock() (in module cd), 309
 msftoframe() (in module cd), 308
 msg() (in module telnetlib), 239
 MSG_* (in module socket), 154
 msvcr7 (built-in module), **325**
 mt_interact() (in module telnetlib), 240
 mtime() (in module robotparser), 280
 mul() (in module audioop), 289
 mul() (in module operator), 32
 MultiFile (in module multifile), 266
 multifile (standard module), **266**
 MULTILINE (in module re), 82
 mutable
 sequence types, 7
 sequence types, operations on, 8
 MutableString (in module UserString), 32
 mutex (in module mutex), 149
 mutex (standard module), **149**
 mvwin() (in module curses), 134

N

name, 12
 name (in module os), 112
 name (in module pycbr), 59
 NameError (built-in exception), 14
 namespaces
 XML, 257
 NaN, 18, 76
 NannyNag (in module tabnanny), 58
 National Security Agency, 304
 neg() (in module operator), 32
 netrc (in module netrc), 280
 netrc (standard module), **279**
 Network News Transfer Protocol, 232
 new (built-in module), **71**
 new() (in module md5), 301
 new() (in module sha), 302
 new_alignment() (in module formatter), 260
 new_font() (in module formatter), 260
 new_margin() (in module formatter), 260
 new_module() (in module imp), 45
 new_spacing() (in module formatter), 260
 new_styles() (in module formatter), 260
 newconfig() (in module al), 305
 newgroups() (in module nntplib), 234
 newnews() (in module nntplib), 234
 newrotor() (in module rotor), 304

newwin() (in module curses), 133
 next() (in module bsddb), 170
 next() (in module dbhash), 169
 next() (in module mailbox), 276
 next() (in module multifile), 267
 next() (in module nntplib), 234
 nextfile() (in module fileinput), 105
 nextkey() (in module gdbm), 182
 nextpart() (in module MimeWriter), 266
 nice() (in module os), 119
 nis (extension module), **191**
 NIST, 302
 nl() (in module curses), 133
 nlst() (in module ftplib), 227
 NNTP
 protocol, 232
 NNTP (in module nntplib), 233
 NNTPDataError (in module nntplib), 234
 NNTPError (in module nntplib), 233
 nntplib (standard module), **232**
 NNTPPermanentError (in module nntplib), 233
 NNTPProtocolError (in module nntplib), 234
 NNTPReplyError (in module nntplib), 233
 NNTPTemporaryError (in module nntplib), 233
 nocbreak() (in module curses), 133
 nodelay() (in module curses), 136
 NODISC (in module cd), 308
 noecho() (in module curses), 133
 nofill (in module htmlib), 254
 nok_builtin_names (in module rexec), 284
 None, 3
 NoneType (in module types), 29
 nonl() (in module curses), 133
 noop() (in module imaplib), 231
 noop() (in module poplib), 229
 NoOptionError (in module ConfigParser), 103
 nooutrefresh() (in module curses), 134
 noraw() (in module curses), 134
 normalvariate() (in module random), 98
 normcase() (in module os.path), 122
 normpath() (in module os.path), 122
 NoSectionError (in module ConfigParser), 103
 not
 operator, 4
 not in
 operator, 4, 6
 not_() (in module operator), 33
 NotANumber (in module fpformat), 92
 notify() (in module threading), 163
 notifyAll() (in module threading), 163
 notimeout() (in module curses), 136
 NotImplementedError (built-in exception), 14
 NSA, 304
 NSIG (in module signal), 152

ntohl() (in module socket), 155
 ntohs() (in module socket), 155
 ntransfercmd() (in module ftplib), 227
 NullFormatter (in module formatter), 260
 NullWriter (in module formatter), 261
 numeric
 conversions, 5
 literals, 5
 object, 4
 types, 5
 types, operations on, 5
 Numerical Python, 22
 nurbscurve() (in module gl), 318
 nurbssurface() (in module gl), 318
 ndarray() (in module gl), 318

O

O_APPEND (in module os), 115
 O_CREAT (in module os), 115
 O_DSYNC (in module os), 115
 O_EXCL (in module os), 115
 O_NDELAY (in module os), 115
 O_NOCTTY (in module os), 115
 O_NONBLOCK (in module os), 115
 O_RDONLY (in module os), 115
 O_RDWR (in module os), 115
 O_RSYNC (in module os), 115
 O_SYNC (in module os), 115
 O_TRUNC (in module os), 115
 O_WRONLY (in module os), 115
 object
 code, 10, 44
 file, 11
 frame, 153
 method, 10
 numeric, 4
 socket, 153
 traceback, 26, 34
 type, 23
 objects
 comparing, 4
 flattening, 36
 marshalling, 36
 persistent, 36
 pickling, 36
 serializing, 36
 obufcount() (in module sunaudiodev), 324
 oct() (built-in function), 20
 octal
 literals, 5
 octdigits (in module string), 75
 ok_builtin_modules (in module rexec), 284
 ok_path (in module rexec), 284
 ok_posix_names (in module rexec), 284

- ok_sys_names (in module rexec), 284
- oncmd () (in module cmd), 107
- open (), 11
- open () (built-in function), 20
- open () (in module aifc), 291
- open () (in module anydbm), 167
- open () (in module cd), 308
- open () (in module codecs), 94
- open () (in module dbhash), 168
- open () (in module dbm), 181
- open () (in module dl), 180
- open () (in module dumbdbm), 168
- open () (in module gdbm), 182
- open () (in module gzip), 173
- open () (in module imaplib), 231
- open () (in module os), 114
- open () (in module pipes), 187
- open () (in module posixfile), 187
- open () (in module sunau), 293
- open () (in module sunaudiodev), 323
- open () (in module telnetlib), 239
- open () (in module urllib), 222
- open () (in module wave), 295
- open_osfhandle () (in module msvcrt), 325
- open_unknown () (in module urllib), 222
- opendir () (in module dircache), 123
- openfolder () (in module mhlib), 277
- openfp () (in module sunau), 293
- openfp () (in module wave), 295
- OpenGL, 319
- openhook () (in module shlex), 108
- openlog () (in module syslog), 192
- openmessage () (in module mhlib), 278
- openport () (in module al), 305
- operation
 - concatenation, 6
 - repetition, 6
 - slice, 6
 - subscript, 6
- operations
 - bit-string, 6
 - Boolean, 3, 4
 - masking, 6
 - shifting, 6
- operations on
 - dictionary type, 8
 - integer types, 6
 - list type, 8
 - mapping types, 8
 - mutable sequence types, 8
 - numeric types, 5
 - sequence types, 6, 8
- operator
 - ==, 4
 - and, 3, 4
 - comparison, 4
 - in, 4, 6
 - is, 4
 - is not, 4
 - not, 4
 - not in, 4, 6
 - or, 3, 4
- operator (built-in module), **32**
- opname (in module dis), 67
- options () (in module ConfigParser), 104
- or
 - operator, 3, 4
- or_ () (in module operator), 33
- ord () (built-in function), 21
- os (standard module), 28, **111**, 177
- os.path (standard module), **121**
- OSError (built-in exception), 14
- OutputType (in module cStringIO), 93
- OverflowError (built-in exception), 15
- Overmars, Mark, 311

P

- P_DETACH (in module os), 119
- P_NOWAIT (in module os), 119
- P_NOWAITO (in module os), 119
- P_OVERLAY (in module os), 119
- P_WAIT (in module os), 119
- pack () (in module struct), 90
- pack_array () (in module xdrlib), 272
- pack_bytes () (in module xdrlib), 271
- pack_double () (in module xdrlib), 271
- pack_farray () (in module xdrlib), 272
- pack_float () (in module xdrlib), 271
- pack_fopaque () (in module xdrlib), 271
- pack_fstring () (in module xdrlib), 271
- pack_list () (in module xdrlib), 271
- pack_opaque () (in module xdrlib), 271
- pack_string () (in module xdrlib), 271
- package, 72
- Packer (in module xdrlib), 271
- packing
 - binary data, 90
- \$PAGER, 197
- pardir (in module os), 121
- paretovariate () (in module random), 98
- parse () (in module cgi), 216
- parse () (in module robotparser), 280
- parse_header () (in module cgi), 216
- parse_multipart () (in module cgi), 216
- parse_qs () (in module cgi), 216
- parse_qs1 () (in module cgi), 216
- parsedate () (in module rfc822), 262
- parsedate_tz () (in module rfc822), 262

ParseFlags() (in module imaplib), 230
parseframe() (in module cd), 310
parser (built-in module), **47**
ParserError (in module parser), 50
parsesequence() (in module mhtml), 278
parsing
 Python source code, 47
 URL, 241
ParsingError (in module ConfigParser), 103
partial() (in module imaplib), 231
pass_() (in module poplib), 228
\$PATH, 121, 217, 219
path
 configuration file, 72
 module search, 27, 36, 72
 operations, 121
path (in module BaseHTTPServer), 244
path (in module os), 112
path (in module sys), 27
pathconf() (in module os), 116
pathconf_names (in module os), 116
pathsep (in module os), 121
pattern (in module re), 84
pause() (in module signal), 152
PAUSED (in module cd), 308
Pdb (in module pdb), 195
pdb (standard module), 27, **195**
persistence, 36
persistent
 objects, 36
pformat() (in module pprint), 62, 63
PGP, 301
pi (in module cmath), 97
pi (in module math), 96
pick() (in module gl), 318
pickle (standard module), **36**, 41, 43, 44
pickle() (in module copy_reg), 41
Pickler (in module pickle), 38
pickling
 objects, 36
PicklingError (in module pickle), 39
pid (in module popen2), 193
PIL (the Python Imaging Library), 320
pipe() (in module os), 114
pipes (standard module), **186**
PKG_DIRECTORY (in module imp), 46
platform (in module sys), 28
play() (in module cd), 309
playabs() (in module cd), 309
PLAYING (in module cd), 308
PlaySound() (in module winsound), 326
playtrack() (in module cd), 309
playtrackabs() (in module cd), 309
plock() (in module os), 119
pm() (in module pdb), 196
pnum (in module cd), 308
poll() (in module popen2), 193
pop(), 8
pop() (in module multifile), 267
POP3
 protocol, 228
POP3 (in module poplib), 228
pop_alignment() (in module formatter), 259
pop_font() (in module formatter), 259
pop_margin() (in module formatter), 259
pop_style() (in module formatter), 259
popen() (in module os), 113
popen() (in module select), 158
popen2 (standard module), **192**
popen2() (in module popen2), 193
Popen3 (in module popen2), 193
popen3() (in module popen2), 193
poplib (standard module), **228**
pos (in module re), 85
pos() (in module operator), 32
posix (built-in module), 11, **177**
posixfile (built-in module), **187**
POSIX
 file object, 187
 I/O control, 183, 184
 threads, 159
post() (in module nntplib), 235
post_mortem() (in module pdb), 196
postcmd() (in module cmd), 107
postloop() (in module cmd), 107
pow() (built-in function), 21
pow() (in module math), 96
powm() (in module mpz), 303
pprint (standard module), **61**
pprint() (in module pprint), 62, 63
prcal() (in module calendar), 106
precmd() (in module cmd), 107
prefix (in module sys), 28
preloop() (in module cmd), 107
prepend() (in module pipes), 187
Pretty Good Privacy, 301
PrettyPrinter (in module pprint), 61
preventremoval() (in module cd), 309
previous() (in module bsddb), 170
previous() (in module dbhash), 169
print
 statement, 3
print_callees() (in module pstats), 207
print_callers() (in module pstats), 206
print_directory() (in module cgi), 216
print_envron() (in module cgi), 216
print_envron_usage() (in module cgi), 216
print_exc() (in module traceback), 34

print_exception() (in module traceback), 34
 print_form() (in module cgi), 216
 print_last() (in module traceback), 34
 print_stack() (in module traceback), 34
 print_stats() (in module pstats), 206
 print_tb() (in module traceback), 34
 printdir(), 175
 prmonth() (in module calendar), 106
 process
 group, 112
 id, 112
 id of parent, 113
 killing, 118
 signalling, 118
 process_request() (SocketServer protocol),
 243
 processes, light-weight, 159
 profile (standard module), **204**
 profile function, 28
 profiler, 28
 profiling, deterministic, 201
 prompt (in module cmd), 107
 prompts, interpreter, 28
 protocol
 CGI, 213
 FTP, 222, 224
 Gopher, 222, 227
 HTTP, 213, 222, 223, 243
 IMAP4, 229
 NNTP, 232
 POP3, 228
 SMTP, 235
 PROTOCOL_VERSION (in module imaplib), 232
 protocol_version (in module Base-
 HTTPServer), 245
 prstr() (in module fm), 316
 ps1 (in module sys), 28
 ps2 (in module sys), 28
 pstats (standard module), **205**
 pthreads, 159
 ptime (in module cd), 308
 pty (standard module), **185**
 push() (in module code), 61
 push() (in module multifile), 266
 push_alignment() (in module formatter), 259
 push_font() (in module formatter), 259
 push_margin() (in module formatter), 259
 push_style() (in module formatter), 259
 push_token() (in module shlex), 108
 put() (in module Queue), 167
 put_nowait() (in module Queue), 167
 putch() (in module msvcrt), 326
 putenv() (in module os), 113
 putheader() (in module httplib), 224

putrequest() (in module httplib), 224
 putsequences() (in module mhlib), 278
 pwd (built-in module), 121, **178**
 pwd() (in module ftplib), 227
 pwlcurve() (in module gl), 318
 py_compile (standard module), **65**
 PY_COMPILED (in module imp), 45
 PY_FROZEN (in module imp), 46
 PY_RESOURCE (in module imp), 45
 PY_SOURCE (in module imp), 45
 pyclbr (standard module), **58**
 PyOpenGL, 319
 Python Imaging Library, 320
 \$PYTHONPATH, 28, 217, 330
 \$PYTHONSTARTUP, 73, 176
 \$PYTHON2K, 127, 128

Q

qdevice() (in module fl), 312
 qenter() (in module fl), 312
 qread() (in module fl), 312
 qreset() (in module fl), 312
 qsize() (in module Queue), 166
 QTest() (in module fl), 312
 queryparams() (in module al), 305
 Queue (in module Queue), 166
 Queue (standard module), **166**
 quit() (in module ftplib), 227
 quit() (in module nntplib), 235
 quit() (in module poplib), 229
 quit() (in module smtplib), 238
 quopri (standard module), **276**
 quote() (in module urllib), 221
 quote_plus() (in module urllib), 221
 quoted-printable
 encoding, 276
 quotes (in module shlex), 109

R

r_eval() (in module rexec), 285
 r_exec() (in module rexec), 285
 r_execfile() (in module rexec), 285
 r_import() (in module rexec), 285
 R_OK (in module os), 115
 r_open() (in module rexec), 285
 r_reload() (in module rexec), 285
 r_unload() (in module rexec), 285
 raise
 statement, 13
 randint() (in module random), 99
 randint() (in module whrandom), 99
 random (standard module), **98**
 random() (in module random), 99
 random() (in module whrandom), 99

`range()` (built-in function), 21
`Rat` (in module `mpz`), 302
`ratecv()` (in module `audioop`), 289
rational numbers, 302
`raw()` (in module `curses`), 133
`raw_input()` (built-in function), 21
`raw_input()` (in module `code`), 61
`raw_input()` (in module `sys`), 28
`re` (in module `re`), 85
`re` (standard module), 7, 75, **78**, 85, 144
`read()`, 11, 175
`read()` (in module `ConfigParser`), 104
`read()` (in module `array`), 102
`read()` (in module `chunk`), 298
`read()` (in module `imgfile`), 320
`read()` (in module `multifile`), 267
`read()` (in module `os`), 115
`read()` (in module `robotparser`), 280
`read()` (in module `sunaudiodev`), 324
`read_all()` (in module `telnetlib`), 239
`read_eager()` (in module `telnetlib`), 239
`read_lazy()` (in module `telnetlib`), 239
`read_mime_types()` (in module `mimetypes`), 274
`read_some()` (in module `telnetlib`), 239
`read_token()` (in module `shlex`), 108
`read_until()` (in module `telnetlib`), 239
`read_very_eager()` (in module `telnetlib`), 239
`read_very_lazy()` (in module `telnetlib`), 239
`readable()` (in module `asyncore`), 248
`readadd()` (in module `cd`), 309
`readfp()` (in module `ConfigParser`), 104
`readframes()` (in module `aifc`), 292
`readframes()` (in module `sunau`), 294
`readframes()` (in module `wave`), 296
`readline()`, 11
`readline()` (in module `multifile`), 267
`readlines()`, 11
`readlines()` (in module `multifile`), 267
`readlink()` (in module `os`), 117
`readmodule()` (in module `pyclbr`), 58
`readsamps()` (in module `al`), 306
`readscaled()` (in module `imgfile`), 320
`READY` (in module `cd`), 308
Real Media File Format, 297
`realpat` (regex attribute), 89
`recent()` (in module `imaplib`), 231
`reconvert` (standard module), 85
`recv()` (in module `asyncore`), 249
`recv()` (in module `socket`), 156
`recvfrom()` (in module `socket`), 157
`redraw_form()` (in module `fl`), 312
`redraw_object()` (in module `fl`), 315
`reduce()` (built-in function), 21
`refilemessages()` (in module `mhlib`), 278
`refresh()` (in module `curses`), 134
`regex` (built-in module), **85**
`regex_syntax` (standard module), 88
`register()` (in module `codecs`), 93
`regs` (regex attribute), 89
`regsub` (standard module), **89**
relative
 URL, 241
`release()` (in module `thread`), 159
`release()` (in module `threading`), 161–164
`reload()` (built-in function), 22
`reload()` (in module `imp`), 45, 47
`reload()` (in module `sys`), 27
`remove()`, 8
`remove()` (in module `os`), 117
`removecallback()` (in module `cd`), 310
`removedirs()` (in module `os`), 117
`removemessages()` (in module `mhlib`), 278
`rename()` (in module `ftplib`), 227
`rename()` (in module `imaplib`), 231
`rename()` (in module `os`), 117
`renames()` (in module `os`), 117
`reorganize()` (in module `gdbm`), 182
`repeat()` (in module `operator`), 33
repetition
 operation, 6
`replace()` (in module `string`), 77
`report_unbalanced()` (in module `sgmlib`), 253
`Repr` (in module `repr`), 63
`repr` (standard module), **63**
`repr()` (built-in function), 22
`repr()` (in module `repr`), 64
`repr1()` (in module `repr`), 64
`request_queue_size` (SocketServer protocol), 242
`request_version` (in module `BaseHTTPServer`), 244
`RequestHandlerClass` (SocketServer protocol), 242
`reset()` (in module `pipes`), 186
`reset()` (in module `sgmlib`), 252
`reset()` (in module `statcache`), 125
`reset()` (in module `xdrlib`), 271, 272
`reset()` (in module `xmllib`), 255
`resetbuffer()` (in module `code`), 61
`resetparser()` (in module `cd`), 310
`resource` (built-in module), **189**
`response()` (in module `imaplib`), 231
`responses` (in module `BaseHTTPServer`), 245
`retr()` (in module `poplib`), 228
`retrbinary()` (in module `ftplib`), 226
`retrieve()` (in module `urllib`), 222
`retrlines()` (in module `ftplib`), 226
`reverse()`, 8

reverse() (in module array), 102
reverse() (in module audioop), 289
reverse_order() (in module pstats), 206
rewind() (in module aifc), 292
rewind() (in module sunau), 294
rewind() (in module wave), 296
rewindbody() (in module rfc822), 262
RExec (in module rexec), 284
rexec (standard module), 16, **284**
RFC
 RFC 1014, 270
 RFC 1321, 301
 RFC 1521, 275, 276
 RFC 1524, 273
 RFC 1725, 228
 RFC 1730, 229
 RFC 1738, 241
 RFC 1808, 241
 RFC 1866, 253, 254
 RFC 1869, 235, 236
 RFC 2060, 229
 RFC 821, 235, 236
 RFC 822, 103, 224, 237, 238, 261, 262
 RFC 854, 238, 239
 RFC 959, 224
 RFC 977, 232
rfc822 (standard module), **261**, 264
rfile (in module BaseHTTPServer), 244
rfind() (in module string), 76
rgb_to_hls() (in module colorsys), 298
rgb_to_hsv() (in module colorsys), 298
rgb_to_yiq() (in module colorsys), 298
rgbimg (built-in module), **299**
rindex() (in module string), 76
rjust() (in module string), 77
rlcompleter (standard module), **175**
rlecode_hqx() (in module binascii), 270
rledecode_hqx() (in module binascii), 270
RLIMIT_AS (in module resource), 190
RLIMIT_CORE (in module resource), 189
RLIMIT_CPU (in module resource), 190
RLIMIT_DATA (in module resource), 190
RLIMIT_FSIZE (in module resource), 190
RLIMIT_MEMLOC (in module resource), 190
RLIMIT_NOFILE (in module resource), 190
RLIMIT_NPROC (in module resource), 190
RLIMIT_OFIL (in module resource), 190
RLIMIT_RSS (in module resource), 190
RLIMIT_STACK (in module resource), 190
RLIMIT_VMEM (in module resource), 190
RLock() (in module threading), 160
rmd() (in module ftplib), 227
rmdir() (in module os), 117
RMFF, 297
rms() (in module audioop), 289
rmtree() (in module shutil), 145
rnpopen() (in module bsddb), 170
RobotFileParser (in module robotparser), 280
robotparser (standard module), **280**
robots.txt, 280
rotor (built-in module), **303**
round() (built-in function), 22
rpop() (in module poplib), 228
rset() (in module poplib), 229
rshift() (in module operator), 33
rstrip() (in module string), 77
RTLD_LAZY (in module dl), 180
RTLD_NOW (in module dl), 180
ruler (in module cmd), 107
run() (in module pdb), 196
run() (in module profile), 204
run() (in module sched), 131
run() (in module threading), 165
runcall() (in module pdb), 196
runcode() (in module code), 60
runeval() (in module pdb), 196
runsource() (in module code), 60
RuntimeError (built-in exception), 15
RUSAGE_BOTH (in module resource), 191
RUSAGE_CHILDREN (in module resource), 191
RUSAGE_SELF (in module resource), 191

S

S (in module re), 82
s_eval() (in module rexec), 285
s_exec() (in module rexec), 285
s_execfile() (in module rexec), 285
S_IFMT() (in module stat), 124
S_IMODE() (in module stat), 124
s_import() (in module rexec), 285
S_ISBLK() (in module stat), 124
S_ISCHR() (in module stat), 124
S_ISDIR() (in module stat), 124
S_ISFIFO() (in module stat), 124
S_ISLNK() (in module stat), 124
S_ISREG() (in module stat), 124
S_ISSOCK() (in module stat), 124
s_reload() (in module rexec), 285
s_unload() (in module rexec), 285
saferepr() (in module pprint), 63
samefile() (in module os.path), 122
sameopenfile() (in module os.path), 122
samestat() (in module os.path), 122
save_bgn() (in module htmllib), 254
save_end() (in module htmllib), 255
scale() (in module imageop), 290
scalefont() (font handle method), 316
sched (standard module), **130**

scheduler (in module sched), 130
 sci() (in module fpformat), 92
 scroll() (in module curses), 135
 search
 path, module, 27, 36, 72
 search() (in module imaplib), 231
 search() (in module re), 82, 83
 search() (in module regex), 87
 search() (regex method), 88
 SEARCH_ERROR (in module imp), 46
 section_divider() (in module multifile), 267
 sections() (in module ConfigParser), 104
 Secure Hash Algorithm, 302
 seed() (in module whrandom), 99
 seek(), 11
 seek() (in module cd), 309
 seek() (in module chunk), 298
 seek() (in module multifile), 267
 SEEK_CUR (in module posixfile), 187
 SEEK_END (in module posixfile), 187
 SEEK_SET (in module posixfile), 187
 seekblock() (in module cd), 309
 seektrack() (in module cd), 310
 select (built-in module), **158**
 select() (in module gl), 318
 select() (in module imaplib), 231
 select() (in module select), 158
 Semaphore (in module threading), 164
 Semaphore() (in module threading), 160
 semaphores, binary, 159
 send() (in module asyncore), 249
 send() (in module httplib), 224
 send() (in module socket), 157
 send_error() (in module BaseHTTPServer), 245
 send_flowng_data() (in module formatter),
 261
 send_header() (in module BaseHTTPServer),
 245
 send_hor_rule() (in module formatter), 260
 send_label_data() (in module formatter), 261
 send_line_break() (in module formatter), 260
 send_literal_data() (in module formatter),
 261
 send_paragraph() (in module formatter), 260
 send_query() (in module gopherlib), 228
 send_response() (in module BaseHTTPServer),
 245
 send_selector() (in module gopherlib), 227
 sendcmd() (in module ftplib), 226
 sendmail() (in module smtplib), 237
 sendto() (in module socket), 157
 sep (in module os), 121
 sequence
 types, 6
 types, mutable, 7
 types, operations on, 6, 8
 types, operations on mutable, 8
 sequence2ast() (in module parser), 48
 sequenceIncludes() (in module operator), 33
 serializing
 objects, 36
 serve_forever() (SocketServer protocol), 242
 server
 WWW, 213, 243
 server_activate() (SocketServer protocol),
 243
 server_address (SocketServer protocol), 242
 server_bind() (SocketServer protocol), 243
 server_version (in module BaseHTTPServer),
 244
 server_version (in module SimpleHTTPServer),
 246
 set() (in module threading), 164
 set_call_back() (in module fl), 314
 set_debuglevel() (in module ftplib), 225
 set_debuglevel() (in module httplib), 223
 set_debuglevel() (in module nntplib), 234
 set_debuglevel() (in module smtplib), 236
 set_debuglevel() (in module telnetlib), 239
 set_event_call_back() (in module fl), 311
 set_form_position() (in module fl), 312
 set_graphics_mode() (in module fl), 311
 set_location() (in module bsddb), 170
 set_pasv() (in module ftplib), 226
 set_position() (in module xdrlib), 272
 set_spacing() (in module formatter), 259
 set_syntax() (in module regex), 88
 set_trace() (in module pdb), 196
 set_url() (in module robotparser), 280
 setattr() (built-in function), 22
 setattr() (in module curses), 134
 setblocking() (in module socket), 157
 setcbreak() (in module tty), 184
 setchannels() (in module al), 306
 setcheckinterval() (in module sys), 28
 setcomptype() (in module aifc), 292
 setcomptype() (in module sunau), 294
 setcomptype() (in module wave), 296
 setconfig() (in module al), 307
 setcontext() (in module mhlib), 277
 setcurrent() (in module mhlib), 278
 setDaemon() (in module threading), 166
 setfillpoint() (in module al), 307
 setfloatmax() (in module al), 306
 setfont() (font handle method), 316
 setframerate() (in module aifc), 292
 setframerate() (in module sunau), 294
 setframerate() (in module wave), 296

setgid() (in module os), 113
 setinfo() (in module sunaudiodev), 324
 setitem() (in module operator), 33
 setkey() (in module rotor), 304
 setlast() (in module mhlib), 278
 setliteral() (in module sgmlib), 252
 setliteral() (in module xmllib), 256
 setlocale() (in module locale), 146
 setlogmask() (in module syslog), 192
 setmark() (in module aifc), 293
 setmode() (in module msvcrt), 325
 setName() (in module threading), 166
 setnchannels() (in module aifc), 292
 setnchannels() (in module sunau), 294
 setnchannels() (in module wave), 296
 setnframes() (in module aifc), 292
 setnframes() (in module sunau), 294
 setnframes() (in module wave), 296
 setnomoretags() (in module sgmlib), 252
 setnomoretags() (in module xmllib), 255
 setoption() (in module jpeg), 320
 setparams() (in module aifc), 292
 setparams() (in module al), 306
 setparams() (in module sunau), 294
 setparams() (in module wave), 296
 setpath() (in module fm), 316
 setpgid() (in module os), 113
 setpgrp() (in module os), 113
 setpos() (in module aifc), 292
 setpos() (in module sunau), 294
 setpos() (in module wave), 296
 setprofile() (in module sys), 28
 setqueuesize() (in module al), 306
 setraw() (in module tty), 184
 setrlimit() (in module resource), 189
 setsampfmt() (in module al), 306
 setsampwidth() (in module aifc), 292
 setsampwidth() (in module sunau), 294
 setsampwidth() (in module wave), 296
 setscreg() (in module curses), 136
 setsid() (in module os), 113
 setslice() (in module operator), 34
 setsockopt() (in module socket), 157
 settrace() (in module sys), 28
 setuid() (in module os), 113
 setup() (SocketServer protocol), 243
 setwidth() (in module al), 306
SGML, 251
 sgmlib (standard module), **251**, 253
 SGMLParser (in module htmlib), 253
 SGMLParser (in module sgmlib), 251
 sha (built-in module), **302**
 shelve (standard module), 37, **41**, 44
 shifting
 operations, 6
 shlex (in module shlex), 108
 shlex (standard module), **108**
 show_choice() (in module fl), 311
 show_file_selector() (in module fl), 312
 show_form() (in module fl), 312
 show_input() (in module fl), 311
 show_message() (in module fl), 311
 show_object() (in module fl), 315
 show_question() (in module fl), 311
 showsyntaxerror() (in module code), 60
 showtraceback() (in module code), 60
 shutdown() (in module socket), 157
 shutil (standard module), **145**
 SIG* (in module signal), 152
 SIG_DFL (in module signal), 152
 SIG_IGN (in module signal), 152
 signal (built-in module), **151**, 160
 signal() (in module signal), 152
 Simple Mail Transfer Protocol, 235
 SimpleHTTPRequestHandler (in module SimpleHTTPServer), 246
 SimpleHTTPServer (standard module), 243, **246**
 sin() (in module cmath), 97
 sin() (in module math), 96
 sinh() (in module cmath), 97
 sinh() (in module math), 96
 site (standard module), **72**, 73
 site-packages
 directory, 72
 site-python
 directory, 72
 sitecustomize (module), 73
 size() (in module ftplib), 227
 sizeofimage() (in module rgbimg), 299
 skip() (in module chunk), 298
 slave() (in module nntplib), 235
 sleep() (in module time), 129
 slice
 assignment, 8
 operation, 6
 slice() (built-in function), 22
 slice() (byte code insns), 71
 slice() (in module types), 30
 SliceType (in module types), 30
SMTP
 protocol, 235
 SMTP (in module smtplib), 235
 SMTPConnectError (in module smtplib), 236
 SMTPDataError (in module smtplib), 236
 SMTPException (in module smtplib), 236
 SMTPHeloError (in module smtplib), 236
 smtplib (standard module), **235**

SMTPRecipientsRefused (in module smtplib), 236
SMTPResponseException (in module smtplib), 236
SMTPSenderRefused (in module smtplib), 236
SMTPServerDisconnected (in module smtplib), 236
SND_ALIAS (in module winsound), 326
SND_ASYNC (in module winsound), 326
SND_FILENAME (in module winsound), 326
SND_LOOP (in module winsound), 326
SND_MEMORY (in module winsound), 326
SND_NODEFAULT (in module winsound), 326
SND_NOSTOP (in module winsound), 327
SND_NOWAIT (in module winsound), 327
SND_PURGE (in module winsound), 326
sndhdr (standard module), **300**
SO_* (in module socket), 154
SOCK_DGRAM (in module socket), 154
SOCK_RAW (in module socket), 154
SOCK_RDM (in module socket), 154
SOCK_SEQPACKET (in module socket), 154
SOCK_STREAM (in module socket), 154
socket
 object, 153
socket (SocketServer protocol), 242
socket (built-in module), 11, **153**, 213
socket() (in module imaplib), 231
socket() (in module select), 158
socket() (in module socket), 155
socket_type (SocketServer protocol), 242
SocketServer (standard module), **241**
SocketType (in module socket), 155
softspace, 12
SOL_* (in module socket), 154
SOMAXCONN (in module socket), 154
sort(), 8
sort_stats() (in module pstats), 205
source (in module shlex), 109
span() (in module re), 85
spawn() (in module pty), 185
spawnv() (in module os), 119
spawnve() (in module os), 119
split() (in module os.path), 122
split() (in module re), 82, 84
split() (in module re.sub), 89
split() (in module string), 77
splitdrive() (in module os.path), 123
splittext() (in module os.path), 123
splitfields() (in module string), 77
splitx() (in module re.sub), 89
sqrt() (in module cmath), 97
sqrt() (in module math), 96
sqrt() (in module mpz), 303
sqrtrem() (in module mpz), 303
ST_ATIME (in module stat), 124
ST_CTIME (in module stat), 125
ST_DEV (in module stat), 124
ST_GID (in module stat), 124
ST_INO (in module stat), 124
ST_MODE (in module stat), 124
ST_MTIME (in module stat), 125
ST_NLINK (in module stat), 124
ST_SIZE (in module stat), 124
ST_UID (in module stat), 124
stackable
 streams, 93
StandardError (built-in exception base class), 13
standend() (in module curses), 134
standout() (in module curses), 134
start() (in module re), 84
start() (in module threading), 165
start_new_thread() (in module thread), 159
startbody() (in module MimeWriter), 266
startmultipartbody() (in module MimeWriter), 266
stat (standard module), 117, **123**
stat() (in module nntplib), 234
stat() (in module os), 117
stat() (in module poplib), 228
stat() (in module statcache), 125
statcache (standard module), **125**
statement
 assert, 14
 del, 8
 except, 13
 exec, 10
 if, 3
 import, 16, 44
 print, 3
 raise, 13
 try, 13
 while, 3
Stats (in module pstats), 205
status() (in module imaplib), 231
statvfs (standard module), 117, **126**
statvfs() (in module os), 117
stderr (in module sys), 28
stdin (in module sys), 28
stdout (in module sys), 28
stdwin (built-in module), 158, 195
STILL (in module cd), 308
stop() (in module cd), 310
storbinary() (in module ftplib), 226
store() (in module imaplib), 231
storlines() (in module ftplib), 226
str() (built-in function), 22
str() (in module locale), 147

strcoll() (in module locale), 147
 streams, 93
 stackable, 93
 strerror() (in module os), 113
 strftime() (in module time), 129
 string
 documentation, 51
 type, 6
 string (in module re), 85
 string (standard module), 7, **75**, 148, 149
 StringIO (in module StringIO), 93
 StringIO (standard module), **93**
 StringType (in module types), 30
 strip() (in module string), 77
 strip_dirs() (in module pstats), 205
 strop (built-in module), 78, 149
 strptime() (in module time), 130
 struct (built-in module), **90**, 157
 structures
 C, 90
 strxfrm() (in module locale), 147
 sub() (in module operator), 32
 sub() (in module re), 82, 84
 sub() (in module regrab), 89
 subn() (in module re), 83, 84
 subscribe() (in module imaplib), 231
 subscript
 assignment, 8
 operation, 6
 subwin() (in module curses), 134
 suffix_map (in module mimetypes), 275
 suite() (in module parser), 48
 sunau (standard module), **293**
 SUNAUDIODEV (standard module), 323, **324**
 sunaudiodev (built-in module), **323**, 324
 super (in module pycbr), 59
 swapcase() (in module string), 77
 sym() (in module dl), 181
 sym_name (in module symbol), 56
 symbol (standard module), **56**
 symbol table, 3
 symcomp() (in module regex), 88
 symlink() (in module os), 117
 sync() (in module bsddb), 171
 sync() (in module dbhash), 169
 sync() (in module gdbm), 183
 syntax_error() (in module xmllib), 257
 SyntaxError (built-in exception), 15
 sys (built-in module), **25**
 sys_version (in module BaseHTTPServer), 244
 sysconf() (in module os), 120
 sysconf_names (in module os), 120
 syslog (built-in module), **192**
 syslog() (in module syslog), 192

system() (in module os), 119
 SystemError (built-in exception), 15
 SystemExit (built-in exception), 15

T

tabnanny (standard module), **58**
 tan() (in module cmath), 97
 tan() (in module math), 96
 tanh() (in module cmath), 97
 tanh() (in module math), 96
 tb_lineno() (in module traceback), 35
 tcdrain() (in module termios), 183
 tcflow() (in module termios), 183
 tcflush() (in module termios), 183
 tcgetattr() (in module termios), 183
 tcgetpgrp() (in module os), 115
 tcsendbreak() (in module termios), 183
 tcsetattr() (in module termios), 183
 tcsetpgrp() (in module os), 115
 tell(), 11
 tell() (in module aifc), 292, 293
 tell() (in module chunk), 298
 tell() (in module multifile), 267
 tell() (in module sunau), 294, 295
 tell() (in module wave), 296
 Telnet (in module telnetlib), 238
 telnetlib (standard module), **238**
 tempdir (in module tempfile), 138
 tempfile (standard module), **137**
 Template (in module pipes), 186
 template (in module tempfile), 138
 tempnam() (in module os), 117
 temporary
 file, 137
 file name, 137
 TERMIOS (standard module), 183, **184**
 termios (built-in module), **183**, 184
 test() (in module cgi), 216
 test() (in module mutex), 150
 testandset() (in module mutex), 150
 tests (in module imgchr), 300
 Thread (in module threading), 161, 165
 thread (built-in module), **159**
 threading (standard module), **160**
 threads
 IRIX, 160
 POSIX, 159
 tie() (in module fl), 312
 time (built-in module), **127**
 time() (in module time), 130
 Time2Internaldate() (in module imaplib), 230
 time2zip(), 174
 timegm() (in module calendar), 106
 times() (in module os), 119

timezone (in module time), 130
 TMP_MAX (in module os), 118
 \$TMPDIR, 138
 tmpfile() (in module os), 114
 tmpnam() (in module os), 117
 TOC, 174
 tochild (in module popen2), 193
 tofile() (in module array), 102
 togglepause() (in module cd), 310
 tok_name (in module token), 57
 token (in module shlex), 109
 token (standard module), **57**
 tokeneater() (in module tabnanny), 58
 tokenize (standard module), **57**
 tokenize() (in module tokenize), 57
 tolist() (in module array), 102
 tolist() (in module parser), 50
 tomono() (in module audioop), 289
 top() (in module poplib), 229
 tostereo() (in module audioop), 289
 tostring() (in module array), 102
 totuple() (in module parser), 50
 touchline() (in module curses), 136
 touchwin() (in module curses), 135
 tovideo() (in module imageop), 290
 trace function, 28
 traceback
 object, 26, 34
 traceback (standard module), **34**
 tracebacklimit (in module sys), 29
 TracebackType (in module types), 30
 transfercmd() (in module ftplib), 226
 translate (regex attribute), 89
 translate() (in module string), 77
 translate_references() (in module xmllib),
 256
 true, 3
 truncate(), 11
 truth
 value, 3
 truth() (in module operator), 33
 try
 statement, 13
 ttob() (in module imgfile), 320
 ttob() (in module rgbimg), 299
 tty
 I/O control, 183, 184
 tty (standard module), **184**
 ttyname() (in module os), 115
 tuple
 type, 6
 tuple() (built-in function), 23
 tuple2ast() (in module parser), 49
 TupleType (in module types), 30

type
 Boolean, 3
 complex number, 5
 dictionary, 8
 floating point, 5
 integer, 5
 list, 6, 7
 long integer, 5
 object, 23
 operations on dictionary, 8
 operations on list, 8
 string, 6
 tuple, 6
 type(), 10
 type() (built-in function), 23
 type() (in module types), 29
 typecode (in module array), 101
 TypeError (built-in exception), 15
 types
 built-in, 3
 integer, 5
 mapping, 8
 mutable sequence, 7
 numeric, 5
 operations on integer, 6
 operations on mapping, 8
 operations on mutable sequence, 8
 operations on numeric, 5
 operations on sequence, 6, 8
 sequence, 6
 types (standard module), 10, 23, **29**
 types_map (in module mimetypes), 275
 TypeType (in module types), 29
 tzname (in module time), 130

U

u-LAW, 287, 292, 300, 323
 uid() (in module imaplib), 231
 uidl() (in module poplib), 229
 ulaw2lin() (in module audioop), 289
 umask() (in module os), 113
 uname() (in module os), 113
 UnboundLocalError (built-in exception), 15
 UnboundMethodType (in module types), 30
 unbuffered I/O, 20
 undoc_header (in module cmd), 107
 unfreeze_form() (in module fl), 313
 unfreeze_object() (in module fl), 315
 ungetch() (in module curses), 133
 ungetch() (in module msvcrt), 326
 unichr() (built-in function), 23
 Unicode, 93
 unicode() (built-in function), 23
 UnicodeError (built-in exception), 15

- UnicodeType (in module types), 30
- uniform() (in module random), 99
- uniform() (in module whrandom), 99
- UNIX
 - file control, 185
 - I/O control, 185
- UnixMailbox (in module mailbox), 276
- unknown_charref() (in module sgmlib), 253
- unknown_charref() (in module xmllib), 257
- unknown_endtag() (in module sgmlib), 253
- unknown_endtag() (in module xmllib), 257
- unknown_entityref() (in module sgmlib), 253
- unknown_entityref() (in module xmllib), 257
- unknown_starttag() (in module sgmlib), 253
- unknown_starttag() (in module xmllib), 257
- unlink() (in module os), 118
- unlock() (in module mutex), 150
- unmimify() (in module mimify), 279
- unpack() (in module struct), 90
- unpack_array() (in module xdrlib), 273
- unpack_bytes() (in module xdrlib), 272
- unpack_double() (in module xdrlib), 272
- unpack_farray() (in module xdrlib), 273
- unpack_float() (in module xdrlib), 272
- unpack_fopaque() (in module xdrlib), 272
- unpack_fstring() (in module xdrlib), 272
- unpack_list() (in module xdrlib), 272
- unpack_opaque() (in module xdrlib), 272
- unpack_string() (in module xdrlib), 272
- Unpacker (in module xdrlib), 271
- Unpickler (in module pickle), 38
- unqdevice() (in module fl), 312
- unquote() (in module urllib), 221
- unquote_plus() (in module urllib), 221
- unsubscribe() (in module imaplib), 232
- unused_data (in module zlib), 172
- update(), 8
- update() (in module md5), 302
- upper() (in module string), 77
- uppercase (in module string), 75
- URL, 213, 219, 241, 243, 280
 - parsing, 241
 - relative, 241
- urlcleanup() (in module urllib), 221
- urlencode() (in module urllib), 221
- urljoin() (in module urlparse), 241
- urllib (standard module), **219**, 223
- urlopen() (in module urllib), 220
- URLopener (in module urllib), 221
- urlparse (standard module), 222, **241**
- urlparse() (in module urlparse), 241
- urlretrieve() (in module urllib), 220
- urlunparse() (in module urlparse), 241
- \$USER, 132, 226

- user
 - configuration file, 73
 - effective id, 112
 - id, 113
 - id, setting, 113
- user (standard module), **73**
- user() (in module poplib), 228
- UserDict (in module UserDict), 31
- UserDict (standard module), **31**
- UserList (in module UserList), 31
- UserList (standard module), **31**
- \$USERNAME, 132
- UserString (in module UserString), 32
- UserString (standard module), **31**
- UTC, 127
- utime() (in module os), 118
- uu (standard module), 269, **269**

V

- value
 - truth, 3
- ValueError (built-in exception), 15
- values(), 8
- varray() (in module gl), 318
- vars() (built-in function), 23
- VERBOSE (in module re), 82
- verbose (in module tabnanny), 58
- verify() (in module smtplib), 237
- verify_request() (SocketServer protocol), 243
- version (in module curses), 132
- version (in module sys), 29
- version_info (in module sys), 29
- version_string() (in module Base-HTTPServer), 245
- vline() (in module curses), 135
- vnarray() (in module gl), 318
- voidcmd() (in module ftplib), 226
- vonmisesvariate() (in module random), 98

W

- W_OK (in module os), 116
- wait() (in module os), 119
- wait() (in module popen2), 193
- wait() (in module threading), 163, 164
- waitpid() (in module os), 119
- walk() (in module os.path), 123
- wave (standard module), **295**
- wdb (standard module), 195
- weekday() (in module calendar), 106
- weibullvariate() (in module random), 99
- WEXITSTATUS() (in module os), 120
- wfile (in module BaseHTTPServer), 244
- what() (in module imghdr), 299
- what() (in module sndhdr), 300

whathdr() (in module sndhdr), 300
 whichdb (standard module), **169**
 whichdb() (in module whichdb), 169
 while
 statement, 3
 whitespace (in module shlex), 109
 whitespace (in module string), 75
 whrandom (standard module), **99**
 WIFEXITED() (in module os), 120
 WIFSIGNALED() (in module os), 120
 WIFSTOPPED() (in module os), 120
 Windows ini file, 103
 WindowsError (built-in exception), 16
 winsound (built-in module), **326**
 winver (in module sys), 29
 WNOHANG (in module os), 120
 wordchars (in module shlex), 108
 World-Wide Web, 213, 219, 241, 280
 write(), 11, 175
 write() (in module array), 102
 write() (in module code), 60
 write() (in module imgfile), 320
 write() (in module os), 115
 write() (in module sunaudiodev), 324
 write() (in module telnetlib), 240
 writeable() (in module asyncore), 248
 writeframes() (in module aifc), 293
 writeframes() (in module sunau), 295
 writeframes() (in module wave), 297
 writeframesraw() (in module aifc), 293
 writeframesraw() (in module sunau), 295
 writeframesraw() (in module wave), 297
 writelines(), 12
 writepy(), 175
 writer (in module formatter), 258
 writesamps() (in module al), 307
 writestr(), 175
 WSTOPSIG() (in module os), 120
 WTERMSIG() (in module os), 120
 WWW, 213, 219, 241, 280
 server, 213, 243

X

X (in module re), 82
 X_OK (in module os), 116
 xatom() (in module imaplib), 232
 XDR, 37, 270
 xdrlib (standard module), **270**
 xgtitle() (in module nntplib), 235
 xhdr() (in module nntplib), 235
 XML, 255
 namespaces, 257
 xmllib (standard module), **255**
 XMLParser (in module xmllib), 255

xor() (in module operator), 33
 xover() (in module nntplib), 235
 xpath() (in module nntplib), 235
 xrange() (built-in function), 23
 xrange() (in module types), 30
 xrangeType (in module types), 30

Y

Y2K, 127
 Year 2000, 127
 Year 2038, 127
 yiq_to_rgb() (in module colorsys), 298

Z

ZeroDivisionError (built-in exception), 16
 zfill() (in module string), 77
 zip2date(), 174
 zip2time(), 174
 ZIP_DEFLATED, 174
 ZIP_STORED, 174
 ZipFile, 174
 zlib (built-in module), **171**